**SMITH**® LOCATION JAY R. **SMITH** MFG. CO.<sup>®</sup> В MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith CUSTOMER DRIVEN LAUNDRY TRENCH (TROUGH) DRAIN & LINT INTERCEPTOR DRAWING NUMBER FUNCTION: Used at low end of laundry trench (trough) for drainage & lint interception. OF SUPERSEDED OR VOID DATA Cast Iron Dome 102.5 SQ IN 15 1/4 DIA (661) SQ CM Bottom of (390)Trench (Trough) Free Area SIZE 3 1/4 (83) USE ( 2 (51) SCALE: CAN ASSUME NO RESPONSIBILITY FOR . 0 4 1/2 (115) 3-19-03 ۰۵٬۵۰ Removable Stainless Steel DATE: 14 x 14 Mesh Lint/Sediment Bucket WE APPROVED BY 32 1/2 (825) 4 .0 0 0 26 (660) DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE NOTE: Recommended for a Maximum ₽ of Two Washers, not to Exceed 20 CHECKED 겅 GPM Flow. 9 3/4 DIA. (250)DRAWN BY: 8 (200) . . 4 20 SQ. (510)"A" (Pipe Size) = 02 (50), 03 (75) or 04 (100) 891 Fig. 8913T.....Threaded Outlet **REGULARLY FURNISHED: VARIATIONS: OPTIONAL MATERIALS:** Duco Coated Fabricated Steel Drain Body Y NO-HUB Outlet Type 304 Stainless Steel Body with Removable Cast Iron Dome, Cast Iron C Caulk Outlet Galvanized Coated Clamping Collar and Removable Stainless

Lifting Handle.

BA

REV.

IGURE

11-3-03 7-9-03

Steel 14x14 Mesh Lint/Sediment Bucket with

Add Pipe Size Add Trough

CL McD

CKD. BY

RN RN

BY

WEIGHT

POUNDS

VOLUME

CUBIC FEET

FIGURE NUMBER

8913