



Hand Shower System

1-250VT-T24-V

Specification Submittal



Feature Highlights

- Symmons Safetymix® Visu-Temp® Hand Shower System with Clear-View™ thermometer.
- Hand Shower #T600B-24, ADA compliant brushed stainless finish 24 inch vertical grab bar with adjustable sliding cradle for mounting white finish hand shower wand #HS-01207, 5 foot flexible metal hose with inline vacuum breaker and wall connection
- Symmons Safetymix® Visu-Temp® pressure-balancing mixing valve with adjustable stop screw to limit handle turn, #4-5000VT.
- Standard flow rate 2.5 gpm (9.5 L/min)
Optional lower flow rate restrictors available
- Polished chrome finish (standard)

Model Numbers

- ☐ 1-250VT-T24-V
THand Shower System with Symmons Safetymix® Visu-Temp® mixing valve, #4-5000VT and 24 inch Grab / Slide Bar
- ☐ 1-250VT-T24-V-TRM
Trim only, valves are not included

Finish Options / Modifications

Append appropriate -suffix to model number

- ☐ -STN Satin nickel
- Polished chrome (standard finish)

Standards / Certifications

ASME A112.18.1/CSA B125.1

ADAAG Grab Bar assembly complies with applicable requirements for ADA Accessibility Guidelines (ADAAG) as amended through 2002.



Options / Modifications

Append appropriate -suffix to model number

- ☐ -X Integral Service Stops included with Temptrol® valve to allow water shut-off for service
- ☐ -IPS 1/2 inch female IPS connections on Temptrol® mixing valve
- ☐ -REV Reverse coring in valve for back to back installations; hot on right, cold on left
(only available with -X integral service stops)
- ☐ -CHKS Integral check stops - for use where a positive shut-off device is used downstream of valve
(only available with -X integral service stops)
- ☐ -3/4 3/4 inch valve to increase water flow approximately 20 percent
(only available with -X integral service stops)
- ☐ -2.0 2.0 gpm (7.6 L/min) flow rate restrictor
- ☐ -1.5 1.5 gpm (5.7 L/min) flow rate restrictor
- ☐ -72 6 foot flexible metal hose in place of standard 5 foot hose
- ☐ -R60 5 foot white vinyl hose in place of flexible metal hose
- ☐ -R72 6 foot white vinyl hose in place of flexible metal hose
- ☐ -R84 7 foot white vinyl hose in place of flexible metal hose
- ☐ -T36 36 inch grab/slide bar in place of standard 24 inch length
- ☐ -QD Quick-disconnect on hand shower
- ☐ -VB Elevated vacuum breaker with wall flange on hand shower unit in place of standard in-line vacuum breaker

Warranty

- Limited Lifetime - to the original end purchaser in consumer installations
- 5 years - for commercial installations

Dimensions *Visu-Temp Hand Shower System, 1-250VT-T24*

Male 1/2" I.P.S. thread must protrude 3/8" (10mm) from finished wall for proper installation of street ell and flange.

