

# Rajalakshmi Engineering College

Name: Darshan C.S

Email: 241801039@rajalakshmi.edu.in

Roll no:

Phone: 7358528466

Branch: REC

Department: I AI & DS FA

Batch: 2028

Degree: B.E - AI & DS

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 1\_COD\_Question 5

Attempt : 1

Total Mark : 10

Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Imagine you are tasked with developing a simple GPA management system using a singly linked list. The system allows users to input student GPA values, insertion should happen at the front of the linked list, delete record by position, and display the updated list of student GPAs.

##### ***Input Format***

The first line of input contains an integer  $n$ , representing the number of students.

The next  $n$  lines contain a single floating-point value representing the GPA of each student.

The last line contains an integer position, indicating the position at which a student record should be deleted. Position starts from 1.

### ***Output Format***

After deleting the data in the given position, display the output in the format "GPA: " followed by the GPA value, rounded off to one decimal place.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 4

3.8

3.2

3.5

4.1

2

Output: GPA: 4.1

GPA: 3.2

GPA: 3.8

### ***Answer***

```
// You are using GCC
```

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node{
```

```
    float data;
```

```
    struct Node* next;
```

```
};
```

```
struct Node* insert(struct Node* head, float value){
```

```
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
```

```
    newNode->data=value;
```

```
    newNode->next=head;
```

```
    head=newNode;
```

```
    return head;
```

```
}
```

```
struct Node* del(struct Node* head,int pos){
```

```
    if(head==NULL){
```

```
        return NULL;
```

```
}
```

```

struct Node* temp=head;
if(pos==1){
    head=head->next;
    free(temp);
    return head;
}
struct Node* prev=NULL;
int i=1;
while(i!=pos && temp!=NULL){
    prev=temp;
    temp=temp->next;
    i++;
}
if(temp==NULL){
    return head;
}
prev->next=temp->next;
free(temp);
return head;
}

void printList(struct Node* head){
    struct Node* temp=head;
    while(temp!=NULL){
        printf("GPA: %.1f\n",(float)temp->data);
        temp=temp->next;
    }
}

void freeList(struct Node* head){
    struct Node* temp;
    while(head!=NULL){
        temp=head;
        head=head->next;
        free(temp);
    }
}

int main(){
    float n;
    scanf("%f",&n);
    struct Node* head=NULL;
    for(int i=0;i<n;i++){
        float value;

```

```
        scanf("%f",&value);
        head=insert(head,value);
    }
    float t;
    scanf("%f",&t);
    head=del(head,t);
    printList(head);
    freeList(head);
    return 0;
}
```

**Status :** Correct

**Marks :** 10/10