

# Rajalakshmi Engineering College

Name: Darshan C.S

Email: 241801039@rajalakshmi.edu.in

Roll no:

Phone: 7358528466

Branch: REC

Department: I AI & DS FA

Batch: 2028

Degree: B.E - AI & DS

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 4\_COD\_Question 3

Attempt : 1

Total Mark : 10

Marks Obtained : 10

### Section 1 : Coding

#### 1. Problem Statement

Write a program to implement a queue using an array and pointers. The program should provide the following functionalities:

Insert an element into the queue.Delete an element from the queue.Display the elements in the queue.

The queue has a maximum capacity of 5 elements. If the queue is full and an insertion is attempted, a "Queue is full" message should be displayed. If the queue is empty and a deletion is attempted, a "Queue is empty" message should be displayed.

#### *Input Format*

Each line contains an integer representing the chosen option from 1 to 3.

Option 1: Insert an element into the queue followed by an integer representing the element to be inserted, separated by a space.

Option 2: Delete an element from the queue.

Option 3: Display the elements in the queue.

### ***Output Format***

For option 1 (insertion):-

1. The program outputs: "<data> is inserted in the queue." if the data is successfully inserted.
2. "Queue is full." if the queue is already full and cannot accept more elements.

For option 2 (deletion):-

1. The program outputs: "Deleted number is: <data>" if an element is successfully deleted and returns the value of the deleted element.
2. "Queue is empty." if the queue is empty no elements can be deleted.

For option 3 (display):-

1. The program outputs: "Elements in the queue are: <element1> <element2> ... <elementN>" where <element1>, <element2>, ..., <elementN> represent the elements present in the queue.
2. "Queue is empty." if the queue is empty no elements can be displayed.

For invalid options, the program outputs: "Invalid option."

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 1 10

3  
5

Output: 10 is inserted in the queue.  
Elements in the queue are: 10  
Invalid option.

### ***Answer***

```
#include <stdio.h>
#include <stdlib.h>

#define max 5

int queue[max];
int front = -1, rear = -1;

int insertq(int *data) {
    if ((rear + 1) % max == front) {
        return 0; // Queue is full
    }

    if (front == -1) {
        front = rear = 0;
    } else {
        rear = (rear + 1) % max;
    }

    queue[rear] = *data;

    return 1;
}

int delq() {
    if (front == -1) {
        printf("Queue is empty.\n");
        return -1;
    }

    int data = queue[front];
    if (front == rear) {
        front = rear = -1;
    } else {
        front = (front + 1) % max;
    }
}
```

```

    }

    printf("Deleted number is: %d\n", data);
    return data;
}

void display() {
    if (front == -1) {
        printf("Queue is empty.\n");
        return;
    }

    printf("Elements in the queue are:");
    int i = front;
    while (1) {
        printf(" %d", queue[i]);
        if (i == rear) break;
        i = (i + 1) % max;
    }
    printf("\n");
}

int main()
{
    int data, reply, option;
    while (1)
    {
        if (scanf("%d", &option) != 1)
            break;
        switch (option)
        {
            case 1:
                if (scanf("%d", &data) != 1)
                    break;
                reply = insertq(&data);
                if (reply == 0)
                    printf("Queue is full.\n");
                else
                    printf("%d is inserted in the queue.\n", data);
                break;
            case 2:
                delq(); // Called without arguments
                break;
        }
    }
}

```

```
        case 3:
            display();
            break;
        default:
            printf("Invalid option.\n");
            break;
    }
}
return 0;
}
```

**Status :** Correct

**Marks :** 10/10