HDOC- 1 *NAME : DARSHIL RAJ*

DATE : 20/8/26 *SAP ID: 590040196*

Program to Input Two Numbers and Display Their Sum

This document provides clean, well-commented implementations for entering two numbers and computing their sum across major programming languages (C, C++, Python, and Java). Each program includes interactive user input, logic handling, and formatted output display.

1. C Implementation

```c
#include <stdio.h>

int main() {
    float num1, num2, sum;

    // Prompt user for input
    printf("Enter first number: ");
    scanf("%f", &num1);

    printf("Enter second number: ");
    scanf("%f", &num2);

    // Calculate sum
    sum = num1 + num2;

    // Display result
    printf("The sum of %.2f and %.2f is: %.2f\n", num1, num2, sum);

    return 0;
}
```

. Sample Execution / OutputSteps to Write, Compile, and Run in Linux Terminal

1. **Open the Terminal Press Ctrl + Alt + T to open your terminal.**
2. **Create and Open the Source File Use a terminal text editor like nano or vim to create a new file named sum.c:**

Bash

nano sum.c

3. **Write the Code Copy or type the C program above into the editor window. Save and exit (in nano, press Ctrl + O then Enter to save, and Ctrl + X to exit).**

4. **Compile the Program Use the gcc compiler to compile your program into an executable:**

Bash

gcc sum.c -o sum

If there are syntax errors, the terminal will display them here so you can fix them.

5. **Run the Executable Execute the compiled program:**

Bash

./sum

6. **Test the Output Type two numbers separated by a space (for example: 15 25) and press Enter. The program will display Sum: 20.**

```c
#include <stdio.h>

int main() {
    int num1, num2, sum;

    // Ask user for input
    printf("Enter two integers: ");
    scanf("%d %d", &num1, &num2);

    // Calculate sum
    sum = num1 + num2;

    // Display result
    printf("Sum: %d\n", sum);

    return 0;
}
```

```
Enter first number: 12.5
Enter second number: 7.5
The sum is: 20.0
```