

## NDTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.
- 2. D AND E DO NOT INCLUDE MOLD FLASH.
- 3. MOLD FLASH OR PROTRUSION SHALL NOT EXCEED 0.15mm (.006").
- 4. MEETS JEDEC TO253.



THESE DIMENSIONS APPLY TO THE FLAT SECTION OF THE LEAD BETWEEN 0.08mm AND 0.15mm FROM THE LEAD TIP.

- 6. MATERIAL MUST COMPLY WITH BANNED AND RESTRICTED SUBSTANCES SPEC # 10-0131.
- 7. ALL DIMENSIONS APPLY TO BOTH LEADED (-) AND LEAD FREE (+) PACKAGE CODES.
- 8. PKG CDDES: U4+1, U4+1A, U4+2, U4+1C

	INCHES			MILLIMETERS		
DIM	MIN	NDM	MAX	MIN	NDM	MAX
Α	0.031	0.0394	0.048	0.80	1.000	1.22
A1	0.000	0.0022	0.006	0.01	0.056	0.15
b	0.014	0.0157	0.020	0.35	0.400	0.50
b1	0.012	-	0.018	0.30	1	0.45
b2	0.030	0.0323	0.035	0.76	0.820	0.89
b3	0.012	1	0.033	0.76	1	0.84
С	0.003	0.0051	0.008	0.08	0.130	0.20
⊂1	0.003	-	0.006	0.08	1	0.16
D	0.110	0.1150	0.120	2.80	2.920	3.04
Ε	0.083	0.0933	0.104	2.10	2.370	2.64
E1	0.047	0.0512	0.055	1.20	1.300	1.40
е	0.076 BSC.			1.92 BSC.		
e1	0'008 B2C'			0.20 BSC.		
L	0.016	_	0.024	0.40	1	0.60
L1	0.021 REF.			0.54 REF.		
S	0.018	0.0207	0.024	0.45	0.525	0.60
α	0°	2*	8*	0°	2◆	8*



TITLE:
PACKAGE DUTLINE,
4L SDT23

APPROVAL
RDHINI KESAVAN

DOCUMENT CONTROL NO. 21-0052