

# Package ‘PhenotypeLibraryDiagnostics’

July 7, 2022

**Type** Package

**Title** Generating Cohort Diagnostics for the OHDSI Phenotype Library

**Version** 3.1.1

**Date** 2022-07-07

**Author** Gowtham Rao [aut, cre]

**Maintainer** Gowtham Rao <rao@ohdsi.org>

**Description** Generating cohort diagnostics for the cohort definitions in the OHDSI Phenotype Library.

**Depends** DatabaseConnector (>= 5.0.0)

**Imports** CohortDiagnostics (>= 3.0.2),  
CohortGenerator (>= 0.5.0),  
OhdsiSharing,  
ParallelLogger,  
PhenotypeLibrary (>= 3.1.1)

**Remotes** ohdsi/PhenotypeLibrary,  
ohdsi/CohortGenerator,  
ohdsi/CohortDiagnostics

**License** Apache License 2.0

**LazyData** TRUE

**RoxygenNote** 7.2.0

## R topics documented:

executePhenotypeLibraryDiagnostics . . . . .	1
uploadResults . . . . .	3
<b>Index</b>	<b>4</b>

---

executePhenotypeLibraryDiagnostics  
*Execute the cohort diagnostics*

---

## Description

Execute the cohort diagnostics

**Usage**

```
executePhenotypeLibraryDiagnostics(
  connectionDetails,
  cdmDatabaseSchema,
  vocabularyDatabaseSchema = cdmDatabaseSchema,
  cohortDatabaseSchema = cdmDatabaseSchema,
  cohortTable = "cohort",
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  verifyDependencies = TRUE,
  outputFolder,
  incrementalFolder = file.path(outputFolder, "incrementalFolder"),
  databaseId = "Unknown",
  databaseName = databaseId,
  databaseDescription = databaseId
)
```

**Arguments**

connectionDetails	An object of type connectionDetails as created using the <a href="#">createConnectionDetails</a> function in the DatabaseConnector package.
cdmDatabaseSchema	Schema name where your patient-level data in OMOP CDM format resides. Note that for SQL Server, this should include both the database and schema name, for example 'cdm_data.dbo'.
vocabularyDatabaseSchema	Schema name where your OMOP vocabulary data resides. This is commonly the same as cdmDatabaseSchema. Note that for SQL Server, this should include both the database and schema name, for example 'vocabulary.dbo'.
cohortDatabaseSchema	Schema name where intermediate data can be stored. You will need to have write privileges in this schema. Note that for SQL Server, this should include both the database and schema name, for example 'cdm_data.dbo'.
cohortTable	The name of the table that will be created in the work database schema. This table will hold the exposure and outcome cohorts used in this study.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
verifyDependencies	Check whether correct package versions are installed?
outputFolder	Name of local folder to place results; make sure to use forward slashes (/). Do not use a folder on a network drive since this greatly impacts performance.
incrementalFolder	Name of local folder to hold the logs for incremental run; make sure to use forward slashes (/). Do not use a folder on a network drive since this greatly impacts performance.
databaseId	A short string for identifying the database (e.g. 'Synpuf').
databaseName	The full name of the database (e.g. 'Medicare Claims Synthetic Public Use Files (SynPUFs)').

databaseDescription

A short description (several sentences) of the database.

### Details

This function executes the cohort diagnostics.

---

uploadResults	<i>Upload results to OHDSI server</i>
---------------	---------------------------------------

---

### Description

Upload results to OHDSI server

### Usage

```
uploadResults(outputFolder, privateKeyFileName, userName)
```

### Arguments

outputFolder	Name of local folder where the results were generated; make sure to use forward slashes (/).
privateKeyFileName	A character string denoting the path to the RSA private key provided by the study coordinator.
userName	A character string containing the user name provided by the study coordinator.

### Details

This function uploads the 'AllResults\_<databaseId>.zip' to the OHDSI SFTP server. Before sending, you can inspect the zip file, which contains (zipped) CSV files. You can send the zip file from a different computer than the one on which it was created.

# Index

`createConnectionDetails`, [2](#)

`executePhenotypeLibraryDiagnostics`, [1](#)

`uploadResults`, [3](#)