

Package ‘TreatmentPatterns’

January 26, 2024

Type Package

Title Analyzes Real-World Treatment Patterns of a Study Population of Interest

Version 2.6.4

Maintainer Maarten van Kessel <m.l.vankessel@erasmusmc.nl>

Description Computes treatment patterns within a given cohort using the Observational Medical Outcomes Partnership (OMOP) common data model (CDM). As described in Markus, Verhamme, Kors, and Rijnbeek (2022) <[doi:10.1016/j.cmpb.2022.107081](https://doi.org/10.1016/j.cmpb.2022.107081)>.

URL <https://github.com/darwin-eu-dev/TreatmentPatterns>

BugReports <https://github.com/darwin-eu-dev/TreatmentPatterns/issues>

Language en-US

Depends R (>= 4.2)

Imports checkmate,
dplyr,
stringr,
stringi,
utils,
rjson,
googleVis,
stats,
Andromeda,
tidyr,
R6,
sunburstR,
networkD3,
htmlwidgets,
shiny,
shinydashboard

Suggests knitr,
rmarkdown,
tibble,
testthat (>= 3.0.0),
usethis,
Eunomia,
CDMConnector,
DatabaseConnector (>= 6.0.0),
SqlRender,

CohortGenerator,
webshot2,
CirceR,
duckdb,
DBI,
withr,
plotly,
ggplot2,
Capr

License Apache License 2.0

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

VignetteBuilder knitr

Config/testthat/edition 3

Config/testthat/parallel true

Additional_repositories <https://ohdsi.github.io/drat>

Roxygen list(markdown = TRUE)

R topics documented:

CharacterizationPlots	2
computePathways	4
createSankeyDiagram	6
createSankeyDiagram2	7
createSunburstPlot	8
createSunburstPlot2	9
executeTreatmentPatterns	10
export	12
InputHandler	14
InteractivePlots	16
launchResultsExplorer	17
Module	17
Index	19

CharacterizationPlots	<i>CharacterizationPlots</i>
-----------------------	------------------------------

Description

Class to handle the characterization plots.

Super class

`TreatmentPatterns::Module` -> CharacterizationPlots

Methods

Public methods:

- [CharacterizationPlots\\$uiMenu\(\)](#)
- [CharacterizationPlots\\$uiBody\(\)](#)
- [CharacterizationPlots\\$server\(\)](#)
- [CharacterizationPlots\\$clone\(\)](#)

Method [uiMenu\(\)](#): Method to include a [menuItem](#) to link to the body.

Usage:

```
CharacterizationPlots$uiMenu(  
  label = "Characteristics",  
  tag = "characteristics"  
)
```

Arguments:

label (character(1))
Label to show for the menuItem.
tag (character(1))
Tag to use internally in input.

Returns: (menuItem)

Method [uiBody\(\)](#): Method to include a [tabItem](#) to include the body.

Usage:

```
CharacterizationPlots$uiBody()
```

Returns: (tabItem)

Method [server\(\)](#): Method to handle the back-end.

Usage:

```
CharacterizationPlots$server(input, output, session, inputHandler)
```

Arguments:

input (input)
Input from the server function.
output (output)
Output from the server function.
session (session)
Session from the server function.
inputHandler (inputHandler)
[InputHandler](#) class.

Returns: (NULL)

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
CharacterizationPlots$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

computePathways	<i>computePathways</i>
-----------------	------------------------

Description

Compute treatment patterns according to the specified parameters within specified cohorts.

Usage

```
computePathways(
  cohorts,
  cohortTableName,
  cdm = NULL,
  connectionDetails = NULL,
  cdmSchema = NULL,
  resultSchema = NULL,
  tempEmulationSchema = NULL,
  includeTreatments = "startDate",
  periodPriorToIndex = 0,
  minEraDuration = 0,
  splitEventCohorts = NULL,
  splitTime = NULL,
  eraCollapseSize = 30,
  combinationWindow = 30,
  minPostCombinationDuration = 30,
  filterTreatments = "First",
  maxPathLength = 5
)
```

Arguments

cohorts	(data.frame()) Data frame containing the following columns and data types: cohortId numeric(1) Cohort ID's of the cohorts to be used in the cohort table. cohortName character(1) Cohort names of the cohorts to be used in the cohort table. type character(1) [" target ", " event ", " exit "] Cohort type, describing if the cohort is a target, event, or exit cohort
cohortTableName	(character(1)) Cohort table name.
cdm	(CDMConnector::cdm_from_con(): NULL) Optional; Ignores connectionDetails, cdmSchema, and resultSchema.
connectionDetails	(DatabaseConnector::createConnectionDetails(): NULL) Optional; In congruence with cdmSchema and resultSchema. Ignores cdm.
cdmSchema	(character(1): NULL) Optional; In congruence with connectionDetails and resultSchema. Ignores cdm.

resultSchema (character(1): NULL)
 Optional; In congruence with connectionDetails and cdmSchema. Ignores cdm.

tempEmulationSchema
 Schema used to emulate temp tables

includeTreatments
 (character(1): "startDate")

 "startDate" Include treatments after the target cohort start date and onwards.
 "endDate" Include treatments before target cohort end date and before.

periodPriorToIndex
 (integer(1): 0)
 Number of days prior to the index date of the target cohort | that event cohorts are allowed to start

minEraDuration (integer(1): 0)
 Minimum time an event era should last to be included in analysis

splitEventCohorts
 (character(n): "")
 Specify event cohort to split in acute (< X days) and therapy (>= X days)

splitTime (integer(1): 30)
 Specify number of days (X) at which each of the split event cohorts should be split in acute and therapy

eraCollapseSize
 (integer(1): 30)
 Window of time between which two eras of the same event cohort are collapsed into one era

combinationWindow
 (integer(1): 30)
 Window of time two event cohorts need to overlap to be considered a combination treatment

minPostCombinationDuration
 (integer(1): 30)
 Minimum time an event era before or after a generated combination treatment should last to be included in analysis

filterTreatments
 (character(1): "First" ["first", "Changes", "all"])
 Select first occurrence of ('First'); changes between ('Changes'); or all event cohorts ('All').

maxPathLength (integer(1): 5)
 Maximum number of steps included in treatment pathway

Value

(Andromeda::andromeda()) [andromeda](#) object containing non-sharable patient level data outcomes.

Examples

```
library(TreatmentPatterns)
library(CDMConnector)
library(dplyr)
```

```

if (require("CirceR", character.only = TRUE, quietly = TRUE)) {
  withr::local_envvar(
    EUNOMIA_DATA_FOLDER = Sys.getenv("EUNOMIA_DATA_FOLDER", unset = tempfile())
  )

  downloadEunomiaData(overwrite = TRUE)

  con <- DBI::dbConnect(duckdb::duckdb(), dbdir = eunomia_dir())
  cdm <- cdmFromCon(con, cdmSchema = "main", writeSchema = "main")

  cohortSet <- readCohortSet(
    path = system.file(package = "TreatmentPatterns", "exampleCohorts")
  )

  cdm <- generateCohortSet(
    cdm = cdm,
    cohortSet = cohortSet,
    name = "cohort_table"
  )

  cohorts <- cohortSet %>%
    # Remove 'cohort' and 'json' columns
    select(-"cohort", -"json") %>%
    mutate(type = c("event", "event", "event", "event", "exit", "event", "event", "target")) %>%
    rename(
      cohortId = "cohort_definition_id",
      cohortName = "cohort_name",
    ) %>%
    select("cohortId", "cohortName", "type")

  outputEnv <- computePathways(
    cohorts = cohorts,
    cohortTableName = "cohort_table",
    cdm = cdm
  )

  Andromeda::close(outputEnv)
  DBI::dbDisconnect(con, shutdown = TRUE)
}

```

createSankeyDiagram *createSankeyDiagram*

Description

Create sankey diagram.

Usage

```

createSankeyDiagram(
  treatmentPathways,
  groupCombinations = FALSE,
  colors = NULL,

```

```
    ...  
  )
```

Arguments

```
treatmentPathways  
    (data.frame())  
    The contents of the treatmentPathways.csv-file as a data.frame().  
groupCombinations  
    (logical(1): FALSE)  
  
    TRUE Group all combination treatments in category "Combination".  
    FALSE Do not group combination treatments.  
colors  
    (character(n)) Vector of hex color codes.  
...  
    Paramaters for sankeyNetwork.
```

Value

```
(htmlwidget)
```

Examples

```
# Dummy data, typically read from treatmentPathways.csv  
treatmentPathways <- data.frame(  
  path = c("Acetaminophen", "Acetaminophen-Amoxicillin+Clavulanate",  
           "Acetaminophen-Aspirin", "Amoxicillin+Clavulanate", "Aspirin"),  
  freq = c(206, 6, 14, 48, 221),  
  sex = rep("all", 5),  
  age = rep("all", 5),  
  index_year = rep("all", 5)  
)  
  
createSankeyDiagram(treatmentPathways)
```

```
createSankeyDiagram2  createSankeyDiagram2
```

Description

DEPRECATED Create sankey diagram.

Usage

```
createSankeyDiagram2(  
  treatmentPathways,  
  groupCombinations = FALSE,  
  colors = NULL,  
  ...  
)
```

Arguments

treatmentPathways
 (data.frame())
 The contents of the treatmentPathways.csv-file as a data.frame().
groupCombinations
 (logical(1): FALSE)
 TRUE Group all combination treatments in category "Combination".
 FALSE Do not group combination treatments.
colors
 (character(n)) Vector of hex color codes.
 ... Paramaters for [sankeyNetwork](#).

Value

(htmlwidget)

Examples

```

# Dummy data, typically read from treatmentPathways.csv
treatmentPathways <- data.frame(
  path = c("Acetaminophen", "Acetaminophen-Amoxicillin+Clavulanate",
           "Acetaminophen-Aspirin", "Amoxicillin+Clavulanate", "Aspirin"),
  freq = c(206, 6, 14, 48, 221),
  sex = rep("all", 5),
  age = rep("all", 5),
  index_year = rep("all", 5)
)

createSankeyDiagram(treatmentPathways)

```

createSunburstPlot *createSunburstPlot*

Description

New sunburstPlot function

Usage

```
createSunburstPlot(treatmentPathways, groupCombinations = FALSE, ...)
```

Arguments

treatmentPathways
 (data.frame())
 The contents of the treatmentPathways.csv-file as a data.frame().
groupCombinations
 (logical(1): FALSE)
 TRUE Group all combination treatments in category "Combination".
 FALSE Do not group combination treatments.
 ... Paramaters for [sunburst](#).

Value

(htmlwidget)

Examples

```
# Dummy data, typically read from treatmentPathways.csv
treatmentPatwhays <- data.frame(
  path = c("Acetaminophen", "Acetaminophen-Amoxicillin+Clavulanate",
           "Acetaminophen-Aspirin", "Amoxicillin+Clavulanate", "Aspirin"),
  freq = c(206, 6, 14, 48, 221),
  sex = rep("all", 5),
  age = rep("all", 5),
  index_year = rep("all", 5)
)

createSunburstPlot(treatmentPatwhays)
```

createSunburstPlot2 *createSunburstPlot2*

Description

DEPRECATED New sunburstPlot function

Usage

```
createSunburstPlot2(treatmentPathways, groupCombinations = FALSE, ...)
```

Arguments

```
treatmentPathways
  (data.frame())
  The contents of the treatmentPathways.csv-file as a data.frame().

groupCombinations
  (logical(1): FALSE)

  TRUE Group all combination treatments in category "Combination".
  FALSE Do not group combination treatments.

...
  Paramaters for sunburst.
```

Value

(htmlwidget)

Examples

```
# Dummy data, typically read from treatmentPathways.csv
treatmentPatwhays <- data.frame(
  path = c("Acetaminophen", "Acetaminophen-Amoxicillin+Clavulanate",
           "Acetaminophen-Aspirin", "Amoxicillin+Clavulanate", "Aspirin"),
  freq = c(206, 6, 14, 48, 221),
  sex = rep("all", 5),
```

```

    age = rep("all", 5),
    index_year = rep("all", 5)
  )

  createSunburstPlot2(treatmentPatwhays)

```

```
executeTreatmentPatterns
```

```
executeTreatmentPatterns
```

Description

Compute treatment patterns according to the specified parameters within specified cohorts. For more customization, or investigation of patient level outcomes, you can run [computePathways](#) and [export](#) separately.

Usage

```

executeTreatmentPatterns(
  cohorts,
  cohortTableName,
  outputPath,
  cdm = NULL,
  connectionDetails = NULL,
  cdmSchema = NULL,
  resultSchema = NULL,
  tempEmulationSchema = NULL,
  minEraDuration = 0,
  eraCollapseSize = 30,
  combinationWindow = 30,
  minCellCount = 5
)

```

Arguments

cohorts	(data.frame()) Data frame containing the following columns and data types: cohortId numeric(1) Cohort ID's of the cohorts to be used in the cohort table. cohortName character(1) Cohort names of the cohorts to be used in the cohort table. type character(1) [" target ", " event ", " exit "] Cohort type, describing if the cohort is a target, event, or exit cohort
cohortTableName	(character(1)) Cohort table name.
outputPath	(character(1))
cdm	(CDMConnector::cdm_from_con(): NULL) Optional; Ignores connectionDetails, cdmSchema, and resultSchema.

connectionDetails	(DatabaseConnector::createConnectionDetails(): NULL) Optional; In congruence with cdmSchema and resultSchema. Ignores cdm.
cdmSchema	(character(1): NULL) Optional; In congruence with connectionDetails and resultSchema. Ignores cdm.
resultSchema	(character(1): NULL) Optional; In congruence with connectionDetails and cdmSchema. Ignores cdm.
tempEmulationSchema	(character(1)) Schema to emulate temp tables.
minEraDuration	(integer(1): 0) Minimum time an event era should last to be included in analysis
eraCollapseSize	(integer(1): 30) Window of time between which two eras of the same event cohort are collapsed into one era
combinationWindow	(integer(1): 30) Window of time two event cohorts need to overlap to be considered a combination treatment
minCellCount	(integer(1): 5) Minimum count required per pathway. Censors data below x as <x. This minimum value will carry over to the sankey diagram and sunburst plot.

Value

(invisible(NULL))

Examples

```
library(TreatmentPatterns)
library(CDMConnector)
library(dplyr)
if (require("CirceR", character.only = TRUE, quietly = TRUE)) {
  withr::local_envvar(
    EUNOMIA_DATA_FOLDER = Sys.getenv("EUNOMIA_DATA_FOLDER", unset = tempfile())
  )

  downloadEunomiaData(overwrite = TRUE)

  con <- DBI::dbConnect(duckdb::duckdb(), dbdir = eunomia_dir())
  cdm <- cdmFromCon(con, cdmSchema = "main", writeSchema = "main")

  cohortSet <- readCohortSet(
    path = system.file(package = "TreatmentPatterns", "exampleCohorts")
  )

  cdm <- generateCohortSet(
    cdm = cdm,
    cohortSet = cohortSet,
    name = "cohort_table"
  )
}
```

```

cohorts <- cohortSet %>%
  # Remove 'cohort' and 'json' columns
  select(-"cohort", -"json") %>%
  mutate(type = c("event", "event", "event", "event", "exit", "event", "event", "target")) %>%
  rename(
    cohortId = "cohort_definition_id",
    cohortName = "cohort_name",
  ) %>%
  select("cohortId", "cohortName", "type")

executeTreatmentPatterns(
  cohorts = cohorts,
  cohortTableName = "cohort_table",
  cdm = cdm,
  outputPath = tempdir()
)

DBI::dbDisconnect(con, shutdown = TRUE)
}

```

export

export

Description

Export andromeda generated by [computePathways](#) object to sharable csv-files and/or a zip archive.

Usage

```

export(
  andromeda,
  outputPath,
  ageWindow = 10,
  minCellCount = 5,
  censorType = "minCellCount",
  archiveName = NULL
)

```

Arguments

andromeda	(Andromeda::andromeda()) Andromeda object.
outputPath	(character(1))
ageWindow	(integer(n): 10) Number of years to bin age groups into. It may also be a vector of integers. I.e. <code>c(0, 18, 150)</code> which will results in age group 0-18 which includes subjects < 19. And age group 18-150 which includes subjects > 18.
minCellCount	(integer(1): 5) Minimum count required per pathway. Censors data below x as <x. This minimum value will carry over to the sankey diagram and sunburst plot.

```

  censorType      (character(1))

                    "minCellCount" Censors pathways <minCellCount to minCellCount.
                    "remove" Censors pathways <minCellCount by removing them completely.
                    "mean" Censors pathways <minCellCount to the mean of all frequencies below
                        minCellCount
  archiveName     (character(1): NULL)
                    If not NULL adds the exported files to a ZIP-file with the specified archive name.

```

Value

```
(invisible(NULL))
```

Examples

```

library(TreatmentPatterns)
library(CDMConnector)
library(dplyr)

if (require("CirceR", character.only = TRUE, quietly = TRUE)) {
  withr::local_envvar(
    EUNOMIA_DATA_FOLDER = Sys.getenv("EUNOMIA_DATA_FOLDER", unset = tempfile())
  )

  downloadEunomiaData(overwrite = TRUE)

  con <- DBI::dbConnect(duckdb::duckdb(), dbdir = eunomia_dir())
  cdm <- cdmFromCon(con, cdmSchema = "main", writeSchema = "main")

  cohortSet <- readCohortSet(
    path = system.file(package = "TreatmentPatterns", "exampleCohorts")
  )

  cdm <- generateCohortSet(
    cdm = cdm,
    cohortSet = cohortSet,
    name = "cohort_table"
  )

  cohorts <- cohortSet %>%
    # Remove 'cohort' and 'json' columns
    select(-"cohort", -"json") %>%
    mutate(type = c("event", "event", "event", "event", "exit", "event", "event", "target")) %>%
    rename(
      cohortId = "cohort_definition_id",
      cohortName = "cohort_name",
    ) %>%
    select("cohortId", "cohortName", "type")

  outputEnv <- computePathways(
    cohorts = cohorts,
    cohortTableName = "cohort_table",
    cdm = cdm
  )

```

```

export(
  andromeda = outputEnv,
  outputPath = tempdir()
)

Andromeda::close(outputEnv)
DBI::dbDisconnect(con, shutdown = TRUE)
}

```

InputHandler

InputHandler

Description

Class to handle input from the user. Supports direct paths or input fields through `setDataPath()`.

Super class

`TreatmentPatterns::Module` -> InputHandler

Active bindings

`reactiveValues` (`reactiveValues`)
`reactiveValues` class created by [reactiveValues](#).

Methods

Public methods:

- [InputHandler\\$uiMenu\(\)](#)
- [InputHandler\\$uiBody\(\)](#)
- [InputHandler\\$server\(\)](#)
- [InputHandler\\$uiDatabaseSelector\(\)](#)
- [InputHandler\\$setDataPath\(\)](#)
- [InputHandler\\$clone\(\)](#)

Method `uiMenu()`: Method to include a [menuItem](#) to link to the body.

Usage:

```
InputHandler$uiMenu(label = "File upload", tag = "fileUpload")
```

Arguments:

`label` (`character(1)`)

Label to show for the menuItem.

`tag` (`character(1)`)

Tag to use internally in input.

Returns: (`menuItem`)

Method `uiBody()`: Method to include a [tabItem](#) to include the body.

Usage:

InputHandler\$uiBody()

Returns: (tabItem)

Method server(): Method to handle the back-end.

Usage:

InputHandler\$server(input, output, session)

Arguments:

input (input)

Input from the server function.

output (output)

Output from the server function.

session (session)

Session from the server function.

Returns: (NULL)

Method uiDatabaseSelector(): Method to include a [uiOutput](#) to select between multiple uploaded files.

Usage:

InputHandler\$uiDatabaseSelector()

Returns: (uiOutput)

Method setDataPath(): Method to dictate where the data is coming from, either from the input through the shiny application, or from a specified path. When one is provided, the other is ignored.

Usage:

InputHandler\$setDataPath(tag = "uploadField", input = NULL, path = NULL)

Arguments:

tag (character(1))

Tag to use internally in input.

input (input)

Input from the server function of the shiny app.

path (character(1))

Path to a zip-file containing TreatmentPatterns output files.

Returns: (invisible(self))

Method clone(): The objects of this class are cloneable with this method.

Usage:

InputHandler\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

InteractivePlots	<i>InteractivePlots</i>
------------------	-------------------------

Description

Class to handle the interactive plots of TreatmentPatterns (Sunburst plot & Sankey diagram)

Super class

`TreatmentPatterns::Module` -> InteractivePlots

Methods

Public methods:

- `InteractivePlots$uiMenu()`
- `InteractivePlots$uiBody()`
- `InteractivePlots$server()`
- `InteractivePlots$clone()`

Method `uiMenu()`: Method to include a [menuItem](#) to link to the body.

Usage:

```
InteractivePlots$uiMenu(label = "Plots", tag = "plots")
```

Arguments:

label (character(1))

Label to show for the menuItem.

tag (character(1))

Tag to use internally in input.

Returns: (menuItem)

Method `uiBody()`: Method to include a [tabItem](#) to include the body.

Usage:

```
InteractivePlots$uiBody()
```

Returns: (tabItem)

Method `server()`: Method to handle the back-end.

Usage:

```
InteractivePlots$server(input, output, session, inputHandler)
```

Arguments:

input (input)

Input from the server function.

output (output)

Output from the server function.

session (session)

Session from the server function.

inputHandler (inputHandler)

[InputHandler](#) class.

Returns: (NULL)

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
InteractivePlots$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

launchResultsExplorer *launchResultsExplorer*

Description

Launches the ResultExplorer shinyApp.

Usage

```
launchResultsExplorer()
```

Value

(shinyApp)

Examples

```
if (interactive()) {
  launchResultsExplorer()
}
```

Module	<i>Module</i>
--------	---------------

Description

Module super class

Active bindings

`namespace` Namespace of the module.

Methods

Public methods:

- `Module$new()`
- `Module$validate()`
- `Module$uiMenu()`
- `Module$uiBody()`
- `Module$server()`
- `Module$clone()`

Method `new()`: Initializer method

Usage:

Module\$new(namespace)

Arguments:

namespace (character(1))

Returns: (invisible(self))

Method validate(): Validator method

Usage:

Module\$validate()

Returns: (invisible(self))

Method uiMenu(): Method to include a [menuItem](#) to link to the body.

Usage:

Module\$uiMenu(label, tag)

Arguments:

label (character(1))

Label to show for the menuItem.

tag (character(1))

Tag to use internally in input.

Returns: (menuItem)

Method uiBody(): Method to include a [tabItem](#) to include the body.

Usage:

Module\$uiBody()

Returns: (tabItem)

Method server(): Method to handle the back-end.

Usage:

Module\$server(input, output, session)

Arguments:

input (input)

Input from the server function.

output (output)

Output from the server function.

session (session)

Session from the server function.

Returns: (NULL)

Method clone(): The objects of this class are cloneable with this method.

Usage:

Module\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Index

andromeda, [5](#)

CharacterizationPlots, [2](#)

computePathways, [4](#), [10](#), [12](#)

createSankeyDiagram, [6](#)

createSankeyDiagram2, [7](#)

createSunburstPlot, [8](#)

createSunburstPlot2, [9](#)

executeTreatmentPatterns, [10](#)

export, [10](#), [12](#)

InputHandler, [3](#), [14](#), [16](#)

InteractivePlots, [16](#)

launchResultsExplorer, [17](#)

menuItem, [3](#), [14](#), [16](#), [18](#)

Module, [17](#)

reactiveValues, [14](#)

sankeyNetwork, [7](#), [8](#)

sunburst, [8](#), [9](#)

tabItem, [3](#), [14](#), [16](#), [18](#)

TreatmentPatterns::Module, [2](#), [14](#), [16](#)

uiOutput, [15](#)