

Package ‘TreatmentPatterns’

February 3, 2025

Type Package

Title Analyzes Real-World Treatment Patterns of a Study Population of Interest

Version 3.0.0

Maintainer Maarten van Kessel <m.l.vankessel@erasmusmc.nl>

Description Computes treatment patterns within a given cohort using the Observational Medical Outcomes Partnership (OMOP) common data model (CDM). As described in Markus, Verhamme, Kors, and Rijnbeek (2022) <[doi:10.1016/j.cmpb.2022.107081](https://doi.org/10.1016/j.cmpb.2022.107081)>.

URL <https://github.com/darwin-eu/TreatmentPatterns>, <https://darwin-eu-dev.github.io/TreatmentPatterns/>

BugReports <https://github.com/darwin-eu/TreatmentPatterns/issues>

Language en-US

Depends R (>= 4.2)

Imports checkmate,

dplyr,
stringr,
utils,
stats,
Andromeda,
tidyr,
R6,
sunburstR,
networkD3,
htmlwidgets,
shiny,
shinydashboard,
ggplot2,
dbplyr,
jsonlite

Suggests knitr,
rmarkdown,
tibble,
testthat (>= 3.0.0),
usethis,
Eunomia,
CDMConnector,
DatabaseConnector (>= 6.0.0),

SqlRender,
 CohortGenerator,
 ResultModelManager,
 webshot2,
 CirceR,
 duckdb,
 DBI,
 withr,
 plotly,
 PaRe

License Apache License (≥ 2)

Encoding UTF-8

LazyData true

RoxygenNote 7.3.2

VignetteBuilder knitr

Config/testthat/edition 3

Config/testthat/parallel true

Additional_repositories <https://ohdsi.github.io/drat>

Roxygen list(markdown = TRUE)

Collate 'CDMInterface.R'
 'ShinyModule.R'
 'CharacterizationPlots.R'
 'InputHandler.R'
 'InteractivePlots.R'
 'SankeyDiagram.R'
 'ShinyApp.R'
 'SunburstPlot.R'
 'TreatmentPatterns-package.R'
 'TreatmentPatternsResults.R'
 'attrition.R'
 'computePathways.R'
 'constructPathways.R'
 'createSankeyDiagram.R'
 'createSunburstPlot.R'
 'executeTreatmentPatterns.R'
 'export.R'
 'getResultsDataModelSpecification.R'
 'plotEventDuration.R'

Contents

CharacterizationPlots	3
computePathways	4
createSankeyDiagram	7
createSunburstPlot	8
executeTreatmentPatterns	9
export	11
getResultsDataModelSpecifications	13

InputHandler	14
launchResultsExplorer	16
plotEventDuration	16
SankeyDiagram	18
ShinyModule	18
SunburstPlot	20
TreatmentPatternsResults	20
Index	25

CharacterizationPlots *CharacterizationPlots*

Description

Class to handle the characterization plots.

Super class

[TreatmentPatterns::ShinyModule](#) -> CharacterizationPlots

Methods

Public methods:

- [CharacterizationPlots\\$uiMenu\(\)](#)
- [CharacterizationPlots\\$uiBody\(\)](#)
- [CharacterizationPlots\\$server\(\)](#)
- [CharacterizationPlots\\$clone\(\)](#)

Method [uiMenu\(\)](#): Method to include a [menuItem](#) to link to the body.

Usage:

```
CharacterizationPlots$uiMenu(
  label = "Characteristics",
  tag = "characteristics"
)
```

Arguments:

```
label (character(1))
  Label to show for the menuItem.
tag (character(1))
  Tag to use internally in input.
```

Returns: (menuItem)

Method [uiBody\(\)](#): Method to include a [tabItem](#) to include the body.

Usage:

```
CharacterizationPlots$uiBody()
```

Returns: (tabItem)

Method [server\(\)](#): Method to handle the back-end.

Usage:

```
CharacterizationPlots$server(input, output, session, inputHandler)
```

Arguments:

input (input)

Input from the server function.

output (output)

Output from the server function.

session (session)

Session from the server function.

inputHandler (inputHandler)

[InputHandler](#) class.

Returns: (NULL)

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
CharacterizationPlots$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

computePathways

computePathways

Description

Compute treatment patterns according to the specified parameters within specified cohorts.

Usage

```
computePathways(
  cohorts,
  cohortTableName,
  cdm = NULL,
  connectionDetails = NULL,
  cdmSchema = NULL,
  resultSchema = NULL,
  analysisId = 1,
  description = "",
  tempEmulationSchema = NULL,
  includeTreatments = "startDate",
  indexDateOffset = 0,
  minEraDuration = 0,
  splitEventCohorts = NULL,
  splitTime = NULL,
  eraCollapseSize = 30,
  combinationWindow = 30,
  minPostCombinationDuration = 30,
  filterTreatments = "First",
  maxPathLength = 5
)
```

Arguments

cohorts	(data.frame()) Data frame containing the following columns and data types: cohortId numeric(1) Cohort ID's of the cohorts to be used in the cohort table. cohortName character(1) Cohort names of the cohorts to be used in the cohort table. type character(1) ["target", "event", "exit"] Cohort type, describing if the cohort is a target, event, or exit cohort
cohortTableName	(character(1)) Cohort table name.
cdm	(CDMConnector::cdm_from_con(): NULL) Optional; Ignores connectionDetails, cdmSchema, and resultSchema.
connectionDetails	(DatabaseConnector::createConnectionDetails(): NULL) Optional; In congruence with cdmSchema and resultSchema. Ignores cdm.
cdmSchema	(character(1): NULL) Optional; In congruence with connectionDetails and resultSchema. Ignores cdm.
resultSchema	(character(1): NULL) Optional; In congruence with connectionDetails and cdmSchema. Ignores cdm.
analysisId	(character(1)) Identifier for the TreatmentPatterns analysis.
description	(character(1)) Description of the analysis.
tempEmulationSchema	Schema used to emulate temp tables
includeTreatments	(character(1): "startDate") "startDate" Include treatments after the target cohort start date and onwards. "endDate" Include treatments before target cohort end date and before.
indexDateOffset	(integer(1): 0) Offset the index date of the Target cohort.
minEraDuration	(integer(1): 0) Minimum time an event era should last to be included in analysis
splitEventCohorts	(character(n): "") Specify event cohort to split in acute (< X days) and therapy (>= X days)
splitTime	(integer(1): 30) Specify number of days (X) at which each of the split event cohorts should be split in acute and therapy
eraCollapseSize	(integer(1): 30) Window of time between which two eras of the same event cohort are collapsed into one era

```

combinationWindow
    (integer(1): 30)
    Window of time two event cohorts need to overlap to be considered a combination treatment
minPostCombinationDuration
    (integer(1): 30)
    Minimum time an event era before or after a generated combination treatment should last to be included in analysis
filterTreatments
    (character(1): "First" ["first", "Changes", "all"])
    Select first occurrence of ('First'); changes between ('Changes'); or all event cohorts ('All').
maxPathLength
    (integer(1): 5)
    Maximum number of steps included in treatment pathway

```

Value

(Andromeda::andromeda()) [andromeda](#) object containing non-sharable patient level data outcomes.

Examples

```

ableToRun <- all(
  require("CirceR", character.only = TRUE, quietly = TRUE),
  require("CDMConnector", character.only = TRUE, quietly = TRUE),
  require("TreatmentPatterns", character.only = TRUE, quietly = TRUE),
  require("dplyr", character.only = TRUE, quietly = TRUE)
)

if (ableToRun) {
  library(TreatmentPatterns)
  library(CDMConnector)
  library(dplyr)

  withr::local_envvar(
    R_USER_CACHE_DIR = tempfile(),
    EUNOMIA_DATA_FOLDER = Sys.getenv("EUNOMIA_DATA_FOLDER", unset = tempfile())
  )

  tryCatch({
    if (Sys.getenv("skip_eunomia_download_test") != "TRUE") {
      CDMConnector::downloadEunomiaData(overwrite = TRUE)
    }
  }, error = function(e) NA)

  con <- DBI::dbConnect(duckdb::duckdb(), dbdir = eunomia_dir())
  cdm <- cdmFromCon(con, cdmSchema = "main", writeSchema = "main")

  cohortSet <- readCohortSet(
    path = system.file(package = "TreatmentPatterns", "exampleCohorts")
  )

  cdm <- generateCohortSet(
    cdm = cdm,
    cohortSet = cohortSet,
    name = "cohort_table"
  )
}

```

```

cohorts <- cohortSet %>%
  # Remove 'cohort' and 'json' columns
  select(-"cohort", -"json") %>%
  mutate(type = c("event", "event", "event", "event", "exit", "event", "event", "target")) %>%
  rename(
    cohortId = "cohort_definition_id",
    cohortName = "cohort_name",
  ) %>%
  select("cohortId", "cohortName", "type")

outputEnv <- computePathways(
  cohorts = cohorts,
  cohortTableName = "cohort_table",
  cdm = cdm
)

Andromeda::close(outputEnv)
DBI::dbDisconnect(con, shutdown = TRUE)
}

```

createSankeyDiagram	<i>createSankeyDiagram</i>
---------------------	----------------------------

Description

Create sankey diagram.

Usage

```

createSankeyDiagram(
  treatmentPathways,
  groupCombinations = FALSE,
  colors = NULL,
  ...
)

```

Arguments

treatmentPathways	(data.frame()) The contents of the treatmentPathways.csv-file as a data.frame().
groupCombinations	(logical(1): FALSE) TRUE Group all combination treatments in category "Combination". FALSE Do not group combination treatments.
colors	(character(n)) Vector of hex color codes.
...	Paramaters for sankeyNetwork .

Value

(htmlwidget)

Examples

```
# Dummy data, typically read from treatmentPathways.csv
treatmentPathways <- data.frame(
  pathway = c("Acetaminophen", "Acetaminophen-Amoxicillin+Clavulanate",
             "Acetaminophen-Aspirin", "Amoxicillin+Clavulanate", "Aspirin"),
  freq = c(206, 6, 14, 48, 221),
  sex = rep("all", 5),
  age = rep("all", 5),
  index_year = rep("all", 5)
)

createSankeyDiagram(treatmentPathways)
```

createSunburstPlot	<i>createSunburstPlot</i>
--------------------	---------------------------

Description

New sunburstPlot function

Usage

```
createSunburstPlot(treatmentPathways, groupCombinations = FALSE, ...)
```

Arguments

treatmentPathways	(data.frame()) The contents of the treatmentPathways.csv-file as a data.frame().
groupCombinations	(logical(1): FALSE) TRUE Group all combination treatments in category "Combination". FALSE Do not group combination treatments.
...	Paramaters for sunburst .

Value

(htmlwidget)

Examples

```
# Dummy data, typically read from treatmentPathways.csv
treatmentPatwhays <- data.frame(
  pathway = c("Acetaminophen", "Acetaminophen-Amoxicillin+Clavulanate",
             "Acetaminophen-Aspirin", "Amoxicillin+Clavulanate", "Aspirin"),
  freq = c(206, 6, 14, 48, 221),
  sex = rep("all", 5),
```



```

    age = rep("all", 5),
    index_year = rep("all", 5)
  )

  createSunburstPlot(treatmentPatwhays)

```

executeTreatmentPatterns

executeTreatmentPatterns

Description

Compute treatment patterns according to the specified parameters within specified cohorts. For more customization, or investigation of patient level outcomes, you can run [computePathways](#) and [export](#) separately.

Usage

```

executeTreatmentPatterns(
  cohorts,
  cohortTableName,
  cdm = NULL,
  connectionDetails = NULL,
  cdmSchema = NULL,
  resultSchema = NULL,
  tempEmulationSchema = NULL,
  minEraDuration = 0,
  eraCollapseSize = 30,
  combinationWindow = 30,
  minCellCount = 5
)

```

Arguments

cohorts	(data.frame()) Data frame containing the following columns and data types: cohortId numeric(1) Cohort ID's of the cohorts to be used in the cohort table. cohortName character(1) Cohort names of the cohorts to be used in the cohort table. type character(1) [" target ", " event ", " exit "] Cohort type, describing if the cohort is a target, event, or exit cohort
cohortTableName	(character(1)) Cohort table name.
cdm	(CDMConnector::cdm_from_con(): NULL) Optional; Ignores connectionDetails, cdmSchema, and resultSchema.
connectionDetails	(DatabaseConnector::createConnectionDetails(): NULL) Optional; In congruence with cdmSchema and resultSchema. Ignores cdm.

cdmSchema	(character(1): NULL) Optional; In congruence with connectionDetails and resultSchema. Ignores cdm.
resultSchema	(character(1): NULL) Optional; In congruence with connectionDetails and cdmSchema. Ignores cdm.
tempEmulationSchema	(character(1)) Schema to emulate temp tables.
minEraDuration	(integer(1): 0) Minimum time an event era should last to be included in analysis
eraCollapseSize	(integer(1): 30) Window of time between which two eras of the same event cohort are collapsed into one era
combinationWindow	(integer(1): 30) Window of time two event cohorts need to overlap to be considered a combination treatment
minCellCount	(integer(1): 5) Minimum count required per pathway. Censors data below x as <x. This minimum value will carry over to the sankey diagram and sunburst plot.

Value

TreatmentPatternsResults

Examples

```
ableToRun <- all(
  require("CirceR", character.only = TRUE, quietly = TRUE),
  require("CDMConnector", character.only = TRUE, quietly = TRUE),
  require("TreatmentPatterns", character.only = TRUE, quietly = TRUE),
  require("dplyr", character.only = TRUE, quietly = TRUE)
)

if (require("CirceR", character.only = TRUE, quietly = TRUE)) {
  library(TreatmentPatterns)
  library(CDMConnector)
  library(dplyr)

  withr::local_envvar(
    R_USER_CACHE_DIR = tempfile(),
    EUNOMIA_DATA_FOLDER = Sys.getenv("EUNOMIA_DATA_FOLDER", unset = tempfile())
  )

  tryCatch({
    if (Sys.getenv("skip_eunomia_download_test") != "TRUE") {
      CDMConnector::downloadEunomiaData(overwrite = TRUE)
    }
  },
  error = function(e) NA)

  con <- DBI::dbConnect(duckdb::duckdb(), dbdir = eunomia_dir())
  cdm <- cdmFromCon(con, cdmSchema = "main", writeSchema = "main")
}
```

```

cohortSet <- readCohortSet(
  path = system.file(package = "TreatmentPatterns", "exampleCohorts")
)

cdm <- generateCohortSet(
  cdm = cdm,
  cohortSet = cohortSet,
  name = "cohort_table"
)

cohorts <- cohortSet %>%
  # Remove 'cohort' and 'json' columns
  select(-"cohort", -"json") %>%
  mutate(type = c("event", "event", "event", "event", "exit", "event", "event", "target")) %>%
  rename(
    cohortId = "cohort_definition_id",
    cohortName = "cohort_name",
  ) %>%
  select("cohortId", "cohortName", "type")

executeTreatmentPatterns(
  cohorts = cohorts,
  cohortTableName = "cohort_table",
  cdm = cdm
)

DBI::dbDisconnect(con, shutdown = TRUE)
}

```

export

export

Description

Export andromeda generated by [computePathways](#) object to sharable csv-files and/or a zip archive.

Usage

```

export(
  andromeda,
  outputPath = NULL,
  ageWindow = 10,
  minCellCount = 5,
  censorType = "minCellCount",
  archiveName = NULL,
  nonePaths = FALSE,
  stratify = FALSE
)

```

Arguments

<code>andromeda</code>	(<code>Andromeda::andromeda()</code>) Andromeda object.
<code>outputPath</code>	(<code>character</code> : <code>NULL</code>) Output path where to write output files to. When set to <code>NULL</code> no files will be written, and only the results object is returned.
<code>ageWindow</code>	(<code>integer</code> (<code>n</code>): 10) Number of years to bin age groups into. It may also be a vector of integers. I.e. <code>c(0, 18, 150)</code> which will results in age group 0-18 which includes subjects < 19. And age group 18-150 which includes subjects > 18.
<code>minCellCount</code>	(<code>integer</code> (1): 5) Minimum count required per pathway. Censors data below <code>x</code> as <code><x</code> . This minimum value will carry over to the sankey diagram and sunburst plot.
<code>censorType</code>	(<code>character</code> (1)) "minCellCount" Censors pathways <code><minCellCount</code> to <code>minCellCount</code> . "remove" Censors pathways <code><minCellCount</code> by removing them completely. "mean" Censors pathways <code><minCellCount</code> to the mean of all frequencies below <code>minCellCount</code>
<code>archiveName</code>	(<code>character</code> (1): <code>NULL</code>) If not <code>NULL</code> adds the exported files to a ZIP-file with the specified archive name.
<code>nonePaths</code>	(<code>logical</code> (1)) Should None paths be included? This will fetch all persons included in the target cohort and assign them a "None" pathway. Significantly impacts performance.
<code>stratify</code>	(<code>logical</code> (1)) Should pathways be stratified? This will perform pairwise stratification between age, sex, and index year. Significantly impacts performance.

Value

TreatmentPatternsResults object

Examples

```
ableToRun <- all(
  require("CirceR", character.only = TRUE, quietly = TRUE),
  require("CDMConnector", character.only = TRUE, quietly = TRUE),
  require("TreatmentPatterns", character.only = TRUE, quietly = TRUE),
  require("dplyr", character.only = TRUE, quietly = TRUE)
)

if (ableToRun) {
  library(TreatmentPatterns)
  library(CDMConnector)
  library(dplyr)

  withr::local_envvar(
    R_USER_CACHE_DIR = tempfile(),
    EUNOMIA_DATA_FOLDER = Sys.getenv("EUNOMIA_DATA_FOLDER", unset = tempfile())
  )

  tryCatch({
    if (Sys.getenv("skip_eunomia_download_test") != "TRUE") {
      CDMConnector::downloadEunomiaData(overwrite = TRUE)
    }
  }, error = function(e) {
    message("Download Eunomia data failed: ", e$message)
  })
}
```

```

    }
  }, error = function(e) NA)

  con <- DBI::dbConnect(duckdb::duckdb(), dbdir = eunomia_dir())
  cdm <- cdmFromCon(con, cdmSchema = "main", writeSchema = "main")

  cohortSet <- readCohortSet(
    path = system.file(package = "TreatmentPatterns", "exampleCohorts")
  )

  cdm <- generateCohortSet(
    cdm = cdm,
    cohortSet = cohortSet,
    name = "cohort_table"
  )

  cohorts <- cohortSet %>%
    # Remove 'cohort' and 'json' columns
    select(-"cohort", -"json") %>%
    mutate(type = c("event", "event", "event", "event", "exit", "event", "event", "target")) %>%
    rename(
      cohortId = "cohort_definition_id",
      cohortName = "cohort_name",
    ) %>%
    select("cohortId", "cohortName", "type")

  outputEnv <- computePathways(
    cohorts = cohorts,
    cohortTableName = "cohort_table",
    cdm = cdm
  )

  results <- export(
    andromeda = outputEnv
  )

  Andromeda::close(outputEnv)
  DBI::dbDisconnect(con, shutdown = TRUE)
}

```

getResultsDataModelSpecifications

getResultsDataModelSpecifications

Description

Gets the results data model specifications of TreatmentPatterns.

Usage

```
getResultsDataModelSpecifications()
```

Value

`data.frame`

Examples

```
{
  getResultsDataModelSpecifications()
}
```

InputHandler	<i>InputHandler</i>
--------------	---------------------

Description

Class to handle input from the user. Supports direct paths or input fields through `setDataPath()`.

Super class

`TreatmentPatterns::ShinyModule` -> InputHandler

Active bindings

`reactiveValues` (`reactiveValues`)
`reactiveValues` class created by [reactiveValues](#).

Methods**Public methods:**

- [InputHandler\\$uiMenu\(\)](#)
- [InputHandler\\$uiBody\(\)](#)
- [InputHandler\\$server\(\)](#)
- [InputHandler\\$uiDatabaseSelector\(\)](#)
- [InputHandler\\$setDataPath\(\)](#)
- [InputHandler\\$clone\(\)](#)

Method `uiMenu()`: Method to include a [menuItem](#) to link to the body.

Usage:

```
InputHandler$uiMenu(label = "File upload", tag = "fileUpload")
```

Arguments:

`label` (`character(1)`)

Label to show for the menuItem.

`tag` (`character(1)`)

Tag to use internally in input.

Returns: (`menuItem`)

Method `uiBody()`: Method to include a [tabItem](#) to include the body.

Usage:

InputHandler\$uiBody()

Returns: (tabItem)

Method server(): Method to handle the back-end.

Usage:

InputHandler\$server(input, output, session)

Arguments:

input (input)

Input from the server function.

output (output)

Output from the server function.

session (session)

Session from the server function.

Returns: (NULL)

Method uiDatabaseSelector(): Method to include a [uiOutput](#) to select between multiple uploaded files.

Usage:

InputHandler\$uiDatabaseSelector()

Returns: (uiOutput)

Method setDataPath(): Method to dictate where the data is coming from, either from the input through the shiny application, or from a specified path. When one is provided, the other is ignored.

Usage:

InputHandler\$setDataPath(tag = "uploadField", input = NULL, path = NULL)

Arguments:

tag (character(1))

Tag to use internally in input.

input (input)

Input from the server function of the shiny app.

path (character(1))

Path to a zip-file containing TreatmentPatterns output files.

Returns: (invisible(self))

Method clone(): The objects of this class are cloneable with this method.

Usage:

InputHandler\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

launchResultsExplorer *launchResultsExplorer*

Description

Launches the ResultExplorer shinyApp.

Usage

```
launchResultsExplorer()
```

Value

(shinyApp)

Examples

```
if (interactive()) {
  launchResultsExplorer()
}
```

plotEventDuration *plotEventDuration*

Description

plotEventDuration

Usage

```
plotEventDuration(
  eventDurations,
  minCellCount = 0,
  treatmentGroups = "both",
  eventLines = NULL,
  includeOverall = TRUE
)
```

Arguments

eventDurations (data.frame) Contents of summaryEventDuration.csv file.

minCellCount (numeric(1): 0) Min Cell Count per event group.

treatmentGroups (character(1): "both") "group": Only mono-, and combination-events. "individual": Only individual (combination) events. "both": Both mono-, and combination-events, and individual (combination) events.

eventLines (numeric(n): NULL) Event lines to include, i.e. c(1, 2, 3) includes first (1), second (2), and third (3) lines of events. NULL will include all eventLines.

includeOverall (logical(1): TRUE) TRUE: Include an overall column with the eventLines. FALSE: Exclude the overall column.

Value

ggplot

Examples

```

ableToRun <- all(
  require("CirceR", character.only = TRUE, quietly = TRUE),
  require("CDMConnector", character.only = TRUE, quietly = TRUE),
  require("TreatmentPatterns", character.only = TRUE, quietly = TRUE),
  require("dplyr", character.only = TRUE, quietly = TRUE)
)

if (ableToRun) {
  withr::local_envvar(
    R_USER_CACHE_DIR = tempfile(),
    EUNOMIA_DATA_FOLDER = Sys.getenv("EUNOMIA_DATA_FOLDER", unset = tempfile())
  )

  tryCatch({
    if (Sys.getenv("skip_eunomia_download_test") != "TRUE") {
      CDMConnector::downloadEunomiaData(overwrite = TRUE)
    }
  }, error = function(e) NA)

  con <- DBI::dbConnect(duckdb::duckdb(), dbdir = eunomia_dir())
  cdm <- cdmFromCon(con, cdmSchema = "main", writeSchema = "main")

  cohortSet <- readCohortSet(
    path = system.file(package = "TreatmentPatterns", "exampleCohorts")
  )

  cdm <- generateCohortSet(
    cdm = cdm,
    cohortSet = cohortSet,
    name = "cohort_table"
  )

  cohorts <- cohortSet %>%
    # Remove 'cohort' and 'json' columns
    select(-"cohort", -"json") %>%
    mutate(type = c("event", "event", "event", "event", "exit", "event", "event", "target")) %>%
    rename(
      cohortId = "cohort_definition_id",
      cohortName = "cohort_name",
    ) %>%
    select("cohortId", "cohortName", "type")

  outputEnv <- computePathways(
    cohorts = cohorts,
    cohortTableName = "cohort_table",
    cdm = cdm
  )

  results <- export(outputEnv)

  plotEventDuration(

```

```
      eventDurations = results$summary_event_duration,
      minCellCount = 5,
      treatmentGroups = "group",
      eventLines = 1:4,
      includeOverall = FALSE
    )

    Andromeda::close(outputEnv)
    DBI::dbDisconnect(con, shutdown = TRUE)
  }
```

SankeyDiagram	<i>SankeyDiagram</i>
---------------	----------------------

Description

Class to handle the Sankey diagram of TreatmentPatterns.

Super classes

[TreatmentPatterns::ShinyModule](#) -> TreatmentPatterns::InteractivePlot -> SankeyDiagram

Methods

Public methods:

- [SankeyDiagram\\$clone\(\)](#)

Method clone(): The objects of this class are cloneable with this method.

Usage:

`SankeyDiagram$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

ShinyModule	<i>ShinyModule</i>
-------------	--------------------

Description

ShinyModule super class

Active bindings

`namespace` Namespace of the module.

Methods

Public methods:

- [ShinyModule\\$new\(\)](#)
- [ShinyModule\\$validate\(\)](#)
- [ShinyModule\\$uiMenu\(\)](#)
- [ShinyModule\\$uiBody\(\)](#)
- [ShinyModule\\$server\(\)](#)
- [ShinyModule\\$clone\(\)](#)

Method `new()`: Initializer method

Usage:

`ShinyModule$new(namespace)`

Arguments:

`namespace` (character(1))

Returns: (invisible(self))

Method `validate()`: Validator method

Usage:

`ShinyModule$validate()`

Returns: (invisible(self))

Method `uiMenu()`: Method to include a [menuItem](#) to link to the body.

Usage:

`ShinyModule$uiMenu(label, tag)`

Arguments:

`label` (character(1))

Label to show for the menuItem.

`tag` (character(1))

Tag to use internally in input.

Returns: (menuItem)

Method `uiBody()`: Method to include a [tabItem](#) to include the body.

Usage:

`ShinyModule$uiBody()`

Returns: (tabItem)

Method `server()`: Method to handle the back-end.

Usage:

`ShinyModule$server(input, output, session)`

Arguments:

`input` (input)

Input from the server function.

`output` (output)

Output from the server function.

`session` (session)

Session from the server function.

Returns: (NULL)

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`ShinyModule$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

SunburstPlot	<i>SunburstPlot</i>
--------------	---------------------

Description

Class to handle the Sunburst plot of TreatmentPatterns.

Super classes

`TreatmentPatterns::ShinyModule` -> `TreatmentPatterns::InteractivePlot` -> `SunburstPlot`

Methods

Public methods:

- `SunburstPlot$clone()`

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`SunburstPlot$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

TreatmentPatternsResults	<i>TreatmentPatternsResults Class</i>
--------------------------	---------------------------------------

Description

Houses the results of a TreatmentPatterns analysis. Each field corresponds to a file. Plotting methods are provided.

Active bindings

```

attrition (data.frame)
metadata (data.frame)
treatment_pathways (data.frame)
summary_event_duration (data.frame)
counts_age (data.frame)
counts_sex (data.frame)
counts_year (data.frame)
cdm_source_info (data.frame)
analyses (data.frame)
arguments (list)

```

Methods**Public methods:**

- [TreatmentPatternsResults\\$new\(\)](#)
- [TreatmentPatternsResults\\$saveAsZip\(\)](#)
- [TreatmentPatternsResults\\$saveAsCsv\(\)](#)
- [TreatmentPatternsResults\\$uploadResultsToDb\(\)](#)
- [TreatmentPatternsResults\\$load\(\)](#)
- [TreatmentPatternsResults\\$plotSunburst\(\)](#)
- [TreatmentPatternsResults\\$plotSankey\(\)](#)
- [TreatmentPatternsResults\\$plotEventDuration\(\)](#)
- [TreatmentPatternsResults\\$clone\(\)](#)

Method new(): Initializer method*Usage:*

```

TreatmentPatternsResults$new(
  attrition = NULL,
  metadata = NULL,
  treatmentPathways = NULL,
  summaryEventDuration = NULL,
  countsAge = NULL,
  countsSex = NULL,
  countsYear = NULL,
  cdmSourceInfo = NULL,
  analyses = NULL,
  arguments = NULL,
  filePath = NULL
)

```

Arguments:

```

attrition (data.frame) attrition result.
metadata (data.frame)) metadata result.
treatmentPathways (data.frame)) treatmentPathways result.
summaryEventDuration (data.frame)) summaryEventDuration result.
countsAge (data.frame)) countsAge result.

```

countsSex (data.frame)) countsSex result.
 countsYear (data.frame)) countsYear result.
 cdmSourceInfo (data.frame) cdmSourceInfo result.
 analyses (data.frame) Analyses result.
 arguments (list) Named list of arguments used.
 filePath (character) File path to either a directory or zip-file, containing the csv-files.

Method saveAsZip(): Save the results as a zip-file.

Usage:

```
TreatmentPatternsResults$saveAsZip(path, name, verbose = TRUE)
```

Arguments:

path (character(1)) Path to write to.
 name (character(1)) File name.
 verbose (logical: TRUE) Verbose messaging.

Returns: self

Method saveAsCsv(): Save the results as csv-files.

Usage:

```
TreatmentPatternsResults$saveAsCsv(path, verbose = TRUE)
```

Arguments:

path (character(1)) Path to write to.
 verbose (logical: TRUE) Verbose messaging.

Returns: self

Method uploadResultsToDb(): Upload results to a resultsDatabase using ResultModelManager.

Usage:

```
TreatmentPatternsResults$uploadResultsToDb(
  connectionDetails,
  schema,
  prefix = "tp_",
  overwrite = TRUE,
  purgeSiteDataBeforeUploading = FALSE
)
```

Arguments:

connectionDetails (ConnectionDetails) ConnectionDetails object from DatabaseConnector.
 schema (character(1)) Schema to write tables to.
 prefix (character(1): "tp_") Table prefix.
 overwrite (logical(1): TRUE) Should tables be overwritten?
 purgeSiteDataBeforeUploading (logical: FALSE) Should site data be purged before uploading?

Returns: self

Method load(): Load data from files.

Usage:

```
TreatmentPatternsResults$load(filePath)
```

Arguments:

filePath (character(1)) Path to a directory or zip-file containing the result csv-files.

Returns: self

Method plotSunburst(): Wrapper for TreatmentPatterns::createSunburstPlot(), but with data filtering step.

Usage:

```
TreatmentPatternsResults$plotSunburst(
  age = "all",
  sex = "all",
  indexYear = "all",
  nonePaths = FALSE,
  ...
)
```

Arguments:

age (character(1)) Age group.

sex (character(1)) Sex group.

indexYear (character(1)) Index year group.

nonePaths (logical(1)) Should None paths be included?

... Parameters for TreatmentPatterns::createSunburstPlot()

Returns: htmlwidget

Method plotSankey(): Wrapper for TreatmentPatterns::createSankeyDiagram(), but with data filtering step.

Usage:

```
TreatmentPatternsResults$plotSankey(
  age = "all",
  sex = "all",
  indexYear = "all",
  nonePaths = FALSE,
  ...
)
```

Arguments:

age (character(1)) Age group.

sex (character(1)) Sex group.

indexYear (character(1)) Index year group.

nonePaths (logical(1)) Should None paths be included?

... Parameters for TreatmentPatterns::createSankeyDiagram()

Returns: htmlwidget

Method plotEventDuration(): Wrapper for TreatmentPatterns::plotEventDuration().

Usage:

```
TreatmentPatternsResults$plotEventDuration(...)
```

Arguments:

... Parameters for TreatmentPatterns::plotEventDuration()

Returns: ggplot

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
TreatmentPatternsResults$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Index

andromeda, [6](#)

CharacterizationPlots, [3](#)
computePathways, [4](#), [9](#), [11](#)
createSankeyDiagram, [7](#)
createSunburstPlot, [8](#)

executeTreatmentPatterns, [9](#)
export, [9](#), [11](#)

getResultsDataModelSpecifications, [13](#)

InputHandler, [4](#), [14](#)

launchResultsExplorer, [16](#)

menuItem, [3](#), [14](#), [19](#)

plotEventDuration, [16](#)

reactiveValues, [14](#)

SankeyDiagram, [18](#)
sankeyNetwork, [7](#)
ShinyModule, [18](#)
sunburst, [8](#)
SunburstPlot, [20](#)

tabItem, [3](#), [14](#), [19](#)
TreatmentPatterns::ShinyModule, [3](#), [14](#),
[18](#), [20](#)
TreatmentPatternsResults, [20](#)

uiOutput, [15](#)