

Useful R code

Matthew Malishev^{1*}

¹ *Department of Biology, Emory University, 1510 Clifton Road NE, Atlanta, GA, USA, 30322*

Contents

Overview	2
Install dependencies	2
Attributes	2
Classes	2
Dataframes	3
Generic functions	3
ggplot functions	3
Messages	4
NAs	5
Plotting	6
Reading in files/data	9
Regular expressions (regex)	11
R Markdown	11
Subsetting	11
Web scraping	11

Date: 2018-11-02

R version: 3.5.0

*Corresponding author: matthew.malishev@gmail.com

This document can be found at <https://github.com/darwinanddavis/UsefulCode>

Overview

This document outlines some useful R code for plotting, cool functions, and other random tidbits.

Install dependencies

```
packages <- c("rgdal","dplyr","zoo","RColorBrewer","viridis","plyr","digitize","jpeg","devtools","image")
if (require(packages)) {
  install.packages(packages,dependencies = T)
  require(packages)
}
lapply(packages,library,character.only=T)
sessionInfo()
```

Attributes

Access structural attributes of unique classes, such as raster and ggmap.

```
# Normal example
df <- data.frame("X"=c(1:5),"Y"=c(6:10))
str(df)
df$X

# `attr` method
require(ggmap)
map <- get_map("Atlanta",zoom=12,source="stamen",maptype="toner-lines")
str(map)
attr(map,"bb")$ll.lat
```

Classes

Convert character to factor to numeric without conversion error

```
read.table(f,header=T,sep=",",row.names=NULL,stringsAsFactors=FALSE, strip.white=TRUE)
f$V2<-as.numeric(f$V2)
```

See call options for class

```
methods(class="estUDm")
```

Set dynamic input for variable / assign variable to char vector

```
shadedens<-function(shadedens){ # set shade density to clumped (to match food) or sparse
  if (shadedens == "Random"){
    NLCommand("set Shade-density \"Random\" ")
  }else{
    NLCommand("set Shade-density \"Clumped\" ")
  }
}
shadedens("Clumped") # set clumped resources
```

Dataframes

Optimal empty data frame

```
df <- data.frame(Date=as.Date(character()),
                  X=numeric(),
                  Y=integer(),
                  stringsAsFactors=FALSE)
```

Add df cols with mutate

```
require(dplyr)
df <- data.frame("a"=rnorm(10),"b"=(1:20))
df %>%
  mutate(
    "c"=rnorm(20),
    b = b *67
  )
```

Change df column names

```
colnames(data)[c(1,2,3)] <- c("TimeStamp","Lat","Long")
```

Generic functions

Generic useful functions that I can't place under any other headings here

```
# dput() for converting outputs such as copied text or data tables into vectors
xx <- "Some copied text or table from the internet"
dput(xx)
```

ggplot functions

Remove annoying stock gridlines from plot window

```
plot + theme_bw() +
  theme(panel.border = element_blank(), panel.grid.major = element_blank(),
        panel.grid.minor = element_blank(), axis.line = element_line(colour = "black"))
# alternative (after loading ggridges library)
theme_ridges(grid=F,center_axis_labels = T)
```

Setting global graphics theme for ggplot

```
plot_it_gg <- function(bg,family){ # bg = colour to plot bg, family = font family
  theme_tufte(base_family = family) +
  theme(panel.border = element_blank(),
        panel.grid.major = element_blank(),
        panel.grid.minor = element_blank(),
        panel.background = element_rect(fill = bg,
                                         colour = bg),
        plot.background = element_rect(fill=bg)
  ) +
  theme(axis.line = element_line(color = "white")) +
  theme(axis.ticks = element_line(color = "white")) +
  theme(plot.title = element_text(colour = "white")) +
  theme(axis.title.x = element_text(colour = "white"),
```

```

    axis.title.y = element_text(colour = "white")) +
  theme(axis.text.x = element_text(color = "white"),
        axis.text.y = element_text(color = "white")) +
  theme(legend.key = element_rect(fill = bg)) + # fill bg of legend
  theme(legend.title = element_text(colour="white")) + # legend title
  theme(legend.text = element_text(colour="white")) # legend labels
}

```

Put plot in function to take dynamic data inputs

Ref: <http://jcborras.net/carpet/visualizing-political-divergences-2012-local-elections-in-helsinki.html>

```

hr.mass.plot <- function(d) {
  p <- ggplot(d, aes(HR, Mass, color = colfunc)) +
    geom_density_2d(data=d, aes(x = HR, y = Mass),
                    stat = "density2d", position="identity",
                    color=adjustcolor("orange",alpha=0.8), size=1.5, contour = T, lineend="square", line)
  p <- p + geom_point(data=d, aes(x = HR, y = Mass),
                      color=colfunc,
                      fill=colfunc) +
    scale_color_manual(values = magma(8))
  p <- p + scale_y_continuous(limits=c(-200,200), name="Mass lost (g)")
  p <- p + scale_x_continuous(limits=c(0,0.35),name=expression("Home range area (km^2)"))
  p <- p + theme_classic()
  print(p)
}
hr.mass.plot(d)

```

Using ggplot when looping through for loop and saving to dir

```

pdf("mypdf.pdf", onefile = T)
for(i in 1:3){
  par(bty="n", las = 1)
  grid.arrange(
    ggplot(data, aes(x = X, y = Y, fill=..x..)) + # geom_density_ridges()
    # scale = overlap
    geom_density_ridges_gradient(scale = 5, size=0.2,color="black", rel_min_height = 0.01, panel_scaling=TRUE) +
    geom_density_ridges(scale = 5, size=0.2,color="black", rel_min_height = 0.01, fill="white", alpha=0.2) +
    # geom_density_ridges(scale = 5, size=0.2,color="white", rel_min_height = 0.01, fill=col, alpha=0.5) +
    scale_fill_viridis(name = "Diameter", alpha=0.1, option = "magma", direction=-1) + # "magma", "inferno"
    xlim(c(0,25)) +
    labs(title = paste0("Title_",i)) +
    xlab("X") +
    ylab("Y") +
    # plot_it_gg("white")
  )
} # end loop
dev.off()

```

Messages

Display status message of progress

```

for(i in 1:10) {
  Sys.sleep(0.2)
  # Dirk says using cat() like this is naughty ;-)
}

```

```

#cat(i, "\r")
# So you can use message() like this, thanks to Sharpie's
# comment to use appendLF=FALSE.
message(i, "\r", appendLF=FALSE) # appendLF = new line
flush.console()
}

```

Display popup progress bar

```

require(tcltk)
pb <- tkProgressBar("test progress bar", "Some information in %",
  0, 100, 50)
Sys.sleep(0.5)
u <- c(0, sort(runif(20, 0, 100)), 100)
for(i in u) {
  Sys.sleep(0.1)
  info <- sprintf("%d%% done", round(i))
  setTkProgressBar(pb, i, sprintf("test (%s)", info), info)
}
Sys.sleep(5)
close(pb)

```

NAs

Replace NAs with 0's

```
df[is.na(df)] <- 0
```

Replace X values less than given value (V) with 0

```
df$X[df$X<V] <- 0
```

Check for NAs

```
sapply(df, function(x) sum(is.na(x)))
```

Replace NaN and Inf values with NA

```
df$col1[which(!is.finite(df$col1))] <- NA
```

Fill in missing data values in sequence with NA

```

# /Users/malishev/Documents/Manuscripts/Chapter4/Sims/Chapter4_figs.R
library(zoo)
data <- data.frame(index = c(1:4, 6:10),
  data = c(1.5,4.3,5.6,6.7,7.1,12.5,14.5,16.8,3.4))
#you can create a series
z <- zoo(data$data, data$index)
#end extend it to the grid 1:10
z <- merge(zoo(,1:10), z)

#worked example
# fill in missing Tb values
minTb.d <- zoo(minTb$Tick,minTb$Days)
minTb.d <- merge(zoo(NULL,1:days), minTb.d) # make the minTb series match the temp series (117 days)
minTb.d <- as.numeric(minTb.d) # = time individuals reached VTMIN in ticks
minTb <- minTb.d - temp$Tick # get diff between starting time and time to reach VTMIN

```

```
minTb <- minTb/2 # convert ticks to minutes
minTb <- minTb/60 #convert to hours
minTb <- data.frame("Days"=1:days,"Time"=minTb)
```

```
# then fill in missing values
approx(minTb$Time,method = "linear")
```

Remove rows with NA

```
data <- data[!is.na(data$X),]
```

Plotting

Plot one plot window above and two below

```
layout(matrix(c(1,1,2,3), 2, 2, byrow = TRUE))
```

Bookend axis ticks for plot E.g. at 0 and 100 when data is 1:99

```
axis(1,at=c(0,length(loco$X)),labels=c("", ""))# bookending axis tick marks
```

Optimal legend formatting for base

```
legend("right",legend=c("Small","Intermediate","Large"),col=c(colfunc[colvec[1:3]]),
      bty="n",pch=20,pt.cex=1.5,cex=0.7,y.intersp = 0.5, xjust = 0.5,
      title="Size class",title.adj = 0.3,text.font=2,
      trace=T,inset=0.1)
```

Plot inset plot in current plot (<https://stackoverflow.com/questions/17041246/how-to-add-an-inset-subplot-to-topright-of-an-r-plot>)

```
# calculate position of inset
plotdim <- par("plt")# get plot window dims as fraction of current plot dims
xleft    = plotdim[2] - (plotdim[2] - plotdim[1]) * 0.5
xright   = plotdim[2] #
ybottom  = plotdim[4] - (plotdim[4] - plotdim[3]) * 0.5 #
ytop     = plotdim[4] #

# set position for plot inset
par(fig = c(xleft, xright, ybottom, ytop),mar=c(0,0,0,0),new=TRUE)

boxplot(Eggs~Size,data=meso2,
        col=adjustcolor(colfunc[colvec[1:3]],alpha=0.5),
        notch = T,xlab="Week",ylab="Diameter (mm)",
        xaxs = "i", yaxs = "i"
        )
```

Interactive plots with rCharts (javascript and d3 viz)

<http://ramnathv.github.io/rCharts/>

```
require(devtools)
install_github('rCharts', 'ramnathv')
```

Cluster plot

<https://rpubs.com/dgrtwo/technology-clusters>

```

library(readr)
library(dplyr)
library(igraph)
library(ggraph)
library(ggforce)

# This shared file contains the number of question that have each pair of tags
# This counts only questions that are not deleted and have a positive score
tag_pair_data <- read_csv("http://varianceexplained.org/files/tag_pairs.csv.gz")

relationships <- tag_pair_data %>%
  mutate(Fraction = Cooccur / Tag1Total) %>%
  filter(Fraction >= .35) %>%
  distinct(Tag1)

v <- tag_pair_data %>%
  select(Tag1, Tag1Total) %>%
  distinct(Tag1) %>%
  filter(Tag1 %in% relationships$Tag1 |
         Tag1 %in% relationships$Tag2) %>%
  arrange(desc(Tag1Total))

a <- grid::arrow(length = grid::unit(.08, "inches"), ends = "first", type = "closed")

set.seed(2016)

relationships %>%
  graph_from_data_frame(vertices = v) %>%
  ggraph(layout = "fr") +
  geom_edge_link(aes(alpha = Fraction), arrow = a) +
  geom_node_point(aes(size = Tag1Total), color = "lightblue") +
  geom_node_text(aes(size = Tag1Total, label = name), check_overlap = TRUE) +
  scale_size_continuous(range = c(2, 9)) +
  ggforce::theme_no_axes() +
  theme(legend.position = "none")

```

Define global plotting graphics function.

The plot_it.R function is updated on the [plot_it Github page](#).

```

require(ggplot2)
require(ggthemes)
### set plotting params
plot_it <- function(manuscript,bg,cp1,cp2,alpha,family){ # plotting function (plot for MS or not, set b
  graphics.off()
  if(manuscript==0){
    if(bg=="black"){
      colvec <-- magma(200,1) # plot window bg # USES <-- OPERATOR
      par(bg = colvec[1],col.axis="white",col.lab="white",col.main="white",fg="white",bty="n",las=1,mar=
      border=adjustcolor("purple",alpha=0.5)
    }else{
      colvec <-- bpy.colors(200) # plot window bg # USES <-- OPERATOR
      par(bg = colvec[1],col.axis="white",col.lab="white",col.main="white",fg="white",bty="n",las=1,mar=
      border=adjustcolor("blue",alpha=0.5)
    }
  }
}

```

```

}else{
  # graphics.off()
  par(bty="n",las=1,family=family)
  colv<-"white"
}
# color palettes
# ifelse(manuscript==1,colvec<-adjustcolor(brewer.pal(9,cp1)[9], alpha = alpha),colvec <- adjustcolor
# colfunc <- colorRampPalette(brewer.pal(9,cp1),alpha=alpha)
cp1_info <- brewer.pal.info[cp1,]$maxcolors
cp2_info <- brewer.pal.info[cp2,]$maxcolors
colv <- brewer.pal(cp1_info,cp1) # USES <- OPERATOR
colv2 <- brewer.pal(cp2_info,cp2) # USES <- OPERATOR
}

# Setting ggplot theme graphics
plot_it_gg <- function(bg){ # bg = colour to plot bg, family = font family
  if(bg=="white"){
    bg <- "white"
    fg <- "black"
    theme_tufte(base_family = "HersheySans") +
      theme(panel.border = element_blank(),panel.grid.major = element_blank(),panel.grid.minor = element_blank(),
            theme(axis.line = element_line(color = fg)) +theme(axis.ticks = element_line(color = fg)) + theme
  }
}# end gg

### Set plotting function

require("RCurl")
script <- getURL("https://raw.githubusercontent.com/darwinanddavis/plot_it/master/plot_it.R", ssl.verif
eval(parse(text = script))

cat("plot_it( \n0 for presentation, 1 for manuscript, \nset colour for background, \nset colour palette
plot_it(0,"blue","Spectral","Greens",1,"mono") # set col function params
plot_it_gg("white") # same as above

```

Make plot cycle on one page

```
plot(m_abundance$gam,pages=1)
```

Get plot summaries and values from plot

```

plot.gam(m_abundance$gam,shade=T,pages=1,seWithMean = T)[1] # everything
plot.gam(m_abundance$gam,shade=T,pages=1,seWithMean = T)[1][[1]]$x #subset x
plot.gam(m_abundance$gam,shade=T,pages=1,seWithMean = T)[1][[1]]$fit #get values to produce fit curve

```

Package for stock world maps

```

#worldmap
library(choroplethrMaps)

```

Circle packing, tree, dendrogram, network plots

```

# dendrogram tree nested bubble circle packing network
# https://www.r-graph-gallery.com/313-basic-circle-packing-with-several-levels/
# circle packing plot
# Libraries
p <- c("ggraph","igraph","tidyverse","DeducerSpatial","Rcpp","car")

```



```

install.packages(p,dependencies = T)
lapply(p,library,character.only=T)

# We need a data frame giving a hierarchical structure. Let's consider the flare dataset:
edges=flare$edges
# edges cols = character

# Usually we associate another dataset that give information about each node of the dataset:
vertices = flare$vertices
# vertices cols = character, numeric, character

# Then we have to make a 'graph' object using the igraph library:
??graph_from_data_frame
mygraph <- graph_from_data_frame( edges, vertices=vertices )

# circle packing
ggraph(mygraph, layout = 'circlepack') +
  geom_node_circle() +
  theme_void()

#circular dendro
str(mygraph)
ggraph(mygraph, layout='dendrogram', circular=T) +
  geom_edge_diagonal() +
  theme_void() +
  theme(legend.position="none")

# tree map
ggraph(mygraph, 'treemap', weight = 'size') +
  geom_node_tile(aes(fill = depth), size = 0.25) +
  theme_void() +
  theme(legend.position="none")

# circular partition
ggraph(mygraph, 'partition', circular = TRUE) +
  geom_node_arc_bar(aes(fill = depth), size = 0.25) +
  theme_void() +
  theme(legend.position="none")

# node
ggraph(mygraph) +
  geom_edge_link() +
  geom_node_point() +
  theme_void() +
  theme(legend.position="none")

```

Reading in files/data

Read in file manually

```

get.file.vol <- read.table(file.choose())#read file manually
v.file <- get.file.vol[1:100,1]#get the volume

```

Loop through files from dir and append to list

```
# reading in spdf (hrpath) files from drive
setwd("/Users/camel/Desktop/Matt2016/Manuscripts/MalishevBullKearney/Resubmission/2016/barcoo sims/barcoo")
file.list<-list.files()
hrs75<-as.list(rep(1,100)) # empty list
for (f in 1:100){
  load(file.list[f])
  hrs75[f]<-hrpath
}

# working version
#converting spdf into mcp(spdf,100,unout="m2")
ghr<-list()
for (i in hrs75[1:10]) {
  m<-mcp(i,100,unout='m2')
  ghr<-c(ghr,m)
};ghr
```

Read in PDF files from online source in R and save to drive.

```
# from https://github.com/ropensci/pdftools

require(pdftools)
url <- "https://raw.githubusercontent.com/darwinanddavis/499R/master/exp_pop_growth.pdf"
dir <- "FOLDER ON YOUR COMPUTER WHERE YOU WANT THE FILE SAVED"
f <- "NAME OF THE FILE"
f <- paste0(f, ".pdf")

# run all this
download.file(url, paste0(dir, "/", f), mode = "wb")
txt <- pdf_text(paste0(dir, "/", f))

# first page text
page <- 1 # enter the page number
cat(txt[page])

toc <- pdf_toc(paste0(dir, "/", f))

require(jsonlite)
# Show as JSON
jsonlite::toJSON(toc, auto_unbox = TRUE, pretty = TRUE)

# show author, version, etc
info <- pdf_info(f)

# renders pdf to bitmap array
bitmap <- pdf_render_page(f, page = 1)

# save bitmap image
png::writePNG(bitmap, "page.png")
jpeg::writeJPEG(bitmap, "page.jpeg")
webp::write_webp(bitmap, "page.webp")
```

Regular expressions (regex)

Get just numbers or characters

```
vec <- "16-Feb-2018 20:08:04 PM"
vecN <- gsub("[^[:digit:]]", "", vec); vec; print(paste0("Just numbers: ",vecN))
vecC <- gsub("[[:digit:]]", "", vec); vec; print(paste0("Just characters: ", vecC))

# with tidyr. requires data frame
require(tidyr)
df <- data.frame(N1=c("APPLE348744", "BANANA77845", "OATS2647892", "EGG98586456"))
print("tidyr doesn't work with strings separated by spaces")
df %>%
  separate(N1, into = c("text", "num"), sep = "(?<=[A-Za-z])(?=[0-9])")
```

Insert or replace a character in a string at a specific location

```
require(stringi)
vec <- "ABCEF"
stri_sub(vec, 4, 2) <- "d"
print(paste0("Original: ABCEF")); print(paste0("New: ",vec))
```

```
[1] "Original: ABCEF"
```

```
[1] "New: ABCdEF"
```

R Markdown

Hide unwanted code output, such as inherent examples for functions

```
# ``{r, cache = TRUE, tidy = TRUE, lazy = TRUE, results='markup'}
```

Subsetting

Select specific rows E.g. select rows of speed_move not in foodh

```
library(sqldf)
a1NotIna2_h <- sqldf('SELECT * FROM speed_move EXCEPT SELECT * FROM foodh')
a1NotIna2_l <- sqldf('SELECT * FROM speed_move EXCEPT SELECT * FROM foodl')
# select rows from speed_move that also appear in foodh
a1Ina2_h <- sqldf('SELECT * FROM speed_move INTERSECT SELECT * FROM foodh')
a1Ina2_l <- sqldf('SELECT * FROM speed_move INTERSECT SELECT * FROM foodl')
```

Count occurrences of values in data frame

```
table(unlist(df$X))
```

Remove a specific column from a data frame

```
within(df, rm("Col1"))
```

Web scraping

Scraping web tables

http://web.mit.edu/~r/current/arch/i386_linux26/lib/R/library/XML/html/readHTMLTable.html%

5Bhttp://web.mit.edu/~r/current/arch/i386_linux26/lib/R/library/XML/html/readHTMLTable.html%
5D

```
library(XML)
readHTMLTable()
```

Scraping Twitter timelines

See complete example at <http://varianceexplained.org/r/trump-tweets/>

```
# https://cran.r-project.org/web/packages/twitterR/
library(dplyr)
library(purrr)
library/twitterR
```