



A+ API MANUAL

A+ Checkout API

Document version: v1.0

API version: V2.0



TABLE OF CONTENTS

1. DATA FORMAT	3
1.1 Data Submission	3
1.2 XML data format.....	4
2. DIGITAL SIGNATURE	5
2.1 Original string of signature.....	5
2.2 Methods of Signature.....	6
3. . CHECKOUT API	7
3..1Checkout Payment API.....	7
3.2Functions.....	7
3.3Interaction	7
3.4Request parameter list.....	8
3.5Returned results	9
4 ALIPAY WALLET QUERY API	10
4.1Alipay Wallet Query API	10
4.2Functions.....	10
4.3Interaction mode	10
4.4Request parameter list.....	10
4.5Returned results	11
5. QUERY API	12
5.1Order query API	12
5.2Functions.....	12
5.3Interaction mode	12
5.4Request parameter list.....	12
5.5Return result	13

6. REFUND API	15
6.1 Refund API	15
6.2Functions.....	15
6.3Interaction model	15
6.4Request parameter list.....	15
6.5Returned results	16
7 REFUND QUERY API	18
7.1Functions.....	18
7.2Interaction model	18
7.3Request parameter list.....	18
7.4Returned results	19
8 NOTIFICATION API	21
8.1Notification API	21
8.2Notification result parameter list.....	21
8.3Backend feedback.....	23
9. NOTES.....	23

1. Data Format

1.1 Data Submission

The transmission data uses the POST protocol under HTTPS standard. To ensure that the recipients

are able to correctly receive the data, all transmission data must be signed.

```
<xml><attach><![CDATA[attach]]></attach>
<body><![CDATA[1 1 1]]></body>
<mch_create_ip><![CDATA[127.0.0.1]]></mch_create_ip>
<mch_id><![CDATA[100540000088]]></mch_id>
<nonce_str><![CDATA[1662605480]]></nonce_str>
<notify_url><![CDATA[http://www.xxx.com/]]></notify_url>
<out_trade_no><![CDATA[1662605480]]></out_trade_no>
<service><![CDATA[pay.khqr.native]]></service>
<sign><![CDATA[001AF90817FFB62D8402E57AE8E54270]]></sign>
<sign_type><![CDATA[MD5]]></sign_type>
<total_fee><![CDATA[1000]]></total_fee>
</xml>
```

1.2 XML data format

Uses standard XML protocol, which stores all parameters in the single level node, instead of multiple nodes.

Protocol error return

```
<xml>
<status>500</status>
<message><![CDATA[SYSERR]]></message>
</xml>
```

Correct returned data:

```
<xml><charset><![CDATA[UTF-8]]></charset>
<code_img_url><![CDATA[http://127.0.0.1:9000/qr/code/code?uuid=2a2f2526adfc446456dbde19cd02642]]></code_img_url>
<code_url><![CDATA[00020101021230550018KHQR_MERCHANT@bkch01121005400000880213Bank of China52049399530311654071000.005802KH5920Cambodian-Riel (KHQR) 6004PHOH62520331Cambodian-Riel (KHQR) _SHORT_NAME0713PID5980344599991316626055048746304163F]]></code_url>
<mch_id><![CDATA[100540000088]]></mch_id>
<nonce_str><![CDATA[1662605480]]></nonce_str>
<out_trade_no><![CDATA[1662605480]]></out_trade_no>
<result_code><![CDATA[0]]></result_code>
<sign><![CDATA[81A83460BFC42C7843818050A8CC53C7]]></sign>
<sign_type><![CDATA[MD5]]></sign_type>
<status><![CDATA[0]]></status>
<transaction_id><![CDATA[10202209081076651082]]></transaction_id>
```

```
<uuid><![CDATA[2a2f2526adfca446456dbde19cd02642]]></uuid>
<version><![CDATA[2.0]]></version>
</xml>
```

Business error return:

```
<xml>
<status>0</status>
<message><![CDATA[OK]]></message>
<appid><![CDATA[wx2421b1c4370ec43b]]></appid>
<mch_id><![CDATA[10000100]]></mch_id>
<device_info><![CDATA[1000]]></device_info>
<nonce_str><![CDATA[sthBJ9QyUG6vkrjJ]]></nonce_str>
<sign><![CDATA[6277A96D7875D4FF23AA7B6A4C3046AB]]></sign>
<result_code>1</result_code>
<err_code><![CDATA[AUTHCODE_EXPIRE]]></err_code>
<err_code_des><![CDATA[QR code expired, please try again
later]]></err_code_des>
</xml>
```

Normally, status parameter will be returned: 0 stands for a successful call, value other than 0 stands for a failed call.

2. Digital Signature

To ensure the truthfulness and completeness of the data transmission process, we need to digitally sign the data, and verify the signature after receiving signed data.

There are two steps in the digital signature: 1) piece the original string that needs to be signed according to certain rules; 2) select the algorithm and key to calculate the signature result.

Failed results will not be signed normally.

2.1 Original string of signature

The original string of signature will be assembled into character strings according to the following modes (applicable to both request and response):

1. All parameter fields (except for sign field) will be ranked in ascending order according to the ASCII of the field name and then connected in the format of QueryString (i.e. key1=value1&key2=value2...). Null value will neither transfer nor participate in formation of string of signature.

2. In the original string of signature, both field name and field value will adopt original values and

will not conduct URL Encode.

3. Response or notification information returned by the platform might bring more parameters due to upgrade. This case should be allowed when the response signature is verified.

For instance:

Calling an interface with the following fields:

```
<xml>
<body><![CDATA[test_payment]]></body>
<mch_create_ip><![CDATA[127.0.0.1]]></mch_create_ip>
<mch_id><![CDATA[101520000465]]></mch_id>
<nonce_str><![CDATA[1409196838]]></nonce_str>
<notify_url><![CDATA[http://227.0.0.1:9001/javak/]]></notify_url>
<out_trade_no><![CDATA[141903606228]]></out_trade_no>
<service><![CDATA[pay.weixin.native.intl]]></service>
<sign><![CDATA[94B0F11B228BA9DDA2E20E3A9C8B3A2F]]></sign>
<total_fee><![CDATA[1]]></total_fee>
</xml>
```

The correct signature field sequence should be:

```
body=test
payment&mch_create_ip=127.0.0.1&mch_id=101520000465&nonce_str=140
9196838&notify_url=http://227.0.0.1:9001/javak/&out_trade_no=1419
03606228&service=pay.weixin.native.intl&total_fee=1
```

2.2 Methods of Signature

MD5 signature

MD5 is an abstractive generation algorithm, which adds the merchant communication key to the end of the original signature string, conducts the MD5 calculation, and generates an abstract string as the signature result. For the sake of comparison, the signature result will be converted to upper case letters.

Note: The set of coded characters specified when converting a string to a byte stream at signature should match the parameter charset.

MD5 signature calculation formula:

sign = Md5(original string&key=merchant key). toUpperCase

For example:

Suppose the following is the XML incoming parameter:

```
<xml>
<body><![CDATA[Test payment]]></body>
<mch_create_ip><![CDATA[127.0.0.1]]></mch_create_ip>
<mch_id><![CDATA[101520000465]]></mch_id>
```

```
<nonce_str><![CDATA[1409196838]]></nonce_str>
<notify_url><![CDATA[http://227.0.0.1:9001/javak/]]></notify_url>
<out_trade_no><![CDATA[141903606228]]></out_trade_no>
<service><![CDATA[pay.khqr.native]]></service>
<sign><![CDATA[94B0F11B228BA9DDA2E20E3A9C8B3A2F]]></sign>
<total_fee><![CDATA[1]]></total_fee>
</xml>
```

Suppose the merchant key is: 58bb7db599afc86ea7f7b262c32ff42f
 I: After sorted by URL key pair dictionary, the string1 will be:
 body=test_payment&mch_create_ip=127.0.0.1&mch_id=101520000465&nonce_str=1409196838¬ify_url=http://227.0.0.1:9001/javak/&out_trade_no=141903606228&service= pay.khqr.native &total_fee=1

ii: sign after process b will be:

```
sign
=md5(string1&key=58bb7db599afc86ea7f7b262c32ff42f).toUpperCase
=md5(body=test_payment&mch_create_ip=127.0.0.1&mch_id=101520000465&nonce_str=1409196838&notify_url=http://227.0.0.1:9001/javak/&out_trade_no=141903606228&service=pay.khqr.native &total_fee=1&key=58bb7db599afc86ea7f7b262c32ff42f).toUpperCase()
="94B0F11B228BA9DDA2E20E3A9C8B3A2F"
```

3. . Checkout API

3.1Checkout Payment API

3.2Functions

Initialize payment request and return to third-party checkout page through the request (WEB/WAP)

3.3Interaction

Request: The interface will be called from the backend.

Return result & notification: Backend request interaction mode + **Backend notification interaction mode**

3.4 Request parameter list

Request url: <https://gateway.wepayez.com/pay/gateway>

Request type: POST

Request format: XML

Variable	Required	Type	Description
service	Yes	String(32)	API type: pay.aps.alipay.wappay
version	No	String(8)	Version number. Default: 2.0
charset	No	String(8)	Character set, value: UTF-8
sign_type	Yes	String(16)	Signature type. Value: MD5
body	Yes	String(127)	Product description
mch_id	Yes	String(32)	Specifies a unique ID assigned by platform.
out_trade_no	Yes	String(32)	Unique order number within 32 characters in the merchant system. Can include only letters, numbers, and underscore. Upper and lower case sensitive.
total_fee	Yes	Int	Amount (cents) in payment currency. E.g. Payment is made in HKD, 1000 stands for HKD 10.00. Test merchant order maximum limit: 100 cents per count
mch_create_ip	Yes	String(16)	Machine IP created by IP order
notify_url	Yes	String(255)	URL for receiving platform notifications. Must be absolute URL within 255 characters, such as: https://notifytest.wepayez.com/qrcode/ Ensure the platform can access the address via Internet.
nonce_str	Yes	String(32)	Random character string (no longer than 32 digits)
sign	Yes	String(344)	Please refer to the section 2 “Digital Signature”.
time_expire	No	String(14)	Order expiration time. Format: yyyyMMddhhmmss. E.g. 09:10:10, December 27, 2009 will be written as 20091227091010. Time zone: GMT+8 Alipay Plus order validity is 10 minutes, so only a shorter period can be uploaded.
callback_url	No	String(128)	1. For API, it will be Alipay plus url based on merchant’s choice 2. For SwiftPass checkout, it will be the checkout page url
terminal_type	Yes	String(128)	WEB/WAP/APP/MINI_APP

			Uploaded from the merchant side or verified by SwiftPass checkout front end.
os_type	No	String(16)	If terminalType=WAP/APP is included when uploaded, it must be uploaded from the merchant side or verified by SwiftPass checkout. IOS/ANDROID

3.5Returned results

Returned in XML format in real-time

Variable	Required	Type	Description
version	Yes	String(8)	Version number. Default value: 2.0
charset	Yes	String(8)	Value: UTF-8
sign_type	Yes	String(16)	Value: MD5
status	Yes	String(16)	“0”: success. Other values: fail. Specifies communicating label (not transaction label). The status of a transaction is determined by the value of result_code.
message	No	String(128)	Return message. Only return when the signature verification is invalid.
The following fields will be returned when both “status” is 0			
result_code	Yes	String(16)	“0”: success; Other values: fail.
mch_id	Yes	String(32)	Specifies a unique ID assigned by platform.
nonce_str	Yes	String(32)	Random character string (no longer than 32 digits)
err_code	No	String(32)	Please refer to error code documentation
err_msg	No	String (128)	Error message description
sign	No	String(344)	See section 2 “Digital Signature”
The following fields will be returned when both status and result_code are “0”.			
pay_url	Yes	String(1024)	Alipay Plus checkout page url to pass-through to merchants/SwiftPass checkout page url
pay_info	No	String(1024)	Will return when merchant calls SDK. The field needs to be passed-through to the merchant
uuid	No	String(33)	uuid

4 Alipay Wallet Query API

4.1 Alipay Wallet Query API

4.2 Functions

Query Alipay wallet with merchant information.

4.3 Interaction mode

The interface will be called from the backend.

4.4 Request parameter list

Request url: <https://gateway.wepayez.com/pay/gateway>

Request type: POST

Request format: XML

Variable	Required	Type	Description
service	Yes	String(32)	API Type: pay.aps.query.wallet
version	No	String(8)	Version number. Default: 2.0
charset	No	String(8)	Character set, value: UTF-8
sign_type	Yes	String(16)	Signature type. Value: MD5
mch_id	Yes	String(32)	Specifies a unique ID assigned by platform.
nonce_str	Yes	String(32)	Random string no longer than 32 characters
sign	Yes	String(344)	Signature result. See section 2 “Digital Signature” for details.
terminal_type	Yes	String(128)	WEB/WAP/APP/MINI_APP Uploaded from merchant side or verified by SwiftPass checkout frontend.
os_type	No	String(16)	If terminalType=WAP/APP is included when

			uploaded, it must be uploaded from the merchant side or verified by SwiftPass checkout. IOS/ANDROID
--	--	--	--

4.5Returned results

Data will be returned in XML format in real-time

Variable	Required	Type	Description
version	Yes	String(8)	Version number. Default: 2.0
charset	Yes	String(8)	Character set, value: UTF-8
sign_type	Yes	String(16)	Signature type. Value: MD5
status	Yes	String(16)	0: Successful Other values: Failed Specifies communicating label (not transaction label). The status of a transaction is determined by the value of trade_state .
message	No	String(128)	Return message. Only return when the signature verification parameter format is invalid.
The following fields will be returned when status is "0":			
result_code	Yes	String(16)	"0": successful; Other results: failed
mch_id	Yes	String(32)	Specifies a unique ID assigned by platform.
device_info	No	String(32)	Terminal serial number
nonce_str	Yes	String(32)	Random string no longer than 32 characters
err_code	No	String(32)	Please refer to error code documentation
err_msg	No	String (128)	Error message
sign	Yes	String(344)	See section 2 "Digital Signature"
The following fields will be returned when both "status" and "result_code" are 0			
result_code	Yes	String(16)	0: Successful; Other values: failed 0 stands for successful cancellation, the order cannot be paid; if the order is already paid, it will be refunded. Other values indicate abnormal status with the cancellation API, and cancellation may be initiated again.

payment_options	No	String(2048)	Wallet list passed-through from Alipay Plus
uuid	No	String(32)	uuid

5. Query API

5.1 Order query API

5.2 Functions

Query order information based on merchant order number or platform order number.

5.3 Interaction mode

The interface will be called from the backend.

5.4 Request parameter list

Request url: `https://gateway.wepayez.com/pay/gateway`

Request type: POST

Request format: XML

Variable	Required	Type	Description
service	Yes	String(32)	API Type: unified.trade.query
version	No	String(8)	Version number. Default: 2.0
charset	No	String(8)	Character set, value: UTF-8
sign_type	Yes	String(16)	Signature type. Value: MD5
mch_id	Yes	String(32)	Merchant ID assigned by platform
out_trade_no	No	String(32)	Internal order no. in the merchant system. Please

			fill out at least one of “out_trade_no”and “transaction_id”. When both exist, “transaction_id”shall prevail.
transaction_id	No	String(32)	Platform transaction number. Please fill out at least one of “out_trade_no”and “transaction_id”. When both exist, “transaction_id”shall prevail.
nonce_str	Yes	String(32)	Random character string no longer than 32 characters.
sign	Yes	String(344)	See section 2 “Digital Signature”

5.5Return result

Variable	Required	Type	Description
version	Yes	String(8)	Version number. Default: 2.0
charset	Yes	String(8)	Character set, value: UTF-8
sign_type	Yes	String(16)	Signature type. Value: MD5
status	Yes	String(16)	0: Successful Other values: Failed Specifies communicating label (not transaction label). The status of a transaction is determined by the value of result_code
message	No	String(128)	Return message. Only return when the signature verification parameter format is invalid.
The following fields will be returned when status is “0” :			
result_code	Yes	String(16)	“0” : successful; Other results: failed
mch_id	Yes	String(32)	Specifies a unique ID assigned by platform.
device_info	No	String(32)	Terminal serial number
nonce_str	Yes	String(32)	Random character string no longer than 32 characters.

err_code	No	String(32)	Please refer to error code documentation
err_msg	No	String (128)	Error message
sign	Yes	String(344)	See section 2 “Digital Signature”
The following fields will be returned when status and result_code is “0” :			
trade_state	Yes	String(344)	SUCCESS REFUND NOTPAY CLOSED REVOKED USERPAYING PAYERROR
The following fields will be returned when both status and result_code are “0” , and trade_state is “success” or “refund”			
trade_type	Yes	String (32)	pay.aps,alipay.micropay
sub_appid	No	String	Sub-merchant appid
openid	No	String(128)	Unique symbol of user under service provider appid
sub_openid	No	String(128)	Unique symbol of user under sub-merchant of service provider appid
transaction_id	Yes	String(32)	Platform transaction number
out_transaction_id	Yes	String(32)	Alipay Plus transaction number
out_trade_no	Yes	String(32)	Unique order number in the merchant system. 5-32 characters that include only letters, numbers, and underscore. Upper and lower case sensitive.
total_fee	Yes	Int	Total amount in cents. Characters and symbols are not allowed.
coupon_fee	No	Int	Cash coupon payment amount $\leq$ Total order amount. Total order amount - Cash coupon amount = Cash payment amount
fee_type	No	String(8)	Currency type, 3-digit code under ISO 4217 standard.
attach	No	String(127)	Merchant data package to be returned unchanged
bank_type	No	String(16)	Bank type
time_end	Yes	String(14)	Payment completion time. Format: yyyyMMddhhmmss. E.g. 09:10:10, December 27, 2009 will be written as 20091227091010. Time zone: GMT+8 Time is taken from platform server.
local_fee_type	No	String(8)	Merchant pricing currency. E.g. HKD

local_total_fee	No	Int	Merchant pricing amount
order_fee	Yes	Int	Order amount (in pricing currency)
uuid	No	String(64)	uuid

Data returned in XML format in real-time.

6. Refund API

6.1 Refund API

6.2 Functions

Initiate refund according to the request order number

6.3 Interaction model

The interface will be called from the backend.

6.4 Request parameter list

Request url: <https://gateway.wepayez.com/pay/gateway>

Requested in POST XML

Variable	Required	Type	Description
service	Yes	String(32)	API Type: unified.trade.refund
version	No	String(8)	Version number. Default: 2.0
charset	No	String(8)	Character set, value: UTF-8
sign_type	Yes	String(16)	Signature type. Value: MD5
mch_id	Yes	String(32)	Specifies a unique ID assigned by platform.

out_trade_no	No	String(32)	Internal order no. in the merchant system. Please fill out at least one of “out_trade_no” and “transaction_id”. When both exist, “transaction_id” shall prevail.
transaction_id	No	String(32)	Platform transaction number. Please fill out at least one of “out_trade_no” and “transaction_id”. When both exist, “transaction_id” shall prevail.
out_refund_no	No	String(32)	Unique merchant refund order number no longer than 32 characters (letters are allowed). Requests made under the same refund order ID can only be refunded once. If refund is unsuccessful, please request again using the same refund order ID.
total_fee	Yes	Int	Total amount in cents.
refund_fee	Yes	Int	Total refund amount in cents. Partial refund is available.
op_user_id	Yes	String(32)	Operator account (as merchant ID by default)
refund_channel	No	String(16)	Value: ORIGINAL
nonce_str	Yes	String(32)	Random string no longer than 32 characters
sign	Yes	String(344)	See section 2 “Digital Signature”

6.5Returned results

Data will return in XML format in real-time.

Variable	Required	Type	Description
version	Yes	String(8)	Version number. Default: 2.0

charset	Yes	String(8)	Character set, value: UTF-8
sign_type	Yes	String(16)	Signature type. Value: MD5
status	Yes	String(16)	0: Successful Other values: Failed Specifies communicating label (not transaction label). The status of a transaction is determined by the value of trade_state .
message	No	String(128)	Return message. Only return when the signature verification parameter format is invalid.
The following fields will be returned when status is "0" :			
result_code	Yes	String(16)	0: Successful Other values: Failed
mch_id	Yes	String(32)	Merchant ID specified by the platform
device_info	No	String(32)	Terminal serial number
nonce_str	Yes	String(32)	Random string no longer than 32 digits
err_code	No	String(32)	Please refer to the error code list
err_msg	No	String (128)	Error message
sign	Yes	String(344)	See section 2 "Digital Signature" for more details
The following fields will be returned when both "status" and "result_code" are 0			
transaction_id	Yes	String(32)	Platform transaction order number
out_trade_no	No	String(32)	Internal order number in merchant system
out_refund_no	Yes	String(32)	Merchant refund order number
refund_id	Yes	String(32)	Platform refund order number
refund_fee	Yes	Int	Total refund amount in cents. Partial refund is available.
total_fee	No	Int	Total amount (in agent defined currency)
fee_type	No	String(8)	Agent designated currency
order_fee	No	Int	Order amount
local_total_fee	No	Int	Merchant pricing amount
local_total_type	No	String(8)	Merchant pricing currency
out_transaction_id	No	String(32)	Third party order number (Alipay Plus)

trade_type	No	String(32)	Transaction type such as: pay.aps.alipay.native/./
------------	----	------------	---

7 Refund Query API

7.1 Functions

Query platform order information with merchants' refund order number

7.2 Interaction model

The interface will be called from the backend.

7.3 Request parameter list

Request url: <https://gateway.wepayez.com/pay/gateway>

Request type: POST

Request format: XML

Variable	Required	Type	Description
service	Yes	String(32)	API type: unified.trade.refundquery
version	No	String(8)	Version number. Default: 2.0
charset	No	String(8)	Character set, value: UTF-8
sign_type	Yes	String(16)	Signature type. Value: MD5
mch_id	Yes	String(32)	Specifies a unique ID assigned by platform.
out_trade_no	No	String(32)	Internal order no. in the merchant system. Please fill out at least one of “out_trade_no” and “transaction_id”.

			When both exist, “transaction_id” shall prevail.
transaction_id	No	String(32)	Platform transaction number. Please fill out at least one./ of “out_trade_no” and “transaction_id”. When both exist, “transaction_id” shall prevail.
nonce_str	Yes	String(32)	Random character string no longer than 32 characters.
sign	Yes	String(344)	See section 2 “Digital Signature”
out_refund_no	No	String(32)	Unique refund order number in the merchant system with 32 digits. Letters are allowed.
refund_id	No	String(32)	Platform refund ID. One of refund_id, out_refund_no, out_trade_no, transaction_id is required. If all four exist at the same time, the priority will be: refund_id > out_refund_no > transaction_id > out_trade_no At least one among out_refund_no and refund_id must exist.

7.4Returned results

Data will be returned in XML format in real-time.

Variable	Required	Type	Description
version	Yes	String(8)	Version number. Default: 2.0
charset	Yes	String(8)	Character set, value: UTF-8
sign_type	Yes	String(16)	Signature type. Value: MD5
status	Yes	String(16)	0: Successful Other values: Failed Specifies communicating label (not transaction label). The status of a transaction is determined by the value of trade_state .

message	No	String(128)	Return message. Only return when the signature verification parameter format is invalid.
The following fields will be returned when status is "0" :			
result_code	Yes	String(16)	0: Successful Other values: failed
mch_id	Yes	String(32)	Merchant ID specified by the platform
device_info	No	String(32)	Terminal serial number
nonce_str	Yes	String(32)	Random string no longer than 32 characters
err_code	No	String(32)	Please refer to error code list
err_msg	No	String (128)	Error message
sign	Yes	String(344)	See section 2 "Digital Signature"
The following fields will be returned when both "status" and "result_code" are 0			
transaction_id	Yes	String(32)	Platform transaction order number
out_transaction_id	No	String(64)	Third party order number (returned when payment is successful, and no returns if otherwise)
out_refund_no_0	Yes	String(32)	Merchant refund order number
refund_id_0	Yes	String(32)	Platform refund order number
refund_channel_0	Yes	String(16)	Value: ORIGINAL
refund_fee_0	Yes	Int	Total refund amount in cents. Partial refund is available.
refund_status_0	Yes	String(16)	Refund status: SUCCESS - Refund successful FAIL - Refund failed PROCESSING - Refund processing NOTSURE - Uncertain status. Merchant must re-initiate the refund with the original order number CHANGE - Refund fails due to the suspension or freezing of the original payment bank account. Merchant needs to manually refund

			by onsite or platform transfer
total_fee	No	Int	Total amount (in payment channel currency)
fee_type	No	String(8)	Order channel currency
order_fee	No	Int	Order amount
local_total_fee	No	Int	Merchant pricing amount
local_total_type	No	String(8)	Merchant pricing currency
out_transaction_id	No	String(32)	Third party order number (Alipay Plus)
trade_type	No	String(32)	E. g. : pay.aps.alipay.native/./
refund_time_0	No	String(16)	yyyyMMddHHmmss

8 Notification API

8.1 Notification API

8.2 Notification result parameter list

The notification URL is the parameter notify_url submitted in the single interface. After the payment is completed, the platform will send the relevant payment and user information to the URL, and the merchant needs to receive the processing information. When interacting with the background notification, if the platform receives a response from the merchant that is not a pure string success or returns after more than 5 seconds, the platform considers the notification failed, and the platform will indirectly re-initiate the notification through a certain strategy (**notification frequency: 0/15/30/180/1800/1800/1800/1800/3600, unit: seconds**), so as to improve the success rate of the notification as much as possible, but it does not guarantee that the notification will ultimately succeed.

The same notification may be sent to the merchant system multiple times due to the re-sending of background notifications. **The merchant system must be able to correctly handle duplicate notifications.** It is recommended that when receiving a notification for processing, the status of the corresponding business data is first checked to determine whether the notification has been processed. If not, the notification shall be processed again. If processed, the result is returned to success directly. Before checking and processing the status of business data, concurrency control should be implemented by using data locks to avoid data confusion caused by function reentry.

Note: When merchant backend receives notification parameter, it needs to verify the order and amount using out_trade_no and total_fee in the parameter first, then

update database order status when the verification is completed.

Backend notification will be posted to merchant system via notify_url in the request

(parameter will be character string in XML)

Variable	Required	Type	Description
version	Yes	String(8)	Version number. Default: 2.0
charset	Yes	String(8)	Character set, value: UTF-8
sign_type	Yes	String(16)	Signature type. Value: MD5
status	Yes	String(16)	0: Successful Other values: Failed Specifies communicating label (not transaction label). The status of a transaction is determined by the value of result_code .
message	No	String(128)	Return message. Only return when the signature verification parameter format is invalid.
The following fields will be returned when status is "0" :			
result_code	Yes	String(16)	"0" : successful; Other results: failed
mch_id	Yes	String(32)	Specifies a unique ID assigned by platform.
nonce_str	Yes	String(32)	Random character string no longer than 32 characters.
err_code	No	String(32)	Please refer to error code documentation
err_msg	No	String (128)	Error message
sign	Yes	String(344)	See section 2 "Digital Signature"
The following fields will be returned when both "status" and "result_code" are 0			
trade_type	Yes	String(32)	pay.aps.alipay.native
pay_result	Yes	Int	Payment result: "0" : Successful; Other values: Failed
transaction_id	Yes	String(32)	Platform order number
out_transaction_id	Yes	String(64)	Third party order number
out_trade_no	Yes	String(32)	Unique order number within 32 characters in the

			merchant system. Can include only letters, numbers, and underscore. Upper and lower case sensitive.
total_fee	Yes	Int	Total amount in cents. Characters and symbols are not allowed.
fee_type	Yes	String(8)	Currency type, 3-digit code under ISO 4217 standard.
time_end	Yes	String(14)	Payment completion time. Format: yyyyMMddhhmmss. E.g. 09:10:10, December 27, 2009 will be written as 20091227091010. Time zone: GMT+8

8.3 Backend feedback

Platform server sends the notification, post sends XML data flow, and merchant receives the notification via notify_url. Merchants needs to provide feedback of business process in pure character string with the following content:

Returned result	Description
success	Processing successful. No further notifications afterwards.
fail or other values	Processing unsuccessful. System will notify again.

9. Notes

1. All amount units are in cents, and the smallest unit is 1 cent. Decimals are not allowed.
2. notify_url means that the platform server directly initiates a request to the merchant server from the background, and the merchant cannot check the cookie or session of the user when processing; Shipping processes such as merchant updating DB need to be completed after notify_url to ensure that platform replenishment can be successfully completed when the order is dropped
3. notify_url may be notify repeatedly. The merchant needs to reprocess to avoid multiple

shipments.

4. For the notification received by notify_url, if the merchant has successfully processed or checked the order, it is necessary to return the pure string success to indicate successful processing. The string success is not case-sensitive. If we do not receive the returned success, our server will continue to send you the notice and will not give you any further notice after three hours. Assuming that all orders have not returned to success, it will increase the notification load on our server. At worst, it may cause a delay in notifying the merchants normally; In addition, we will urge you to improve the situation. If no improvement is made, the research and development or operation and maintenance technology will take control measures over the payment interface.
5. If yes is required among the returned parameters, it will be returned; if no is required, it will not always be returned. **The actual returned parameters may not be exactly the same as the document due to upgrade or configuration, and must be based on the actual received parameters.**

6. Other issues to note

(1) Case issue

Please pay attention to the case in the document. E.g. **"For the sake of comparison, the signature result will be converted to upper case letters"**.

(2) Parameter format

All incoming parameter will be character string Type, please be aware of the requirements in the documents.

(3) Time stamp

Please use Linux time stamp in character string format.

(4) Pay with the same merchant order number

Failed payment shall be paid again with a new order number. Thus, a validity time shall be set for the original order number.