

Source: EAVision J100 User Manual (2024), Specifications & Lifting precautions. Drone max payload entered by YOU (manual max lift 60 kg). Altitude above 1000 m ASL: reduce allowed payload by 2.5 kg per 500 m (or part) above 1000 m. Temp -10 to 45 °C; humidity 30 to 90% RH. No further temp/humidity payload derating in the manual.

1

Load

What you're lifting

Load weight (kg)

Rigging weight (kg) line+hook+slings

Line length (m)

Line type

TOTAL lifted (kg)

☐ Synthetic ☐ Steel ☐ Chain ☐ Other _____

Total = load + rigging

2

Capacity

Drone max payload (kg) - max 60

Weakest rigging rating (kg)

Temp (°C) -10..45

Humidity (%) 30..90

Altitude (m ASL)

If alt > 1000: reduction = ceil((alt-1000)/500)×2.5 kg. Allowed = payload - reduction. Compare total to LESSER of (allowed, weakest).

Altitude working: _____ Allowed drone payload _____ kg

Total ≤ lesser limit? ☐ Yes ☐ No

☐ GREEN

☐ RED - DO NOT LIFT

3

Flight

Distance (m)

Height (m)

People ☐ Y ☐ N Roads ☐ Y ☐ N Water ☐ Y ☐ N

Powerlines? ☐ Y ☐ N if Y height _____ m Trees? ☐ Y ☐ N if Y height _____ m

4

Weather

Your wind limit

Unit

Wind now

Gust

Wind & gust ≤ limit? ☐ Yes ☐ No - OVER LIMIT

5

Quick checks (tick all 15)

☐ Props

☐ Batteries

☐ Hook release test

☐ Line condition

☐ Rigging inspected – no damage

☐ Load rigged & secure

☐ Hover test

☐ Area clear

☐ Landing zones clear & guarded

☐ Observer in place

☐ NavDrone plan active

☐ Height under 30 m / speed under 7 m/s (manual)

☐ Route does not cross wires

☐ Battery swap at 30%

☐ Load weighed (no unknown weight)

GO only if ALL true:

- Capacity GREEN (total ≤ lesser of allowed drone payload and weakest rigging; payload ≤ 60 kg)
- Temp/humidity in range (if entered); wind & gust within limit
- All 15 quick checks ticked (incl. manual flight limits, no wires, battery 30%, load weighed)
- Powerlines/trees: if Yes, height written

☐ GO

☐ NO-GO