

---

# Quantization-free Lossy Image Compression Using Integer Matrix Factorization

---

**Pooya Ashtari<sup>1\*†</sup>**  
pooya.ashtari@esat.kuleuven.be

**Pourya Behmandpoor<sup>1†</sup>**  
pooya.ashtari@esat.kuleuven.be

**Fateme Nateghi Haredasht<sup>2</sup>**  
fnateghi@stanford.edu

**Jonathan H. Chen<sup>2</sup>**  
jonc101@stanford.edu

**Lieven De Lathauwer<sup>1</sup>**  
lieven.delathauwer@kuleuven.be

**Sabine Van Huffel<sup>1</sup>**  
sabine.vanhuffel@esat.kuleuven.be

<sup>1</sup>Department of Electrical Engineering (ESAT), STADIUS Center, KU Leuven, Belgium

<sup>2</sup>Department of Medicine, Stanford University, Stanford, CA, USA

---

\*Corresponding author. Emails: pooya.ashtari@esat.kuleuven.be, pooya.ash@gmail.com


<sup>†</sup>Equal contribution

## **Abstract**

one paragraph

## **1 Introduction**

## **2 Related Work**



**Figure 1** An illustration of our image compression method based on integer matrix factorization.

### 3 Method

#### 3.1 Overall Framework

**Encoder.**

**Decoder.**

#### 3.2 Integer Matrix Factorization (IMF)

#### 3.3 Block Coordinate Descent Scheme for IMF

**Theorem 1.** *The IMF cost function,  $\|X - UV^T\|_F^2$ , is monotonically nonincreasing under each of the multiplicative update rules.*

*Proof.* See Appendix A for the proof. □

#### 3.4 Implementation Details

(a)

(b)

**Figure 2** Rate-distortion performance on the Kodak dataset. In panels (a) and (b), the average PSNR and SSIM are plotted against bits per pixel (bpp), respectively.

(a)

(b)

**Figure 3** Rate-distortion performance on the CLIC dataset. In panels (a) and (b), the average PSNR and SSIM are plotted against bits per pixel (bpp), respectively.

## 4 Experiments

### 4.1 Rate-Distortion Performance

### 4.2 ImageNet Classification Performance

### 4.3 Ablation Studies

**Patchification.** without patchification, patch size 4, 8, 16, 32

**Factor bounds.**

**BCD iteration.**

(a)

(b)

**Figure 4** Impact of different compression methods on ImageNet classification accuracy. Panels (a) and (b) show the validation top-1 and top-5 accuracy plotted against bits per pixel (bpp), respectively. A ResNet-50 model pretrained on the original ImageNet images was evaluated using validation images compressed by different methods.

## **5 Conclusion and Future Work**



## **Acknowledgments and Disclosure of Funding**

## References

- [1] Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4RL: Datasets for deep data-driven reinforcement learning. *arXiv preprint arXiv:2004.07219*, Apr 2020.

## A Proof of Theorem 1

## **B Ablation Study on Color Space Transformation**