

# System design

## Part I

**System design** is the process of **planning and designing the overall architecture** of a software system—how different components interact, scale, store data, handle traffic, stay secure, and remain reliable.

Overall: How should we build this system so it works efficiently, reliably, at scale.

### **What System Design Includes?**

#### **1. Architecture:**

How components fit together:

- Client → Backend → Database
- Monolithic
- Microservices
- Event-driven systems
- APIs and communication patterns

#### **2. Scalability:**

How to handle more users:

- Horizontal and vertical scaling
- Load Balancer
- Caching
- Sharding
- Replication

#### **3. Data Storage:**

Choosing the right DB:

- SQL
- NoSQL
- Distributed databases
- Indexing
- Partitioning

#### **4. Performance:**

- Caching (Redis/Memcached)
- CDN
- Queues (Kafka/RabbitMQ)
- Asynchronous processing

#### **5. Reliability:**

Ensuring system is always available:

- Failover
- Replication
- Redundancy
- Backups
- Avoiding single points of failure

## 6. Security:

- Authentication
- Authorization
- Encryption
- Rate limiting
- Secure API design

## Why System Design Is Needed?

Because real apps must handle:

- Millions of users
- High throughput (Throughput is a measure of the actual amount of data successfully transmitted or processed by a system in a given time frame)
- Low latency (very little delay)
- Fault tolerance (system keeps working even when some parts fail)
- Rapid scaling
- Data consistency

## Describe every Points:

### 1. Client → Backend → Database:

The most common flow:

- **Client (browser/app)** sends requests
- **Backend (server)** processes logic
- **Database** stores/returns data
- Can include middle layers like API gateway or service mesh

### 2. Microservices:

- Application is broken into **small independent services**
- Each service does one job (e.g., user service, payment service)
- They communicate via APIs or messaging
- Each service can be deployed independently
- Each service can use a **different programming language**
- Databases can be **separate per service**
- Easier to scale individual services
- Failure in one service doesn't break the entire app

### 3. Monolith:

- The entire application is **one single codebase**
- All features tightly connected
- Simple to develop initially, harder to scale as it grows
- If one-part crashes, whole system may go down

### 4. Event-driven systems:

A system where **something happens (an event)** → and that **triggers another action automatically**.

- Components communicate via **events**
- Example: "Order Placed" → triggers "Payment Processing" → triggers "Send Email"
- Very good for asynchronous workflows
- Useful for real-time actions (notifications, logs, analytics)

- Uses message brokers (Kafka, RabbitMQ)
- Loose coupling → systems depend on **events**, not on direct calls
- High throughput and fault-tolerant

Event: **User places an order**

This single event triggers many other tasks:

- Deduct money
- Reduce inventory
- Send email
- Notify warehouse
- Update analytics
- Generate invoice

5. APIs & communication patterns:

- REST, GraphQL, gRPC
- How services talk to each other
- Defines request/response formats and communication style (sync/async)
- Synchronous: REST/gRPC (client waits for response)
- Asynchronous: events/queues (client does not wait)
- Helps define service boundaries
- API Gateway routes, validates, and secures calls

6. Horizontal vs Vertical scaling:

- **Vertical:** Add more power to the same machine (more CPU/RAM)
- **Horizontal:** Add more machines and distribute load (preferred at scale)
- Horizontal scaling supports **infinite growth**
- Vertical scaling has hardware limits

7. Load balancers:

- Distribute incoming requests across multiple servers
- Prevents any one server from being overloaded
- Prevent system overload
- Enable zero-downtime deployment
- Can perform health checks

8. Caching:

- Store frequently used data in memory (Redis, Memcached)
- Reduces database load and makes response faster
- Reduces server load
- Improves latency
- Can be used at DB level, API level, or CDN level

9. Sharding:

- Splitting data across multiple databases
- Good for huge datasets (millions of rows)
- Reduces DB bottleneck
- Requires careful key selection
- Example: users A–K in DB1, L–Z in DB2

10. Replication:

- Having multiple copies of the same database
- Helps with read scaling and redundancy
- Helps with read-heavy systems

- Provides high availability
  - Supports multi-region systems
11. SQL:
- Structured data
  - ACID transactions
  - Good for finance, orders, critical systems
  - Ensures strong consistency
  - Good for complex queries (joins, transactions)
12. NoSQL:
- Flexible schema
  - Supports huge scale
  - Good for logs, social networks, real-time apps
  - Handles unstructured data
  - Best for large-scale distributed systems
13. Distributed databases:
- Data stored across multiple nodes
  - Systems like Cassandra, CockroachDB
  - Designed for global scale
  - Provide automatic failover
  - Ensure data durability across nodes
14. Indexing:
- Speeds up search queries by creating quick-lookup data structures
  - Like an index at the back of a book
  - Slows down writes but speeds up reads
  - Critical for search-heavy apps
15. Partitioning:
- Splitting large tables into smaller parts
  - Improves performance and manageability
  - Avoids huge table performance degradation
  - Helps query only relevant partitions (faster reads)
16. Caching (Redis/Memcached):
- Store hot data in memory
  - Avoid hitting the database frequently
  - In-memory = fastest
  - Reduces database cost
17. CDN (Content Delivery Network):
- Stores static content (images, CSS, videos) near the user
  - Reduces latency globally
  - Offloads traffic from origin server
  - Essential for global applications
18. Queues (Kafka/RabbitMQ):
- Used for asynchronous tasks
  - Helps handle spikes in traffic
  - Smoothens traffic spikes
  - Ensures reliability during failures
  - Example: send email, generate report, process notifications

19. Asynchronous processing:

- Background jobs handle heavy work
- Keeps the main request fast
- Keeps UI responsive
- Ideal for long-running tasks

20. Failover:

- When a primary server fails, automatically switch to a backup server
- Can be active-active or active-passive
- Ensures system stays online

21. Replication:

- Multiple copies of data to avoid loss and ensure availability
- Creates durability
- Helps recovery during disasters

22. Redundancy:

- Duplicate components (servers, databases, networks)
- If one breaks, another takes over
- Used at multiple layers (network, servers, databases)

23. Backups:

- Periodic snapshots of data
- Used for disaster recovery
- Cold backups, warm backups, snapshots

24. Avoiding single points of failure:

- No single component should bring the whole system down
- Redundant servers, multi-AZ, multi-region setups
- Use multiple servers in different availability zones (AZs)

25. Authentication:

- Verifying who the user is
- Includes MFA (multi-factor authentication)
- Example: login with email/password, OAuth, tokens

26. Authorization:

- Verifying what the user is allowed to do
- Roles and permissions
- RBAC (Role-based access control)
- Example: admins vs normal users

27. Encryption:

- Secure data so no one can read it without the key
- Encryption at rest + encryption in transit
- HTTPS, encrypted database fields

28. Rate limiting:

- Restrict how many requests a user can make
- Protects against abuse/DDOS attacks
- Prevents brute-force login attempts
- Protects against API spamming

29. Secure API design:

- Input validation
- Avoid SQL injection
- Token-based access
- Proper error handling
- Should log suspicious behaviour
- Should hide sensitive error messages



**In next part, we will discuss about every single point in details**