

Buckling and dynamic collapse of the bicycle wheel

M. Ford^{*}, J.M. Papadopoulos[#], O. Balogun[†]

^{*} Department of Mechanical Engineering
Northwestern University
2145 Sheridan Road, Evanston, IL 60208, USA
e-mail: mford@u.northwestern.edu

[#] Department of Mechanical and Industrial Engineering
Northeastern University
360 Huntington Ave., Boston, MA 02115, USA
e-mail: j.papadopoulos@neu.edu

[†] Department of Civil Engineering
Northwestern University
2145 Sheridan Road, Evanston, IL 60208, USA
e-mail: o-balogun@northwestern.edu

ABSTRACT

The first page begins with the title of the paper, the authors, affiliations, abstract and keywords as it is shown in this document. The title of the paper should be typed in 14 pt bold font and be centred. It should be separated from the symposium name by a 12 pt space and from authors' names by an 18 pt space. Authors' names should be typed in bold font. Affiliations should be typed in a general formatting style, centred within a corresponding bounding box. The abstract part of the final paper should not be longer than about 300 words, so it fits on the title page. The abstract begins with the "ABSTRACT" header typed in bold 11 pt font. The abstract text should be separated from the header by an 11 pt space. The abstract should be followed by a list of keywords after the header "Keywords:" typed in bold 11 pt font. The keywords should be separated by commas. A dot should be placed after the last keyword. Up to about five keywords are allowed. Title, affiliations, abstract and keywords have to fit on the title page. The Introduction paragraph may start already on the title page provided there is enough space.

Keywords: bicycle wheel, buckling, bifurcation.

1 INTRODUCTION

The bicycle wheel is a prestressed structure and is susceptible to buckling under internal forces. As the spokes are tightened uniformly, the rim deforms radially to accommodate the spoke strain. At a critical tension, the system reaches a bifurcation point and the rim buckles out of its initial plane. The post-buckling configuration is generally stable and the original shape of the wheel can be recovered by reducing the tension. Buckling can also be triggered by external forces in an otherwise stable wheel leading to a release of strain energy. This is an unstable process which generally leads to catastrophic failure.

Despite its implications for wheel strength, the buckling problem has never received a rigorous treatment to our knowledge. Jobst Brandt alludes to buckling in his practical manual for wheel-builders [1]:

“If the wheel becomes untrue in two large waves during stress relieving, the maximum, safe tension has been exceeded. Approach this tension carefully to avoid major rim distortions. When the wheel loses alignment from stress relieving, loosen all spokes a half turn before retrueing the wheel.”

He did not discuss the problem further, but suggested that wheel failure commonly occurs due to a loss of lateral stability caused by spoke buckling. Pippard and Francis [2] derived a model for lateral stiffness based on the elastic foundation model, but did not discuss stability and neglected any effects of spoke tension.

Flexural-torsional buckling of rings can be treated as a special case of buckling of arches, where the included angle is allowed to go to 2π . Timoshenko and Gere [3] gave a formula for the critical load for a ring with doubly-symmetric cross-section subjected to radial loads. The theory of flexural-torsional buckling of monosymmetric arches (bicycle rims have only one plane of symmetry) was broadly formalized by Trahair and Papangelis [4] using the virtual work approach to derive the equilibrium and stability equations. Their theory has been extended to treat arches restrained by continuous [5] or discrete [6] elastic supports and elastic end restraints [7].

The problem of the prestressed bicycle wheel is unique for a number of reasons. First, the buckling load is internal to the structure. Second, the spokes act both as elastic restraints resisting buckling and as prestressing elements causing buckling. Third, the lateral, radial, and torsional restraining actions of the spokes are coupled—i.e. lateral deflection at a spoke may produce lateral, radial, and torsional reactions. These considerations extend to other structural systems. Large observation wheels such as the London Eye [8] and the Singapore Flyer [9] resemble large bicycle wheels and achieve lateral stability due to the bracing angle of prestressed cables, and must be designed against flexural-torsional buckling.

Here we derive a general theory for buckling of a spoked bicycle wheel under self-tension and investigate several special cases. Furthermore, we analyze large deformation post-buckling behavior and show how local buckling of individual spokes can lead to collapse of an otherwise sub-critical wheel.

2 DEFORMATION OF THE WHEEL

2.1 Rim equations

The rim is modeled as an initially circular beam with a constant cross-section.

2.2 Spoke equations

In this paper we consider bicycle wheels with slender prestressed spokes. We model a single spoke as an elastic bar pinned at each end. This ensures that the spoke force is always collinear with the spoke axis. We fix our global coordinate system to the hub, which is assumed to be rigid. Therefore, the displacement of the hub node of a spoke is zero. The linearized elongation of a spoke is given by

$$\Delta l = \mathbf{u}_n \cdot \hat{\mathbf{n}}_1 \quad (1)$$

where \mathbf{u}_n is the displacement vector of the spoke nipple and $\hat{\mathbf{n}}_1$ is a unit vector pointing from the spoke nipple to the hub eyelet. The linearized rotation of the spoke is given by

$$\Omega_1 = \frac{1}{l} \mathbf{u}_n \cdot \hat{\mathbf{n}}_2 \quad (2)$$

$$\Omega_2 = \frac{1}{l} \mathbf{u}_n \cdot \hat{\mathbf{n}}_3 \quad (3)$$

where $\hat{\mathbf{n}}_2$ and $\hat{\mathbf{n}}_3$ are two orthogonal unit vectors orthogonal to $\hat{\mathbf{n}}_1$, and l is the spoke length.

The elongation produces a net force on the rim parallel to the original spoke axis equal to

$$f_1 = \left(\frac{E_s A_s \Delta l}{l} \hat{\mathbf{n}}_1 \right) = \frac{E_s A_s}{l} \hat{\mathbf{n}}_1 \cdot \mathbf{u}_n \quad (4)$$

The rotation of the spoke produces net forces on the rim perpendicular to the original spoke axis due to the rotation of the initial tension vector.

$$f_2 = T \sin \Omega_1 \approx \frac{T}{l} \hat{\mathbf{n}}_2 \cdot \mathbf{u}_n \quad (5)$$

$$f_3 = T \sin \Omega_2 \approx \frac{T}{l} \hat{\mathbf{n}}_3 \cdot \mathbf{u}_n \quad (6)$$

since $\hat{\mathbf{n}}_1, \hat{\mathbf{n}}_2, \hat{\mathbf{n}}_3$ are mutually orthogonal, the total force on the rim is given by $\mathbf{f} = \mathbf{k}_f \cdot \mathbf{u}_n$, where the spoke stiffness matrix is given by

$$\mathbf{k}_f = \frac{E_s A_s}{l} \hat{\mathbf{n}}_1 \hat{\mathbf{n}}_1 + \frac{T}{l} (\hat{\mathbf{n}}_2 \hat{\mathbf{n}}_2 + \hat{\mathbf{n}}_3 \hat{\mathbf{n}}_3) \quad (7)$$

The first term in Eqn. 7 is the **elastic stiffness** and the second term is the **tension stiffness**. The tension stiffness is the component responsible for the transverse vibrations of a guitar string, e.g.

Following the approach of Smith [10] and Pippard [2], we will approximate the spoke system as a continuum which exerts a distributed load on the rim. The stiffness per unit length is defined by the sum of the spoke stiffnesses in one periodic grouping of spokes, divided by the arc length of the grouping.

$$\bar{\mathbf{k}} = \frac{1}{2\pi R} \left(\frac{n_s}{n_p} \right) \sum_i^{n_p} \mathbf{k}_{f,i} \quad (8)$$

3 CONCLUSIONS

...

REFERENCES

- [1] Brandt, J. The Bicycle Wheel (Avocet, Palo Alto, CA, 1993), 3rd edn.
- [2] Pippard, A. S. & Francis, W. The Stresses in a Wire Wheel under Side Loads on the Rim. Philos. Mag. **14**, 436–445 (1932).
- [3] Timoshenko, S. P. & Gere, J. M. Theory of Elastic Stability (McGraw-Hill, New York, NY, 1961), 2nd edn.
- [4] Trahair, N. S. & Papangelis, J. P. Flexural-torsional buckling of monosymmetric arches. J. Struct. Eng. **113**, 2271–2288 (1987).
- [5] Pi, Y.-L. & Bradford, M. Elastic flexural-torsional buckling of continuously restrained arches. Int. J. Solids Struct. **39**, 2299–2322 (2002).
- [6] Bradford, M. A. & Pi, Y.-L. Elastic Flexural-Torsional Buckling of Discretely Restrained Arches. J. Struct. Eng. **128**, 719–727 (2002).

- [7] Guo, Y. L., Zhao, S. Y., Dou, C. & Pi, Y. L. Out-of-Plane Elastic Buckling of Circular Arches with Elastic End Restraints. J. Struct. Eng. **140**, 9 (2014).
- [8] Mann, A., Thompson, N. & Smits, M. Building the British Airways London Eye. Proc. Inst. Civ. Eng. - Civ. Eng. **144**, 60–72 (2001).
- [9] Allsop, A., Dallard, P. & McNiven, B. The Singapore Flyer and Design of Giant Observation Wheels, Singapore. Struct. Eng. Int. **19**, 12–16 (2009).
- [10] Smith, B. A. The Bicycle Wheel. Rep. Aust. As. **8**, 197–203 (1901).