dastaZ80 Mark II
Programmer's Reference Guide

Disclaimer

The products described in this manual are intended for educational purposes, and should not be used for controlling any machinery, critical component in life support devices or any system in which failure could result in personal injury if any of the described here products fail.

These products are subject to continuous development and improvement. All information of a technical nature and particulars of the products and its use are given by the author in good faith. However, it is acknowledged that there may be errors or omissions in this manual. Therefore, the author cannot accept any liability for any loss or damage arising from the use of any information or particulars in this manual.

Licenses

Document Conventions

The following conventions are used in this manual:

MUST	MUST denotes that the definition is and absolute requirement.
SHOULD	SHOULD denotes that it is recommended, but that there may exist valid reasons to ignore it.
DEVICE	Device names are displayed in bold all upper case letters, and refer to hardware devices.
`Courier`	Text appearing in the `Courier` font represents either an OS System Variable a Z80 CPU Register or a Z80 Flag. OS System Variables are identifiers for specific **MEMORY** addresses that can be used to read statuses and to pass information between routines or programs.
`0x14B0`	Numbers prefixed by 0x indicate an Hexadecimal value. Unless specified, memory addresses are always expressed in Hexadecimal.
F_abcdef	Text starting with F_ refers to the name of an OS routine that can be called via Jumpblocks.
jp abcdef	Refers to the Z80 mnemonic for *jump*, which transfers the CPU Program Counter to a specific **MEMORY** address.

The SD card is referred as **DISK**.

The Floppy Disk Drive is referred as **DISK** or as **FDD**.

The 80 column text VGA output is referred as **CONSOLE** or as **High Resolution Display**.

The 40 column graphics Composite Video output is referred as **Low Resolution Display**.

The Operating System may be referred as DZOS, dzOS or simply OS.

MEMORY refers to both **ROM** and **RAM**.

Memory used by the **Low Resolution Display** is referred as **VRAM** (Video RAM).

In the list of routines, the **Destroys** lists the **CPU** registers and **MEMORY** System Variables that are destroyed by the routine in question. But bare in mind that a routine may call other routines that may destroy other registers and variables. Refer to the **Calls** list to check the entire flow. By *Destroys* is understood that the listed register or variable value is overwritten within the routine.

Related Documentation

- dastaZ80 User's Manual[1]
- dastaZ80 Technical Reference Manual[2]
- dzOS Github Repository[3]

Contents

1 Memory Map

1.1 ROM

The **ROM** is a 16KB EEPROM, and is divided as follows:

Address		Description		Size (bytes)
`0x0000`	`0x0007`	Cold Boot	**BIOS**	8
`0x0008`	`0x0216`	init SIO/2		527
`0x0217`	`0x133F`	BIOS code		4,393
`0x1340`	`0x2663`	Kernel code	**Kernel**	4,900
`0x2653`	`0x2663`	dzOS version build		17
`0x2664`	`0x3A24`	CLI code	**CLI**	5,057
`0x3A25`	`0x3A52`	Bootstrap	**BOOTSTRAP**	46
`0x3A53`	`0x3DAA`	VDP dastaZ80 Logo		856
`0x3E7A`	`0x3EFD`	BIOS Jumpblock	**Jumpblocks**	132
`0x3EFE`	`0x3FFF`	Kernel Jumpblock		258

1.2 RAM

The **RAM** is a 64KB SRAM, and is divided as follows:

Address		Description	Size (bytes)
`0x4000`	`0x401F`	**Stack**	32
`0x4020`	`0x4174`	**System Variables**	356
`0x4184`	`0x421F`	**Reserved for future use**	156
`0x4220`	`0x441F`	**DISK Buffer**	512
`0x4420`	`0xFFFF`	**Free RAM**	48,096

1.2.1 Stack

A *Stack* is a list of words (2 bytes) that uses Last In First Out (LIFO) access method. It is used by the **CPU** to keep track of **MEMORY** addresses when executing a *call* instruction.

The programmer can also store (*PUSH*) or retrieve (*POP*) values on/from the top of the stack.

Usage of the Stack requires very careful attention. doing (*PUSH*) without the corresponding (*POP*) or vice versa, will set the CPU on the wrong path of execution. Most of the time just hanging the computer, but also potentially destroying information if an access to disk is triggered by the wrong call.

1.2.2 System Variables (SYSVARS)

The area of **RAM** called *System Variables (SYSVARS)* is an area heavily used by the OS, but it can also be used by a program to communicate with the OS.

The area has been *split* as follows:

- **SIO**
  - `0x4020` - **SIO_CH_A_BUFFER** (64 bytes): Buffer for SIO Channel A.
  - `0x4060` - **SIO_CH_A_IN_PTR** (2 bytes)
  - `0x4062` - **SIO_CH_A_RD_PTR** (2 bytes)
  - `0x4064` - **SIO_CH_A_BUFFER_USED** (1 byte)
  - `0x4065` - **SIO_CH_B_BUFFER** (64 bytes): Buffer for SIO Channel B.
  - `0x40A5` - **SIO_CH_B_IN_PTR** (2 bytes)
  - `0x40A7` - **SIO_CH_B_RD_PTR** (2 bytes)
  - `0x40A9` - **SIO_CH_B_BUFFER_USED** (1 byte)
- **DISK Superblock**
  - `0x40AA` - **DISK_is_formatted** (1 byte): tells to the OS if the **DISK** can be used.
    - `0xFF` = formatted with *DZFS*.
    - `0x00` = not formatted.
  - `0x40AB` - **DISK_show_deleted** (1 byte)
    - `0x00` = do not show deleted files in *cat* command results.
    - `0x01` = show also deleted files in *cat* command results.
  - `0x40AC` - **DISK_cur_sector** (2 bytes): current Sector being used by the OS.
- **DISK BAT**
  - `0x40AE` - **DISK_cur_file_name** (14 bytes): Filename of file currently being load or saved.
  - `0x40BC` - **DISK_cur_file_attribs** (1 byte): Attributes of file currently being load or saved.
    - Bit 0: if set, file is Read Only.

    * Bit 1: if set, file is Hidden (it does not display in *cat* command results).
    * Bit 2: if set, file is System (it does not display in *cat* command results).
    * Bit 3: if set, file is Executable.
    * Bits 4-7: not used.

  - `0x40BD` - **DISK_cur_file_time_created** (2 bytes): time when currently being load or saved file was created.
  - `0x40BE` - **DISK_cur_file_date_created** (2 bytes): date when currently being load or saved file was created.
  - `0x40C1` - **DISK_cur_file_time_modified** (2 bytes): time when currently being load or saved file was last modified.
  - `0x40C3` - **DISK_cur_file_date_modified** (2 bytes): date when currently being load or saved file was last modified.
  - `0x40C5` - **DISK_cur_file_size_bytes** (2 bytes): size in bytes of file currently being load or saved.
  - `0x40C7` - **DISK_cur_file_size_sectors** (1 byte): size in sectors of file currently being load or saved.
  - `0x40C8` - **DISK_cur_file_entry_number** (2 bytes): entry number in the BAT, of file currently being load or saved.
  - `0x40CA` - **DISK_cur_file_1st_sector** (2 bytes): sector number, of the first sector, where the bytes of file currently being load or saved are stored in the **DISK**.
  - `0x40CC` - **DISK_cur_file_load_addr** (2 bytes): address where the bytes of file currently being load will be stored in **RAM**.

- **CLI**: buffers used by CLI to store temporary data.
  - `0x40CE` - **CLI_prompt_addr** (2 bytes): The address of the CLI Prompt subroutine. Programs that need to return control to CLI on exit, MUST jump to the address stored here.
  - `0x40D0` - **CLI_buffer** (6 bytes): generic buffer.
  - `0x40D6` - **CLI_buffer_cmd** (16 bytes): when a user enters a command and its parameters, the command alone is stored here.
  - `0x40E6` - **CLI_buffer_parm1_val** (16 bytes): when a user enters a command and its parameters, the first parameter is stored here.

- `0x40F6` - **CLI_buffer_parm2_val** (16 bytes): when a user enters a command and its parameters, the second parameter is stored here.
- `0x4106` - **CLI_buffer_pgm** (32 bytes): generic buffer.
- `0x4126` - **CLI_buffer_full_cmd** (64 bytes): when a user enters a command and its parameters, the entire line entered by the user is stored here. This is useful for passing parameters to programs called with *run* command.

- **RTC**
  - `0x4166` - **RTC_hour** (1 byte): 24h format, in hexadecimal (`0x00`-`0x17`).
  - `0x4167` - **RTC_minutes** (1 byte): in hexadecimal (`0x00`-`0x3B`).
  - `0x4168` - **RTC_seconds** (1 byte): in hexadecimal (`0x00`-`0x3B`).
  - `0x4169` - **RTC_century** (1 byte): 20 part of year 20xx, in hexadecimal (`0x14` = 20).
  - `0x416A` - **RTC_year** (1 byte): xx part of year 20xx, in hexadecimal (e.g. `0x16` = 22). The **RTC** supports until 2079, therefore maximum value is `0x4F`.
  - `0x416B` - **RTC_year4** (2 bytes): four digit year, in hexadecimal (e.g. `0x07E6` = 2022). The **RTC** supports until 2079, therefore maximum value is `0x081F`.
  - `0x416D` - **RTC_month** (1 byte): in hexadecimal (`0x00`-`0x0C`).
  - `0x416E` - **RTC_day** (1 byte): in hexadecimal (`0x00`-`0x1F`).
  - `0x416F` - **RTC_day_of_the_week** (1 byte): `0x00`=Sunday, `0x01`=Monday, `0x02`=Tuesday, `0x03`=Wednesday, `0x04`=Thursday, `0x05`= Friday, `0x06`=Saturday

- **Math**
  - `0x4170` - `MATH_CRC` (2 bytes): CRC-16 CRC.
  - `0x4172` - `MATH_polynomial` (2 bytes): CRC-16 Polynomial.

- **Generic**
  - `0x4174` - **SD_images_num** (1 byte): number of Disk Image Files found by **ASMDC**.
  - `0x4175` - **DISK_current** (1 byte): current **DISK** unit active. All disk operations will be on this **DISK**.

  - `0x4176` - **DISK_status** (1 byte): status of the **FDD**.
    * Low Nibble (`0x00` if all OK)
      · bit 0 = not used.
      · bit 1 = not used.
      · bit 2 = set if last command resulted in error.
      · bit 3 = not used.
    * High Nibble: error code of last operation.
  - `0x4176` - **DISK_status** (1 byte): status of the **SD card**.
    * Low Nibble (`0x00` if all OK)
      · bit 0 = set if **SD card** was not found.
      · bit 1 = set if Disk Image File was not found.
      · bit 2 = set if last command resulted in error.
      · bit 3 = not used.
    * High Nibble: number of Disk Image Files found.
  - `0x4177` - **DISK_file_type** (1 byte): File Type when creating (*save*) next file.
  - `0x4178` - **DISK_loadsave_addr** (2 bytes): see Read data from DISK and Write data to DISK.
  - `0x417A` - **tmp_addr1** (2 bytes): temporary storage for an address.
  - `0x417C` - **tmp_addr2** (2 bytes): temporary storage for an address.
  - `0x417E` - **tmp_addr3** (2 bytes): temporary storage for an address.
  - `0x4180` - **tmp_byte** (1 byte): temporary storage for a byte.
  - `0x4181` - **tmp_byte2** (1 byte): temporary storage for a byte.

- **VDP**
  - `0x4182` - **VDP_cursor_x** (1 byte): Current horizontal position of the cursor on the VDP screen.
  - `0x4183` - **VDP_cursor_y** (1 byte): Current vertical position of the cursor on the VDP screen.

1.2.3 DISK Buffer

Read and Write operations on **DISK** are done Sector by Sector (i.e 512 Bytes).

When loading a file, dzOS asks **ASMDC** for the first 512 bytes of the file, and stores it in this buffer. After the bytes are moved to **RAM**, dzOS asks **ASMDC** for the next 512 bytes, and so on until the file is read entirely.

When saving a file, dzOS copies the first 512 bytes of the file from **RAM** to this buffer. After sending the bytes to **ASMDC**, dzOS copies the next 512 bytes of the file, and so on until the file is saved entirely.

When doing a *cat* of a **DISK**, dzOS asks **ASMDC** for the first 512 bytes of the BAT, and stores it in this buffer. After the list of files is shown on the screen, dzOS asks **ASMDC** for the next 512 bytes, and so on until the entire catalogue has been shown.

2 I/O Map

VDP	`0x10`	Mode 0 (VRAM)
	`0x11`	Mode 1 (Register)
ROM / RAM	`0x38`	ROM Paging
SIO	`0x80`	Channel A Control
	`0x81`	Channel A Data
	`0x82`	Channel B Control
	`0x83`	Channel B Data

3 BIOS Jumpblocks

3.1 Non-Maskable Interrupt (NMI)

The chip used for the generation of the Composite Video (the Texas Instruments TMS9918A) generates an interrupt at the end of each active-display scan (also known as *raster interrupt*), which is about every 1/60th second, by setting the */INT* active low pin.

But this chip doesn't have the *priority daisy-chain* feature of, for example the SIO/2 and other Zilog chips, and when raising an interrupt to the **CPU** pin */INT* could create bus contention[1]. Therefore, the interrupt pin */INT* of the TMS9918A is connected to the */NMI* pin of the **CPU**.

This means that every 1/60th second the **CPU** will receive a Non-Maskable Interrupt and therefore, store the current Program Counter (PC) in the stack and jump to the location `0x0066`.

At that address, dzOS contains a small piece of code that allows programs to enable and disable a jump to their own subroutine. For example, a video game playing a tune will need to update the **PSG** in an interrupt basis.

The code works as follows:

- First, all **CPU** registers are saved (with *PUSH*).
- Next, the subroutine checks the byte stored at *BIOS_NMI_FLAG*. This byte emulates the Enable Interrupt (*EI*) and Disable Interrupt (*DI*) that the **CPU** has for Maskable Interrupts.
  - If the byte is equal to zero (i.e. disabled), it will restore all previously saved **CPU** registers, and finish the subroutine with a Return from non maskable interrupt (*RETN*).
  - If the byte is equal to one (i.e. enabled), it will jump to whatever address is stored in the bytes 2 and 3 of *BIOS_NMI_JP*

In summary, if you want your program to perform any actions each time the **VDP** raises an interrupt (i.e. each 1/60th second), do the following:

- The end of your subroutine MUST be a *jp F_BIOS_NMI_END* This is the part that restores the previously saved **CPU** registers and ends the subrutine with *RETN*.
- Store the address of your subroutine, in little-endian, in the bytes *BIOS_NMI_JP* + 2 and *BIOS_NMI_JP* + 3.

[1] Bus contention occurs when all devices communicate directly with each other through a single shared channel (Address and Data buses), and more than one device attempts to place values on the channel at the same time.

- Enable the calling to your subroutine, by storing a 1 in the byte *BIOS_NMI_FLAG*

3.1.1 F_BIOS_NMI_END

Action	Performs *POP* instructions for all **CPU** registers and performs a Return from non maskable interrupt (*RETN*)
Entry	None
Exit	None
Destroys	Restores **CPU** registers `AF`, `BC`,`DE`, `HL`, `IX` and `IY` to the values they had before the NMI was triggered.
Calls	Programmable *jp*, by changing the address of the *BIOS_NMI_JP* and enabling the jump by setting *BIOS_NMI_FLAG* to 1.

3.1.2 BIOS_NMI_JP

This is the start address of three bytes corresponding to the instruction *jp BIOS_NMI_END*. The first byte (*C3*) MUST not be changed. The next two bytes are the ones a program can change to make the interrupt jump to a desired subroutine.

3.1.3 BIOS_NMI_FLAG

This is the address of a single byte that emulates the Enable Interrupt (*EI*) and Disable Interrupt (*DI*) that the **CPU** has for Maskable Interrupts.

By setting this byte to 1, the NMI subroutine will execute the jump at BIOS_NMI_JP.

By setting this byte to 0, the NMI subroutine will execute the F_BIOS_NMI_END.

3.2 General Routines

3.2.1 F_BIOS_WBOOT

Action	Warm Boot. Executed after **SIO/2** initialisation, or after a *reset* command
Entry	None
Exit	None
Destroys	None
Calls	*jp* F_KRN_START

3.2.2 F_BIOS_SYSHALT

Action	Halts the computer. Executed after a *halt* command
Entry	None
Exit	Disables Interrupts (DI)
Destroys	None
Calls	None

3.3 Serial Routines

3.3.1 F_BIOS_SERIAL_INIT

Action	Initialises **SIO/2**: sets Channels A and B as 115,000 bps, 8N1, Interrupt in all characters Configures the interrupt vector to `0x60` Sets the CPU to Interrupt Mode 2 Enables Interrupts
Entry	None
Exit	None
Destroys	`A`, `HL`
Calls	*jp* F_BIOS_WBOOT

3.3.2 F_BIOS_SERIAL_CONIN_A

Action	Reads a character from the **SIO/2** Channel A
Entry	None
Exit	`A` = character read
Destroys	`A`
Calls	None

3.3.3 F_BIOS_SERIAL_CONIN_B

Action	Reads a character from the **SIO/2** Channel B
Entry	None
Exit	`A` = character read
Destroys	`A`
Calls	None

3.3.4 F_BIOS_SERIAL_CONOUT_A

Action	Sends a character to the **SIO/2** Channel A
Entry	`A` = character to be send
Exit	None
Destroys	None
Calls	None

3.3.5 F_BIOS_SERIAL_CONOUT_B

Action	Sends a character to the **SIO/2** Channel B
Entry	`A` = character to be send
Exit	None
Destroys	None
Calls	None

3.4 DISK Routines

3.4.1 F_BIOS_SD_BUSY_WAIT

Action	Calls **ASMDC** to check if the **DISK** is busy, and loops until it is not busy.
Entry	None
Exit	None
Destroys	`A`
Calls	F_BIOS_SERIAL_CONOUT_B F_BIOS_SERIAL_CONIN_B

3.4.2 F_BIOS_SD_GET_STATUS

Action	Calls **ASMDC** to check the status of the SD Card module.
Entry	None
Exit	*SD_status* bit 0 = set if SD card was not found bit 1 = set if image file was not found bit 2 = set if last command resulted in error
Destroys	`A`
Calls	F_BIOS_SD_BUSY F_BIOS_SERIAL_CONOUT_B F_BIOS_SERIAL_CONIN_B

3.4.3 F_BIOS_SD_PARK_DISKS

Action	Tells **ASMDC** to close the Image File
Entry	None
Exit	None
Destroys	`A`
Calls	F_BIOS_SD_BUSY F_BIOS_SERIAL_CONOUT_B

3.4.4 F_BIOS_SD_MOUNT_DISKS

Action	Tells **ASMDC** to open the Image File
Entry	None
Exit	None
Destroys	A
Calls	F_BIOS_SD_BUSY F_BIOS_SERIAL_CONOUT_B

3.4.5 F_BIOS_DISK_READ_SEC

Action	Reads a Sector (512 bytes), from the **DISK** and places the bytes into the CF_BUFFER_START
Entry	E = sector address LBA 0 (bits 0-7) D = sector address LBA 1 (bits 8-15) C = sector address LBA 2 (bits 16-23) B = sector address LBA 3 (bits 24-27) BC are not used (set to zero), because max sector is 65,535
Exit	CF_BUFFER_START contains the 512 bytes read
Destroys	A, B, HL, DISK_BUFFER_START
Calls	F_BIOS_SD_BUSY F_BIOS_SERIAL_CONOUT_B F_BIOS_SERIAL_CONIN_B

3.4.6 F_BIOS_DISK_WRITE_SEC

Action	Writes a Sector (512 bytes), from the DISK_BUFFER_START into the **DISK**
Entry	E = sector address LBA 0 (bits 0-7) D = sector address LBA 1 (bits 8-15) C = sector address LBA 2 (bits 16-23) B = sector address LBA 3 (bits 24-27) BC are not used (set to zero), because max sector is 65,535
Exit	DISK_BUFFER_START contains the 512 bytes written
Destroys	A, HL, DISK_BUFFER_START
Calls	F_BIOS_SD_BUSY F_BIOS_SERIAL_CONOUT_B F_BIOS_SERIAL_CONIN_B

3.4.7 F_BIOS_FDD_BUSY_WAIT

Action	Calls **ASMDC** to check if the **FDD** is busy, and loops until it is not busy.
Entry	None
Exit	None
Destroys	`A`
Calls	F_BIOS_SERIAL_CONOUT_B F_BIOS_SERIAL_CONIN_B

3.4.8 F_BIOS_FDD_CHANGE

Action	Tells the **ASMDC** that the current **DISK** for operations is now the **FDD**.
Entry	None
Exit	`DISK_status` is updated
Destroys	`A`
Calls	F_BIOS_SERIAL_CONOUT_B

3.4.9 F_BIOS_FDD_LOWLVL_FORMAT

Action	Tells the **ASMDC** to low-level format a **DISK** in the **FDD**. This function does not set up any file system. It just fills with `0xF6` all bytes of all sectors.
Entry	None
Exit	`A` = `0x00` if everything OK. Bit 2 set if command resulted in error.
Destroys	`A`
Calls	F_BIOS_SERIAL_CONOUT_B F_BIOS_SERIAL_CONIN_B

3.4.10 F_BIOS_FDD_MOTOR_ON

Action	Tells the **ASMDC** to switch the **FDD** motor on. It is a recommended practice to switch the motor on and off manually if multiple sectors are to read or written.
Entry	None
Exit	None
Destroys	`A`
Calls	F_BIOS_SERIAL_CONOUT_B

3.4.11 F_BIOS_FDD_MOTOR_OFF

Action	Tells the **ASMDC** to switch the **FDD** motor off. It is a recommended practice to switch the motor on and off manually if multiple sectors are to read or written.
Entry	None
Exit	None
Destroys	`A`
Calls	F_BIOS_SERIAL_CONOUT_B

3.4.12 F_BIOS_FDD_CHECK_DISKIN

Action	Asks the **ASMDC** to check if a Floppy Disk is inside the **FDD**.
Entry	None
Exit	`A` = `0x00` yes / `0xFF` no
Destroys	`A`
Calls	F_BIOS_SERIAL_CONOUT_B F_BIOS_SERIAL_CONIN_B

3.4.13 F_BIOS_FDD_CHECK_WPROTECT

Action	Asks the **ASMDC** to check if the Floppy Disk is write protected.
Entry	None
Exit	`A` = `0x00` yes / `0xFF` no
Destroys	`A`
Calls	F_BIOS_SERIAL_CONOUT_B F_BIOS_SERIAL_CONIN_B

3.5 Real-Time Clock Routines

3.5.1 F_BIOS_RTC_GET_TIME

Action	Gets the current time from the **ASMDC**, and stores hour, minutes and seconds as hexadecimal values in SYSVARS.
Entry	None
Exit	`RTC_hour`, `RTC_minutes`, `RTC_seconds`
Destroys	`A`
Calls	F_BIOS_SERIAL_CONOUT_B F_BIOS_SERIAL_CONIN_B

3.5.2 F_BIOS_RTC_GET_DATE

Action	Gets the current date from the **ASMDC**, and stores day, month, year and day of the week as hexadecimal values in SYSVARS.
Entry	None
Exit	`RTC_day`, `RTC_month`, `RTC_year`, `RTC_day_of_the_week`
Destroys	`A`, `HL`
Calls	F_BIOS_SERIAL_CONOUT_B F_BIOS_SERIAL_CONIN_B

3.5.3 F_BIOS_RTC_SET_TIME

Action	Tells **ASMDC** to store a new hour, minutes and seconds.
Entry	`RTC_hour`, `RTC_minutes`, `RTC_seconds`
Exit	None
Destroys	`A`
Calls	F_BIOS_SERIAL_CONOUT_B

3.5.4 F_BIOS_RTC_SET_DATE

Action	Tells **ASMDC** to store a new day, month, year and day of the week.
Entry	`RTC_day`, `RTC_month`, `RTC_year`, `RTC_day_of_the_week`
Exit	None
Destroys	`A`
Calls	F_BIOS_SERIAL_CONOUT_B

3.5.5 F_BIOS_CHECK_BATTERY

Action	Asks the **ASMDC** if the battery is healthy or has to be replaced.
Entry	None
Exit	A = `0x0A` (Healthy) / `0x00` (Dead)
Destroys	`A`
Calls	F_BIOS_SERIAL_CONOUT_B F_BIOS_SERIAL_CONIN_B

3.6 NVRAM Routines

3.6.1 F_BIOS_NVRAM_DETECT

Action	Asks the **ASMDC** if the NVRAM is present.
Entry	None
Exit	length (in bytes) of the NVRAM, or `0xFF` if not detected.
Destroys	`A`
Calls	F_BIOS_SERIAL_CONOUT_B F_BIOS_SERIAL_CONIN_B

3.7 VDP Routines

3.7.1 F_BIOS_VDP_SET_ADDR_WR

Action	Set a **VRAM** address for writting.
Entry	`HL` = address to be set
Exit	None
Destroys	`C`, `H`
Calls	None

3.7.2 F_BIOS_VDP_SET_ADDR_RD

Action	Set a **VRAM** address for reading.
Entry	`HL` = address to be read
Exit	None
Destroys	`A`, `C`
Calls	None

3.7.3 F_BIOS_VDP_SET_REGISTER

Action	Set a value to a **VDP** register.
Entry	`A` = register number, `B` = value to set
Exit	None
Destroys	`A`, `C`
Calls	None

3.7.4 F_BIOS_VDP_VRAM_CLEAR

Action	Set all cells of the **VRAM** (`0x0000`- `0x3FFF`) to zero.
Entry	None
Exit	None
Destroys	`A`, `BC`, `D`, `HL`
Calls	F_BIOS_VDP_SET_ADDR_WR

3.7.5 F_BIOS_VDP_VRAM_TEST

Action	Set a value to each **VRAM** cell and then reads it back. If the value is not the same, something went wrong.
Entry	None
Exit	`C Flag` set if an error ocurred.
Destroys	`A`, `BC`, `D`, `HL`
Calls	F_BIOS_VDP_SET_ADDR_WR F_BIOS_VDP_SET_ADDR_RD

3.7.6 F_BIOS_VDP_SET_MODE_G2

Action	Set **VDP** to *Graphics II Bit-mapped Mode* display.
Entry	None
Exit	None
Destroys	`A`, `BC`, `D`, `HL`
Calls	F_BIOS_VDP_SET_ADDR_WR F_BIOS_VDP_SET_REGISTER

3.7.7 F_BIOS_VDP_SHOW_DZ_LOGO

Action	Show dastaZ80 logo on the **Low Resolution Display**.
Entry	None
Exit	None
Destroys	`A`, `BC`, `DE`, `HL`, `IX`
Calls	F_BIOS_VDP_SET_ADDR_WR

3.7.8 F_BIOS_VDP_BYTE_TO_VRAM

Action	Writes a byte to currently pointed VRAM cell.
Entry	`A` = byte to be written
Exit	None
Destroys	`C`
Calls	None

4 Kernel Jumpblocks

4.1 General Routines

4.1.1 F_KRN_SYSHALT

Action	Prepares the computer for a *HALT*.
Entry	None.
Exit	None
Destroys	`A`, `HL`
Calls	F_BIOS_SD_PARK_DISKS F_KRN_SERIAL_WRSTRCLR

4.2 Serial Routines

4.2.1 F_KRN_SERIAL_SETFGCOLR

Action	Set the colour that will be used for the foreground (text). The colour will remain until a different one is set.
Entry	`A` = Colour number (as listed in Appendixes section)
Exit	None
Destroys	`B`, `DE`
Calls	F_BIOS_SERIAL_CONOUT_A *jp* F_KRN_SERIAL_SEND_ANSI_CODE

4.2.2 F_KRN_SERIAL_WRSTR

Action	Outputs a string, terminated with Carriage Return to the **CONSOLE**.
Entry	`HL` = address in **MEMORY** where the first character of the string to be output is.
Exit	None
Destroys	`A`, `HL`
Calls	F_BIOS_SERIAL_CONOUT_A

4.2.3 F_KRN_SERIAL_WRSTRCLR

Action	Outputs a string, terminated with Carriage Return to the **CONSOLE**, with a specific foreground colour.
Entry	`A` = Colour number (as listed in Appendixes section) `HL` = address in **MEMORY** where the first character of the string to be output is.
Exit	None
Destroys	`B`, `DE`
Calls	F_KRN_SERIAL_SETFGCOLR *jp* F_KRN_SERIAL_WRSTR

4.2.4 F_KRN_SERIAL_WR6DIG_NOLZEROS

Action	Outputs to the **CONSOLE** a string of ASCII characters representing a number, without outputing the leading zeros. (.e.g. 30 30 31 32 30 34 is 001204, but the output wil be 1024)
Entry	`IX` = address in **MEMORY** where the ASCII characters are stored.
Exit	None
Destroys	`A`, `B`, `DE`, `IX`
Calls	F_BIOS_SERIAL_CONOUT_A

4.2.5 F_KRN_SERIAL_RDCHARECHO

Action	Reads with echo. Reads a character from the **SIO/2** Channel A, and outputs it to the **CONSOLE**.
Entry	None
Exit	`A` = read character.
Destroys	None
Calls	F_BIOS_SERIAL_CONIN_A F_BIOS_SERIAL_CONOUT_A

4.2.6 F_KRN_SERIAL_EMPTYLINES

Action	Outputs n number of empty lines to the **CONSOLE**.
Entry	`B` = number (n) of empty lines to output.
Exit	None
Destroys	`A`
Calls	F_BIOS_SERIAL_CONOUT_A

4.2.7 F_KRN_SERIAL_PRN_NIBBLE

Action	Outputs a single hexadecimal nibble in hexadecimal notation.
Entry	`A` = nibble to output. Nibble will be the less significant 4 bits of the byte.
Exit	None
Destroys	`A`
Calls	F_BIOS_SERIAL_CONOUT_A

4.2.8 F_KRN_SERIAL_PRN_BYTE

Action	Outputs a single hexadecimal byte in hexadecimal notation.
Entry	`A` = byte to output.
Exit	None
Destroys	`A`
Calls	F_BIOS_SERIAL_CONOUT_A

4.2.9 F_KRN_SERIAL_PRN_BYTES

Action	Outputs n number of bytes as ASCII characters.
Entry	`B` = number (n) of bytes to output. `HL` = address in **MEMORY** where the first byte to output is.
Exit	None
Destroys	`A`, `HL`
Calls	F_BIOS_SERIAL_CONOUT_A

4.2.10 F_KRN_SERIAL_PRN_WORD

Action	Outputs the 4 hexadecimal digits of a word in hexadecimal notation.
Entry	`HL` = word to be output.
Exit	None
Destroys	`A`
Calls	F_KRN_SERIAL_PRN_BYTE

4.2.11 F_KRN_SERIAL_SEND_ANSI_CODE

Action	Writes an ANSI code to the **SIO/2** Channel A.
Entry	`DE` = address in **MEMORY** where the first byte of ANSI escape code is. `B` = number of bytes in the ANSI escape code.
Exit	None
Destroys	`A`, `DE`
Calls	F_BIOS_SERIAL_CONOUT_A

4.3 DZFS (file system) Routines

4.3.1 F_KRN_DZFS_READ_SUPERBLOCK

Action	Reads 512 bytes from Sector 0 (corresponding to the DZFS *Superblock*) into the disk buffer in **MEMORY**. If the *Superblock* does not containe the correct DZFS signature, `DISK_is_formatted` is set to `0x00`. Otherwise, is set to `0x01`.
Entry	None
Exit	None
Destroys	`A`, `DE`, `DISK_is_formatted`
Calls	F_BIOS_SD_READ_SEC

4.3.2 F_KRN_DZFS_READ_BAT_SECTOR

Action	Reads a BAT Sector from **DISK** into **MEMORY**.
Entry	`DISK_cur_sector` holds the sector number for the BAT.
Exit	`DISK Buffer` contains the BAT sector.
Destroys	`HL`
Calls	F_KRN_DZFS_SEC_TO_BUFFER

4.3.3 F_KRN_DZFS_BATENTRY_TO_BUFFER

Action	Extracts the data of a BAT entry from the `DISK Buffer` in **MEMORY** and populates the values into System variables.
Entry	`A` = BAT entry number to extract data from.
Exit	DISK BAT System Variables are populated. See RAM Memory Map for for details.
Destroys	`A`, `BC`, `DE`, `HL`, `IX`, `tmp_addr1`
Calls	F_KRN_MULTIPLY816_SLOW

4.3.4 F_KRN_DZFS_SEC_TO_BUFFER

Action	Loads a Sector (512 bytes) from the **DISK** and copies the bytes into the `DISK Buffer` in **MEMORY**.
Entry	`HL` = Sector number to load.
Exit	`DISK Buffer` contains the bytes of Sector loaded.
Destroys	`DE`, `HL`
Calls	F_BIOS_SD_READ_SEC

4.3.5 F_KRN_DZFS_GET_FILE_BATENTRY

Action	Gets the BAT's entry number of a specified filename.
Entry	`HL` = Address where the filename to check is stored
Exit	BAT Entry values are stored in the SYSVARS. `DE` = $0000 if filename found. Otherwise, whatever value had at start.
Destroys	`A`, `B`, `DE`, `HL`, `tmp_byte`, `tmp_addr2`, `tmp_addr3`
Calls	F_KRN_DZFS_SEC_TO_BUFFER F_KRN_DZFS_BATENTRY_TO_BUFFER F_KRN_STRLENMAX F_KRN_STRCMP

4.3.6 F_KRN_DZFS_LOAD_FILE_TO_RAM

Action	Load a file from **DISK**. Copies the bytes stored in the **DISK** into **MEMORY**, at the specified **MEMORY** address in the BAT.
Entry	`DE` = 1st sector number in the **DISK**. `IX` = file length in sectors.
Exit	None
Destroys	`BC`, `DE`, `HL`, `IX`, `tmp_addr1`
Calls	F_BIOS_SD_READ_SEC

4.3.7 F_KRN_DZFS_DELETE_FILE

Action	Marks a file as deleted. The mark is done by changing the first character of the filename to `0x7E` (˜)
Entry	`DE` = BAT Entry number.
Exit	None
Destroys	`A`, `DE`, `HL`,
Calls	F_KRN_MULTIPLY816_SLOW F_KRN_DZFS_SECTOR_TO_SD

4.3.8 F_KRN_DZFS_CHGATTR_FILE

Action	Changes the attributes (RHSE) of a file.
Entry	`DE` = BAT Entry number. `A` = attributes mask byte.
Exit	None
Destroys	`DE`, `HL`,
Calls	F_KRN_MULTIPLY816_SLOW F_KRN_DZFS_SECTOR_TO_SD

4.3.9 F_KRN_DZFS_RENAME_FILE

Action	Changes the name of a file.
Entry	`IY` = **MEMORY** address where the new filename is stored. `DE` = BAT Entry number.
Exit	None
Destroys	`A`, `BC`, `DE`, `HL`, `IY`
Calls	F_KRN_MULTIPLY816_SLOW F_KRN_DZFS_SECTOR_TO_SD

4.3.10 F_KRN_DZFS_FORMAT_DISK

Action	Formats a **DISK** with DZFS.
Entry	`HL` = **MEMORY** address where the disk label is stored.
Exit	None
Destroys	`A`, `BC`, `DE`, `HL`, `IX`, `IY`, `tmp_addr1`, `tmp_byte`
Calls	F_KRN_SERIAL_WRSTR F_KRN_DZFS_CALC_SN F_KRN_RTC_GET_DATE F_BIOS_RTC_GET_TIME F_KRN_BCD_TO_ASCII F_KRN_BIN_TO_BCD4 F_KRN_BIN_TO_BCD6 F_KRN_DZFS_SECTOR_TO_SD F_KRN_SETMEMRNG F_BIOS_SERIAL_CONOUT_A F_BIOS_SD_PARK_DISKS F_BIOS_SD_MOUNT_DISKS

4.3.11 F_KRN_DZFS_CALC_SN

Action	Calculates the Serial Number (4 bytes) for a **DISK**.
Entry	`IX` = **MEMORY** address where the serial number will be stored.
Exit	None
Destroys	`A`, `BC`, `DE`, `HL`, `IX`
Calls	F_BIOS_RTC_GET_DATE F_BIOS_RTC_GET_TIME F_KRN_MULTIPLY816_SLOW

4.3.12 F_KRN_DZFS_SECTOR_TO_DISK

Action	Calls the **BIOS** subroutine that will store the data (512 bytes) currently in `DISK Buffer` in **MEMORY**, to the **DISK**.
Entry	`DISK_cur_sector` = the sector number in the **DISK** that will be written.
Exit	None
Destroys	`BC`, `DE`
Calls	F_BIOS_SD_WRITE_SEC

4.3.13 F_KRN_DZFS_GET_BAT_FREE_ENTRY

Action	Get number of available BAT entry.
Entry	None
Exit	`DISK_cur_file_entry_number` = entry number.
Destroys	`A`, `IY`, `CF_cur_sector`, `CF_cur_file_entry_number`
Calls	F_KRN_DZFS_READ_BAT_SECTOR F_KRN_DZFS_BATENTRY_TO_BUFFER

4.3.14 F_KRN_DZFS_ADD_BAT_ENTRY

Action	Adds a BAT entry into the **DISK**.
Entry	`DE` = BAT entry number. `DISK_cur_sector` = Sector number where the BAT Entry is in the **DISK**. `DISK_BUFFER_START` = Sector (512 bytes) containing the BAT where the entry is. `DISK BAT` = BAT Entry data that will be saved to **DISK**.
Exit	None
Destroys	`A`, `BC`, `DE`, `HL`
Calls	F_KRN_MULTIPLY816_SLOW

4.3.15 F_KRN_DZFS_CREATE_NEW_FILE

Action	Creates a new file (and its corresponding BAT Entry) in the **DISK**, from bytes stored in **MEMORY**.
Entry	`HL` = **MEMORY** address of the first byte to be stored. `BC` = number of bytes to be stored in the **DISK**. `IX` = **MEMORY** address where the filename is stored.
Exit	None
Destroys	`A`, `BC`, `DE`, `HL`, `IX`, `tmp_addr1`, `tmp_addr2`, `tmp_addr3`, `tmp_byte`
Calls	F_KRN_DZFS_GET_BAT_FREE_ENTRY F_KRN_DIV1616 F_KRN_MULTIPLY1616 F_KRN_COPYMEM512 F_KRN_CLEAR_MEMAREA F_KRN_CLEAR_DISKBUFFER F_KRN_DZFS_SECTOR_TO_SD F_BIOS_SD_BUSY_WAIT F_KRN_SERIAL_WRSTRCLR F_KRN_DZFS_CALC_FILETIME F_KRN_DZFS_CALC_FILEDATE F_KRN_DZFS_SEC_TO_BUFFER F_KRN_DZFS_ADD_BAT_ENTRY

4.3.16 F_KRN_DZFS_CALC_FILETIME

Action	Packs current Real-Time Clock time into two bytes, which is the format used to store times (created/modified) for files in the **DISK**. The formula used is: $2048 * hours + 32 * minutes + seconds/2$
Entry	None
Exit	`HL` = RTC time
Destroys	`A`, `DE`, `HL`
Calls	F_BIOS_RTC_GET_TIME

4.3.17 F_KRN_DZFS_CALC_FILEDATE

Action	Packs current Real-Time Clock date into two bytes, which is the format used to store dates (created/modified) for files in the **DISK**. The formula used is: $512 * (year - 2000) + month * 32 + day$
Entry	None
Exit	`HL` = RTC date
Destroys	`A`, `DE`, `HL`
Calls	F_BIOS_RTC_GET_DATE

4.3.18 F_KRN_DZFS_SHOW_DISKINFO_SHORT

Action	Outputs to the **CONSOLE** some information of the **DISK**: volume label, serial number, date/time creation.
Entry	None
Exit	None
Destroys	`A`, `BC`, `DE`, `HL`
Calls	F_KRN_SERIAL_WRSTRCLR F_KRN_SERIAL_PRN_BYTE F_KRN_SERIAL_PRN_BYTES F_BIOS_SERIAL_CONOUT_A F_KRN_SERIAL_EMPTYLINES

4.3.19 F_KRN_DZFS_SHOW_DISKINFO

Action	Outputs to the **CONSOLE** all information of the **DISK**: volume label, serial number, date/time creation, file system ID, number of partitions, number of bytes per sector, number of sectors per block.
Entry	None
Exit	None
Destroys	`A`, `BC`, `DE`, `HL`, `tmp_addr1`
Calls	F_KRN_DZFS_SHOW_DISKINFO_SHORT F_KRN_SERIAL_WRSTRCLR F_KRN_SERIAL_PRN_BYTE F_KRN_SERIAL_PRN_BYTES F_BIOS_SERIAL_CONOUT_A F_KRN_SERIAL_EMPTYLINES

4.3.20 F_KRN_DZFS_CHECK_FILE_EXISTS

Action	Checks if a specified filename exsists in the **DISK**.
Entry	`HL` = **MEMORY** address where the filename to check is stored.
Exit	`Z Flag` set if filename is not found.
Destroys	`A`, `DE`, `tmp_addr3`
Calls	F_KRN_DZFS_GET_FILE_BATENTRY

4.4 Math Routines

4.4.1 F_KRN_MULTIPLY816_SLOW

Action	Multiplies an 8-bit number by a 16-bit number (HL = A * DE). It does a slow multiplication by adding the multiplier to itself as many times as multiplicand (e.g. 8 * 4 = 8+8+8+8).
Entry	`A` = Multiplicand `DE` = Multiplier
Exit	`HL` = Product
Destroys	`B`, `HL`
Calls	None

4.4.2 F_KRN_MULTIPLY1616

Action	Multiplies two 16-bit numbers (HL = HL * DE)
Entry	`HL` = Multiplicand `DE` = Multiplier
Exit	`HL` = Product
Destroys	`A`, `BC`, `DE`, `HL`
Calls	None

4.4.3 F_KRN_DIV1616

Action	Divides two 16-bit numbers (BC = BC / DE, HL = remainder)
Entry	`BC` = Dividend `DE` = Divisor
Exit	`BC` = Quotient `HL` = Remainder
Destroys	`A`, `BC`, `HL`
Calls	None

4.4.4 F_KRN_CRC16_INI

Action	Initialises the CRC to 0 and the polynomial to the appropriate bit pattern, to generate a CRC-16/BUYPASS1[2].
Entry	None
Exit	`MATH_CRC` = 0 (initial CRC value) `MATH_polynomial` = CRC polynomial
Destroys	`HL`
Calls	None

4.4.5 F_KRN_CRC16_GEN

Action	Combines the previous CRC with the CRC generated from the current data byte, to generate a CRC-16/BUYPASS1[3].
Entry	`A` = current data byte. `MATH_CRC` = previous CRC `MATH_polynomial` = CRC polynomial
Exit	`MATH_CRC` = CRC with current data byte included
Destroys	`A`, `BC`, `DE`, `HL`
Calls	None

4.5 String manipulation Routines

4.5.1 F_KRN_IS_PRINTABLE

Action	Checks if a character is a printable ASCII character.
Entry	`A` = character to check.
Exit	`C Flag` is set if character is printable.
Destroys	None
Calls	None

4.5.2 F_KRN_IS_NUMERIC

Action	Checks if a character is numeric (0, 1, 2, 3, 4, 5, 6, 7, 8 or 9).
Entry	`A` = character to check.
Exit	`C Flag` is set if character is numeric.
Destroys	None
Calls	None

4.5.3 F_KRN_TOUPPER

Action	Converts a charcater to uppercase (e.g. *a* is converted to `A`).
Entry	`A` = character to convert.
Exit	`A` = uppercased character.
Destroys	None
Calls	None

4.5.4 F_KRN_STRCMP

Action	Compares two strings.
Entry	`A` = length of string 1. `HL` = **MEMORY** address where the first byte of string 1 is located. `B` = length of string 2. `DE` = **MEMORY** address where the first byte of string 2 is located.
Exit	if str1 = str 2, `Z Flag` set and `C Flag` not set. if str1 != str 2 and str1 longer than str2, `Z Flag` not set and `C Flag` not set. if str1 != str 2 and str1 shorter than str2, `Z Flag` not set and `C Flag` set.
Destroys	`A`, `BC`, `DE`,`HL`
Calls	None

4.5.5 F_KRN_STRCPY

Action	Copies *n* characters from string 1 to string 2.
Entry	`HL` = **MEMORY** address where the first byte of string 1 is located. `DE` = **MEMORY** address where the first byte of string 2 is located. `B` = number of characters to copy.
Exit	None
Destroys	`A`, `DE`, `HL`
Calls	None

4.5.6 F_KRN_STRLEN

Action	Gets the length of a string that is terminated with a specified character.
Entry	`HL` = **MEMORY** address where the first byte of the string is located. `A` = terminating character.
Exit	`B` = lenght of the string.
Destroys	`BC`, `HL`
Calls	None

4.5.7 F_KRN_STRLENMAX

Action	Gets the length of a string that is terminated with a specified character, but only check up to a maximum of characters.
Entry	`HL` = **MEMORY** address where the first byte of the string is located. `A` = terminating character. `B` = maximum length to be checked.
Exit	`B` = lenght of the string.
Destroys	`BC`, `DE`, `HL`
Calls	None

4.6 Conversion Routines

4.6.1 F_KRN_ASCIIADR_TO_HEX

Action	Convert an address (or any 2 bytes) from hex ASCII to its hexadecimal value (e.g. 32 35 37 30 are converted into 2570).
Entry	`IX` = **MEMORY** address where the first byte is located.
Exit	`HL` = hexadecimal converted value.
Destroys	`HL`
Calls	F_KRN_ASCII_TO_HEX

4.6.2 F_KRN_ASCII_TO_HEX

Action	Converts two ASCII characters (representing two hexadecimal digits) ; to one byte in hexadecimal (e.g. `0x33` and `0x45` are converted into `3E`).
Entry	`H` = Most significant ASCII digit. `L` = Less significant ASCII digit.
Exit	`A` = Converted value.
Destroys	`A`, `BC`
Calls	None

4.6.3 F_KRN_HEX_TO_ASCII

Action	Converts one byte in hexadecimal to two ASCII printable characters (e.g. `0x3E` is converted into 33 and 45, which are the ASCII values of `3` and `E`).
Entry	`A` = Byte to convert.
Exit	`H` = Most significant ASCII digit. `L` = Less significant ASCII digit.
Destroys	`A`, `BC`, `HL`
Calls	None

4.6.4 F_KRN_BCD_TO_BIN

Action	Converts a byte of BCD to a byte of hexadecimal (e.g. 12 is converted into `0x0C`).
Entry	`A` = BCD.
Exit	`A` = Hexadecimal.
Destroys	`A`, `BC`
Calls	None

4.6.5 F_KRN_BIN_TO_BCD4

Action	Converts a byte of unsigned integer hexadecimal to 4-digit BCD (e.g. `0x80` is converted into 0128).
Entry	`A` = Unsigned integer to convert.
Exit	`H` = Hundreds digits. `L` = Tens digits.
Destroys	`A`, `BC`, `HL`
Calls	None

4.6.6 F_KRN_BIN_TO_BCD6

Action	Converts two bytes of unsigned integer hexadecimal to 6-digit BCD (e.g. `0xFFFF` is converted into 065535).
Entry	`HL` = Unsigned integer to convert.
Exit	`C` = Thousands digits. `D` = Hundreds digits. `E` = Tens digits.
Destroys	`A`, `BC`, `DE`, `HL`
Calls	None

4.6.7 F_KRN_BCD_TO_ASCII

Action	Converts 6-digit BCD to hexadecimal ASCII string (e.g. 512 is converted into 30 30 30 35 31 32).
Entry	`DE` = **MEMORY** address where the converted string will be stored. `C` = first two digits of the 6-digit BCD to convert. `H` = next two digits of the 6-digit BCD to convert. `L` = last two digits of the 6-digit BCD to convert.
Exit	None
Destroys	`A`, `DE`
Calls	None

4.6.8 F_KRN_BITEXTRACT

Action	Extracts a group of bits from a byte and returns the group in the LSB position.
Entry	`E` = byte from where to extract bits. `D` = number of bits to extract. `A` = start extraction at bit number.
Exit	`A` = extracted group of bits
Destroys	`A`, `BC`, `DE`, `HL`
Calls	None

4.6.9 F_KRN_BIN_TO_ASCII

Action	Converts a 16-bit signed binary number (-32768 to 32767) to ASCII data (e.g. 32767 is converted into 33 32 37 36 37).
Entry	`D` = High byte of value to convert. `E` = Low byte of value to convert.
Exit	`CLI_buffer_pgm` = converted ASCII data. First byte us the length.
Destroys	`A`, `BC`, `DE`, `HL`, `CLI_buffer_pgm`
Calls	None

4.6.10 F_KRN_DEC_TO_BIN

Action	Converts an ASCII string consisting of the length of the number (in bytes), a possible ASCII - or + sign, and a series of ASCII digits to two bytes of binary data. Note that the length is an ordinary binary number, not an ASCII number. (e.g. 33 32 37 36 37 is converted into 7FFF).
Entry	`HL` = **MEMORY** address where the string to be converted is.
Exit	`HL` = converted bytes.
Destroys	`A`, `BC`, `DE`, `HL`, `tmp_byte`
Calls	None

4.6.11 F_KRN_PKEDDATE_TO_DMY

Action	Extracts day, month and year from a packed date (used by DZFS to store dates).
Entry	`HL` = packed date.
Exit	`A` = day. `B` = month. `C` = year.
Destroys	`A`, `BC`, `HL`, `tmp_addr1`
Calls	None

4.6.12 F_KRN_PKEDTIME_TO_HMS

Action	Extracts hour, minutes and seconds from a packed time (used by DZFS to store times).
Entry	`HL` = packed time.
Exit	`A` = hour. `B` = minutes. `C` = seconds.
Destroys	`A`, `BC`, `HL`, `tmp_addr1`
Calls	None

4.7 MEMORY Routines

4.7.1 F_KRN_SETMEMRNG

Action	Sets (changes) a value in a **MEMORY** position range.
Entry	`HL` = **MEMORY** start position (first byte). `BC` = number of bytes to set. `A` = value to set.
Exit	None
Destroys	`BC`, `HL`
Calls	None

4.7.2 F_KRN_COPYMEM512

Action	Copies bytes from one area of **MEMORY** to another, in group of 512 bytes (i.e. max. 512 bytes). If less than 512 bytes are to be copied, the rest will be filled with zeros.
Entry	`HL` = **MEMORY** origin position (from where to copy the bytes). `DE` = **MEMORY** destination position (to where to copy the bytes). `BC` = number of bytes to copy (MUST be less or equal to 512).
Exit	None
Destroys	`A`, `BC`, `DE`, `HL`
Calls	None

4.7.3 F_KRN_SHIFT_BYTES_BY1

Action	Moves bytes (by one) to the right and replaces first byte with bytes counter.
Entry	`HL` = **MEMORY** address of last byte to move. `BC` = number of bytes to move.
Exit	None
Destroys	`A`, `DE`, `HL`
Calls	None

4.7.4 F_KRN_CLEAR_MEMAREA

Action	Clears (with zeros) a number of bytes, starting at a specified **MEMORY** address. Maximum 256 bytes can be cleared.
Entry	`IX` = **MEMORY** address of first byte to clear. `B` = number of bytes to clear.
Exit	None
Destroys	`A`, `BC`, `IX`
Calls	None

4.7.5 F_KRN_CLEAR_DISKBUFFER

Action	Clears (with zeros) the **MEMORY** area of the **DISK** buffer.
Entry	None
Exit	None
Destroys	`BC`, `IX`
Calls	F_KRN_CLEAR_MEMAREA

4.8 Real-Time Clock Routines

4.8.1 F_KRN_RTC_GET_DATE

Action	Calls the BIOS function to get date from the RTC, and then calculates the year in four digits.
Entry	None
Exit	`RTC_year4`
Destroys	`A`, `DE`, `HL`
Calls	None F_KRN_MULTIPLY816_SLOW

4.8.2 F_KRN_RTC_SHOW_TIME

Action	Sends to the **Serial Channel** A the values of hour, minutes and seconds from SYSVARS, as hh:mm:ss
Entry	None
Exit	None
Destroys	`A`, `BC`, `DE`, `tmp_addr1`
Calls	F_KRN_BIN_TO_BCD4 F_KRN_BCD_TO_ASCII F_BIOS_SERIAL_CONOUT_A

4.8.3 F_KRN_RTC_SHOW_DATE

Action	Sends to the **Serial Channel A** the values of day, month, year (4 digits) and day of the week (3 letters) from SYSVARS, as dd/mm/yyyy www
Entry	None
Exit	None
Destroys	`A`, `BC`, `DE`, `tmp_addr1`
Calls	F_KRN_BIN_TO_BCD4 F_KRN_BIN_TO_BCD6 F_KRN_BCD_TO_ASCII F_BIOS_SERIAL_CONOUT_A

4.8.4 F_KRN_RTC_SET_TIME

Action	Converts ASCII values to Hexadecimal, `RTC_hour`, `RTC_minutes`, `RTC_seconds` and calls the BIOS function to change time via **ASMDC**.
Entry	`IX` = **MEMORY** address where the new time is stored in ASCII format.
Exit	None
Destroys	`A`, `HL`, `RTC_hour`, `RTC_minutes`, `RTC_seconds`
Calls	F_KRN_ASCII_TO_HEX F_KRN_BCD_TO_BIN F_BIOS_RTC_SET_TIME

4.8.5 F_KRN_RTC_SET_DATE

Action	Converts ASCII values to Hexadecimal, `RTC_year`, `RTC_month`, `RTC_day`, `RTC_day_of_the_week`, and calls the BIOS function to change date via **ASMDC**.
Entry	`IX` = **MEMORY** address where the new date is stored in ASCII format.
Exit	None
Destroys	`A`, `HL`, `RTC_year`, `RTC_month`, `RTC_day`, `RTC_day_of_the_week`
Calls	F_KRN_ASCII_TO_HEX F_KRN_BCD_TO_BIN F_BIOS_RTC_SET_DATE

5 dastaZ80 File System (DZFS)

In summary, a file system is a layer of abstraction to store, retrieve and update a set of files.

A file system manages access to the data and the metadata of the files, and manages the available space of the device, dividing the storage area into units of storage and keeping a map of every storage unit of the device.

DZFS main goal is to be very simple to implement. As the free **MEMORY** (i.e. **RAM** - OS - System variables and buffers) of the dastaZ80 is about 55,952 bytes, it makes no sense to have files bigger than that, as will not fit. Therefore, DZFS defines that *a Block can store only a single file*.

dastaZ80 access the **DISK** via Logical Block Addressing (LBA), which is a particularly simple linear addressing schema, in which each sector is assigned a unique number rather than referring to a cylinder, head, and sector (CHS) to access the disk.

A typical LBA scheme uses a 28-bit value that allows up to 8.4 GB of data storage capacity. DZFS schema is as follows:

LBA 3	LBA 2	LBA 1	LBA 0
XXXX	XXXX XXXX	BBBB BBBB	BBSS SSSS

Where:

- S is Sector (6 bits)
- B is Block (10 bits)
- X not used (12 bits)

5.1 DZFS characteristics

- **Bytes per Sector**: 512
- **Sectors per Block**: 64
- **Bytes per Block**: 32,768 (64 * 512). This also defines the maximum size of a file and the BAT maximum size.
- **Bytes per BAT entry**: 32
- **BAT entries**: 1024 (32,768 / 32). This also defines the maximum number of files per **DISK**.
- **Maximum bytes per File**: 1 Block (32,768 bytes)
- **Maximum bytes per DISK**: 1024 Blocks (1 Block = 1 File) * 32,768 bytes per Block = 33,554,432 bytes (33.5 MB)

5.2 DISK anatomy

A **DISK** is divided into areas:

- **Superblock** = 512 bytes (1 Sector)
- **Block Allocation Table (BAT)** = 1 Block (64 Sectors = 32,768 bytes)
- **Data Area** = 1023 Blocks (65,472 Sectors = 33,521,664 bytes)

5.2.1 Superblock

The first 512 bytes on the **DISK** contain fundamental information about the geometry, and is used by the OS to know how to access every other information on the **DISK**. On IBM PC-compatibles, this is known as the *Master Boot Record* or *MBR* for short. In DZFS, it is called *Superblock*, as it is an orphan sector that doesn't belong to any block.

Offset	Length (bytes)	Description	Example
`0x00`	2	Signature. Used to check that this is a Superblock. Set to `0xABBA`	`AB BA`
`0x02`	1	Not used	`00`
`0x03`	8	File system identifier. ASCII values for human-readable. Padded with spaces.	`DZFSV1`
`0x0B`	4	Volume serial number	`35 2A 15 F2`
`0x0F`	1	Not used.	`00`
`0x10`	16	Volume Label. ASCII values. Padded with spaces.	`dastaZ80 Main`
`0x20`	8	Volume Date creation. ASCII values (ddmmyyyy).	`03102022`
`0x28`	6	Volume Time creation. ASCII values (hhmmss).	`142232`
`0x2E`	2	Bytes per Sector (in Hexadecimal little-endian)	`00 02`
`0x30`	1	Sectors per Block (in Hexadecimal)	`40`
`0x31`	1	Number of Partitions	`01`
`0x32` - `0x64`	51	Copyright notice (ASCII value)	`Copyright 2022David Asta The MIT License (MIT)`

Offset	Length (bytes)	Description	Example
0x65 - 0x1FF	411	Not used (filled with 0x00)	00 00 00 00 00 00 00 ....

5.2.2 Block Allocation Table (BAT)

The BAT is an area of 32 bytes on the **DISK** used to store the details about the files saved in the Data Area, and is comprised of file descriptors called *entry*. Each entry holds information about a single file.

For simplicity, each entry works also as index. The first entry describes the first file on the **DISK**, the second entry describes the second file, and so on.

Offset	Length (bytes)	Description	Example
0x00	14	**Filename** Padded with spaces at the end. (only allowed A to Z and 0 to 9. No spaces allowed. Cannot start with a number.) First character also indicates 00=available, 7E=deleted (will appear as ˜)	46 49 4C 45 30 30 30 30 31 20 20 20 20 20
0x0E	14	**Attributes** (0=Inactive / 1=Active) Bit 0 = Read Only Bit 1 = Hidden Bit 2 = System Bit 3 = Executable Bit 4-7 = File Type (see below)	Read Only, System file, Executable = 1101 = 0D
0x0F	2	**Time created** 5 bits for hour (binary number 0-23) 6 bits for minutes (binary number 0-59) 5 bits for seconds (binary number seconds / 2)	F5 9A
0x11	2	**Date created** 7 bits for year since 2000 (max. is year 2127)	69 1B

Offset	Length (bytes)	Description	Example
		4 bits for month (binary number 0-12) 5 bits for day (binary number 0-31)	
`0x13`	2	Time last modified (same formula as Time created)	`F5 9A`
`0x15`	2	Date last modified (same formula as Date created)	`69 1B`
`0x17`	2	File size in bytes (little-endian)	`26 00`
`0x19`	1	File size in sectors (little-endian)	`01`
`0x1A`	2	Entry number (little-endian)	`00 00`
0x1C	2	**1st Sector** (where the file data starts) It is calculated when the file is created. The formula is: 65 + 64 * entry_number	`41 00`
`0x1E`	2	Load address (The start address little-endian where it will be loaded in RAM)	`68 25`

Bits 4-7	File Type	Description
`0x00`	**USR**	User defined
`0x01`	**EXE**	Executable binary
`0x02`	**BIN**	Binary (non-executable) data
`0x03`	**BAS**	BASIC code
`0x04`	**TXT**	Plain ASCII Text file
`0x05`		Not used
`0x06`		Not used
`0x07`		Not used
`0x08`		Not used
`0x09`		Not used
`0x0A`		Not used
`0x0B`		Not used
`0x0C`		Not used
`0x0D`		Not used
`0x0E`		Not used
`0x0F`		Not used

5.2.3 Data Area

The Data Area is the area of the **DISK** used to store file data (e.g. programs, documents).

It is divided into Blocks of 64 Sectors each.

6 How To

6.1 Read data from DISK

Given `DISK_is_formatted` is equal to `0xFF` (i.e. **DISK** is formatted with DZFS file system), call F_KRN_DZFS_LOAD_FILE_TO_RAM with `DE` equal to first sector (512 bytes) to read and `IX` equal to how many sectors to read.

Read bytes will be copied into **MEMORY**, following these rules:

- if *DISK_loadsave_addr* <> 0, load bytes to this address.
- if *DISK_loadsave_addr* = 0,
  - if *DISK_cur_file_load_addr* <> 0, load bytes to this address.
  - if *DISK_cur_file_load_addr* = 0, load bytes to start of Free RAM (`0x4420`).

6.2 Write data to DISK

Given `DISK_is_formatted` is equal to `0xFF` (i.e. **DISK** is formatted with DZFS file system):

- Store the filename (in ASCII) somewhere in **MEMORY**.
- call F_KRN_DZFS_GET_FILE_BATENTRY, with `HL` equal to the `MEMORY` address where the filename is stored. If a file with the specified filename does not exist, flag `z` will be set to indicate that it is OK to save the file.
- call F_KRN_DZFS_CREATE_NEW_FILE, with:
  - `HL` equal to the address in **MEMORY** of first byte to be stored.
  - `BC` equal to the total number of bytes to be stored.
  - `IX` equal to the address in **MEMORY** where the filename is stored.
  - *DISK_loadsave_addr* equal to:
    - zero, will use the address in **MEMORY** of first byte as the load address when loading the file (i.e. *DISK_loadsave_addr*).
    - non zero, will use this number as the load address when loading the file (i.e. *DISK_loadsave_addr*).

6.3 Convert between HEX and DEC and ASCII

In many situations your programs will need to convert between different number notations (hexadecimal, decimal, ASCII). For example, all characters typed by the user are read by the function F_BIOS_SERIAL_CONIN_A, which stores the ASCII value of the pressed key in the `A` register. In order to do manipulations of data, our program will need to convert this ASCII data into either hexadecimal or decimal notation.

Take as an example the CLI command for saving files to disk (*save*). As shown in the *dastaZ80 User's Manual* section *5.3 Disk Commands*, this command takes two parameters: <*start_address*>, which is expressed in hexadecimal, and <*number_of_bytes*>, which is expressed in decimal. But in both cases, F_BIOS_SERIAL_CONIN_A will give us (in the `A` register) the ASCII representation of the numbers typed by the user.

Before we can set a pointer to the memory address specified by <*start_address*>, and set our counter to <*number_of_bytes*>, we need to convert those ASCII numbers into hexadecimal and decimal respectively.

The Kernel, offers a series of functions to help the programmer with the conversions:

- F_KRN_ASCIIADR_TO_HEX: Converts ASCII 4 chars to HEX 2 bytes. (e.g. 32 35 37 30 to `0x2570`)
- F_KRN_ASCII_TO_HEX: Converts ASCII 2 chars to HEX 1 byte. (e.g. 33 45 to `0x3E`)
- KRN_HEX_TO_ASCII: Converts HEX 1 byte to ASCII 2 chars. (e.g. `0x3E` to 33 45)
- F_KRN_BCD_TO_BIN: Converts a byte of BCD to a byte of hexadecimal. (e.g. 12 is converted into `0x0C`).
- F_KRN_BIN_TO_BCD4: Converts HEX 1 byte to DEC 4 digits. (e.g. `0x80` to 0128)
- F_KRN_BIN_TO_BCD6: Converts HEX 2 bytes to DEC 6 digits. (e.g. `0xFFF` to 065535)
- F_KRN_BCD_TO_ASCII: Converts DEC 6 digits to ASCII 6 chars. (e.g. 512 to 30 30 30 35 31 32)
- F_KRN_BIN_TO_ASCII: Converts HEX 2 bytes to ASCII string. (e.g. `0x7FFF` to 33 32 37 36 37)
- F_KRN_DEC_TO_BIN: Converts HEX 2 bytes to ASCII string. (e.g. 33 32 37 36 37 to `0x7FFF`)

6.4 Develop software for dzOS

6.4.1 Available RAM

Programs can be loaded from disk to any area of **RAM**. Nevertheless, addresses below `0x4420` SHOULD not be used, at these contain the Operating System's variables. Modifying these without the proper care will result in undesired behaviour, system crash or even lost of data on the disk. Therefore, taking in consideration that the free RAM area starts at `0x4420` and ends at `0xFFFF`, the programmer can load programs of maximum 48,095 bytes (48 KB).

6.4.2 Storing your variables

Variables for programs can be store anywhere in the free **RAM** space.

The OS is having its own internal variables that can be accessed by the user. Also, some variables are used only by CLI and therefore could be re-used during the execution of a program.

Refer to the section System Variables (SYSVARS) on this guide to know the exact locations.

- The **DISK Superblock** and **DISK BAT** areas can be re-used if you are not using **DISK** routines.
- The **CLI** area can safely be re-used in your program, as the CLI is not running meanwhile your program is.
- The **RTC** area can be re-used if you are not calling any **RTC** routines.
- The **Math** area can be re-used if you are not calling any **Math** routines.
- The **SIO**, **Generic** and **VDP** areas MUST not be touched.

All in all, you may end up having some extra 700 bytes here.

6.4.3 Receiving parameters from CLI

When a user types a command in CLI, the entered command is stored in an area of 64 bytes in the System Variables (SYSVARS) called *CLI_buffer_full_cmd*. From there, you can read the full command, which will be the name of your binary program, and the parameter or parameters.

6.4.4 Returning to CLI

If your program allows the user to return to CLI, it must then jump to the loop subroutine known as *(*CLI Prompt). The address of this subroutine is stored in the System Variables (SYSVARS)' *CLI_prompt_addr*.

Simply make your program to load the value stored at that location and jump (*jp*) to it.

6.4.5 Developing with Z80 Assembler

In order for dzOS to know where to load the program in **RAM**, the executable code must provide the load address. For compatibility with SDCC [4], we will store it in the bytes 3 and 4 of the executable.

For programs developed in Z80 Assembler, add the following at the top of the source code:

```
.ORG    $4420               ; start of code at
                            ;   start of free RAM
jp      $4425               ; first instruction
                            ;   must jump to the
                            ;   executable code
.BYTE   $20, $44            ; load address
                            ;   (values must be
                            ;   same as .org above)

.ORG    $4425               ; start of program
                            ;   (must be same as jp above)
; your program here
; your program here
; your program here
```

The first .ORG (*.ORG $4420*) indicates the start address used for creating the binary file after compilation.

`0x4420` is where the Free **RAM** starts, giving you 48 KB for your program. Programs SHOULD not be loaded at a lower address, for the reason explained before.

The first instruction MUST be a jump (*jp*) instruction to the actual executable code (i.e. your program code) The *.BYTE* instruction just inserts the two bytes after the jump instruction. The values MUST be in hexadecimal little-endian format.

Because the jp instruction in Z80 is translated as *C3 nn nn* (where *nn* are the bytes where to jump), this will use the first three bytes (`0x00`, `0x01`,

[4] Small Device C Compiler (SDCC) is a retargettable, optimizing Standard C (ANSI C89, ISO C99, ISO C11) compiler suite that targets (amongst others) the Zilog Z80 based MCUs. (http://sdcc.sourceforge.net/)

0x02) in the binary, therefore we store the load address at bytes 3 and 4 and your program can start just after, at byte 0x05.

Once assembled, the binary will be loaded by dzOS at the load address, and when executed, the first thing that will happen is a *jp* instruction and then the execution will continue from the executable code of your program.

If your program allows the user to return to CLI, add the following on your source code:

```
ld      HL, (CLI_prompt_addr)    ; return control
jp      (HL)                     ;   to CLI
```

For convenience, two files are provided in the Github repository [5]: *_header.inc* and *_template.asm*

6.4.6 Developing with SDCC

In the Github repository, there is a file (*crt0.s* that sets:

- the start address for the binary at 0x4420
- the values 0x20 and 0x44 in the binary at bytes 5 and 6.
- first instruction of your program to be started located at 0x4425

Therefore, by using this file all programs will be loaded at the correct address.

[5] https://github.com/dasta400/dzSoftware

7 Appendixes

7.1 ANSI Terminal colours

- ANSI_COLR_BLK - Black
- ANSI_COLR_RED - Red
- ANSI_COLR_GRN - Green
- ANSI_COLR_YLW - Yellow
- ANSI_COLR_BLU - Blue
- ANSI_COLR_MGT - Magenta
- ANSI_COLR_CYA - Cyan
- ANSI_COLR_WHT - White

7.2 VDP Composite colours

- VDP_COLR_TRNSP - Transparent
- VDP_COLR_BLACK - Black
- VDP_COLR_M_GRN - Medium Green
- VDP_COLR_L_GRN - Light Green
- VDP_COLR_D_BLU - Dark Blue
- VDP_COLR_L_BLU - Light Blue
- VDP_COLR_D_RED - Dark Red
- VDP_COLR_CYAN - Cyan
- VDP_COLR_M_RED - Medium Red
- VDP_COLR_L_RED - Light Red
- VDP_COLR_D_YLW - Dark Yellow
- VDP_COLR_L_YLW - Light Yellow
- VDP_COLR_D_GRN - Dark Green
- VDP_COLR_MGNTA - Magenta
- VDP_COLR_GREY - Grey
- VDP_COLR_WHITE - White

7.3 How DZFS Volume Serial Number is calculated

Calculated by combining the date and time at the point of format:

- first byte is calculated as follows:
  - day + miliseconds (converted to hexadecimal)
  - e.g. 3 + 50 = 53 (0x35)
- second byte is calculated as follows:
  - month + seconds (converted to hexadecimal)
  - e.g. 10 + 32 = 42 (0x2A)
- last two bytes are calculated as follows:
  - (hours [if pm + 12] * 256) + minutes + year (converted to hexadecimal)
  - e.g. (2 + 12 = 14 * 256 = 3584) + 22 + 2012 = 5618 (`0x15 0xF2`)

7.4 OS Boot Sequence

After power on or after pressing the **RESET** button:

- **Bootstrap**
  - Copy contents of the ROM into High RAM (`0x8000 - 0xFFFF`).
  - Disable ROM chip and enable Low RAM (`0x0000 - 0x7FFF`). Therefore, all **MEMORY** is RAM from now on.
  - Copy the copy of ROM inm High RAM to Low RAM. Bootstrap code is not copied.
  - Transfer control to BIOS (`jp F_BIOS_SERIAL_INIT`).
- **Initialise SIO/2** (`F_BIOS_SERIAL_INIT`)
  - Initialise SIO/2.
    * Set Channel A as 115,000 bps, 8N1, Interrupt in all received characters.
    * Set Channel B as 115,000 bps, 8N1, Interrupt in all received characters.
    * Set Interrupt Vector to `0x60`.
  - Set CPU to Interrupt Mode 2.
  - `jp F_BIOS_WBOOT`

- **BIOS Boot** (`F_BIOS_WBOOT`)
  - Set SIO/2 Channel A as primary I/O.
  - Transfer control to Kernel (`jp F_KRN_START`).
- **Kernel Boot** (`F_KRN_START`)
  - Display dzOS welcome message.
  - Display dzOS release version.
  - Display Kernel version.
  - Display available **RAM**.
  - Initialise **VDP**.
    * Test write/read **VRAM**.
    * Set **Low Resolution Display** as *Graphics II Bit-mapped Mode*.
    * Show dastaZ80 Logo in the **Low Resolution Display**.
  - Initialise **FDD**.
  - Initialise **SD Card**.
    * Detect **SD Card**.
    * Display number of available Disk Image Files.
    * Display disk unit and name of each Disk Image File.
  - Initialise **Real-Time Clock (RTC)**.
    * Detect **RTC**.
    * Display current date and time.
    * Display **RTC**'s battery status.
    * Detect **NVRAM**.
  - Initialise SYSVARS.
    * Set show deleted files with *cat* command as OFF.
    * Set default File Type as 0 (USR = User defined).
    * Set default loadsave address to `0x0000` (i.e. will save/load starting from Free RAM (`0x4420`)).
  - Set default **DISK** as 1 (i.e. first Disk Image File in the **SD card**).

- Transfer control to Command-line Interpreter (CLI) (`jp F_CLI_START`).

- **CLI** (`F_CLI_START`)
  - Display CLI version.
  - Clear command buffers
  - Display prompt (>).
  - Read command entered by user.
  - Parse command.
  - Execute corresponding subroutine.
  - Loop back to Display prompt.

7.5 dzOS Programming Style

When writting dzOS and software for dzOS, the following style has been followed:

- All CPU registers are witten in uppercase (e.g. *A*, *BC*, *DE*, *HL*).
- All CPU flags are witten in lowercase (e.g. *z*, *nz*, *c*, *nc*, *m*, *p*).
- All assembly mnemonics are written in lowercase (e.g. *ld A,0*).
- Labels for subroutines that will be public (i.e. called via a Jumpblock) are written in uppercase.
- Public subroutines contain comments specifying:
  - Short description.
  - Input CPU registers or variables (SYSVARS).
  - Output CPU registers or variables (SYSVARS).
- All hexadecimal values are written with a dollar sign as prefix.
- Tabs are written as 4 spaces.
- Mnemonics start after 2 tabs (8 spaces).
- When possible, comments are written in column 41. Otherwise in next closest tab.
- Source code is heavily commented. Mostly on each line.
- *The Telemark Assembler* (TASM) specific:
  - *.BYTE* is used instead of *.DB*
  - *.WORD* is used instead of *.DW*

References

[1] David Asta. *dastaZ80 User's Manual*, 2022.

[2] David Asta. *dastaZ80 Technical Reference Manual*, 2022.

[3] David Asta. dzos github repository. https://github.com/dasta400/dzOS, 2022.