


Web Programming

SPA

Single Page Application (SPA)

- After initial page load, we can use only AJAX.
- Build page using JS.



SPA pros and cons

PRO

- Multiple concurrent interaction
- No page refresh (keep state)
- Fast interaction
 - load only data

CONS

- Complex JS code
- Slow initial page load
 - load javascript code
 - update the dom
 - render new dom

Example



[https://github.com/dat310-2025/info/tree/master/](https://github.com/dat310-2025/info/tree/master/examples/spa/mpa)
examples/spa/mpa

Example

Multi page application (MPA)




Example



[https://github.com/dat310-2025/info/tree/master/](https://github.com/dat310-2025/info/tree/master/examples/spa/norouter)
examples/spa/norouter

Example SPA



Routing in JS

Hashrouting

Use #... part of URI for part of route handled in JS

- Links that only change the hash:

```
<a href="/#/">Home</a>  
<a href="/#/about">About</a>  
<a href="/#/contact">Contact</a>
```


- React to change in hash in JS

```
window.onhashchange = function(){ ... };
```

- Read hash part in JS


```
render(window.location.hash);
```

Example



[https://github.com/dat310-2025/info/tree/master/](https://github.com/dat310-2025/info/tree/master/examples/spa/hashrouter)
examples/spa/hashrouter

Example Hashrouter



History API

History API allows to add to browser history

- Add new entry to history, updating URL, without reload

```
history.pushState({}, "", path);
```

- Create flask route that ignores part handled in JS

```
@app.route('/', defaults={'path': ''})  
@app.route('/<path:path>')  
def catch_all(path):  
    return app.send_static_file("index.html")
```

- Read hash part in JS

```
render(window.location.pathname);
```

History API

History API allows to add to browser history

- Go back in history

```
history.go(-1);
```

- Listen for event going back

```
window.addEventListener("popstate", function(event){})
```

- Avoid reloading


```
event.preventDefault();
```

Example



[https://github.com/dat310-2025/info/tree/master/](https://github.com/dat310-2025/info/tree/master/examples/spa/historyrouter)
examples/spa/historyrouter

Exercise #1 & 2



[github.com/dat310-2025/info/tree/master/](https://github.com/dat310-2025/info/tree/master/exercises/spa)
exercises/spa

Resources

- Stack overflow answer: <https://stackoverflow.com/a/67041356>

Local storage

Local storage

Allows pages to store data long time in the browser

- Store data as key value pair:

```
window.localStorage.setItem("key", "valuestring")
```

- Get value by key:

```
window.localStorage.getItem("key")
```

- Available on pages with the same top level domain
- Can store more complex data using JSON

```
window.localStorage.setItem("key", JSON.stringify(value))
```