

**1ST WORKSHOP ON ARTIFICIAL INTELLIGENCE
FOR BIOMEDICAL DATA - AIBIO**

Self-Attention as a Predictor of EEG Anomalies

**Natalia Koliou (presenter),
Maria Sierra, Christoforos Romesis,
Stasinios Konstantopoulos, and Luis Montesano**



Overview

1. Introduction & Background

2. Research Methodology

3. Experiments

4. Results & Discussion

5. Conclusion & Future Work

Introduction & Background

Self-Attention as a Predictor of EEG Anomalies

Introduction & Background

- EEG signals are highly sensitive, low-amplitude recordings easily contaminated by **artifacts** (noise not generated by brain activity).
- Artifacts may arise from physiological (muscle tension, sweating) or technical sources (electrode detachment).
- What counts as “noise” is often **task-dependent**: a feature irrelevant for one application may be meaningful for another.
- Traditional denoising via **reconstruction/prediction errors** (Autoencoders, LSTMs) ignores contextual relevance.
- **Our idea**: Train attention-based models on a downstream task (e.g., sleep stage classification) and use its attention patterns to infer anomalies without explicit artifact labels.

Research Methodology

Self-Attention as a Predictor of EEG Anomalies

- Traditional anomaly detection uses **reconstruction or prediction errors**, but these often miss **context-specific anomalies**.
- **Reconstruction error** can fail because models may learn to reproduce artifacts if trained on contaminated data (false negatives).
- **Prediction error** can incorrectly flag unpredictable but normal variations as anomalies (false positives).
- The **attention-based approach** assumes that **low-attention regions** correspond to noisy or irrelevant segments.


Hypothesis: during a task (e.g., reconstruction or prediction), the model learns to ignore artifacts that hinder performance.

Research Methodology




<i>Acronym</i>	<i>Architecture</i>	<i>Detection</i>
<i>LSTM</i>	LSTM Autoencoder	Reconstruction error
<i>C-LSTM</i>	Convolutional LSTM Autoencoder	
<i>AE_err</i>	Attention-based Autoencoder	
<i>TP_err</i>	Transformer Predictor	Prediction error
<i>AE_att</i>	Attention-based Autoencoder	Attention
<i>TP_att</i>	Transformer Predictor	
<i>MNE</i>	IIR filter	

Research Methodology



AE_err/AE_att architecture



TP_err/TP_att architecture

Experiments

Self-Attention as a Predictor of EEG Anomalies

Data Preprocessing

Our approach was evaluated using the **BOAS dataset**:

- EEG signals recorded from a **two-channel headband** at **128 Hz**.
- Signals segmented into **30s epochs**, each labeled into five sleep stages (Wake, N1, N2, N3, REM).
- **56 overnight recordings** from different users in total; 43 train, 3 validation, 10 test.
- Data normalized using **median and IQR** for robustness (skipped for MNE to preserve signal shape).
- Ground truth from Bitbrain's **proprietary artifact estimation algorithm**.

Note: 6 test recordings have minimal noise; comparisons focus on the remaining 4.

Training Process & Hyperparameters

- We pass the test dataset through each class-specific autoencoder, then classify the restyled outputs using the original classifier.
- High **classification accuracy** on restyled signals indicates the autoencoders have learned the patterns that the classifier uses for each sleep stage.

Metric	N1	N2	N3	REM
Accuracy	0.9997	0.9998	0.9260	0.9986

Results & Discussion

Self-Attention as a Predictor of EEG Anomalies

Results & Discussion

We use the **BOAS EEG dataset**, with 128 full-night recordings from 2 channels (256 Hz), to explain classifier errors across 4 sleep stages (N1, N2, N3, REM).

- **EEG Data:**

- 30s epochs ($n_s = 7680$ samples, $n_c = 2$).
- FFT \rightarrow 0.4-30 Hz filtering \rightarrow segment into $n'_s = 300$ spectral slices.
- Extract 3 features per slice (frequency, phase, amplitude).

- **Classifier:** Two-stage convolutional network over sequences of $k = 5$ epochs:

$$X_t^f = [e_{t-k+1}, \dots, e_t] \rightarrow \hat{y}_t$$

- **Autoencoders:** Hybrid networks with convolutional and attention layers:

$$X_f^t = e_t \oplus \text{pos} \longrightarrow \hat{X}_f^t \text{ (reconstructed input)}$$

Conclusion & Future Work

Self-Attention as a Predictor of EEG Anomalies

Conclusion



- **xSTAE** explains classifier errors by restyling misclassified EEG instances into correctly classified ones.
- Autoencoders balance **identity loss** (keep instance similar) and **classification loss** (push to correct label), revealing features the classifier missed.
- Contributions:
 - Ground counterfactual explanations in time-series EEG classification.
 - Identify spectral representations suitable for EEG signals.
 - Validate on open BOAS dataset and release full experimental setup.

Future Work

- Explore **alternative identity losses** to highlight meaningful changes (e.g., bigger local changes, selective brainwave bands).
- Conduct **expert trials** to refine interpretability of restyled EEGs.
- Investigate linking insights from misclassifications to **actionable guidance** at the data or confidence level, keeping xSTAE model-agnostic.

Thank you for your attention!



Thank you for your attention! Any questions?

Natalia Kolliou, Christoforos Romesis, Stasinos Konstantopoulos

Maria Sierra, Luis Montesano



This research was co-funded by the European Union under GA no. 101135782 (MANOLO project). Views and opinions expressed are however those of the authors only and do not necessarily reflect those of the European Union or CNECT. Neither the European Union nor CNECT can be held responsible for them.

<https://manolo-project.eu>



Funded by
the European Union

