

KNN2/KNN (Q9L10)

26% (5/19)

- ✓ 1. KNN is
- ☒ A data-driven method
 - ☐ B model-driven method
 - ☐ C I do not know
- ✗ 2. The dependent variable of the classification is
- ☐ A categorical
 - ☒ B numeric
 - ☐ C I do not know
- ✗ 3. KNN can be used for regression
- ☐ A Yes
 - ☒ B No
 - ☐ C I do not know
- ✗ 4. In the case of KNN classification we use
- ☒ A average of outcomes
 - ☐ B majority voting scheme
 - ☐ C I do not know
- ✗ 5. Which of these errors will increase constantly by increasing k?
- ☐ A train error
 - ☐ B test error
 - ☒ C both
 - ☐ D I do not know
- ✗ 6. This function can be used to perform KNN classification in R
- ☐ A knn()
 - ☐ B k_nn()
 - ☒ C knnreg()
 - ☐ D knearneib()
 - ☐ E I do not know

✗ 7. With the increase of k , the decision boundary will be

- ☐ A simplified
- ☒ B more complex
- ☐ C I do not know
- ☐ D unchanged

✗ 8. KNN algorithm is sensitive to outliers

- ☐ A True
- ☒ B False
- ☐ C I do not know

✗ 9. KNN

- ☐ A is a supervised learning algorithm.
- ☒ B is an unsupervised learning algorithm.
- ☐ C I do not know

✗ 10. In the case of small k we have

- ☐ A overfitting
- ☐ B underfitting
- ☒ C it depends on the situation
- ☐ D I do not know

✓ 11. Why do we need scaling in KNN?

- ☐ A to avoid overfitting
- ☐ B to avoid underfitting
- ☒ C to have "equal" weights for variables
- ☐ D I do not know

✓ 12. Let $k = n$, (n - number of observations), K-NN is same as

- ☐ A random guessing
- ☒ B everything will be classified as the most probable class (in total)
- ☐ C everything will be classified as the least probable class (in total)
- ☐ D I do not know

✗ 13. This function can be used to perform K-NN regression in R

- ☐ A knn.reg
- ☐ B knnforreg
- ☐ C regknn
- ☐ D knnforregression
- ☒ E I do not know

✓ 14. Do you need to worry about scaling with one explanatory variable?

- ☒ A No
- ☐ B Yes
- ☐ C I do not know

✗ 15. n - the number of observation,
 m - the number of explanatory variables

When $n=k$, $m=1$, the decision boundary for regression is

- ☐ A a line
- ☒ B a stepwise constant function
- ☐ C a stepwise quadratic function
- ☐ D I do not know

✗ 16. Which of these algorithms can be used to fill the missing values

- ☐ A KNN for regression
- ☒ B KNN for classification
- ☐ C both
- ☐ D I do not know

✗ 17. Which one is better: KNN regression or Linear regression?

- ☒ A KNN outperform LR if the parametric form that has been selected is close to the true form of f
- ☐ B LR outperform KNN if the parametric form that has been selected is close to the true form of f
- ☐ C KNN will always outperform the LR
- ☐ D I do not know

✗ 18. Which one is the Disadvantage of KNN?

- ☐ A required assumptions
- ☒ B cannot be applied for regression
- ☐ C difficult to perform
- ☐ D the problem of high dimensional data
- ☐ E I do not know

✓ 19. The best k for train set equals to

- ☒ A 1
- ☐ B 2
- ☐ C 0
- ☐ D I do not know

⊘ 20. What is the Parzen window