

DM-Quiz-2020-Q7

38.89% (7/18)

- ✗ 1. Decision Tree Decision Boundaries
- ☒ A are a step-wise constant function
 - ☐ B I do not know
 - ☐ C continuous function
 - ☐ D are axis-parallel rectangles
- ✓ 2. Root Node has
- ☒ A no incoming edges and zero or more outgoing edges
 - ☐ B one incoming edge and two or more outgoing edges
 - ☐ C one incoming edge and no outgoing edges
 - ☐ D I do not know
- ✗ 3. Pruning the tree means
- ☐ A Simplify the tree
 - ☒ B Split the tree's nodes
 - ☐ C Merge the tree's nodes
 - ☐ D I do not know
- ✓ 4. Gini index equals to
- ☒ A $1 - \sum (p_i^2)$
 - ☐ B $1 + \sum (p_i^2)$
 - ☐ C $\sum (p_i * \log(p_i))$
 - ☐ D $-\sum (p_i * \log(p_i))$
 - ☐ E I do not know

✗ 5. Entropy starts with 0

- ☒ A True
- ☐ B False
- ☐ C I do not know

✓ 6. Overall impurity measure can be obtained by

- ☒ A a weighted average of individual rectangles
- ☐ B majority voting
- ☐ C I do not know

✓ 7. At each stage, we choose the split with

- ☒ A the lowest Gini index
- ☐ B the lowest Chi-square value
- ☐ C the highest entropy
- ☐ D I do not know

✓ 8. We can perform the Decision Trees in r using

- ☒ A rpart()
- ☐ B decisiontree()
- ☐ C destree()
- ☐ D reg.tree()
- ☐ E I do not know

✓ 9. minsplit in R means

- ☒ A the minimum number of observations that must exist in a node in order for a split to be attempted
- ☐ B the minimum number of observations in any terminal node
- ☐ C the minimum number of splits
- ☐ D I do not know

✗ 10. Bagging is a technique used to reduce

- ☐ A the variance of our predictions
- ☐ B the bias of our predictions
- ☒ C both
- ☐ D I do not know

✗ 11. Bootstrap aggregation allows sampling

- ☐ A with replacement
- ☐ B without replacement
- ☐ C I do not know
- ☒ D both

✓ 12. How can Ensemble methods be constructed?

- ☐ A By manipulating the training set
- ☐ B By manipulating the input features
- ☐ C By manipulating the class labels
- ☐ D By manipulating the learning algorithm
- ☒ E All of them
- ☐ F None
- ☐ G I do not know

✗ 13. Repeatedly sampling observations are taken

- ☒ A from general population
- ☐ B original sample data set
- ☐ C I do not know
- ☐ D None

✗ 14. Random Forest differs from bagging

- ☐ A by a random sample of m predictors
- ☐ B by bootstrapped training samples
- ☒ C by adaptive sampling
- ☐ D I do not know

- ✗ 15. Boosting differs from bagging
- ☒ A by a random sample of m predictors
 - ☐ B by bootstrapped training samples
 - ☐ C by adaptive sampling
 - ☐ D I do not know

- ✗ 16. Averaging many highly correlated quantities
- ☒ A lead to as large of a reduction in variance
 - ☐ B does not lead to as large of a reduction in variance
 - ☐ C lead to as large of a reduction in bias
 - ☐ D I do not know

- ✗ 17. We can perform a Random forest in R using the function
- ☐ A randomForest()
 - ☐ B rf()
 - ☐ C randomF()
 - ☒ D boot()
 - ☐ E I do not know

- ✗ 18. Random Forest works
- ☐ A for classification
 - ☒ B for regression
 - ☐ C both
 - ☐ D I do not know