

Lecture 04: Plotting I

NENS 230: Analysis Techniques in Neuroscience

Lecture 04 Outline

Questions?

Graphics Objects, Figures, Properties

Axes, Line Series, Legend

Limits, Line, Patch

3D Plotting

Subplot

Bar Graph, Tick and Tick Labels, Text

Assignment 4 Overview

Lecture 04 Outline

Questions?

Graphics Objects, Figures, Properties

Axes, Line Series, Legend

Limits, Line, Patch


3D Plotting

Subplot

Bar Graph, Tick and Tick Labels, Text

Assignment 4 Overview

Why is plotting important?



Plotting data used for:

- Polished figures for analyzing and presenting results
- Quick visualization to get intuition about data in a variable

Lecture 04 Outline

Questions?

Graphics Objects, Figures, Properties

Axes, Line Series, Legend

Limits, Line, Patch

3D Plotting

Subplot

Bar Graph, Tick and Tick Labels, Text


Assignment 4 Overview

Graphics Objects

All MATLAB graphics are represented by a **graphics objects**

Every object has a name, called a **handle**. You can put the handle into a variable and then use this to manipulate the object.

Demo 1: Figure Handle and Its Properties



Graphics Objects

All MATLAB graphics are represented by a **graphics objects**

Every object has a name, called a **handle**. You can put the handle into a variable and then use this to manipulate the object.

Handles appear in your workspace as just a double with some number; you need to remember that the number in this variable is special.

Check whether some number is a handle with `ishandle(h)`

Objects have **properties**. You can see them all with `get(handle)`

Each property has a corresponding **value**. You can query a property's value with `get(handle, 'PropertyName')`

You can change a property with `set(handle, 'PropertyName', newValue)`

Most built-in functions that work on objects accept multiple **property-value pair** arguments `set(handle, 'Property1Name', value1, 'Property2Name', value2, ...)`

Lecture 04 Outline

Questions?

Graphics Objects, Figures, Properties

Axes, Line Series, Legend

Limits, Line, Patch

3D Plotting

Subplot


Bar Graph, Tick and Tick Labels, Text

Assignment 4 Overview


Axes

Objects can contain objects within them. These are called **children**

The most common child of a figure objects is an **axes object**



Demo 2: Axes, Lineseries, and Legend




Axes

Objects can contain objects within them. These are called **children**

The most common child of a figure objects is an **axes object**

All plots, e.g. a lineseries created by `plot()`, go inside of an axis, and are themselves graphics objects that are children of the axis



Handles of children of an object are listed in its ‘Children’ property

Handles of **parent** of an object is listed in its ‘Parent’ property

Plotting Functions Create Graphics Objects

`plot()` creates a **lineseries** object which is a child of an axis. Its properties can be found in the “lineseries properties” help page

‘Color’ , ‘LineWidth’ , ‘LineStyle’ are a very useful properties of a lineseries object

Color can be specified either as a letter (‘k’ means black, ‘r’ means red) or as an **RGB vector**:
[R G B] where each element is intensity ranging from 0 (none) to 1 (max)

Lineseries, along with every other graphics object, can be deleted with `delete(handle)`

You must do `hold on` before plotting multiple graphics objects in the same axis

Setting the ‘DisplayName’ property of a graphics object prepares you to later create a **legend** with the command `legend_handle = legend(axis_handle, ‘show’)`

A useful property of a legend object is its ‘Location’ . ‘Best’ is a good initial **location**

Lecture 04 Outline

Questions?

Graphics Objects, Figures, Properties

Axes, Line Series, Legend

Limits, Line, Patch


3D Plotting

Subplot

Bar Graph, Tick and Tick Labels, Text

Assignment 4 Overview

Demo 3: Limits, `line()`, and `patch()`



Limits, Line, and Patch

The limits of an axis are queried and set through its `'XLim'` and `'YLim'` property

Axis direction can be reversed, e.g. `set(axis_handle, 'YDir', 'reverse')`

Being able to draw a line is a very powerful tool. The syntax for a line from (x1,y1) to (x2,y2) is:
`linehandle = line([x1 x2], [y1 y2], 'Property1', 'Value1', ...
'Property2', 'Value2', ...)`

You can draw polygons by creating a **patch** object:

`patchHandle = patch(Xcoordinates, Ycoordinates, color, 'Property1', ...
'Value1', ...)`

A useful property of a patch is its `'FaceAlpha'` and `'EdgeAlpha'` transparency.

Alpha can range from 0 (transparent) to 1 (opaque)

Lecture 04 Outline

Questions?

Graphics Objects, Figures, Properties

Axes, Line Series, Legend

Limits, Line, Patch


3D Plotting

Subplot

Bar Graph, Tick and Tick Labels, Text

Assignment 4 Overview

Demo 4: 3D Plotting



3D Plotting

You can make a 3d plot using the `handle = plot3(X, Y, Z , ...)` command

There is also the analogous `handle = scatter3(X, Y, Z, ...)` command with useful properties `'MarkerFaceColor'` and `'SizeData'`

We see everything in a given axis through an imaginary **camera**. The 3d orientation of the camera is defined by the axis properties `'CameraPosition'`, `'CameraTarget'`, and `'CameraUpVector'`.

Lecture 04 Outline

Questions?

Graphics Objects, Figures, Properties

Axes, Line Series, Legend

Limits, Line, Patch

3D Plotting

Subplot

Bar Graph, Tick and Tick Labels, Text

Assignment 4 Overview

Subplot


When you want multiple axes in a figure, the easiest way to do this is by making each a **subplot**

Let's say we want a 3x2 grid of axes. Each axis can be created with

```
axis_handle = subplot( row, column, index )
```

	Column 1	Column 2
	figh	
Row 1	<code>topLefth = subplot(3, 2, 1)</code>	<code>topRighth = subplot(3, 2, 2)</code>
Row 2	<code>midLefth = subplot(3, 2, 3)</code>	<code>midLefth = subplot(3, 2, 4)</code>
Row 3	<code>botLefth = subplot(3, 2, 5)</code>	<code>botRighth = subplot(3, 2, 6)</code>

Demo 5: Subplot



Subplot

When you want multiple axes in a figure, the easiest way to do this is by making each a **subplot**:

Let's say we want a 3x2 grid of axes. Each axis can be created with

```
axis_handle = subplot( column, row, index )
```

	Column 1	Column 2
	figh	
Row 1	<code>topLefth = subplot(3, 2, 1)</code>	<code>topRighth = subplot(3, 2, 2)</code>
Row 2	<code>midLefth = subplot(3, 2, 3)</code>	<code>midLefth = subplot(3, 2, 4)</code>
Row 3	<code>botLefth = subplot(3, 2, 5)</code>	<code>botRighth = subplot(3, 2, 6)</code>

If a subplot already exists, calling `axh = subplot(cols, rows, idx)` gets you the axis handle of that subplot; it does not replace it

Axes can be linked using `linkaxes([axis1_handle, axis2_handle, ...], 'xy')` with the last parameter also able to take value 'x', 'y', and 'off' (to break the link)

Lecture 04 Outline

Questions?

Graphics Objects, Figures, Properties

Axes, Line Series, Legend

Limits, Line, Patch


3D Plotting

Subplot

Bar Graph, Tick and Tick Labels, Text

Assignment 4 Overview

Demo 6: Bar Graph, Tick Labels, and Text



Bar Graph, Tick Labels, and Text

`bar()` has a number of different modes, which you can read about in its help page.

If input is a matrix, by default it will treat it as Groups x Members and make a grouped bar plot

The location of tick marks on an axis are defined in the axis' `'XTick'` and `'YTick'` properties

The strings corresponding to these ticks can be set via the `'XTickLabel'` and `'YTickLabel'` properties; use a cell array of strings with same number of elements as the number of ticks

text objects can be created with the syntax

```
text_handle = text( x, y, string, 'Property1', 'Value1', ... )
```

The x and y coordinate of a text object is in the same coordinate system as the axis

All text objects (which actually include titles and labels) have **text properties**. Useful ones include: `'FontSize'`, `'FontWeight'`, `'Color'`, `'HorizontalAlignment'`, `'VerticalAlignment'`

Lecture 04 Outline

Questions?

Graphics Objects, Figures, Properties

Axes, Line Series, Legend

Limits, Line, Patch

3D Plotting



Subplot

Bar Graph, Tick and Tick Labels, Text


Assignment 4 Overview

Assignment Four: Reach Task Rasters and PSTHs

Dataset consists spike times recorded from an multielectrode array in primary motor cortex of a non-human primate



Task cartoon¹



For each trial, the animal is making a quick reach from a central hold location towards one of eight radially located targets

You are provided twelve trials for each of 8 directions, with a vector of spike times recorded on each of 96 electrodes

¹Afshar et al, 2011, *Submitted*

Write a function which, given the data filename and a specific electrode number, makes a subplot for each reach direction condition




Figure generated
for chan 16

Each subplot shows all of the data from this channel in the form of **spike rasters** *for each trial*

It also shows the average firing rate *averaged across trials* during a given time bin in a **peristimulus time histogram (PSTH)**

Finally, you will add a **line** marking the target onset, a semi-transparent **patch** showing the epoch of interest, and descriptive **text**

Lecture 04 Review

Key Concepts

Graphics objects are controlled via their **handle**, which can be stored in a variable

Properties of objects can be get and set through **property-value pair** syntax

Objects can have **children** and **parents**

Position property of a child (e.g. axes) is relative to the parent (e.g. figure)

Color is specified as a [R G B] vector

All axes are actually 3d; you can control the **camera properties** of the axis to see this

subplot creates a new axis in a specific tile of a grid.

Alternatively, manually create multiple axes in a figure and specify their positions

Conceptually related axes can be linked using **linkaxes**; changing one axis affects the rest

Axes have markings called **ticks**; these are labelled with **tickLabels**

bar graph objects have many grouping modes (vertical, horizontal, stacking, group)

text objects can be put anywhere in an axis and modified through their **text properties**.

Labels, titles, text, and others are all actually text objects with these same text properties

Functions

figure

close

axis

get

set

ishandle

gca (**get current axis**)

gcf (**get current figure**)

line

patch

delete

legend

plot3

marker3

subplot

linkaxes

bar

text