

## **TECHNICAL FEATURES**

## **TFS 400**

## **TFS 500**

FILM WIDTHS	280 - 420 mm. (11"- 16.5")	280 - 520 mm. (11"- 20.5")
ADVANCE (MAX.)	400 mm. (15.7")	500 mm. (19.6")
DEPTH (MAX.)	130 mm. (5.1")	150 mm. (5.9")
ROLL DIAMETER	Top 300 mm. (11.8") Bottom 350 mm (13.7")	Top 350 mm. (11.8") Bottom 450 mm (17.7")
CORE DIAMETER (MAX.)	76/152 mm. (3/6")	
FRAME LENGTH	3000 - 5000 mm. (118"- 197")	4000 - 7000 mm. (157.5" - 275.5")
LOADING AREA	*(Sizes on request expandable)	
WATER CONSUMPTION	80 - 130 l/h, 10°C	
PNEUMATIC CONSUMPTION	*800 - 1000 l/min, 7 - 10 bars	
ELECTRICAL SPECIFICATIONS	230/400V. triphase +/-10% + Neutral + ground 50/60 Hz - *15-30Amp (400V.), 20-63Amp (230V.)	

ULMA reserves the right to change the specifications without prior notice



## ULMA Packaging

Thanks to an experience of 50 years, we are a worldwide reference in the design and manufacturing of high-tech packaging systems and equipment.

By embracing innovation in our core values, and by striving to provide outstanding new solutions and services to our customers & prospective customers, we hope to surpass their expectations.

The whole world is our market, thanks to our extensive network of subsidiaries, distributors & agents.

For further information on ULMA PACKAGING products, please visit:

www.ulmapackaging.com









Harpak-ULMA Packaging, LLC. • 85 Independence Drive • Taunton, MA 02780 • 800-813-6644

www.harpak-ulma.com • info@harpak-ulma.com

<sup>\*</sup> depending on the equipement