



Databend Cloud

云上 IaC 实践

彭川

Content

- 01 为什么我们需要 IaC
- 02 如何使用 IaC
- 03 Databend Cloud 在使用过程中遇到的问题


Part 1

为什么我们需要 IaC

多云环境



多集群需求



部署方式的易用性和稳定性

- Reproducible
- Declarative
- Reliable

Part 2

如何使用 IaC

GitOps

- Terraform
- Pulumi
- Helm

Github Actions

- distribution generation
- actions runner (credentials)
- preview/diff
- release
- notification

```
# cluster name ref: https://www.w3.org/wiki/CSS/Properties/color/keywords
```

```
account: "1234567890"
```

```
stage: production
```

```
parent: "9876543210"
```

```
pulumi:
```

```
• account: "9876543210"
• backend_url: s3://management/pulumi/development
• secrets_provider: awskms:///arn:aws:kms:us-east-2:9876543210:key/4aaccd6
```

```
director:
```

```
• name: silver
• platform: aws
• region: us-east-2
• cidr: 10.1.0.0/16
• is_director: true
```

```
clusters: []
```

```
• # - name: cyan
• # • platform: aws
• # • region: us-east-1
• # • cidr: 10.2.0.0/16

• # - name: lime
• # • provider: azure
• # • region: westus3
• # • cidr: 10.11.0.0/16
• # • pending: true








• # - name: aqua
• # • provider: gcp
• # • region: us-central1-b
• # • cidr: 10.12.0.0/16
```

```
jobs:
  dist:
    runs-on: ubuntu-latest
    outputs:
      matrix-global-development: ${ steps.matrix.outputs.global-development }
      matrix-global-production: ${ steps.matrix.outputs.global-production }
      matrix-china-development: ${ steps.matrix.outputs.china-development }
      matrix-china-production: ${ steps.matrix.outputs.china-production }
    steps:
      - uses: actions/checkout@v3
      - with:
        fetch-depth: 0
      - name: get changed files
        id: changeset
      - uses: tj-actions/changed-files@v35
      - name: generate matrix
        id: matrix
      - uses: ./github/actions/distribution
      - with:
        changed-files: ${ steps.changeset.outputs.all_changed_files }
        target: ${ inputs.target }
        command: ${ inputs.command }
        area: ${ inputs.area }
        stage: ${ inputs.stage }
        cluster: ${ inputs.cluster }
```

```
permissions:
  id-token: write
  pull-requests: write
  contents: read
```

```
jobs:
  dist:
    uses: ./github/workflows/template.dist.yaml
    with:
      target: ${ inputs.target }
      command: ${ inputs.command }
      area: ${ inputs.area }
      stage: ${ inputs.stage }
      cluster: ${ inputs.cluster }

  pulumi-global-development:
    needs: dist
    name: pulumi-${ matrix.command }-${ matrix.cluster.area }-${ matrix.cl
name }-${ matrix.cluster.target }
    if: needs.dist.outputs.matrix-global-development
    runs-on: [self-hosted, internal, "${ matrix.cluster.area }", "${ matrix.
strategy:
    fail-fast: false
    matrix: ${ fromJson(needs.dist.outputs.matrix-global-development) }
    steps:
      - uses: actions/checkout@v3
      - uses: ./github/actions/pulumi
      - with:
        github_token: ${ secrets.GITHUB_TOKEN }
        command: ${ matrix.command }
        area: ${ matrix.cluster.area }
        stage: ${ matrix.cluster.stage }
        cluster: ${ matrix.cluster.name }
        stack: ${ matrix.cluster.target }
        config_passphrase: ${ secrets.PULUMI_DEVELOPMENT_PASSPHRASE }
```

Runners							Status	
 bootstrap.aqua	self-hosted	Linux	ARM64	internal	production	china	<div></div> Idle	...
 bootstrap.sienna	self-hosted	Linux	ARM64	internal	development	china	<div></div> Idle	...
 bootstrap.silver	self-hosted	Linux	ARM64	internal	development	global	<div></div> Idle	...
 bootstrap.white	self-hosted	Linux	ARM64	internal	production	global	<div></div> Idle	...
 cloud-4c8g-52qgw-g2vfs	self-hosted	Linux	X64	4c8g			<div></div> Active	...
 cloud-4c8g-52qgw-h5hjp	self-hosted	Linux	X64	4c8g			<div></div> Active	...
 cloud-8c16g-r59z5-0	self-hosted	Linux	X64	8c16g			<div></div> Active	...

← Deploy MetaSrv

✓ fix: increase memory limit for metasrv dev (#7205) #136

Re-run all jobs

...

Summary

Jobs

✓ dist

✓ global-development (global, de...

✓ china-development (china, deve...

⊗ global-production

⊗ china-production

Run details

Usage

Workflow file

Triggered via push 2 hours ago

everpcpc pushed

601fd5d

main

Status

Success

Total duration

6m 24s

Billable time

1m

Artifacts

—

deploy.metasrv.yaml

on: push

✓ dist / dist

15s

Matrix: china-development

✓ 1 job completed

Show all jobs

Matrix: global-development

✓ 1 job completed

Show all jobs

Matrix: china-production

⊗ 1 job completed

Show all jobs

Matrix: global-production

⊗ 1 job completed

Show all jobs

⌕

−

+

github-actions bot commented 2 hours ago

DEV development preview aws us-east-2 silver stack metasrv

Pulumi report

Previewing update (metasrv.silver):

@ previewing update.....

```
pulumi:pulumi:Stack cloud-metasrv.silver running
pulumi:pulumi:Stack cloud-metasrv.silver running warning: provider cont
pulumi:pulumi:Stack cloud-metasrv.silver running read pulumi:pulumi:Sta
~ pulumi:providers:aws silver update [diff: ~assumeRole,skipCredentialsVa
pulumi:pulumi:Stack cloud-metasrv.silver running read pulumi:pulumi:Sta
```

@ previewing update....

```
pulumi:pulumi:Stack cloud-metasrv.silver running read pulumi:pulumi:Sta
aws:iam:Role silver-metasrv
pulumi:pulumi:Stack cloud-metasrv.silver running read pulumi:pulumi:Sta
aws:iam:Policy metasrv
aws:iam:RolePolicyAttachment silver-metasrv
pulumi:pulumi:Stack cloud-metasrv.silver 1 warning
```

github-actions bot commented 2 hours ago

DEV development preview aws us-east-2 silver helm chart meta-service

Helm Diff

databend-system, meta-service, StatefulSet (apps) has changed:

```
...
  template:
    metadata:
      annotations:
-     nonce: "4932197672"
+     nonce: "4954982857"
    labels:
      app.kubernetes.io/name: meta-service
      app.kubernetes.io/instance: meta-service
  ...
      mountPath: /mnt/data
      resources:
        limits:
-       memory: 2Gi
+       memory: 3Gi
        requests:
          cpu: 200m
-       memory: 2Gi
+       memory: 3Gi
        - name: vector-sidecar
          image: public.ecr.aws/i7g1w5q7/vector:0.24.1-distroless-libc
          imagePullPolicy: IfNotPresent
  ...
```

Changes since last deployment in ./meta-service

Part 3

在使用过程中遇到的问题

慢!

Stack 拆分

```
125 ▶Run pulumi plugin ls | grep aws || pulumi plugin install resource aws
146 aws      resource 5.40.0 510 MB 2 days ago 35 minutes ago
147 aws      resource 5.3.0 372 MB 1 day ago 42 minutes ago
148 alicloud resource 3.36.0 366 MB 2 days ago 35 minutes ago
149 NAME                LAST UPDATE    RESOURCE COUNT
150 .silver              n/a            n/a
151 backup.silver        6 months ago  8
152 connectivity.silver  2 weeks ago   1
153 csi.silver           2 months ago  7
154 database.silver      2 days ago    20
155 ecr.silver           3 months ago  17
156 gateway.silver       3 days ago    8
157 karpenter.silver     2 days ago    10
158 kubernetes.silver    2 days ago    37
159 lb.silver            1 month ago   7
160 logging.silver       2 days ago    8
161 manage-service.silver n/a            n/a
162 metasrv.silver*     35 minutes ago 8
163 monitor.silver      2 days ago    8
164 network.silver       1 week ago    32
165 operator.silver     19 hours ago  11
166 pipe.silver          2 hours ago   17
167 runner.silver        2 days ago    7
168 sharing.silver       n/a            n/a
169 storage.silver       3 days ago    19
170 tracing.silver       8 months ago  8
171 webapi.silver        42 minutes ago 26
```



Stack Reference

```
func GetKubernetesInfo(ctx *pulumi.Context, c *provider.Cluster) (*KubernetesInfo, error) {  
    ref, err := pulumi.NewStackReference(ctx, "ref:kubernetes:"+c.Name,  
        &pulumi.StackReferenceArgs{Name: pulumi.String("kubernetes." + c.Name)},  
    )  
    if err != nil {  
        return nil, errors.Wrap(err, "kubernetes ref")  
    }  
  
    output := &KubernetesInfo{  
        Ref: ref,  
        Endpoint: ref.GetStringOutput(pulumi.String("endpoint")),  
        ClusterSecurityGroup: ref.GetStringOutput(pulumi.String("clusterSecurityGroup")),  
        OidcURL: ref.GetStringOutput(pulumi.String("oidcURL")),  
        OidcARN: ref.GetStringOutput(pulumi.String("oidcARN")),  
    }  
  
    return output, nil  
}
```

权限！

Provider

```
func (c *Cluster) GetOpt(ctx *pulumi.Context, account string) (pulumi.Resource, error) {
    switch c.Platform {
    case "aws":
        var roleArn string
        switch c.Region {
        case "cn-north-1", "cn-northwest-1":
            // amazonaws.cn
            roleArn = fmt.Sprintf("arn:aws-cn:iam::%s:role/Admin", account)
        default:
            // aws.amazon.com
            roleArn = fmt.Sprintf("arn:aws:iam::%s:role/Admin", account)
        }
        p, err := aws.NewProvider(ctx, c.Name, &aws.ProviderArgs{
            Region: pulumi.String(c.Region),
            AssumeRole: aws.ProviderAssumeRoleArgs{
                RoleArn: pulumi.String(roleArn),
            },
        })
        if err != nil {
            return nil, errors.Wrap(err, "get aws provider")
        }
        return pulumi.Provider(p), nil
    case "aliyun":
        p, err := alicloud.NewProvider(ctx, c.Name, &alicloud.ProviderArgs{
```

Part 4

总结

Thank you!