

SOP-PACK-007 — Skincare Packaging Line

Standard Operating Procedure · Revision 4 · Effective 2025-09-01

Scope

This SOP covers the bottle-fill, cap-torque, label-application, and carton-seal stages of the Skincare packaging line. It applies to all primary-pack SKUs across the Lyon and Milan facilities. Packaging is independent of upstream emulsification; packaging-stage findings are tracked separately from formulation incidents.

Line equipment

Station	Equipment	Target	Tolerance
Fill	FIL-VS-1 (volumetric)	±0.5 ml	±1.0 ml reject
Cap	CAP-T-2 (torque applicator)	8 in-lb	6-10 in-lb pass
Label	LBL-AP-3 (auto-applicator)	center ±2 mm	±5 mm pass
Seal	SLR-IS-4 (induction)	full seal	leak test sample 1/100

QC sampling

- Fill weight: 1 unit per 50 sampled, AQL 0.65.
- Torque: 1 per 100 sampled, AQL 1.0.
- Label position: 100% visual (camera).
- Seal integrity: leak-test 1 per 100, AQL 0.65.

Rework

Reject units route to the rework cart; QC re-verifies before merge back into the batch. Rework rate target: <1.5% of batch volume;

sustained excursions above 2% trigger an SOP review.

Line uptime

Packaging line uptime year-to-date: 96.4%. The dominant downtime category is changeover (SKU swaps); mechanical failures contribute <1% of unscheduled stops.

SOP-PACK-007 r4 · Document owner: Henri Charpentier (Packaging Operations)