# Funkcje Grupujące

| Function | Argument Type(s) |
|---|---|
| array_agg(*expression*) | any non-array type |
| array_agg(*expression*) | any array type |
| avg(*expression*) | smallint, int, bigint, real, double precision, numeric, or interval |
| bit_and(*expression*) | smallint, int, bigint, or bit |
| bit_or(*expression*) | smallint, int, bigint, or bit |
| bool_and(*expression*) | bool |
| bool_or(*expression*) | bool |
| count(*) | |
| count(*expression*) | any |
| every(*expression*) | bool |
| json_agg(*expression*) | any |
| jsonb_agg(*expression*) | any |
| json_object_agg(*name*, *value*) | (any, any) |
| jsonb_object_agg(*name*, *value*) | (any, any) |
| max(*expression*) | any numeric, string, date/time, network, or enum type, or arrays of these types |
| min(*expression*) | any numeric, string, date/time, network, or enum type, or arrays of these types |
| string_agg(*expression*, *delimiter*) | (text, text) or (bytea, bytea) |
| sum(*expression*) | smallint, int, bigint, real, double precision, numeric, interval, or money |
| xmlagg(*expression*) | xml |

https://www.postgresql.org/docs/12/functions-aggregate.html

# Co z NULL-em?

“It should be noted that except for count, these functions return a null value when no rows are selected.

In particular, sum of no rows returns null, not zero as one might expect,
and array_agg returns null rather than an empty array when there are no input rows.”

https://www.postgresql.org/docs/12/functions-aggregate.html