OVER()

Function	Return Type	Description
`row_number()`	`bigint`	number of the current row within its partition, counting from 1
`rank()`	`bigint`	rank of the current row with gaps; same as `row_number` of its first peer
`dense_rank()`	`bigint`	rank of the current row without gaps; this function counts peer groups
`percent_rank()`	`double precision`	relative rank of the current row: (rank - 1) / (total partition rows - 1)
`cume_dist()`	`double precision`	cumulative distribution: (number of partition rows preceding or peer with current row) / total partition rows
`ntile(num_buckets integer)`	`integer`	integer ranging from 1 to the argument value, dividing the partition as equally as possible
`lag(value anyelement [, offset integer [, default anyelement ]])`	`same type as value`	returns *value* evaluated at the row that is *offset* rows before the current row within the partition; if there is no such row, instead return *default* (which must be of the same type as *value*). Both *offset* and *default* are evaluated with respect to the current row. If omitted, *offset* defaults to 1 and *default* to null
`lead(value anyelement [, offset integer [, default anyelement ]])`	`same type as value`	returns *value* evaluated at the row that is *offset* rows after the current row within the partition; if there is no such row, instead return *default* (which must be of the same type as *value*). Both *offset* and *default* are evaluated with respect to the current row. If omitted, *offset* defaults to 1 and *default* to null
`first_value(value any)`	`same type as value`	returns *value* evaluated at the row that is the first row of the window frame
`last_value(value any)`	`same type as value`	returns *value* evaluated at the row that is the last row of the window frame
`nth_value(value any, nth integer)`	`same type as value`	returns *value* evaluated at the row that is the *nth* row of the window frame (counting from 1); null if no such row

https://www.postgresql.org/docs/12/functions-window.html

OVER()

```
FROM [...]
ON [...]
JOIN [...]
WHERE [...]
GROUP BY [...]
HAVING [...]
SELECT [...]
ORDER BY [...]
```

https://www.postgresql.org/docs/12/functions-window.html