Widok Zmaterializowany (Materialized View)

Obiekt widoku zmaterializowanego jest odzwierciedleniem zapytania, które chcesz "mieć pod ręką", w formie gotowej do odczytu.

- **PRZECHOWUJE W SOBIE DANE**
- **Pamięta zapytanie!**

```
CREATE MATERIALIZED VIEW [ IF NOT EXISTS ] table_name
    [ (column_name [, ...] ) ]
    [ TABLESPACE tablespace_name ]
AS query
[ WITH [ NO ] DATA ]
```

https://www.postgresql.org/docs/12/sql-creatematerializedview.html

Widok Zmaterializowany (Materialized View)

“Odświeżanie” widoku – wykonywanie zapytania i nadpisywanie wyników.

CONCURRENTLY – pozwala na nie blokowanie innych operacji SELECT (potrzebny UNIQUE indeks)

```
REFRESH MATERIALIZED VIEW [ CONCURRENTLY ] name
```

https://www.postgresql.org/docs/12/sql-creatematerializedview.html

Widok Zmaterializowany (Materialized View)

```
ALTER MATERIALIZED VIEW [ IF EXISTS ] name
    action [, ... ]
    --ALTER [ COLUMN ] column_name SET STATISTICS integer
    --ALTER [ COLUMN ] column_name SET ( attribute_option = value [, ... ] )
    --OWNER TO { new_owner | CURRENT_USER | SESSION_USER }
ALTER MATERIALIZED VIEW [ IF EXISTS ] name
    RENAME [ COLUMN ] column_name TO new_column_name
ALTER MATERIALIZED VIEW [ IF EXISTS ] name
    RENAME TO new_name
```

```
DROP MATERIALIZED VIEW [IF EXISTS] name
  [CASCADE | RESTRICT]
```

https://www.postgresql.org/docs/12/sql-creatematerializedview.html