Tablice (ARRAYS)

```
CREATE TABLE sales (
    name             text,
    pay_by_quarter   integer[],
    schedule         text[][]
);


INSERT INTO sales (name, pay_by_quarter, schedule)
    VALUES ('ABC', ARRAY[100], '{{monday, tuesday}, {thursday, friday}}');


SELECT pay_by_quarter[1] FROM sales;
```

Każdy typ danych ma swój odpowiednik tablicowy!

INTEGER -> INTEGER[] / TEXT -> TEXT[] ...

https://www.postgresql.org/docs/12/arrays.html

Tablice (ARRAYS) – Operatory i Funkcje

Function	Return Type
array_append(anyarray, anyelement)	anyarray
array_cat(anyarray, anyarray)	anyarray
array_ndims(anyarray)	int
array_dims(anyarray)	text
array_fill(anyelement, int[] [, int[]])	anyarray
array_length(anyarray, int)	int
array_lower(anyarray, int)	int
array_position(anyarray, anyelement [, int])	int
array_positions(anyarray, anyelement)	int[]
array_prepend(anyelement, anyarray)	anyarray
array_remove(anyarray, anyelement)	anyarray
array_replace(anyarray, anyelement, anyelement)	anyarray
array_to_string(anyarray, text [, text])	text
array_upper(anyarray, int)	int
cardinality(anyarray)	int
string_to_array(text, text [, text])	text[]
unnest(anyarray)	setof anyelement
unnest(anyarray, anyarray [, ...])	setof anyelement, anyelement [, ...]

Operator	Description
=	equal
<>	not equal
<	less than
>	greater than
<=	less than or equal
>=	greater than or equal
@>	contains
<@	is contained by
&&	overlap (have elements in common)
||	array-to-array concatenation
||	array-to-array concatenation
||	element-to-array concatenation
||	array-to-element concatenation

https://www.postgresql.org/docs/12/functions-array.html