# JOIN w instrukcji UPDATE

```
[ WITH [ RECURSIVE ] with_query [, ...] ]
UPDATE [ ONLY ] table_name [ * ] [ [ AS ] alias ]
    SET { column_name = { expression | DEFAULT } |
          ( column_name [, ...] ) = [ ROW ] ( { expression | DEFAULT } [, ...] ) |
          ( column_name [, ...] ) = ( sub-SELECT )
        } [, ...]
    [ FROM from_item [, ...] ]
    [ WHERE condition | WHERE CURRENT OF cursor_name ]
    [ RETURNING * | output_expression [ [ AS ] output_name ] [, ...] ]
```

- **FROM nie jest częścią standard ISO SQL**
- **Nie jest wspierane przez wszystkie bazy danych**

```
UPDATE TABLE1
   SET TABLE1.COLUMN = <VALUE>
 WHERE <WARUNKI>
   AND EXISTS (PODZAPYTANIE
               NAWIAZUJACE
               DO TABLE1);
```

```
UPDATE TABLE1
   SET TABLE1.COLUMN = (PODZAPYTANIE
                        NAWIAZUJACE
                        DO TABLE1
                        I PRZYPISUJACE
                        ODPOWIEDNIA
                        WARTOSC)
 WHERE ...;
```

https://www.postgresql.org/docs/12/sql-update.html

# JOIN w instrukcji DELETE

```
[ WITH [ RECURSIVE ] with_query [, ...] ]
DELETE FROM [ ONLY ] table_name [ * ] [ [ AS ] alias ]
    [ USING from_item [, ...] ]
    [ WHERE condition | WHERE CURRENT OF cursor_name ]
    [ RETURNING * | output_expression [ [ AS ] output_name ] [, ...] ]
```

- **USING nie jest częścią standard ISO SQL**
- **Nie jest wspierane przez wszystkie bazy danych**
- W innych bazach danych FROM zamiast USING

```
DELETE FROM TABLE1
      WHERE <WARUNKI>
        AND EXISTS (PODZAPYTANIE
                    NAWIAZUJACE
                    DO TABLE1);
```

https://www.postgresql.org/docs/12/sql-delete.html