PostgreSQL – pg_dump / pg_restore

```
Usage:
  pg_dump [OPTION]... [DBNAME]

General options:
  -f, --file=FILENAME          output file or directory name
  -F, --format=c|d|t|p         output file format (custom, directory, tar,
                               plain text (default))
  -j, --jobs=NUM               use this many parallel jobs to dump
  -v, --verbose                verbose mode
  -V, --version                output version information, then exit
  -Z, --compress=0-9           compression level for compressed formats
  --lock-wait-timeout=TIMEOUT  fail after waiting TIMEOUT for a table lock
  --no-sync                    do not wait for changes to be written safely to disk
  -?, --help                   show this help, then exit

Options controlling the output content:
  -a, --data-only              dump only the data, not the schema
  -b, --blobs                  include large objects in dump
  -B, --no-blobs               exclude large objects in dump
  -c, --clean                  clean (drop) database objects before recreating
  -C, --create                 include commands to create database in dump
  -E, --encoding=ENCODING      dump the data in encoding ENCODING
  -n, --schema=PATTERN         dump the specified schema(s) only
  -N, --exclude-schema=PATTERN do NOT dump the specified schema(s)
  -O, --no-owner               skip restoration of object ownership in
                               plain-text format
  -s, --schema-only            dump only the schema, no data
  -S, --superuser=NAME         superuser user name to use in plain-text format
  -t, --table=PATTERN          dump the specified table(s) only
  -T, --exclude-table=PATTERN  do NOT dump the specified table(s)
  -x, --no-privileges          do not dump privileges (grant/revoke)
```

https://www.postgresql.org/docs/12/app-pgdump.html

PostgreSQL – pg_dump / pg_restore

```
Usage:
  pg_restore [OPTION]... [FILE]

General options:
  -d, --dbname=NAME        connect to database name
  -f, --file=FILENAME      output file name (- for stdout)
  -F, --format=c|d|t       backup file format (should be automatic)
  -l, --list               print summarized TOC of the archive
  -v, --verbose            verbose mode
  -V, --version            output version information, then exit
  -?, --help               show this help, then exit

Options controlling the restore:
  -a, --data-only              restore only the data, no schema
  -c, --clean                  clean (drop) database objects before recreating
  -C, --create                 create the target database
  -e, --exit-on-error          exit on error, default is to continue
  -I, --index=NAME             restore named index
  -j, --jobs=NUM               use this many parallel jobs to restore
  -L, --use-list=FILENAME      use table of contents from this file for
                               selecting/ordering output
  -n, --schema=NAME            restore only objects in this schema
  -N, --exclude-schema=NAME    do not restore objects in this schema
  -O, --no-owner               skip restoration of object ownership
  -P, --function=NAME(args)    restore named function
  -s, --schema-only            restore only the schema, no data
  -S, --superuser=NAME         superuser user name to use for disabling triggers
  -t, --table=NAME             restore named relation (table, view, etc.)
  -T, --trigger=NAME           restore named trigger
  -x, --no-privileges          skip restoration of access privileges (grant/revoke)
  -1, --single-transaction     restore as a single transaction
```

https://www.postgresql.org/docs/12/app-pgrestore.html

Inne bazy danych

Oracle - RMAN

https://docs.oracle.com/cd/E11882_01/backup.112/e10642/rcmbckba.htm#BRADV8003

Microsoft SQL Server – Management Studio or T-SQL

https://docs.microsoft.com/en-us/sql/relational-databases/backup-restore/create-a-full-database-backup-sql-server?view=sql-server-ver15

MySQL – mysqldump

https://dev.mysql.com/doc/mysql-backup-excerpt/5.7/en/mysqldump-sql-format.html