PostgreSQL – SERIAL / SMALLSERIAL / BIGSERIAL

SURROGATE Key

123 product_id	ABC product_no	ABC product_short_code	ABC product_description
1	PRD_1_ABC	PRD1	Product Description.
2	PRD_2_CDE	PRD2	Product Description.
3	PRD_3_DEF	PRD3	Product Description.
4	PRD_4_GHI	PRD4	Product Description.



CREATE TABLE ***tablename*** (***colname*** SERIAL);

CREATE SEQUENCE ***tablename_colname***_seq AS integer;

CREATE TABLE ***tablename*** (***colname*** integer NOT NULL DEFAULT nextval('***tablename_colname***_seq'));

ALTER SEQUENCE ***tablename_colname***_seq OWNED BY ***tablename.colname***;

https://www.postgresql.org/docs/12/datatype-numeric.html#DATATYPE-SERIAL

Inne bazy danych

Oracle – Identity (od 12c)

https://oracle-base.com/articles/12c/identity-columns-in-oracle-12cr1

Oracle – Sekwencja + Trigger (przed 12c)

https://stackoverflow.com/questions/11296361/how-to-create-id-with-auto-increment-on-oracle

Microsoft SQL Server – Identity

https://docs.microsoft.com/en-us/sql/t-sql/statements/create-table-transact-sql-identity-property?view=sql-server-ver15

MySQL – AUTO_INCREMENT

https://dev.mysql.com/doc/refman/8.0/en/example-auto-increment.html