Landesverband der
Tourismusorganisationen
Südtirols

Event API

Documentation of Event API
Version: 2016.08.12 - 11:33

Important!

The most recent version of this document is available at http://www.LTS.it/partner/

Landesverband der Tourismusorganisationen Südtirols | Gerbergasse 60 | I-39100 Bozen | service@lts.it

Changelog

Date	Action	Comment
2016-08-11	change	BB: Translation review – corrections and integrations
2016-06-23	add	LG: GetEveVData: Definition/@GrpEvent GetEveVSeekEngine: Parameter @WithGroups
2016-02-24	change	AM: CDay/@PDF removed Definition/@PDF added Attribute @EveTags removed from GetEveVData request
2016-02-15	add	LG: GetEveVData - EveTags GetEveVSeekEngine – SendData/@EveTags
2016-02-10	add	LG: GetEveVData - OperationScheduleOv GetEveVMap GetEveVData – CDay/@TicketsAv and CDay/@PDF GetEveVSeekEngine – SendData/@PosLatitude, SendData/@PosLongitue, SendData/@Radius
2015-11-18	change	AM: EveVChanged – description optimized; deleted events now available.
2013-09-16	new	AM: GetEveVData with new Node *District*
2013-09-16	new	AM: new function GetEveVChanged
2013-08-02	new	AM: Document translated from German to English

Landesverband der Tourismusorganisationen Südtirols | Gerbergasse 60 | I-39100 Bozen | service@lts.it

Contents

1. General Information 4
1.1. Pictures 4
1.2. Language codes 4
1.3. Publisher 4
1.4. Notation 4
2. GetEveVData 5
3. GetEveVOrganizerData 7
4. GetEveVSeekEngine 7
5. GetEveVAllPublisher 8
6. GetEveVAllTopics – Retruns a list of all possible event-categories 8
7. GetEveVNation 9
8. GetEveVFraktion – Returns the list off all districts 9
9. GetEveVAreas 9
10. EveVChanged 10
11. GetEveVMap 11
12. Description of the parameters 11

Landesverband der Tourismusorganisationen Südtirols | Gerbergasse 60 | I-39100 Bozen | service@lts.it

1. General Information

In this documentation you will find guidelines on how to use the Event-API.

The interface allows:

- To read event data (except tickets and reservations)
- To read organizer data
- To search for events
- To read information about categories, nations and districts (hamlet/Fraktionen/Frazioni) associated to the events.

You can reach the web service at http://tourist.bz.it/data/cdbdata.asmx.
For more information about calling the WebService read the document „LTS-WebS-OverviewAndLogin.pdf".

User credentials for accessing the service and necessary configuration parameters can be requested to LTS.

Please note: The service may provide data (nodes/attributes) that are not described in this documentation. Those are deprecated and will be removed from the service shortly.

In a request ALL attributes are mandatory. An attribute with no value remains empty (empty string).

1.1. Pictures

Please note that pictures beginning with the URL http://tourist.bz.it/DocSite/ImageRender.aspx are delivered by the LTS Document Server ("DocServer"). Those pictures can be modified in their size. Additional browser cache can be activated to show pictures faster without having to be loaded on every call. Please read the document "Description of the DocServer" at http://www.lts.it/partner.

1.2. Language codes

The language codes are two-letter codes that can be either in lower case (de;it;en; . . .) or in upper case (DE;IT;EN;…)
Instead of the incorrect codes „FL" (Netherlands) and „CZ" (Czechoslovakia) you can use „nl" and „cs".

1.3. Publisher

In the LTS database there are a lot of events. Those events, if nothing is done, are neither published nor do they have a rank. Every tourism organisation and every TIC-Web-User has the possibility to create an own portfolio of events among those available and to assign them an importance of their choice (rank.)
The search for events is made always in the portfolio of one or more publishers.
The available events cover various themes and not all of them are suitable to be published on touristic portals. Therefore filtering is necessary.

1.4. Notation

'…'	single value
'…;…'	multiple values separated by semicolon
'…_…'	multiple values separated by space
<Nodename ... />	means that several nodes of this type may follow

Landesverband der Tourismusorganisationen Südtirols | Gerbergasse 60 | I-39100 Bozen | service@lts.it

2. GetEveVData

This function returns one or more events.

XML – Request:

```
<SendData UserID="…" SessionID="…" Function="GetEveVData" Version="…" EvRID="…;…" WithOrganizer="…"
LngID="…" PublRID="…;…" WithCDays="…" EveTags="…" />
```

XML - Response Definition:

```
<RespData>
  <Head EvRID='…' DefDate='…' >
    <Definition OrgRID='…' Phone='…' Zip='…' NatID='…' Ticket='…' FraRID='…' Active='…' ShowSDat='…'
                SignOn='…' GEP='…' GNP='…' PayMet='…' PDF='…' GrpEvent='…' >
      <DefinitionLng LngID='…' Title='…' Street='…' City='…' Location='…' EMail='…' Web='…' Reg='…'
                     MPlace='…' />
    </Definition>
    <Desc DValue='…' DType='…' LngID='…' />
    <Desc … />
    <Foto FPath='…' Order='…' CRight='…' />
    <Foto … />
    <Topic TopRID='…' /><Topic … />
    <Publish PublRID='…' Ranc='…' Publish='…' />
    <Publish … />
    <Price PValue='…' PStd='…' />
      <PriceLng PShort='…' PLong='…' PDesc='…' LngID='…' />
      <PriceDay I6RID='…' />
      <PriceDay … />
    </Price>
    <Price … />
    <OperationScheduleOv Mon='…' Tue='…' Weds='…' Thu='…' Fri='…' Sat='…' Sun='…' />
      <OperationScheduleOvLng Desc='…' LngID='…' />
    </OperationScheduleOv>
    <EveTags>
      <EveTag RID='…' >
        <EveTagLng LngID='…' Name='…' />
      </EveTag>
    </EveTags>
    <Day I6RID='…' Date='…' DateTo='…' Active='…' SingleDays='…' MinP='…' MaxP='…' Ticket='…' Begin='…'
         End='…' Entrance='…' >
      <DayLng LngID='…' DDesc='…' DGuide='…' DLInsc='…' />
      <OTime Days='…' Entr1='…' Begin1='…' End1='…' Entr2='…' Begin2='…' End2='…' />
      <OTime … />
      <CDay Day='…' TicketsAv='…' />
      <CDay … />
    </Day>
    <Day … />
    <District FraRID='…' />
    <District … />
    <Organizer>{Structure of EveOrganizerData}<Organizer>
  </Head>
  <Head … />
<RespData>
```


Landesverband der Tourismusorganisationen Südtirols | Gerbergasse 60 | I-39100 Bozen | service@lts.it

Annotation to the XML structure:

Element/ @Attribute	Description
Head	Root-Node of each event
Definition	Non-language-specific basic data of each event
DefinitionLng	Language-specific basic data of each event
Desc	Specific description or further information about the event - for example, Link to YouTube-Video
Foto	Photos
Topic	Assigned event-categories
Publish	Assigned publisher with his ranking
Price	Prices
PriceLng	Language-specific description of the prices
PriceDay	What price is valid on the single days
Day	Periods in which an event takes place
DayLng	Language specific data for each period
OTime	Opening hours for each period
CDay	Calculated days for the defined period Example: An organizer has an event from 06.03.2011 till 08.03.2011 He sets “every day as a single event.“ “CDays” delivers the days singularly 06., 07., 08.03.2011 If “every day as a single event” is not set, “CDays” delivers only the 06.03.2011
Organizer	Data of the organizer.
OperationScheduleOv	Definies operation schedules for periodic events (e.g. every Monday) **Data not yet implemented!**
EveTags	Defines the tags for the event **Data not yet implemented!**

Landesverband der Tourismusorganisationen Südtirols | Gerbergasse 60 | I-39100 Bozen | service@lts.it

3. GetEveVOrganizerData

This function returns the data of one or more organizer.

XML – Request:

```
<SendData UserID="…" SessionID="…" Function="GetEveVOrganizerData" Version="…" OrgRID="…;…" LngID="…" />
```

XML - Response:

```
<RespData>
  <Head OrgRID='…' >
    <Address Vat='…' Tax='…' Zip='…' Phone='…' Fax='…' Web='…' EMail='…' NatID='…' FName='…' LName='…' >
      <AddressLng LngID='…' Street='…' City='…' OName='…' />
      <AddressLng … />
    </Address>
  </Head>
<RespData>
```

4. GetEveVSeekEngine

This function allows an optimized search for events.

XML – Request:

```
<SendData UserID='…' SessionID='…' Function='GetEveVSeekEngine' Version='…' PublRID='…;…' DateFrom='…'
DateTo='…' TopRID='…;…' Ranc='…' FraRID='…;…' SeekWord='…_…' LngID='…;…' PageAct='…' PageSize='…'
OrgRID='…;…' Title='…;…' SeekID='…' OnlyEveHead='…' ShowSDat='…' Zone='…' WithCDays='…' PosLatitude='…'
PosLongitude='…' Radius='…' EveTags='…;…' WithGroups='…'/>
```

XML - Response:

```
<RespData>
  <Overview PageSize='…' PageAct='…' PagesTotal='…' EventsTotal='…' SeekID='…' />
  <Head EvRID='…' >
    {Structure of EveVData}
  </Head>
  <Head … />
<RespData>
```

XML – Optimal Response with "OnlyEveHead ="1":

```
<RespData>
  <Head EvRID='…' />
  <Head … />
<RespData>
```

Indipendent of „PageAct" and „PageSize" always all Events found are returned.

Notes:

- If in a search-request no publisher is given, the search runs over all publishers. This costs a lot of performance and makes normally no sense.
- If in a new search a valid „SeekID" is given, no new search is made. Based on "PageAct" and "PaceSize" the next page of the result is calculated and returned. The other Filter-Parameters are ignored.
- The request attribute `WithGroups='…'` defines whether event groups will be considered or not. Possible values: 0=no (default), 1=yes.
- A date range can be specified in order to get only the events within those dates (`DateFrom='…'  DateTo='…'`)

5. GetEveVAllPublisher

This function returns all publishers.

XML – Request:

```
<SendData UserID='…' SessionID='…' Function='GetEveVAllPublisher' Version='…' LngID='…' />
```

XML - Response:

```
<RespData>
  <Data PublRID='…' PublType='…' Name='…' Name2='…' FName='…' LName='…' ActEvents='…' />
  <Data … />
<RespData>
```

6. GetEveVAllTopics – Retruns a list of all possible event-categories

This function returns a list of all possible event-categories.

XML – Request:

```
<SendData UserID='…' SessionID='…' Function='GetEveVAllTopics' Version='…' TopRID='…' LngID='…' />
```

XML - Response:

```
<RespData>
  <Data TopRID='…' TopID='…' >
    <DataLng Title='…' LngID='…' />
    <DataLng ... />
  </Data>
  <Data … />
<RespData>
```

Note:
Please note that only the TopRID is the unique key of a category. TopID can change every time.

Landesverband der Tourismusorganisationen Südtirols | Gerbergasse 60 | I-39100 Bozen | service@lts.it

7. GetEveVNation

This function returns a list of nations.

XML – Request:

```
<SendData UserID='…' SessionID='…' Function='GetEveVNation' Version='…' NatID='…' LngID='…' />
```

XML - Response:

```
<RespData>
  <Data NatID='…' Active='…' >
    <DataLng Title='…' LngID='…' />
    <DataLng … />
  </Data>
  <Data … />
<RespData>
```

8. GetEveVFraktion – Returns the list off all districts

This function returns a list of districts.

XML – Request:

```
<SendData UserID='…' SessionID='…' Function='GetEveVFraktion' Version='…' FraRID='…' LngID='…' />
```

XML - Response:

```
<RespData>
  <Data FraRID='…' FraID='…' >
    <DataLng Title='…' LngID='…' />
    <DataLng … />
  </Data>
  <Data … />
</RespData>
```

Note:
Districts: Hamlet (en) ; Fraktionen (de); Frazioni (it)

9. GetEveVAreas

This function returns the geo-zones to be displayed in the instance of EventViewer.

XML – Request:

```
<SendData UserID='…' SessionID='…' Function='GetEveVAreas' Version='…' EveVInstanceID='…' />
```

XML - Response:

```
<RespData>
  <Areas EveVInstanceID='…' >
    <OwnerArea AreaID='0000' PublRID='…;…' FraRID='…' Zone='…'  SelectedAreas='…' >
```

```
      <DataLng LngID='…' Desc='…' />
      <DataLng … />
    </OwnerArea>
    <Area AreaID='…'  PublRID='…;…'  FraRID='…;…'  Zone='…;…' >
    <DataLng LngID='…'  Desc='…'  />
    <DataLng … />
    <SubArea AreaID='…' PublRID='…;…'  Zone='…;…'  FraRID='…;…' >
      <DataLng LngID='…'  Desc='…' />
      <DataLng … />
    </SubArea>
  </Area>
  <Area … >
  </Areas>
</RespData>
```

10.EveVChanged

Function used to get the list of events that have been added, deleted or updated since the StartDate

StartDate	date from that the changes shall be searched
I0RID	RID of event
I0Cha	date of the last change of the event data
I0Act	active events (0=all; 1=yes)

XML – Request:

```
<SendData UserID='…' SessionID='…' Function='GetEveVChanged' StartDate='…' I0Act='…' Version='1.0'/>
```

XML - Response:

```
<RespData>
    <Data I0RID='…' I0Cha='…' I0Act='…' />
    … … …

    <EventsDeleted>
        <Data I0RID='…' >
        … … …
    </EventsDeleted>
</RespData>
```


Landesverband der Tourismusorganisationen Südtirols | Gerbergasse 60 | I-39100 Bozen | service@lts.it

11.GetEveVMap

This function returns data concerning one or more events.

XML – Request:

```
<SendData UserID="…" SessionID="…" Function="GetEveVMap" Version="…" EvRID="…;…" LngID="…" />
```

XML - Response Definition:

```
<RespData>
  <Data EvRID='…' Title='…' Street='…' City='…' Location='…' Zip='…' Phone='…' GEP='…' GNP='…' FPath='…' />
<RespData>
```

12.Description of the parameters

Element/ @Attribute	Description	Field description
@Active	Active	0 = design 1 = active 2 = deleted (or inactive) 3 = out of time
@ActEvents	Number of active Events	Integer
Areas/ @EveVInstanceID	Unique ID of an EventViewer-instance	char(32)
Areas/OwnerArea/ @AreaID	Always “0000”	char(4)
Areas/OwnerArea/ @PublRID	PublRID-Filter to use in the event-search	char(max)
Areas/OwnerArea/ @FraRID	FraRID-Filter to use in the search (district)	char(max)
Areas/OwnerArea/ @Zone	Zone-Filter to use in the search	char(max)
Areas/OwnerArea/ @SelectedAreas	ID of the selected area	char(max)
Areas/OwnerArea/DataLng/ @Desc	Description of the area	char(max)
Areas/Area/ @AreaID	ID of an area Corresponds usually to a holiday region (Tourismusverband/consorzio turistico)	char(max)
Areas/Area/ @PublRID	PublRID-Filter to use in the search	char(max)
Areas/Area/ @FraRID	FraRID-Filter to use in the search (district)	char(max)
Areas/Area/ @Zone	Zone-Filter to use in the search	char(max)
Areas/Area/DataLng/ @Desc	Description of an area Corresponds normally to a holiday region (Tourismusverband/consorzio turistico)	char(max)
Areas/Area/SubArea/ @AreaID	ID of a sub-area Usually corresponds to a tourist board (Tourismusverein)	char(4)
Areas/Area/SubArea/ @PublRID	PublRID-Filter to use in the search	char(max)
Areas/Area/SubArea/	Zone-Filter to use in the search	char(max)

Landesverband der Tourismusorganisationen Südtirols | Gerbergasse 60 | I-39100 Bozen | service@lts.it

@Zone		
Areas/Area/SubArea/ @FraRID	FraRID-Filter to use in the search	char(max)
Areas/Area/SubArea/DataLng/ @Desc	Description of a Sub-Area Corresponds usually to a tourist board (Tourismusverein/Associazione turistica)	char(max)
@Begin	Start of the event	HH:mm
@Begin1	First opening hour (f ex. AM)	HH:mm
@Begin2	Second opening hour (f. ex. PM)	HH:mm
@City	Locality where the event takes place	varchar(50)
@Date	Date	yyyy-MM-dd
@DateFrom	Date from	yyyy-MM-dd
@DateTo	Date to	yyyy-MM-dd
@Day	Day	yyyy-MM-dd
@Days	Defines the opening days from Monday to Sunday. f.ex. "0001111" means closed Monday till Wednesday, open Thursday to Sunday.	Char(7)
@DDesc	Additional description	nvarchar(1200)
@DefDate	If in a search of an event the parameter "ShowSDat" is set to "every day as single event", this parameter returns the actual date to be printed. Note: This attribute is filled only when a global search is made. By searching a single event this field is empty as there is no order there.	yyyy-MM-dd
@DefinitionLng.Title	Title	nvarchar(80)
@DGuide	Guide, Bus operator, …	nvarchar(255)
@DType	Text/Information Type	0 = undefined 1 = normal description 2 = rout description 3 = PDF 4 = Flash 5 = MP3 6 = Zip-File 7 = Website 8 = Video 9 = Facebook 10 = Google+
@DValue	Text/Information	nvarchar(1200)
@DLInsc	Enrol until	nvarchar(255)
@EMail	Email address	nvarchar(80)
@End	End	HH:mm
@End1	End of first opening time (f.ex. AM)	HH:mm
@End2	End of second opening time (f.ex. PM)	HH:mm
@Entrance	Access	HH:mm
@Entrance1	First opening time for access (f.ex. AM)	HH:mm
@Entrance2	Second opening time for access (f.ex. PM)	HH:mm
@EventsTotal	Number of events found by the current search.	int
@PDF	Link to PDF document **Not yet implemented!**	nvarchar(255)
CDay/@TicketsAv	-1 = no info provided 0 = sold out > 0 = amount of available tickets **Not yet implemented!**	int
Data/@EvRID	Event RID	char(32)
@Title	Event Title	nvarchar(80)

Landesverband der Tourismusorganisationen Südtirols | Gerbergasse 60 | I-39100 Bozen | service@lts.it

@Street	Event Street	nvarchar(80)
@City	Event City	nvarchar(50)
@Location	Event Location	nvarchar(80)
@Zip	Event Zip Code	varchar(10)
@Phone	Event Phone	varchar(20)
@GEP	Event Latitude	decimal(18,6)
@GNP	Event Longitude	decimal(18,6)
@FPath	Event First Picture Path	varchar(255)
EveVAllTopics/ @Title	Description of topic	varchar(50)
EveVInstance/ *@EveV*InstanceID	Unique identification of an EventViewer-Instance	char(32)
EveVInstance/Data/ *@Param*	Parameter	char(max)
EveVInstance/Data/ *@Value*	Value of the parameters	char(max)
EveVInstance/Data/ *@Desc*	Description of the parameter	char(max)
@EvRID	ID of the event	varchar(32)
@FName	First name	varchar(50)
Foto/ @Order	Order of the photo	1, 2, 3, …
Foto/ @CRight	Copyright of the photo	varchar(255)
@FPath	URL of the photo	varchar(255)
@FraID	Additional identifier of the district	varchar(20)
@FraRID	Unique identifier of the district	char(32)
@Function	Function to call	varchar(200)
@GEP	GPS coordinates East position	
@GNP	GPS coordinates North position	
@GrpEvent	Describes a group of events	0=no 1=yes
GetEveVFraktion/DataLng/ @Title	Name of the district	varchar(50)
GetEveVNation/DataLng/ @Title	Name of the nation	varchar(30)
@I6RID	Unique identifier for term-groups	char(32)
@LName	Last name	varchar(50)
@LngID	Short form of the language, e.g. de, it, en, fl, cz	varchar(3)
@Location	Location	nvarchar(80)
@MaxP	Max participants	int
@MinP	Min participants	Int
@MPlace	Information about the meeting point	varchar(255)
@NatID	Nation	varchar(2)
@Name	Name	varchar(80)
@Name2	2nd name	varchar(80)
@OName	Name of the organizer	varchar(100)
@OnlyEveHead	Return only (all) EvRID's	0 = no 1 = yes
@OrgRID	Unique identifier of the organizer	char(32)
@PageAct	Page to be returned	smallint
@PageSize	Number of events to show per page	smallint
@PayMet	Payment type	0 = free 1 = on site 2 = free choice

		3 = at the moment of inscrip-tion
@PDesc	Price description	varchar(150)
@Phone	Phone	varchar(20)
@PLong	Price name (long version)	varchar(200)
@PShort	Price name (short version)	varchar(50)
@PStd	Standard price	0 = No 1 = Yes
@Publish	Publish event	0 = undefined 1 = suggested (don't publish) 2 = publish 3 = Publishing denied (don't publish)
@PublRID	Unique identifier of the publisher Note: If this parameter remains empty as search parameter, the search is made over all Publishers. This may cause a considerable loss in performance.	char(32)
@PublType	Publisher type	0 = undefined 1 = View (G0RID) 2 = Address (A0RID)
@PValue	Price	Money
@Ranc	Ranking	1 = not visible 3 = visible 4 = visible / important 5 = Top-event
@Reg	Info about the enrolment	nvarchar(200)
@SeekID	ID of the search (at Paging)	char(32) ""=new search
@SeekWord	Seeking word (divided by blank space) Note: The search runs over more than one field. All results are given which contain one of the words.	varchar(max)
OperationScheduleOv	Description of OperationSchedule **Not yet implemented!**	
@Mon	Monday	bit
@Tue	Tuesday	bit
@Weds	Wednesday	bit
@Thu	Thursday	bit
@Fri	Friday	bit
@Sat	Saturday	bit
@Sun	Sunday	bit
OperationScheduleOvLng/@Desc	Language specific description	nvarchar(255)
SendData/ @Title	Title to search for. Note: The titles must match exactly.	varchar(max)
@SessionID	Session-ID for access-control.	varchar(32)
@ShowSDat	Returns each term as a single event (1/yes) or all terms as one (0=no)	0 = no 1 = yes
@SingleDays	Every day of the term is a single event	0 = no 1 = yes
@SignOn	Enrolment required	0 = no 1 = yes
@Street	Street	varchar(80)
@Tax	Tax number	varchar(16)
@Ticket	Ticked-sale active	0 = no 1 = yes
@TopID	classification	varchar(20)

@TopRID	ID of the classification	varchar(32) “”=all
@UserID	User-ID for access-control	varchar(32)
@Vat	VAT-Number	varchar(13)
@Version	Version of the function to be called	Standard = „1.0“
@Web	Web-address	varchar(255)
@WithCDays	Outputs the calculated terms	0 = no 1 = yes
@WithOrganizer	Outputs the data of the organizer	0 = no 1 = yes
@Zip	Zip	varchar(10)
@Zone	RID’s of the zones that matched the search.	varchar(max)
@PosLatitude	Latitude	float
@PosLongitude	Longitude	float
@PosRadius	Radius	int
@EveTags	Event Tags separated by ;	varchar(max)