

SNOWFLAKE USER ONBOARDING MANUAL FOR ACCESS MANAGEMENT TO SNOWFLAKE ACCOUNTS FOR STARONE.COM

Scope: Onboarding of **PERSON** , **SERVICE** and **LEGACY_SERVICE** users as allowed by Snowflake and enforcing naming conventions, default role assignment.

What are Snowflake Allowed User Types?

1) Personal (Human) Users Used by employees, contractors, or partners accessing Snowflake interactively.

2) Service (Non-Human) Users Used by applications, tools, or automated processes.

- No interactive login
- Password / key-pair authentication
- Rotation policy enforced
- Owned by a business application

What are the Snowflake User Naming Conventions?

Personal Users Format:

- Uppercase prefix USR_
- Lowercase first and last name
- No special characters
- Must match corporate identity records
 - Examples: USR_john_doe, USR_jane_smith

Service Users Format:

- Uppercase prefix SVC_
- Application name in lowercase
- Environment must be one of: dev, test, qa, prod
 - Examples: SVC_airflow_prod, SVC_salesforce_dev

What is Snowflake Default Role Assignment?

All Snowflake users must be assigned the PUBLIC role and have PUBLIC as the default role.

What are Snowflake Role based access control conventions?

- Access beyond PUBLIC is granted via functional roles and a functional role needs to be created first and that has to be done by a separate request.
- No direct grants to users (except PUBLIC)
- Functional Roles are mapped to users via role mapping request that needs to be raised separately.

What are the Snowflake Standard Approved SQLs to be used for user creation?

If the snowflake user is Person or personal:

```
CREATE OR REPLACE USER USR_<username> ;
```

```
GRANT ROLE PUBLIC TO USER USR_<username>;
```

If the snowflake user is service:

```
CREATE OR REPLACE USER SVC_<username> ;
```

```
GRANT ROLE PUBLIC TO USER SVC_<username>;
```

Snowflake User Onboarding Process FAQs

- Requests submitted via internal access management system with mandatory approvals.
- User creation performed only by Snowflake Platform Engineering.
- Service User Security Controls: Key-pair authentication preferred , Password authentication by exception only , Credential rotation every 90 days ,No interactive login allowed