

Introduction to R Programming

Data Science Dojo

Agenda

- R data types
- Basic operations
- Reading and writing data
- Basic statistics
- Basic plotting systems (optional)

What is R?

R is a language and environment for statistical computing and graphics....R provides a wide variety of statistical (linear and nonlinear modeling, classical statistical tests, time-series analysis, classification, clustering, ...) and graphical techniques, and is highly extensible. The S language is often the vehicle of choice for research in statistical methodology, and R provides an Open Source route to participation in that activity.

—*The R Project for Statistical Computing*, <http://www.r-project.org/>

Open source + highly extensibility + era of data science

→ Over **6400 packages** in CRAN package repository (the official one)

R is vectorized

```
f = 1 * 11 + 2 * 22 + 3 * 33
```

```
> A = c(1, 2, 3)
```

```
> B = c(11, 22, 33)
```

```
> f = A * B
```

```
> f
```

```
[1] 11 44 99
```

Good for statistics

Good for data

R for data science

■ Advantages

- Designed for Statistical Analysis
 - Many built-in functions
- Large number of libraries
- Mature open source project

■ Disadvantages

- Overhead (Does not scale well to very large data)
- ## ■ Use R as a “data sandbox” to play with a sample

Hello world

```
c <- "Hello World" # type Enter  
print(c) # print some text  
# anything after a hash (#) is a comment
```

R DATA TYPES

Atomic Classes

- Character
 - Strings
 - Ex “Survived”
- Numeric
 - Floating point type, default for all numbers
 - Ex. “3.147292”
- Integer
 - Append “L” to specify (1L is an integer, 1 is numeric)
 - Ex. “3”
- Complex
 - Two numeric pieces
 - Ex. “3 + 2i”
- Logical
 - TRUE/FALSE

Compound objects

Vector,

List,

Factor,

Matrix,

Data frame, etc.

Vector

The most basic object is a vector

A vector can only contain objects of the same class

Vector – Creating vectors

Empty vectors can be created with the `vector()` function.

```
> x <- vector("numeric", length = 10)
```

```
> x
```

```
[1] 0 0 0 0 0 0 0 0 0 0
```

Vector – Creating vectors

The `c()` function can be used to create vectors of objects.

```
> x <- c(0.5, 0.6) #number  
> x <- c(TRUE, FALSE) # logical  
> x <- c(T, F) #logical  
> x <- c("a", "b", "c") #character  
> x <- c(1+0i, 2+4i) #complex
```

Vector – Creating vectors

: operator

```
> x = 1:20
```

```
> x
```

```
[1] 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20
```

The : operator is used to create integer sequences.

List

List is a special type of vector:

1. Can contain elements of different classes (either basic class or compound class)
2. Each element of list can have a name.

```
> x <- list(1, "a", TRUE, 1 + 4i)
```

```
> x
```

```
> [[1]]
```

```
[1] 1
```

```
> [[2]]
```

```
[1] "a"
```

```
> [[3]]
```

```
[1] TRUE
```

```
> [[4]]
```

```
[1] 1+4i
```

Factor

Factors are used to represent categorical data.

Factors can be unordered or ordered.

One can think of a factor as an integer vector where each integer has a label.

Using factors with labels is better than using integers because factors are self-describing; having a variable that has values "Male" and "Female" is better than a variable that has values 1 and 2.

```
> x <- factor(c("yes", "yes", "no",  
"yes", "no"))
```

```
> x
```

```
[1] yes yes no yes no
```

```
Levels: no yes
```

```
> table(x)
```

```
x
```

```
no yes
```

```
2 3
```

Factor - changing the order of levels

The **order** of the levels can be set using the `levels` argument to `factor()`.

This can be important in **linear modeling** because the first level is used as the baseline level.

```
> x <- factor(c("yes", "yes", "no", "yes",  
"no"))  
> x  
[1] yes yes no  yes no  
Levels: yes no  
  
> x <- factor(x, levels=c("no", "yes"))  
> x  
[1] yes yes no  yes no  
Levels: no yes
```


Matrix

Matrix is a 2-dimensional vector.

The dimension is an attribute, an integer vector of length 2 (nrow, ncol).

```
> m <- matrix(nrow = 2, ncol = 3)
> m
      [,1] [,2] [,3]
[1,] NA  NA  NA
[2,] NA  NA  NA
```

```
> dim(m)
[1] 2 3
> attributes(m)
$dim
[1] 2 3
```

Matrix - cbind() and rbind()

Matrix can be created by *column-binding* or *row-binding* with cbind() and rbind().

```
> x <- 1:3
> y <- 10:12
> cbind(x,y)
  x y
[1,] 1 10
[2,] 2 11
[3,] 3 12
```

```
> rbind(x,y)
[,1] [,2] [,3]
x    1    2    3
y   10   11   12
```

Matrix - naming rows and columns

```
> m <- matrix(1:4, nrow = 2, ncol = 2)
> dimnames(m)
NULL
> dimnames(m) <- list(c("a", "b"), c("c", "d"))
> m
  c d
A 1 3
b 2 4
```

Data frames

Data frames are used to store tabular data.

Unlike matrices, data frames can store different classes of objects in each column; while matrices must have every element be the same class.

Data frames also have a special attribute called `row.names`

Data frames are usually created by calling `read.table()` or `read.csv()`

```
> x <- data.frame(foo = 6:9, bar = c(T, T,
F, F))
> x
  foo bar
1  6 TRUE
2  7 TRUE
3  8 FALSE
4  9 FALSE
> nrow(x)
[1] 4
> ncol(x)
[1] 2
```

Coercion

```
> y <- c(1.7, "a") #character
> y
[1] "1.7" "a"
> y <- c(TRUE, 2) #numeric
> y
[1] 1 2
```

When different objects are mixed in a vector, coercion occurs so that every element in the vector is of the same class.

Coercion - explicit coercion

Objects can be **explicitly** coerced from one class to another using the `as.*` functions.

```
> x <- 0:6
> class(x)
[1] "integer"

> as.numeric(x)
[1] 0 1 2 3 4 5 6
```

```
> as.logical(x)
[1] FALSE TRUE TRUE TRUE TRUE
TRUE TRUE

> as.character(x)
[1] "0" "1" "2" "3" "4" "5" "6"

> as.complex()
complex(0)

> as.complex(x)
[1] 0+0i 1+0i 2+0i 3+0i 4+0i 5+0i 6+0i
```

Missing values

Missing values are denoted by NA or NaN

NaN: Not a Number

NA: a missing value and has various forms - NA_integer_, NA_character_, etc.

NaN value is also NA but the converse is not true.

```
> x <- c(1, 2, NA, 10, 3)
> is.na(x)
[1] FALSE FALSE TRUE FALSE FALSE
> is.nan(x)
[1] FALSE FALSE FALSE FALSE FALSE
```

```
> x <- c(1, 2, NaN, NA, 4)
> is.na(x)
[1] FALSE FALSE TRUE TRUE FALSE
> is.nan(x)
[1] FALSE FALSE TRUE FALSE FALSE
```

Summary of R Data Types

1. Basic data types
2. Compound objects
3. Coercion
4. Missing values

Exercise

Declare two vectors with 3 elements each. Call these x and y. Now do the following:

Use `rbind()` and `cbind()` to create a matrix from these two variables. Observe the difference in structure resulting from `cbind()` and `rbind()` functions.

Name the columns of the matrix.

Create a data frame from x and y and give the columns appropriate names.

Exercise

```
> x <- c(1, 2, 3)
```

```
> y <- c(4, 5, 6)
```

```
> rbind(x, y)
```

```
  [,1] [,2] [,3]
```

```
x    1    2    3
```

```
y    4    5    6
```

```
> cbind(x, y)
```

```
  x y
```

```
[1,] 1 4
```

```
[2,] 2 5
```

```
[3,] 3 6
```

```
> a = cbind(x, y)
```

```
> colnames(a) <- c("x", "y")
```

BASIC OPERATIONS

Subsetting

There are several operators that used to extract subsets of R objects:

`[` always returns an object of the same class as the original object. Can be used to select more than one element.

`[[` is used to extract elements of a list or a data frame

Can only be used to extract a single element and the class of the returned object will not necessarily be a list or data frame.

`$` is used to extract elements of a list or data frame by name. Semantics are similar to that of `[[`.

Subsetting

```
> x <- c("a", "b", "c", "c", "d", "a")
> x[2]
[1] "b"
> x[1:4]
[1] "a" "b" "c" "c"
> x > "a"
[1] FALSE TRUE TRUE TRUE TRUE FALSE
> x[x>"a"]
[1] "b" "c" "c" "d"
```

```
> x <- matrix(1:6, 2, 3)
> x[1,2]
[1] 3
> x[1,] # Entire first row.
[1] 1 3 5
> x[,2] # Entire second column.
[1] 3 4
```

Subsetting

```
> x <- c("a", "b", "c", "c", "d", "a")
> x[2]
[1] "b"
> x[1:4]
[1] "a" "b" "c" "c"
> x > "a"
[1] FALSE TRUE TRUE TRUE TRUE FALSE
> x[x>"a"]
[1] "b" "c" "c" "d"
```

```
> x <- matrix(1:6, 2, 3)
> x[1,2]
[1] 3
> x[1,] # Entire first row.
[1] 1 3 5
> x[,2] # Entire second column.
[1] 3 4
```

Use in data science: drop useless columns

```
titanic.data <- titanic.data[, -c(1, 4, 9, 11)]
titanic.data <- titanic.data[, titanic.data$PassengerId,
titanic.data$Name, titanic.data$Ticket,
titanic.data$Cabin]
```

Built-in functions

Numeric Functions:

`abs(x)` absolute value
`sqrt(x)` square root
`ceiling(x)` `ceiling(3.475)` is 4
`floor(x)` `floor(3.475)` is 3
`trunc(x)` `trunc(5.99)` is 5
`round(x, digits=n)` `round(3.475, digits=2)`
is 3.48
...

Character Functions:

`paste(..., sep="")` Concatenate strings after using
sep string to separate them.
`paste("x", 1:3, sep="")` returns `c("x1", "x2", "x3")`
`paste("x", 1:3, sep="M")` returns `c("xM1", "xM2", "xM3")`

`grep(pattern, x, ignore.case=FALSE, fixed=FALSE)`

Search for pattern in x. If `fixed = FALSE` then pattern is a
regular expression. If `fixed = TRUE` then pattern is a text
string. Returns matching indices.
`grep("A", c("b", "A", "c"), fixed=TRUE)` returns 2
...

Built-in functions

Statistical Functions:

`rnorm()`, `dunif()`, `mean()`, `sum()`...

More complete list:

<http://www.statmethods.net/management/functions.html>

str function

str compactly displays the internal structure of an R object (data object or function)

```
> str(titanic.data)
'data.frame':  891 obs. of  12 variables:
 $ PassengerId: int  1 2 3 4 5 6 7 8 9 10 ...
 $ Survived   : int  0 1 1 1 0 0 0 0 1 1 ...
 $ Pclass     : int  3 1 3 1 3 3 1 3 3 2 ...
 $ Name       : Factor w/ 891 levels "Abbing, Mr. Anthony",...: 109 191 358 277 16 559 520 629 417
81 ...
 $ Sex        : Factor w/ 2 levels "female","male": 2 1 1 1 2 2 2 2 1 1 ...
 $ Age        : num  22 38 26 35 35 NA 54 2 27 14 ...
 $ SibSp      : int  1 1 0 1 0 0 0 3 0 1 ...
 $ Parch      : int  0 0 0 0 0 0 0 1 2 0 ...
 $ Ticket     : Factor w/ 681 levels "110152","110413",...: 524 597 670 50 473 276 86 396 345 133 .
.
 $ Fare       : num  7.25 71.28 7.92 53.1 8.05 ...
 $ Cabin      : Factor w/ 148 levels "", "A10", "A14",...: 1 83 1 57 1 1 131 1 1 1 ...
 $ Embarked   : Factor w/ 4 levels "", "C", "Q", "S": 4 2 4 4 4 3 4 4 4 2 ...
```

Packages

For almost everything you want to do with R, there's probably a package written to do just that.

A list of packages in the official packages repository CRAN can be found here:

<http://cran.fhcrc.org/web/packages/>.

If you need a package, it can be installed very easily from within R using the command:

```
install.packages("packagename") # if package already installed, it'll bypass
```

Libraries in Github can be installed using devtools library.

Working directory

You can set the working directory from the menu if using the R-gui (*Change dir...*) or from the R command line:

```
setwd("C:\\MyWorkingDirectory")  
setwd("C:/MyWorkingDirectory") # can use  
forward slash  
setwd(choose.dir()) # opens a file browser
```

```
getwd() # returns a string with  
# the current working directory
```

To see a list of the files in the current directory:

```
dir() # returns a list of strings of file names  
dir(pattern=".R$") # list of files ending in ".R"  
dir("C:\\Users") # show files in directory  
C:\\Users
```

Run a script:

```
source("helloworld.R") # execute a script
```

Summary of Basic Operations

1. Sub-setting
2. Built-in functions
3. Packages
4. Working directory

READING AND WRITING DATA

Reading/writing local flat files

read.table, read.csv, and readLines

CSV stands for 'Comma Separated Values'

```
> titanic_data <- read.csv("Titanic.csv")
```

```
> head(titanic_data, 3)
```

	X	Class	Sex	Age	Survived	Freq
1	1	1st	Male	Child	No	0
2	2	2nd	Male	Child	No	0
3	3	3rd	Male	Child	No	35

Reading/writing local flat files

Notice the parameters before reading/writing

Ex.: the `read.table` function is one of the most commonly used functions for reading data. It has a few important arguments:

file, the name of a file, or a connection

header, logical indicating if the file has a header line

sep, a string indicating how the columns are separated

colClasses, a character vector indicating the class of each column in the dataset

nrows, the number of rows in the dataset

comment.char, a character string indicating the comment character

skip, the number of lines to skip from the beginning

stringsAsFactors, should character variables be coded as factors?

Reading/writing Excel files

read.xlsx, write.xlsx,
or read.xlsx2, write.xlsx2 (faster, but unstable)

```
# Install the xlsx library
> install.packages('xlsx')
# Load the library
> library(xlsx)
# Now you can Read the Excel file
> titanic_data <- read.xlsx("titanic3.xls", sheetIndex=1)
```


Reading XML/HTML files

```
> library(XML) # you need to install this library
> url <- "http://www.w3schools.com/xml/simple.xml"
> doc <- xmlTreeParse(url, useInternal=TRUE) # also works for html
> rootNode <- xmlRoot(doc)
> rootNode[[1]]
<food>
  <name>Belgian Waffles</name>
  <price>$5.95</price>
  <description>Two of our famous Belgian Waffles with plenty of real maple syrup</description>
  <calories>650</calories>
</food>
```

Reading/writing JSON

JSON: Javascript object notation.

Common format for data from application programming interfaces (APIs). An alternative to XML

```
> library(jsonlite)
> jsonData <- fromJSON("http://citibikenyc.com/stations/json")
> names(jsonData)
[1] "executionTime" "stationBeanList"
> jsonData$stationBeanList[1,1:3]
   id   stationName availableDocks
1 72 W 52 St & 11 Ave           31
```

Connect to a data base

JSONPackages: RmySQL, RpostresSQL, RODBC, RMONGO

```
> library(RMySQL)# load the library
> ucscDb <- dbConnect(MySQL(), user="genome", host="genome-mysql.cse.ucsc.edu")
> data <- dbGetQuery(ucscDb, "show databases;") # get the output of SQL query as data frame in R
> head(data)
  Database
1 information_schema
2      ailMel1
3      allMis1
4      anoCar1
5      anoCar2
6      anoGam1
> dbDisconnect(ucscDb) # don't forget to close the connection
```

BASIC STATISTICS

Basic Statistics

Summary(titanic.data)

- Mean
- Quartiles
- Maximum
- Number of NAs

PassengerId	Survived	Pclass	Name
Min. : 1.0	Min. :0.0000	Min. :1.000	Abbing, Mr. Anthony : 1
1st Qu.:223.5	1st Qu.:0.0000	1st Qu.:2.000	Abbott, Mr. Rossmore Edward : 1
Median :446.0	Median :0.0000	Median :3.000	Abbott, Mrs. Stanton (Rosa Hunt) : 1
Mean :446.0	Mean :0.3838	Mean :2.309	Abelson, Mr. Samuel : 1
3rd Qu.:668.5	3rd Qu.:1.0000	3rd Qu.:3.000	Abelson, Mrs. Samuel (Hannah Wozosky): 1
Max. :891.0	Max. :1.0000	Max. :3.000	Adahl, Mr. Mauritz Nils Martin : 1
			(Other) :885

Sex	Age	SibSp	Parch	Ticket	Fare
female:314	Min. : 0.42	Min. :0.000	Min. :0.0000	1601 : 7	Min. : 0.00
male :577	1st Qu.:20.12	1st Qu.:0.000	1st Qu.:0.0000	347082 : 7	1st Qu.: 7.91
	Median :28.00	Median :0.000	Median :0.0000	CA. 2343: 7	Median :14.45
	Mean :29.70	Mean :0.523	Mean :0.3816	3101295 : 6	Mean :32.20
	3rd Qu.:38.00	3rd Qu.:1.000	3rd Qu.:0.0000	347088 : 6	3rd Qu.:31.00
	Max. :80.00	Max. :8.000	Max. :6.0000	CA 2144 : 6	Max. :512.33
	NA's :177			(Other) :852	

BASIC PLOTTING SYSTEMS

Basic plotting systems

1. **Base R graphics:** Simple and allows plotting to mirror the thought process.
2. **Lattice graphics:** Entire plots created in a simple function call.
3. **ggplot2 graphics:** an implementation of the Grammar of Graphics by Leland Wilkinson. Combines concepts from both base and lattice graphics.
4. **Other graphics packages:** wait for the bootcamp!

A list of interactive visualization in R at:

<http://ouzor.github.io/blog/2014/11/21/interactive-visualizations.html>



Base R plotting systems

Plotting functions

`plot(x, y, ...)` → main function for creating scatterplots

`boxplot()` → box and whisker plots


`hist()` → histograms



Base R plotting systems

```
> library(datasets)
> names(airquality)
[1] "Ozone" "Solar.R" "Wind" "Temp"
"Month" "Day"
```

```
> plot(x = airquality$Temp, y =
airquality$Ozone)
```



Basic plotting systems

Additional functions

lines: adds lines to a plot, given a vector of x values and corresponding vector of y values

points: adds a point to the plot

text: add text labels to a plot using specified x,y coordinates

title: add annotations to x,y axis labels, title, subtitles, outer margin


mtext: add arbitrary text to margins (inner or outer) of plot

axis: specify axis ticks

Basic plotting systems

Add more capability with more commands

```
> with(airquality, {  
+ plot(Wind, Ozone, main="Ozone and Wind")  
+ plot(Temp, Ozone, main="Ozone and Temperature")  
+ mtext("Ozone and Weather in New York City",  
+ outer=TRUE)  
+ })
```



Lattice plotting systems


Plotting functions

xyplot(x, data...) → main function for creating scatterplots

bwplot() → box and whiskers plots (box plots)

histogram() → histograms

densityplot() → shows concentration of numbers




ggplot2 plotting systems

Need to install ggplot2
library

Mix elements of base and
lattice

Good tutorial (3 basic
plotting systems):
[https://sux13.github.io/Data
ScienceSpCourseNotes/4_EX
DATA/Exploratory_Data_An
alysis_Course_Notes.html](https://sux13.github.io/DataScienceSpCourseNotes/4_EXDATA/Exploratory_Data_Analysis_Course_Notes.html)



Reference

<https://cran.r-project.org/doc/manuals/R-intro.pdf>