isc N-Channel MOSFET Transistor IRL1404，IIRL1404

• FEATURES

- Static drain-source on-resistance:
  $R_{DS}(on)$ ≤4.0mΩ
- Enhancement mode
- Fast Switching Speed
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation



• DESCRIPTION

- Combine with the fast switching speed and ruggedized device design,provide the designer with an extremely efficient and reliable device for use in a wide variety of applications.

• ABSOLUTE MAXIMUM RATINGS(T_a=25℃)

SYMBOL	PARAMETER	VALUE	UNIT
V_{DSS}	Drain-Source Voltage	40	V
V_{GS}	Gate-Source Voltage	±20	V
I_D	Drain Current-Continuous	160	A
I_{DM}	Drain Current-Single Pulsed	640	A
P_D	Total Dissipation @T_C=25℃	200	W
T_j	Max. Operating Junction Temperature	175	℃
T_{stg}	Storage Temperature	-55~175	℃

• THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
Rth(ch-c)	Channel-to-case thermal resistance	0.75	℃/W
Rth(ch-a)	Channel-to-ambient thermal resistance	62	℃/W



DIM	mm MIN	MAX
A	15.50	15.90
B	9.90	10.20
C	4.20	4.50
D	0.70	0.90
F	3.40	3.70
G	4.98	5.18
H	2.68	2.90
J	0.44	0.60
K	13.00	13.40
L	1.10	1.45
Q	2.70	2.90
R	2.30	2.70
S	1.29	1.35
U	6.45	6.65
V	8.66	8.86

isc N-Channel MOSFET Transistor IRL1404，IIRL1404

ELECTRICAL CHARACTERISTICS

T_C=25℃ unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS}=0V; I_D =250 μA	40			V
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}; I_D =250 μA	1		3	V
$R_{DS(on)}$	Drain-Source On-Resistance	V_{GS}=10V; I_D=95A			4	mΩ
I_{GSS}	Gate-Source Leakage Current	V_{GS}= ±20V			±200	nA
I_{DSS}	Drain-Source Leakage Current	V_{DS}=40V; V_{GS}= 0V			20	μA
V_{SD}	Diode forward voltage	I_S=95A; V_{GS} = 0V			1.3	V