Drill Driver CXT®

DF033D

12V max • 30 Nm • 0 – 1 700 min^{-1}

Small and light drill driver

A compact drill driver for fitters and maintenance staff and for home use. Thanks to its small size, this tool is easy to use and offers access to tight places. A max. torque of 35 / 21 Nm and two speed ranges. Integrated LED light.

Technical specifications

CXT Battery	✓
No load speed	0 - 450 / 0 - 1700 min^{-1}
Max. fastening torque Hard/Soft	30 / 14 Nm
Torque setting	20
Max. Drilling Diameter in Wood	21 mm
Max. Drilling Diameter in Steel	10 mm
Sound Pressure Level (L_{pA})	≤ 70 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Tool weight with battery	0,9 kg
Nominal Battery Voltage	12 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Drilling Capacity Wood (Self-feed bit)	42 mm
Driving Shank	1/4 "
Vibration Level, Drilling into metal	≤ 2,5 m/s^2
Vibration Uncertainty (K Factor), Drilling into metal	1,5 m/s^2

User benefits

- LED light illuminates the work site
- Ideal for working in tight spaces and overhead applications
- The rubber coating on the handle ensures a firm working grip
- Battery protection system automatically shuts off power when the battery level is low
- Quick mount for 1/4 "screwdriver

Link to product - www.makitauk.com

Related products

Other

User manual

Parts drawing