```sql
INSERT INTO User (user_id, user_name, user_email, account_type, accoun
  ('T312', 'Alex Turner',  'AlexT@company.com',          'Photographer
  ('L520', 'Mia Chen',     'MiaChen@domain.co.uk',       'Public Figur
  ('Q789', 'Leo Sanchez',  'Leo.Sanchez@webmail.com',    'Business',
  ('P120', 'Sophia Wong',  'SophiaW@yahoo.com',          'Model',

INSERT INTO Location (location_name) VALUES
  ('Big Ben, London, UK'),
  ('Times Square, New York, USA'),
  ('Sydney Opera House, Sydney, AUS');

INSERT INTO following (follower_id, followee_id) VALUES
  ('L520', 'T312'),   -- Mia follows Alex
  ('Q789', 'T312'),   -- Leo follows Alex
  ('P120', 'Q789'),   -- Sophia follows Leo
  ('T312', 'P120');   -- Alex follows Sophia

INSERT INTO user_check_in (user_id, location_id, checkin_timestamp) VA
  ('L520', 1, '2025-06-10 14:30:00'),   -- Mia @ Big Ben
  ('Q789', 2, '2025-08-01 09:00:00'),   -- Leo @ Times Square
  ('P120', 3, '2025-09-03 11:00:00');   -- Sophia @ Sydney Opera House

  SELECT
    u.user_name,
    COUNT(f.follower_id) AS total_followers
FROM User u
LEFT JOIN following f ON u.user_id = f.followee_id
WHERE u.user_id NOT IN (
    SELECT DISTINCT user_id FROM user_check_in
)
GROUP BY u.user_id, u.user_name
ORDER BY u.user_name ASC, total_followers DESC;
```

Output: 184 ms

```
+-------------+-----------------+
| user_name   | total_followers |
+-------------+-----------------+
| Alex Turner |               2 |
+-------------+-----------------+
```