

Instancias GPU

	p6-b300.48xlarge	p5en.48xlarge	p5.48xlarge	p4d.24xlarge	g6e.xlarge	g7e.2xlarge
CPU	Intel Xeon 5th Gen (Emerald Rapids)	Intel Xeon 4th Gen (Sapphire Rapids)	Intel Xeon 4th Gen (Sapphire Rapids)	Intel Xeon 2nd Gen (Cascade Lake 8275CL)	AMD EPYC 7R13 Processor	Intel Xeon Scalable (Emerald Rapids)
vCPU	192	192	192	96	4	8
Cores físicos host	96 (SMT on)	96 (SMT on)	96 (SMT on)	48 (dual socket)		
RAM sistema	4,096 GiB	2,048 GiB	2,048 GiB	1,152 GiB	32 GiB	62 GiB
GPU	8× NVIDIA B300	8× NVIDIA H200	8× NVIDIA H100	8× NVIDIA A100	1x NVIDIA L40S	1× NVIDIA GB202
Arquitectura GPU	Blackwell Ultra (sm_100a)	Hopper (sm_90a)	Hopper (sm_90)	Ampere (sm_80)	Ada Lovelace	Blackwell
VRAM por GPU	268 GB HBM3e	141 GB HBM3e	80 GB HBM3	80 GB HBM2e	48 GB GDDR6	96 GB GDDR7
VRAM total	2,144 GB	1,128 GB	640 GB	640 GB	48 GB	96 GB
GPU Memory BW	8 TB/s	4.8 TB/s	3.35 TB/s	4x 100 Gbps	20 Gbps	50 Gbps
GPU Interconnect	NVLink 5 + NVSwitch	NVLink 4 + NVSwitch	NVLink 4 + NVSwitch	NVLink 3 + NVSwitch		
PCIe	Gen5	Gen5	Gen5	Gen4		
NVMe local	30 TB	30 TB	30 TB	8 TB	250 Gib	1900 Gib
Red EFA	6,400 Gbps (EFAv4)	3,200 Gbps (EFAv3)	3,200 Gbps (EFAv2)	400 Gbps (EFAv1)		
ENA (IP traffic)	300 Gbps	300 Gbps	300 Gbps	100 Gbps		
CUDA mínimo	13.0	12.4	12.0	11.0		
Driver NVIDIA mín.	R580	R550	R535	R470		

Instancias CPU

	hpc8a.96xlarge	hpc6id.32xlarge	hpc6a.48xlarge	m8a.48xlarge	c8a.48xlarge
CPU	AMD EPYC 5th Gen 9004 (Turin)	Intel Xeon 3rd Gen (Ice Lake)	AMD EPYC 7R13 Processor (Milan)	AMD EPYC 5th Gen 9004 (Turin)	AMD EPYC 5th Gen 9004 (Turin)
Sockets	2 (96 cores/socket)	1	2	2	2
Cores físicos	192	64	48	96	96
SMT (Hyperthreading)	Off (1 thread/core)	Off (1 thread/core)	On (2 threads/core)	On (2 threads/core = 192 vCPU)	On (2 threads/core = 192 vCPU)
vCPU	192	64	96	192	192
Freq. max	4.5 GHz	3.5 GHz	2.95 GHz	4.5 GHz	4.5 GHz
RAM	768 GiB	1,024 GiB	384 GiB	768 GiB	384 GiB
Canales memoria	12 (DDR5)	8 (DDR4)	12 (DDR5)	12 (DDR5)	12 (DDR5)
NVMe local	No	15.2 TB	No	No	No
Red EFA	300 Gbps	200 Gbps	100 Gbps	~50 Gbps	75 Gbps
ENA (IP traffic)	300 Gbps	200 Gbps	100 Gbps	50 Gbps	75 Gbps
ISA extensions	AVX-512, VNNI, BF16	AVX-512, VNNI		AVX-512, VNNI, BF16	AVX-512, VNNI, BF16

Para obtener más información sobre las especificaciones de cada tipo de instancia es posible consultar la herramienta Vantage Instances: <https://instances.vantage.sh>