

Getting Help in R




R

?




```
## display documentation
?summary
```



```
## display documentation
?summary
```

general
description



The screenshot shows the R Documentation window for the 'summary' function. The window has a menu bar with 'Files', 'Plots', 'Packages', 'Help', and 'Viewer'. Below the menu bar is a toolbar with navigation icons and a search bar. The main content area displays the documentation for 'summary {base}'. The title 'Object Summaries' is prominently displayed. A pink rectangular box highlights the 'Description' section, which states that 'summary' is a generic function used to produce result summaries of the results of various model fitting functions. Below the description is the 'Usage' section, which shows the function signature 'summary(object, ...)' and several S3 methods for different classes: 'data.frame', 'factor', 'matrix', and 'summaryDefault'. The 'summaryDefault' methods are shown with their respective format and print functions.

summary {base} R Documentation

Object Summaries

Description

summary is a generic function used to produce result summaries of the results of various model fitting functions. The function invokes particular [methods](#) which depend on the [class](#) of the first argument.

Usage

```
summary(object, ...)
```

Default S3 method:
summary(object, ..., digits)


S3 method for class 'data.frame'
summary(object, maxsum = 7,
 digits = max(3, getOption("digits")-3), ...)

S3 method for class 'factor'
summary(object, maxsum = 100, ...)

S3 method for class 'matrix'
summary(object, ...)

S3 method for class 'summaryDefault'
format(x, digits = max(3L, getOption("digits") - 3L), ...)
S3 method for class 'summaryDefault'
print(x, digits = max(3L, getOption("digits") - 3L), ...)

```
## display documentation  
?summary
```



The screenshot shows the R Documentation window for the `summary` function. The window has a menu bar with 'Files', 'Plots', 'Packages', 'Help', and 'Viewer'. Below the menu bar is a toolbar with navigation icons and a search bar. The main content area displays the documentation for `summary`. A pink arrow points from the text 'package the function is from' to the `summary {base}` line. A pink box highlights the 'Description' section. The 'Usage' section shows the function signature and several S3 methods.

summary {base} R Documentation

Object Summaries

Description

`summary` is a generic function used to produce result summaries of the results of various model fitting functions. The function invokes particular [methods](#) which depend on the [class](#) of the first argument.

Usage

```
summary(object, ...)
```

Default S3 method:
summary(object, ..., digits)

S3 method for class 'data.frame'
summary(object, maxsum = 7,
 digits = max(3, getOption("digits")-3), ...)

S3 method for class 'factor'
summary(object, maxsum = 100, ...)

S3 method for class 'matrix'
summary(object, ...)

S3 method for class 'summaryDefault'
format(x, digits = max(3L, getOption("digits") - 3L), ...)
S3 method for class 'summaryDefault'
print(x, digits = max(3L, getOption("digits") - 3L), ...)

general
description

package the function is from

```
## display documentation
?summary
```

The screenshot shows the R Documentation window for the 'summary' function. The window has a menu bar with 'Files', 'Plots', 'Packages', 'Help', and 'Viewer'. Below the menu bar is a toolbar with navigation icons and a search bar. The main content area is titled 'R: Object Summaries' and 'summary {base}'. A pink arrow points from the text 'package the function is from' to the '{base}' part of the title. The content is organized into sections: 'Description', 'Usage', and 'Examples'. The 'Description' section is highlighted with a pink box. The 'Usage' section is also highlighted with a pink box. The 'Examples' section contains several code snippets for different classes.

summary {base} R Documentation

Object Summaries

Description

summary is a generic function used to produce result summaries of the results of various model fitting functions. The function invokes particular [methods](#) which depend on the [class](#) of the first argument.

Usage

```
summary(object, ...)
```

Default S3 method:
summary(object, ..., digits)
S3 method for class 'data.frame'
summary(object, maxsum = 7,
 digits = max(3, getOption("digits")-3), ...)

S3 method for class 'factor'
summary(object, maxsum = 100, ...)

S3 method for class 'matrix'
summary(object, ...)

S3 method for class 'summaryDefault'
format(x, digits = max(3L, getOption("digits") - 3L), ...)
S3 method for class 'summaryDefault'
print(x, digits = max(3L, getOption("digits") - 3L), ...)

general
description

syntax
(how to use it)

```
## display documentation
?summary
```

general
description

syntax
(how to use it)

example
code

summary {base} ← package the function is from

Object Summaries

Description

summary is a generic function used to produce result summaries of the results of various model fitting functions. The function invokes particular [methods](#) which depend on the [class](#) of the first argument.

Usage

```
summary(object, ...)
```

```
## Default S3 method:
summary(object, ..., digits)
## S3 method for class 'data.frame'
summary(object, maxsum = 7,
        digits = max(3, getOption("digits")-3), ...)

## S3 method for class 'factor'
summary(object, maxsum = 100, ...)

## S3 method for class 'matrix'
summary(object, ...)

## S3 method for class 'summaryDefault'
format(x, digits = max(3L, getOption("digits") - 3L), ...)
## S3 method for class 'summaryDefault'
print(x, digits = max(3L, getOption("digits") - 3L), ...)
```

Learn, Share, Build

Each month, over 50 million developers come to Stack Overflow to learn, share their knowledge, and build their careers.

Join the world's largest developer community.



OR

Display name

J. Doe

Email address

you@example.com

Password

Sign Up

By registering, you agree to the [privacy policy](#) and [terms of service](#).

Stack Overflow Business Solutions: Looking to understand, engage, or hire developers? [Learn more](#) »

Top Questions

interesting

362 featured

hot

week

month

Ask Question

0 votes

0 answers

2 views

How Does FindSecBug Differ from SonarQube?

sonarqube

find-sec-bugs

asked 33 secs ago Tharushi Geethma 303

0 votes

0 answers

4 views

Magic in the way R evaluates function arguments

r

asked 1 min ago Yatharth Agarwal 2,866

0 votes

0 answers

5 views

csv to dictionary in specific lists (adding values when duplicated keys)

python

list

dictionary

asked 2 mins ago Victor 27

Build with
bare metal.

Designed to
keep data safe.

Learn more





NEW

Questions

Developer Jobs

Tags

Users

objects in R



1 0 1



Search

results found containing **objects in r**

Ask Question

objects in R

search

Advanced Search Tips

22,314 results

relevance

newest

votes

active

107

votes

6

answers

Q: Returning multiple objects in an R function [duplicate]

How can I return multiple **objects in an R** function? In Java, I would make a Class, maybe Person which has some private variables and encapsulates, maybe, height, age, etc. But **in R**, I need to pass ... around groups of data. For example, how can I make an **R** function return both an list of characters and an integer? ...

r

function

tags

date
asked

asked Jan 20 '12 by CodeGuy

192

votes

5

answers

Q: How to check if object (variable) is defined in R?

I'd like to check if some variable is defined **in R** - without getting an error. How can I do this? My attempts (not successful): `> is.na(oxxx)` Error: **object** 'ooxx' not found `> is.finite(oxxx)` Error: **object** 'ooxx' not found Thanks! ...

r

asked Feb 20 '12 by TMS

0

votes

1

answer

Q: Storing plot objects in R [duplicate]

Two methods of storing plot **objects in** list or a name string are mentioned on this page Generating names iteratively **in R** for storing plots . But both do not seem to work on my system. `> plist ... = list() > plist[[1]] = plot(1:30) > > plist(list()) > > plist[[1]]` Error in `plist[[1]]` : subscript out of bounds Second method: `> assign('pp', plot(1:25)) > > pp` NULL I am using: `> R.version` ...

r

object

plot

asked May 10 '15 by mso

Build with
bare metal.Designed to
keep data safe.

Learn more

IBM Cloud

Jobs near you

Digital Network Exploitation Analyst -
Entry/Mid-Level

National Security Agency Fort Meade, MD

\$79K - \$105K

r

c

Data Scientist

National Security Agency Fort Meade, MD

\$79K - \$105K

of
answers



NEW

Questions

Developer Jobs

Tags

Users

objects in R



1 0 1



Search

results found containing **objects in r**

Ask Question

objects in R

search

Advanced Search Tips

22,314 results

relevance

newest

votes

active

107

votes

6

answers

Q: Returning multiple objects in an R function [duplicate]

How can I return multiple **objects in an R** function? In Java, I would make a Class, maybe Person which has some private variables and encapsulates, maybe, height, age, etc. But in **R**, I need to pass ... around groups of data. For example, how can I make an **R** function return both an list of characters and an integer? ...

r

function

asked Jan 20 '12 by CodeGuy

192

votes

5

answers

Q: How to check if object (variable) is defined in R?

I'd like to check if some variable is defined in **R** - without getting an error. How can I do this? My attempts (not successful): `> is.na(oxxx)` Error: **object 'ooxx'** not found `> is.finite(oxxx)` Error: **object 'ooxx'** not found Thanks! ...

r

asked Feb 20 '12 by TMS

0

votes

1

answer

Q: Storing plot objects in R [duplicate]

Two methods of storing plot **objects in** list or a name string are mentioned on this page Generating names iteratively in **R** for storing plots . But both do not seem to work on my system. `> plist ... = list() > plist[[1]] = plot(1:30) > > plist` list() `> > plist[[1]]` Error in `plist[[1]]` : subscript out of bounds Second method: `> assign('pp', plot(1:25)) > > pp` NULL I am using: `> R.version` ...

r

object

plot

asked May 10 '15 by mso

Build with
bare metal.Designed to
keep data safe.

Learn more

IBM Cloud

Jobs near you

Digital Network Exploitation Analyst -
Entry/Mid-Level

National Security Agency Fort Meade, MD

\$79K - \$105K

r

c

Data Scientist

National Security Agency Fort Meade, MD

\$79K - \$105K

Welcome to Stack Overflow!

We'd love to help you, but the reality is that not every question gets answered. To **improve your chances**, here are some tips:

Search, and research

Have you [thoroughly searched for an answer](#) *before* asking your question? Sharing your research helps everyone. Tell us what you found (on this site or elsewhere) and why it didn't meet your needs. This demonstrates that you've taken the time to try to help yourself, it saves us from reiterating obvious answers, and above all, it helps *you* get a more specific and relevant answer!

Try our more [advanced search](#)!

Be on-topic

Our community is defined by a [specific set of topics in the help center](#); please stick to those topics and [avoid asking for opinions or open-ended discussion](#). If your question is about the site itself, ask on our [meta-discussion site](#). If you're looking for a different topic, it might be covered on another [Stack Exchange site](#).

Be specific

If you ask a vague question, you'll get a vague answer. But if you give us details and context, we can provide a useful, relevant answer.

Make it relevant to others

We like to help as many people at a time as we can. Make it clear how your question is relevant to more people than just you, and more of us will be interested in your question and willing to look into it.

Keep an open mind

The answer to your question may not always be the one you wanted, but that doesn't mean it is wrong. A conclusive answer isn't always possible. When in doubt, ask people to cite their sources, or to explain how/where they learned something. Even if we don't agree with you, or tell you exactly what you wanted to hear, remember: we're just trying to help.

☐ thanks, I will keep these tips in mind when asking

[proceed »](#)

Reproducible Examples : reprex

1. Reproducible

- it must run start to finish (up until the part where you're running into trouble)
- includes any packages required
- Includes or creates all necessary objects

2. Minimal

- Remove any code not directly related to the problem
- Often requires making a smaller dataset than the one you're working with.

all categories ▾

all tags ▾

Latest




























New

Unread

Categories

Top

+ New Topic

Topic	Category	Users	Replies	Views	Activity
<input type="checkbox"/> R Unit Testing and Bitbucket Pipelines	General	 	1	12	1m
<input type="checkbox"/>  Welcome to the RStudio Community! Welcome to <community.rstudio.com> — we're glad to have you! This welcome page will give you some advice on how to get the most out of the site if you're getting or giving help. We want this to be a friendly, inclusive c... read more	meta		0	1.4k	Aug '17
<input type="checkbox"/> How to change the color of the lines based on a certain rules in plotly	shiny	 	5	38	3m
<input type="checkbox"/> How to install packages using devtools	General		0	4	32m
<input type="checkbox"/> Dplyr: Alternatives to rowwise dplyr	tidyverse	    	8	142	33m
<input type="checkbox"/> What DO you use R for (other than data science)?	General	    	6	169	1h
<input type="checkbox"/> What is hard about blogdown? 🍷	General	    	15	124	1h
<input type="checkbox"/> Ggplot2: How to specify x labels in a datetime data and two segment lines	tidyverse	   	5	49	1h
<input type="checkbox"/> Trying to calculate standard error and proportions	General		1	10	2h

all categories ▾

all tags ▾

Latest










New

Unread

Categories

Top

+ New Topic

Topic	Category	Users	Replies	Views	Activity
<input type="checkbox"/> R Unit Testing and Bitbucket Pipelines	General		1	12	1m
🔒 <input type="checkbox"/> Welcome to the RStudio Community! Welcome to <community.rstudio.com> — we're glad to have you! This welcome page will give you some advice on how to get the most out of the site if you're getting or giving help. We want this to be a friendly, inclusive c... read more	meta		0	1.4k	Aug '17
<input type="checkbox"/> How to change the color of the lines based on a certain rules in plotly	shiny		5	38	3m
<input type="checkbox"/> How to install packages using devtools	General		0	4	32m
<input type="checkbox"/> Dplyr: Alternatives to rowwise dplyr	tidyverse		8	142	33m
<input type="checkbox"/> What DO you use R for (other than data science)?	General		6	169	1h
<input type="checkbox"/> What is hard about blogdown? 🍷	General		15	124	1h
<input type="checkbox"/> Ggplot2: How to specify x labels in a datetime data and two segment lines	tidyverse		5	49	1h
<input type="checkbox"/> Trying to calculate standard error and proportions	General		1	10	2h