

REFERENCE



Events (onclick)

The user acts · your code reacts

사용자가 행동하면 코드가 반응

BIG IDEA

An **event** is something the user does

JS can listen, then run code when it happens.



click

press a button



type

enter text



hover

move the mouse

이벤트 = 사용자의 행동

ONCLICK

Run a function on click

```
<button onclick="sayHi()">Click me</button>

<script>
  function sayHi() {
    alert("Hi!");
  }
</script>
```

`onclick` names the function to run. The `()` calls it.

클릭하면 함수 실행

THE FUNCTION

Where the action lives

```
function sayHi() {  
  let el = document.getElementById("msg");  
  el.textContent = "You clicked!";  
}
```

Click runs the function. The function changes the page.

함수 안에 할 일을 적음

GROWN-UP WAY

addEventListener

```
let btn = document.getElementById("go");  
btn.addEventListener("click", sayHi);
```

Same idea, kept out of the HTML. Notice: `sayHi` with **no** `()` here.

HTML 밖에서 이벤트 연결

⚠ WATCH

The `()` rule



onclick

`onclick="sayHi()"`
call it – keep `()`



addEventListener

`"click", sayHi`
pass the name – no `()`

In `addEventListener`, `sayHi()` runs it **now** by mistake. Pass `sayHi`.

addEventListener엔 괄호 없이

YOUR TURN!

Make a button react

- ✓ Add a `<button>` and a `<p id="msg">`
- ✓ Write a function that changes the `msg` text
- ✓ Connect it with `onclick`
- ✓ Click → watch the text change

클릭하면 글자 바뀌게

PRACTICE



Build these step by step

Follow along, then fly solo.

Every one is the **same shape**: **1)** HTML — give it an `id` · **2)** JS — `onclick` · **3)** change it.

전부 같은 흐름: id → onclick → 바꾸기

FOLLOW ALONG · A1

Change text on click — set it up

Step 1 — HTML: a button and a paragraph, each with an `id`

```
<button id="btn">Tap</button>  
<p id="msg">Hello</p>
```

No CSS this time — JS will change the text for us.

버튼과 글자에 id만 붙임

FOLLOW ALONG · A2

Change text on click — make it react ⚡

Step 2 — JS: grab both, change the text on click

```
let btn = document.getElementById("btn");
let msg = document.getElementById("msg");

btn.onclick = () => {
  msg.textContent = "Clicked!";
};
```

클릭하면 글자가 바뀜

FOLLOW ALONG · B1

Toggle show / hide — set it up

Step 1 — HTML: name the box

```
<div id="box">Peekaboo</div>
```

Step 2 — CSS: a class that hides it

```
.hidden { display: none; }
```

HTML + CSS 먼저

FOLLOW ALONG · B2

Toggle show / hide — make it react ⚡

Step 3 — JS: flip the class on and off

```
let box = document.getElementById("box");

box.onclick = () => {
  box.classList.toggle("hidden");
};
```

`toggle` adds the class if it's off, removes it if it's on.

`toggle` = 있으면 빼고, 없으면 더함

FOLLOW ALONG · C1

Click counter — set it up

Step 1 — HTML: a button that shows a number

```
<button id="box">0</button>
```

It starts at **0**. JS will count up from there.

버튼에 숫자 0부터 시작

FOLLOW ALONG · C2

Click counter — make it react ⚡

Step 2 — JS: keep a count, add 1 each click

```
let box = document.getElementById("box");
let count = 0;

box.onclick = () => {
  count = count + 1;
  box.textContent = count;
};
```

변수로 세서 버튼에 표시

NOW YOU TRY

Your turn — make a...

Same shape: id → onclick → change it. Pick one, build all three.



like button

toggle ♥ · `classList.toggle`



change background

`style.background`



count clicks

`count + 1`



disable after click

`btn.disabled = true`



show a message

`textContent`



double-click

`ondblclick`

같은 흐름: id → onclick → 바꾸기

BOSS CHALLENGE

Level up



Light switch — toggle a class on and off (`classList.toggle`)



Reset counter — count up, then back to 0 at 10



Two buttons — each one does a different job



Invent your own — pick a "make it ___" and build all 3 steps

한 번의 클릭으로 더 많은 일



Your page reacts!

User clicks · function runs · page changes.

잘했어요!