

REFERENCE



Two ways to grab

getElementById vs querySelector

요소를 잡는 두 가지 방법

BIG IDEA

Both find **one** element

Same goal, different spelling.



getElementById

by id only

"hero"



querySelector

by CSS selector

"#hero"

둘 다 요소 하나를 찾음

GETELEMENTBYID

The id — no

```
let el = document.getElementById("hero");
```

Just the id name. No #, no dots. Only works with id.

id 이름만 — #없음

QUERYSELECTOR

A CSS selector — needs

```
let el = document.querySelector("#hero");
```

Same as in CSS: # for id. The first match wins.

CSS처럼 #붙임

SUPERPOWER

querySelector takes **any** selector

```
document.querySelector("#hero");    // id
document.querySelector(".card");    // class
document.querySelector("button");    // tag
```

`getElementById` only does ids. `querySelector` does them all.

querySelector는 무엇이든 선택

⚠ WATCH

The # trips people up



Correct

```
getElementById("hero")  
querySelector("#hero")
```



Returns null

```
getElementById("#hero")  
querySelector("hero")
```

Wrong # → JS finds nothing → null.

#을 잘못 쓰면 null

YOUR TURN!

Grab it both ways

✓ Add `id="title"` to a heading

✓ Grab it with `getElementById("title")`

✓ Grab it again with `querySelector("#title")`

✓ Change its text — both should work

두 방법 모두 연습

PRACTICE



Grab it, then change it

Follow along first. Then fly solo.

Same move every time: **pick the element** → change its `textContent` or style.

잡고 → 바꾸기, 매번 같은 흐름

FOLLOW ALONG · A

Grab by id — set it up

Step 1 — HTML: give it an `id`

```
<h1 id="title">Hello</h1>
```

One name tag, two ways to grab it on the next slide.

id 하나, 잡는 방법은 두 가지

FOLLOW ALONG · A

Grab by id — two ways ⚡

Step 2 — JS: both find the same element

```
let el = document.getElementById("title");  
// or the querySelector way:  
let el = document.querySelector("#title");  
  
el.textContent = "Hi!";
```

No # for id · # for the selector. Then change the text.

id는 #없이 · 선택자는 #붙임

FOLLOW ALONG · B

Grab by class — set it up

Step 1 — HTML: a paragraph with a class

```
<p class="note">Read me</p>
```

Step 2 — CSS: style the class

```
.note { color: gray; }
```

클래스로 만들고 꾸미기

FOLLOW ALONG · B

Grab by class — make it react ⚡

Step 3 — JS: use a `.` for class

```
document.querySelector(".note").textContent = "Changed!";
```

`.` means class — just like in CSS. `getElementById` can't do this.

클래스는 점(.) — CSS와 똑같이

FOLLOW ALONG · C

Grab a tag — set it up

Step 1 — HTML: just a plain tag

```
<button>Old</button>
```

No id, no class — we'll grab it by its tag name.

id·클래스 없이 태그 이름으로

FOLLOW ALONG · C

Grab a tag — make it react ⚡

Step 2 — JS: name the tag, no symbol

```
document.querySelector("button").textContent = "Click me";
```

No #, no . — just the tag. The **first** match wins.

기호 없이 태그 이름 · 첫 번째가 선택됨

NOW YOU TRY

Your turn — grab it

Same move: pick the element, then change it.

 **grab by id**

```
querySelector("#title")
```

 **grab by class**

```
querySelector(".note")
```

 **grab a tag**

```
querySelector("button")
```

 **grab the FIRST** **.card**

```
querySelector(".card")
```

 **grab all** **.card**

```
querySelectorAll(".card")
```

 **change each one's text**

```
textContent
```

잡고 → 바꾸기

BOSS CHALLENGE

Level up



Three at once — grab 3 different elements and change all 3



Loop them — `querySelectorAll(".item")` + a loop to change every match



Think — when is `getElementById` enough vs `querySelector`?



Invent your own — pick a grab-and-change and build it

한 번에 여러 개 잡고 바꾸기



Same element, two doors

id only · or any CSS selector.

잘했어요!