

REFERENCE



Events (onclick)

The user acts · your code reacts

사용자가 행동하면 코드가 반응

BIG IDEA

An **event** is something the user does

JS can listen, then run code when it happens.



click

press a button



type

enter text



hover

move the mouse

이벤트 = 사용자의 행동

ONCLICK

Run a function on click

```
<button onclick="sayHi()">Click me</button>

<script>
  function sayHi() {
    alert("Hi!");
  }
</script>
```

`onclick` names the function to run. The `()` calls it.

클릭하면 함수 실행

THE FUNCTION

Where the action lives

```
function sayHi() {  
  let el = document.getElementById("msg");  
  el.textContent = "You clicked!";  
}
```

Click runs the function. The function changes the page.

함수 안에 할 일을 적음

GROWN-UP WAY

addEventListener

```
let btn = document.getElementById("go");  
btn.addEventListener("click", sayHi);
```

Same idea, kept out of the HTML. Notice: `sayHi` with **no** `()` here.

HTML 밖에서 이벤트 연결

⚠ WATCH

The `()` rule



onclick

`onclick="sayHi()"`
call it – keep `()`



addEventListener

`"click", sayHi`
pass the name – **no** `()`

In `addEventListener`, `sayHi()` runs it **now** by mistake. Pass `sayHi`.

addEventListener엔 괄호 없이

YOUR TURN!

Make a button react

- ✓ Add a `<button>` and a `<p id="msg">`
- ✓ Write a function that changes the `msg` text
- ✓ Connect it with `onclick`
- ✓ Click → watch the text change

클릭하면 글자 바뀌게



Your page reacts!

User clicks · function runs · page changes.

잘했어요!