

⚡ Daily Planner — Make the Tick Marks Count

Topic: Make each checkbox count its own task — `checked`, `change`, `if / else`, `classList` ·

Course: Web Dev: JavaScript · **Time:** about 50 minutes

Your Daily Planner has four tasks, each with a checkbox. Right now ticking one does not really count anything. In this worksheet you make the page show **TASKS DONE - 2** when two boxes are ticked, and go back down when you untick. You also fade a finished task using the `.done` style you already wrote in your CSS.

💬 Words to know: `checkbox`, `checked`, `change`, `if / else`, `classList`

1 · Predict 🧠

Read each piece of code. Work out what happens, then write your prediction.

```
let tasksDone = 0;
tasksDone = tasksDone + 1;
tasksDone = tasksDone + 1;
tasksDone = tasksDone - 1;
console.log(tasksDone);
```

What number prints?


```
chk1.addEventListener("change", function () {
  console.log(chk1.checked);
});
```

You tick the box, then untick it. What two values print, in order?


```
let tasksDone = 2;  
statusText.textContent = "TASKS DONE - " + tasksDone;
```

What words show on the page?


```
if (chk1.checked) {  
  tasksDone = tasksDone + 1;  
} else {  
  // nothing here  
}
```

`tasksDone` is 1. You untick the box. What is `tasksDone` now — and is that right?

2 · Spot the Bug 🐛

These are from your own To-Do list code. Read what each is **supposed** to do, write the fix, then explain why the original was wrong.

Bug A — This is the listener for the **second** checkbox. Tick box 2 and nothing happens, but tick box 1 and box 2's text changes too.

```
chk2.addEventListener("change", function () {  
  statusText.textContent = "Checked: " + chk1.checked;  
  if (chk1.checked) {  
    tasksDone = tasksDone + 1;  
  }  
});
```

Hint: which checkbox is this listener for? Which checkbox is it reading?

Write the fixed code:

Why was it wrong? Why does your fix work?

Bug B — The page should show **TASKS DONE - 1**. Instead it shows **Checked: true**.

```
let tasksDone = 0;  
  
chk1.addEventListener("change", function () {  
  statusText.textContent = "Checked: " + chk1.checked;  
  if (chk1.checked) {  
    tasksDone = tasksDone + 1;  
  }  
});
```

Hint: `tasksDone` is counted, but is it ever put on the page?

Write the fixed code:

Why was it wrong? Why does your fix work?

Bug C — Tick a box and the count goes up. Untick it and the count **stays** up. Tick and untick the same box five times and it says 5 tasks done.

```
chk1.addEventListener("change", function () {  
  if (chk1.checked) {  
    tasksDone = tasksDone + 1;  
  } else {  
    // not ticked  
  }  
  statusText.textContent = "TASKS DONE - " + tasksDone;  
});
```

Hint: the `else` branch runs when the box is unticked. What should happen to the count there?

Write the fixed code:

Why was it wrong? Why does your fix work?

3 · Explain the Code

This is one finished checkbox. It is the pattern you will copy for all four.

```
<div class="todo-item">
  <input type="text" class="content-gen" placeholder="Add a task...">
  <input type="checkbox" id="chk1">
</div>
<p id="statusText">TASKS DONE - 0</p>

<script>
  const chk1 = document.getElementById("chk1");
  const statusText = document.getElementById("statusText");
  let tasksDone = 0;

  chk1.addEventListener("change", function () {
    if (chk1.checked) {
      tasksDone = tasksDone + 1;
      chk1.parentElement.classList.add("done");
    } else {
      tasksDone = tasksDone - 1;
      chk1.parentElement.classList.remove("done");
    }
    statusText.textContent = "TASKS DONE - " + tasksDone;
  });
</script>
```

You used **"click"** for your buttons. Why does a checkbox use **"change"** instead?

chk1.checked is not a number or words. What kind of value is it, and what are its only two possible values?

Which branch runs when you untick the box — `if` or `else` ? What does it do to `tasksDone` ?

`chk1.parentElement` is the `<div class="todo-item">` around the checkbox. So what exactly does `classList.add("done")` change on the page?

4 · Your Assignment: Make All Four Count

Open your `scripts.js` and make the whole To-Do list work.

Your page already has `chk1` , `chk2` , `chk3` , `chk4` and `<p id="statusText">` . Your `main.css` already has this style — you wrote it, and nothing uses it yet:

```
.done { opacity: .4; text-decoration: line-through; }
```

Every checkbox must do all three:

- **Tick** — add 1 to `tasksDone` and add the `done` class to that task's row.
- **Untick** — take 1 away from `tasksDone` and remove the `done` class from that row.
- **Always** — show `TASKS DONE -` and the number in `statusText` .

Careful: each listener must read and change **its own** checkbox, not `chk1` .

Write the listener you wrote for `chk3` :

Test it. Tick boxes 1, 2 and 3, then untick box 2. What does the page show?

When a row gets the **done** class, what do you see change about that row?

5 · Record Your Walkthrough 🎥

Take a video on a phone while your page runs. Talk like you are teaching someone new. Try to use these words: **checkbox**, **checked**, **change**, **if / else**, **classList**.

1. Show your page, then tick two boxes and read the count out loud.
2. Untick one box and say what the `else` part of your code just did.
3. Read your `chk4` listener out loud and say what each line does.
4. Say what would break if `chk4` read `chk1.checked` instead.

Write what you will say in your video. Plan it here before you record.

Submit ✓

Send this worksheet + your video of the four checkboxes counting to teacher on KakaoTalk.