

RS002 Week 8 — English Worksheet

Topic: Validation Everywhere + Logging Bad Input · **Course:** Pokédex App · **Time:** about 45 minutes

This week you apply the validation pattern to **every** input in your app — name, region, search — and you **log** every bad attempt into a list. At the end you print a little session report. You will meet your first **function** here too: a reusable `safe_input`.

1 · Recall 🗨️

From memory:

Write an `if` that warns and falls back to `"피카츄"` when `choice` is `not in` the list `pokedex`.

2 · Predict 🧠

Read each block. Before you run it, write what you think will happen.

```
invalid_attempts = []
invalid_attempts.append("리자몽")
invalid_attempts.append("타입null")
print(len(invalid_attempts))
print(invalid_attempts)
```

What two lines print?


```
invalid_attempts = ["리자몽", "타입null"]
print(f"잘못 입력: {' '.join(invalid_attempts)}")
```

`', '.join(...)` glues list items with a comma between them. What prints?


```
def safe_input(prompt, default=""):
    answer = input(prompt).strip()
    if answer == "":
        answer = default
    return answer

name = safe_input("이름: ", "이름 모를 트레이너")
print(name)
```

The user presses Enter. What gets printed? Trace the path through the function.

3 · Spot the Bug 🐛

Read what each block is **supposed** to do, fix it, then explain the fix.

Bug A — Each bad answer should be **added** to the log. Right now it replaces the whole log every time, so only the last one survives.

```
invalid_attempts = []
invalid_attempts = "리자몽"
invalid_attempts = "타입null"
print(invalid_attempts)
```

Hint: use `.append(...)` to add to a list.

Write the fixed code:

Why was it wrong? Why does your fix work?

Bug B — This function should **return** the cleaned answer so the caller can use it. Right now it prints inside and returns nothing.

```
def safe_input(prompt, default=""):
    answer = input(prompt).strip()
    if answer == "":
        answer = default
    print(answer)

name = safe_input("이름: ", "트레이너")
print(f"환영합니다, {name}!")
```

Hint: swap the `print` for a `return`.

Write the fixed code:

Why was it wrong? Why does your fix work?

Bug C — The report should only list bad attempts **if there were any**. Right now it prints an empty list and a confusing message even when everything was fine.

```
invalid_attempts = []  
print(f"잘못 입력한 내용: {'', '.join(invalid_attempts)}")
```

Hint: wrap the report in `if invalid_attempts:` .

Write the fixed code:

Why was it wrong? Why does your fix work?

4 · Modify It

Start from this working safe-input + log:

```
invalid_attempts = []

def safe_input(prompt, valid_list=None, default=""):
    answer = input(prompt).strip()

    if valid_list and answer not in valid_list:
        invalid_attempts.append(answer)
        print(f" ⚠️ '{answer}' 은(는) 인식 못해요. 다시 시도하세요.")
        answer = input(prompt).strip()
        if valid_list and answer not in valid_list:
            invalid_attempts.append(answer)
            print(f" 기본값 ({default})으로 진행합니다.")
            answer = default

    if answer == "" and default:
        answer = default

    return answer

pokedex = ["피카츄", "이상해씨", "파이리"]
choice = safe_input("포켓몬 이름: ", pokedex, "피카츄")
print(f"선택: {choice}")

print(f"\n=== 세션 통계 ===")
print(f"잘못된 입력 횟수: {len(invalid_attempts)}")
if invalid_attempts:
    print(f"잘못 입력한 내용: {' '.join(invalid_attempts)}")
```

Make these changes one at a time and run after each:

1. Call `safe_input` a second time for the trainer's **region** (no `valid_list`, just a default).
2. Change the warning emoji or message to your own style.
3. Make the report also print a friendly line when there were **zero** bad attempts.

Write your changed / added lines here:

5 · Make It 📷

Apply `safe_input` to **every** input in your Pokédex (name, region, type, search). Log every bad attempt and print a session report at the end.

When it works, send a **video** on KakaoTalk where you **deliberately type some bad input** so the report has something to show. Then explain what you did. Use these starters — write 4 to 6 sentences.

First, I wrote a function called `safe_input` that ...

I logged bad attempts by ...

I used the same function for ... different inputs.

My session report showed ...

The trickiest part was ...

Reusing one function for every input is better than copying code because ...

6 · Record Your Walkthrough 🎥

Film it running with some bad input on purpose. Try to use: **function**, **safe_input**, **log**, **append**, **report**.

1. Run the app and type a few bad answers on purpose.
2. Show the warnings appear and the defaults kick in.
3. Read your `safe_input` function out loud and explain `return` .
4. Show the session report at the end with the logged attempts.

Plan what you will say here first:

Submit 

Send this worksheet + your walkthrough video to teacher on KakaoTalk.