ECU-Name	BCM BodyControl Module								
For definition of supported services please refer to latest Diagnostics_Specification									
Name of Service:								Default session	Extended session
Diagnostic Session Control Service $10			M		Requirement	Supported	For each service there has	Y	Y
Request message 请求信息							block 1: request messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID 请求ID	0x10						
	2	Session type	0x01/0x81/0x02/0x82/0x03/0x83/0x41/0xC1	0x01/0x81=Default session/Default supress positive response	M	Y			
				0x02/0x82=Reprogramming session/Programming supress positive response	M	Y			
				0x03/0x83=extended diagnostic session/extended session with supress positive response	M	Y			
				0x41=Coding session	M/C	Y			
				0xC1=Coding Session(with suppress-PosRspMsg-Indication-Bit)					
Response message 应答信息							block 2: response messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID	0x50		M	Y			
	2	Session type	0x01/0x02/0x03/0x41	0x01=Default session	M	Y			
				0x02=Reprogramming session	M	Y			
				0x03=Extended diagnostic session	M	Y			
				0x41=Coding session	M	Y			
	3	P2_CAN_Server_max(MSB)	0x00		M	Y			
	4	P2_CAN_Server_max(LSB)	0x32	P2_CAN_Server_max Resolution: 1ms Value: 50ms	M	Y			
	5	P2*_CAN_Server_max(MSB)	0x00	5000ms	M	Y			
	6	P2*_CAN_Server_max(LSB)	0xC8	P2*_CAN_Server_max Resolution: 10ms Value: 2000ms	M	Y			
negative response 失效信息							block 3: supported negative response codes		
	No. of bytes	Description	Byte value (hex)						
	1	negative response	0x7F		M	Y			
	2	Request SID	0x10		M	Y			
	3	Value	Texttable	0x12=Sub function not support	M	Y			
				0x13=Incorrect message length or invalid format	M	Y			
				0x22=Conditions not correct	M	Y			
				0x78=requestCorrectlyReceived-ResponsePending	M	Y			
				0x7E=subFunctionNotSupportedInActiveSession	M	Y			
ECU Reset Service $11			M				For each service there has	Y	Y
Request message 请求信息							block 1: request messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID 请求ID	0x11		M	Y			
	2	Reset type	0x01/0x81	0x01/0x81=Hard reset/Hard reset with supress positive response	M	Y			
			0x03/0x83	0x03/0x83 =Soft reset /Soft reset with supress positive response	M	Y			
Response message 应答信息							block 2: response messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID	0x51		M	Y			
	2	Reset type	0x01	0x01=Hard reset	M	Y			
			0x03	0x03 =Soft reset	M	Y			
Negative response 失效信息							block 3: supported negative response codes		
	No. of bytes	Description	Byte value (hex)						
	1	negative response	0x7F		M	Y			
	2	Request SID	0x11		M	Y			
	3	Value	Texttable	0x12=subFunctionNotSupported	M	Y			
				0x13=incorrectMessageLengthOrInvalidFormat	M	Y			
				0x22=conditionsNotCorrect	M	Y			
Clear Diagnostic Information 0x14							For each service there has	Y	Y
Request message 请求信息							block 1: request messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID 请求ID	0x14		M	Y			
	2	groupOfDTCHighByte	0xFF		M	Y			
	3	groupOfDTCMiddleByte	0xFF		M	Y			
	4	groupOfDTCLowByte	0xFF		M	Y			
Response message 应答信息							block 2: response messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID	0x54		M	Y			
Negative response 失效信息							block 3: supported negative response codes		
	No. of bytes	Description	Byte value (hex)						
	1	Negative response	0x7F		M	Y			
	2	Request SID	0x14		M	Y			
	3	Value	Texttable	0x13=incorrectMessageLengthOrInvalidFormat	M	Y			
				0x31=requestOutOfRange	M	Y			
				0x72=generalProgrammingFailure	M	Y			
				0x78=requestCorrectlyReceived-ResponsePending	M	Y			
					M	Y			
Read DTC Information Service $19- Report Number Of DTC ByStatus Mask			M				For each service there has	Y	Y
Request message 请求信息							block 1: request messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID 请求ID	0x19		M	Y			
	2	Sub function	0x01		M	Y			
	3	DTC Status Mask	0x00~0xFF	Bit Meaning 0 testFailed support 1 testFailedThisMonitoringCycle not support 2 pendingDTC not support 3 confirmedDTC support 4 testNotCompletedSinceLastClear not support 5 testFailedSinceLastClear not support 6 testNotCompletedThisMonitoringCycle not support 7 WarningIndicatorRequested not support	M	Y			
Response message 应答信息							block 2: response messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID	0x59		M	Y			
	2	Sub function	0x01		M	Y			
	3	DTC Status Mask	0x00~0xFF		M	Y			
	4	DTC Format Identifier	0x00	SAE_J2012-DA_DTCFormat_00	M	Y			
	5	DTC Count	0x00~0xFF	DTC Count High Byte	M	Y			
	6	DTC Count	0x00~0xFF	DTC Count Low Byte	M	Y			
Negative response 失效信息							block 3: supported negative response codes		
	No. of bytes	Description	Byte value (hex)						
	1	negative response	0x7F		M	Y			
	2	Request SID	0x19		M	Y			
	3	Value	Texttable	0x12=subFunctionNotSupported	M	Y			
				0x13=incorrectMessageLengthOrInvalidFormat	M	Y			
				0x78=requestCorrectlyReceived-ResponsePending	M	Y			
					M	Y			
								Y	Y
Name of Service: $19 Read DTC Information - Report DTC ByStatus Mask							For each service there has to be 3 blocks		
Request message 请求信息			M				block 1: request messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID 请求ID	0x19		M	Y			
	2	Sub function	0x02		M	Y			
	3	DTC Status Mask	0x00~0xFF	Bit Meaning 0 testFailed support 1 testFailedThisMonitoringCycle not support 2 pendingDTC not support 3 confirmedDTC support 4 testNotCompletedSinceLastClear not support 5 testFailedSinceLastClear not support 6 testNotCompletedThisMonitoringCycle not support 7 WarningIndicatorRequested not support	M	Y			
Response message 应答信息							block 2: response messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID	0x59		M	Y			
	2	Sub function	0x02		M	Y			
	3	DTC Status Mask	0x09		M	Y			
	4	DTC And Status Record #1	0x00~0xFF	DTC High Byte	M	Y			
	5	DTC And Status Record #1	0x00~0xFF	DTC Middle Byte	M	Y			
	6	DTC And Status Record #1	0x00~0xFF	DTC Low Byte	M	Y			
	7	DTC And Status Record #1	0x00~0x09	Status Of DTC	M	Y			
	:				M	Y			
	n	DTC And Status Record #n			M	Y			
Negative response 失效信息							block 3: supported negative response codes		
	No. of bytes	Description	Byte value (hex)						
	1	negative response	0x7F		M	Y			
	2	Request SID	0x19		M	Y			
	3	Value	Texttable	0x12=subFunctionNotSupported	M	Y			
				0x13=incorrectMessageLengthOrInvalidFormat	M	Y			
				0x78=requestCorrectlyReceived-ResponsePending	M	Y			
					M	Y			
Name of Service: Read DTC Information - Report Snapshot Data 0x1904 **(only for US/EU)**								Y	Y
Request message 请求信息			M		M	Y			
	No. of bytes	Description	Byte value (hex)						
	1	Request SID 请求ID	0x19		M	Y			
	2	Sub function	0x04		M	Y			
	3	DTC 1st byte	xx		M	Y			
	4	DCT 2nd Byte	xx		M	Y			
	5	DTC 3rd byte	xx		M	Y			
	6	DTCSnapshotRecordNumber	0x09/0x10/0x11/0xFF		M	Y			
Response message 应答信息					M	Y			
	No. of bytes	Description	Byte value (hex)						
	1	Request SID	0x59		M	Y			
	2	Sub function	0x04		M	Y			
	3	DTC 1st byte	xx		M	Y			
	4	DCT 2nd Byte	xx		M	Y			
	5	DTC 3rd byte	xx		M	Y			
	6	DTC status avilability Mask supported by the	0x00-0xFF		M	Y			
	7	DTCSnapshotRecordNumber#1	xx		M	Y			
	8	DTCSnapshotRecordNumberOfIdentifiers#	xx		M	Y			
	9	dataIdentifier#1 byte#1(MSB)	xx		M	Y			
	10	dataIdentifier#1 byte#2 (LSB)	xx		M	Y			
	11	snapshotData#1 byte#1			M	Y			
	11+(n-1)	snapshotData#1 byte#n	xx		M	Y			
Negative Response 失效信息							Block 3: supported negative response codes		
	Byte Number	Description	Byte value (hex)						
	1	negative response	0x7F		M	Y			
	2	Request SID	0x19		M	Y			
	3	Value	Texttable	0x12=subFunctionNotSupported	M	Y			
				0x13=incorrectMessageLengthOrInvalidFormat	M	Y			
				0x31=requestOutOfRange	M	Y			
				0x78=requestCorrectlyReceived-ResponsePending	M	Y			
					M	Y			
Name of Service: Read DTC Information $19 - Report Extended Data 0x1906 **(only for US/EU)**								Y	Y
Request message 请求信息					M	Y			
59(Service) 06(Sub-function) 9A 04 1A 2E (D	No. of bytes	Description	Byte value (hex)						
	1	Request SID 请求ID	0x19		M	Y			
	2	Sub function	0x06		M	Y			
	3	DTC 1st byte	xx		M	Y			
	4	DCT 2nd Byte	xx		M	Y			
	5	DTC 3rd byte	xx		M	Y			
	6	Status Mask	0x00- 0xFF		M	Y			
Response message 应答信息									
	No. of bytes	Description	Byte value (hex)						
	1	Request SID	0x59		M				
	2	Sub function	0x06		M				
	3	DTC 1st byte	xx		M				
	4	DCT 2nd Byte	xx		M				
	5	DTC 3rd byte	xx		M				
	6	DTC Status	0x00-0xFF		M				
	7	DTCExtDataRecordNumber	0x01	DTC Ext Data Record Number #1	M				
	8	Extended data record Byte1	0x00	DTC Extended Data#1 byte#1	M				
	9	DTCExtDataRecordNumber	0x02	DTC Extended Data#1 byte#p	M				
	10	Extended data record Byte1	0x00						
	11	DTCExtDataRecordNumber	0x03						
	12	Extended data record Byte1	0x00						
	13	DTCExtDataRecordNumber	0x04						
	14	Extended data record Byte1	0x00						
	15	DTCExtDataRecordNumber	0x10						
	16	Extended data record Byte1	0x00						
	17	DTCExtDataRecordNumber	0x11						
	18	Extended data record Byte1	XX						
	19	Extended data record Byte2	XX						
	20	Extended data record Byte3	XX						
	21	Extended data record Byte4	XX						
Negative Response 失效信息							Block 3: supported negative response codes		
	Byte Number	Description	Byte value (hex)						
	1	negative response	0x7F						
	2	Request SID	0x19		M	Y			
	3	Value	Texttable	0x12=subFunctionNotSupported	M	Y			
				0x13=incorrectMessageLengthOrInvalidFormat	M	Y			
				0x31=requestOutOfRange	M	Y			
				0x78=requestCorrectlyReceived-ResponsePending	M	Y			
					M	Y			
Name of Service: Read DTC Information - Report Supported DTC							For each service there has	Y	Y
Request message 请求信息			M				block 1: request messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID 请求ID	0x19		M	Y			
	2	Sub function	0x0A		M	Y			
Response message 应答信息							block 2: response messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID	0x59		M	Y			
	2	Sub function	0x0A		M	Y			
	3	DTC Status Mask	0x09		M	Y			
	4	DTC And Status Record #1	0x00~0xFF	DTC High Byte	M	Y			
	5	DTC And Status Record #1	0x00~0xFF	DTC Middle Byte	M	Y			
	6	DTC And Status Record #1	0x00~0xFF	DTC Low Byte	M	Y			
	7	DTC And Status Record #1	0x00~0xFF		M	Y			
	:				M	Y			
	n	DTC And Status Record #n			M	Y			
Negative response 失效信息							block 3: supported negative response codes		
	No. of bytes	Description	Byte value (hex)						
	1	negative response	0x7F		M	Y			
	2	Request SID	0x19		M	Y			
	3	Value	Texttable	0x12=subFunctionNotSupported	M	Y			
				0x13=incorrectMessageLengthOrInvalidFormat	M	Y			
				0x78=requestCorrectlyReceived-ResponsePending	M	Y			
					M	Y			
								Y	Y
ReadDataByIdentifier Service $22			M				For each service there has to be 3 blocks		
Request message 请求信息							block 1: request messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID 请求ID	0x22		M	Y			
	2	Data Identifier MSB	0x00~0xFF		M	Y			
	3	Data Identifier LSB	0x00~0xFF		M	Y			
Response message 应答信息							block 2: response messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID	0x62		M	Y			
	2	Data Identifier MSB	0x00~0xFF		M	Y			
	3	Data Identifier LSB	0x00~0xFF		M	Y			
	4~n	Data Record		See DIDs Tab	M	Y			
Negative response 失效信息							block 3: supported negative response codes		
	No. of bytes	Description	Byte value (hex)						
	1	negative response	0x7F		M	Y			
	2	Request SID	0x22		M	Y			
	3	Value	Texttable	0x13=incorrectMessageLengthOrInvalidFormat	M	Y			
				0x31=requestOutOfRange	M	Y			
				0x33=securityAccessDenied	M	Y			
				0x78=requestCorrectlyReceived-ResponsePending	M	Y			
				0x78=requestCorrectlyReceived-ResponsePending	M	Y			
					M	Y			
SecurityAccess Service £27			M				For each service there has	N	Y
Request message 请求信息							block 1: request messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID 请求ID	0x27						
	2	Sub-Function	0x01, 0x03, 0x05, 0x07	0x01=Request Seed (Security level 1: After Sales)	M	Y			
				0x03=Request Seed (Security level 2: Manufacturing)	M	Y			
				0x05=Request Seed (Security level 3: ECU- Coding)	M/C	Y			
				0x07=Request Seed (Security level 4: ECU-Programming (Flash))	M	Y			
	2	Sub-Function	0x02, 0x04, 0x06, 0x08	0x02=Send Key (Security level 1: After Sales)	M	Y			
				0x04=Send Key (Security level 2: Manufacturing)	M	Y			
				0x06=Send Key (Security level 3: ECU- Coding)	M/C	Y			
				0x08=Send Key (Security level 4: ECU-Programming (Flash))	M	Y			
	3	Security key byte1	0x00~0xFF	Key#1	M	Y			
	4	Security key byte2	0x00~0xFF	Key#2	M	Y			
	…	…	0x00~0xFF		M	Y			
	18	Security key byte16	0x00~0xFF	Key#16	M	Y			
Response message 应答信息							block 2: response messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID	0x67		M	Y			
	2	Sub-Function	0x01, 0x03, 0x05, 0x07	0x01=Request Seed (Security level 1: After Sales)	M	Y			
				0x03=Request Seed (Security level 2: Manufacturing)	M	Y			
				0x05=Request Seed (Security level 3: ECU- Coding)	M	Y			
				0x07=Request Seed (Security level 4: ECU-Programming (Flash))	M	Y			
	3	Security seed byte1	0x00~0xFF	Seed #1	M	Y			
	4	Security seed byte2	0x00~0xFF	Seed #2	M	Y			
	…	…	0x00~0xFF		M	Y			
	18	Security seed byte16	0x00~0xFF	Seed #16	M	Y			
	2	Sub-Function	0x02, 0x04, 0x06, 0x08	0x02=Send Key (Security level 1: After Sales)	M	Y			
				0x04=Send Key (Security level 2: Manufacturing)	M	Y			
				0x06=Send Key (Security level 3: ECU- Coding)	M	Y			
				0x08=Send Key (Security level 4: ECU-Programming (Flash))	M	Y			
negativee response 失效信息							block 3: supported negative response codes		
	No. of bytes	Description	Byte value (hex)						
	1	negative response	0x7F		M	Y			
	2	Request SID	0x27		M	Y			
	3	Value	Texttable	0x12=Sub function not support	M	Y			
				0x22=Conditions not correct	M	Y			
				0x13=Incorrect message length or invalid format	M	Y			
				0x24=requestSequenceError	M	Y			
				0x35=invalidKey	M	Y			
				0x36=exceededNumberOfAttempts	M	Y			
				0x37=requiredTimeDelayNotExpired	M	Y			
				0x7F=ServiceNotSupportedInActiveDiagnosticSession	M	Y			
								N	Y
CommunicationControl Service $28			M				For each service there has to be 3 blocks		
Request message 请求信息							block 1: request messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID 请求ID	0x28		M	Y			
	2	Control Type	0x00/0x01/0x03/0x80/0x81/0x83	0x00/0x80=Enable Rx And Tx(Only support Normal Communication Messages)/supress positive response	M	Y			
				0x01/0x81=Enable Rx And Disable Tx (Only support Normal Communication Messages)/supress positive response	M	Y			
				0x03/0x83=Disable Rx And Tx (Only support Normal Communication Messages)/supress positive response	M	Y			
	3	Communication Type	0x01/0x02/0x03	0x01=Normal Communication Messages	M	Y			
				0x02=Network Management Communication Messages	M	Y			
				0x03=Network Management Communication Messages and Normal Communication Messages	M	Y			
Response message 应答信息							block 2: response messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID	0x68		M	Y			
	2	controlType	0x00	0x00=Enable Rx And Tx	M	Y			
			0x01	0x01=Enable Rx And Disable Tx	M	Y			
			0x03	0x03=Disable Rx And Tx (Only support Normal Communication Messages)	M	Y			
Negative response 失效信息							block 3: supported negative response codes		
	No. of bytes	Description	Byte value (hex)						
	1	negative response	0x7F		M	Y			
	2	Request SID	0x28		M	Y			
	3	Value	Texttable	0x12=subFunctionNotSupported	M	Y			
				0x13=incorrectMessageLengthOrInvalidFormat	M	Y			
				0x22=conditionsNotCorrect	M	Y			
				0x31=requestOutOfRange	M	Y			
				0x7F=ServiceNotSupportedInActiveDiagnosticSession	M	Y			
WriteDataByIdentifier service 0x2E			M				For each service there has	N	Y
Request message 请求信息							block 1: request messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID 请求ID	0x2E		M	Y			
	2	Data Identifier MSB	0x00~0xFF		M	Y			
	3	Data Identifier LSB	0x00~0xFF		M	Y			
	4~n	Data Record	0x00~0xFF	See DIDs Tab	M	Y			
Response message 应答信息							block 2: response messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID	0x6E		M	Y			
	2	Data Identifier MSB	0x00~0xFF		M	Y			
	3	Data Identifier LSB	0x00~0xFF		M	Y			
Negative response 失效信息							block 3: supported negative response codes		
	No. of bytes	Description	Byte value (hex)						
	1	negative response	0x7F		M	Y			
	2	Request SID	0x2E		M	Y			
	3	Value	Texttable	0x13=incorrectMessageLengthOrInvalidFormat	M	Y			
				0x22=conditionsNotCorrect	M	Y			
				0x31=requestOutOfRange	M	Y			
				0x33=securityAccessDenied	M	Y			
				0x72=generalProgrammingFailure	M	Y			
				0x78=requestCorrectlyReceived-ResponsePending	M	Y			
				0x7F=ServiceNotSupportedInActiveDiagnosticSession	M	Y			
Name of Service: $2F IOControl							For each service there has	N	Y
Request message 请求信息							block 1: request messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID 请求ID	0x2F		M	Y			
	2	DataIdentifier	DataIdentifier#1[ ] = [byte#1 (MSB) byte#2 (LSB)]	see "IOControl" sheet	M	Y			
	4 5 : 5+(m-1)	ControlOptionRecord	ControlOptionRecord#1[ ] = [inputOutputControlParameter controlState#1 : constrolState#m]		M	Y			
	5+m : 5+2m-1	ControlEnableMaskRecord	controlMask#1 : controlMask#m]		M	Y			
Response message 应答信息							block 2: response messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID	0x6F		M	Y			
	2	DataIdentifie	DataIdentifier#1[ ] = [byte#1 (MSB) byte#2 (LSB)]	see "IOControl" sheet	M	Y			
	4 5 : 5+(m-1)	ControlOptionRecord	ControlOptionRecord#1[ ] = [inputOutputControlParameter controlState#1 : constrolState#m]		M	Y			
	5+m : 5+2m-1	ControlEnableMaskRecord	ControlEnableMaskRecord#1[ ] = [controlMask#1 : controlMask#m]		M	Y			
Negative response 失效信息							block 3: supported negative response codes		
	No. of bytes	Description	Byte value (hex)						
	1	negative response	0x7F		M	Y			
	2	Request SID	0x2F		M	Y			
	3	Value	Texttable	0x13=incorrectMessageLengthOrInvalidFormat	M	Y			
				0x22=conditionsNotCorrect	M	Y			
				0x31=requestOutOfRange	M	Y			
				0x33=securityAccessDenied	M	Y			
				0x7F=ServiceNotSupportedInActiveDiagnosticSession	M	Y			
Name of Service: $31 RoutineControl							For each service there has	N	Y
Request message 请求信息							block 1: request messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID 请求ID	0x31		M	Y			
	2	sub-function(routineControlType)	0x01, 0x02, 0x03	0x01=startRoutine	M	Y			
				0x02=stopRoutine	M/C	Y			
				0x03=requestRoutineResults	M	Y			
	3	routineIdentifier byte#1 MSB	0x00~0xFF	See "Routines RIDs"	M	Y			
	4	routineIdentifier byte#2 LSB	0x00~0xFF		M	Y			
Response message 应答信息							block 2: response messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID	0x71		M	Y			
	2	sub-function(routineControlType)	0x01, 0x02, 0x03	0x01=Start Routine	M	Y			
				0x02=Stop Routine	M/C	Y			
				0x03=Request Routine Results	M	Y			
	3	routineIdentifier byte#1 MSB	0x00~0xFF		M	Y	See Routines (0x31) tab		
	4	routineIdentifier byte#2 LSB	0x00~0xFF		M	Y			
	5	routineStatus	0x00~0x03	0x00:Routine IDLE	M	Y			
				0x01:Routine Ongoing	M	Y			
				0x02:Routine success	M	Y			
				0x03:Rountine Fail	M	Y			
	6	Routine Info	see 'Routines RIDs (0x31)' sheet		M	Y			
Negative response 失效信息							block 3: supported negative response codes		
	No. of bytes	Description	Byte value (hex)						
	1	negative response	0x7F		M	Y			
	2	Request SID	0x31		M	Y			
	3	Value	Texttable	0x12=subFunctionNotSupported	M	Y			
				0x13=incorrectMessageLengthOrInvalidFormat	M	Y			
				0x22=conditionsNotCorrect	M	Y			
				0x24=requestSequenceError	M	Y			
				0x31=requestOutOfRange	M	Y			
				0x33=securityAccessDenied	M	Y			
				0x72=generalProgrammingFailure	M	Y			
				0x78=requestCorrectlyReceived-ResponsePending	M	Y			
				0x7F=ServiceNotSupportedInActiveDiagnosticSession	M	Y			
TesterPresent Service $3E			M				For each service there has	Y	Y
Request message 请求信息							block 1: request messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID 请求ID	0x3E		M	Y			
	2	Sub-Function (zeroSubFunction)	0x00/0x80	0x00=TesterPresent	M	Y			
				0x80=TesterPresent with supress positive response	M	Y			
Response message 应答信息							block 2: response messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID	0x7E		M	Y			
	2	SubFunction	0x00	0x00=TesterPresent	M	Y			
Negative response 失效信息							block 3: supported negative response codes		
	No. of bytes	Description	Byte value (hex)						
	1	negative response	0x7F		M	Y			
	2	Request SID	0x3E		M	Y			
	3	Value	Texttable	0x12=Sub function not support	M	Y			
				0x13=Incorrect message length or invalid format	M	Y			
ControlDTCSetting Service $85			M				For each service there has	N	Y
Request message 请求信息							block 1: request messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID 请求ID	0x85		M	Y			
	2	Sub-Function	0x01/0x81, 0x02/0x82	0x01/0x81=on / supress positive response	M	Y			
				0x02/0x82=off / supress positive response	M	Y			
Response message 应答信息							block 2: response messages		
	No. of bytes	Description	Byte value (hex)						
	1	Request SID	0xC5		M	Y			
	2	DTCSettingType	0x01, 0x02	0x01=on	M	Y			
				0x02=off	M	Y			
Negative response 失效信息							block 3: supported negative response codes		
	No. of bytes	Description	Byte value (hex)						
	1	negative response	0x7F		M	Y			
	2	Request SID	0x85		M	Y			
	3	Value	Texttable	0x12=subFunctionNotSupported	M	Y			
				0x13=incorrectMessageLengthOrInvalidFormat	M	Y			
				0x78=requestCorrectlyReceived-ResponsePending	M	Y			
				0x7F=ServiceNotSupportedInActiveDiagnosticSession	M	Y			