

# Hướng dẫn cài đặt Openstack Icehouse

Trong bài hướng dẫn này chúng ta sẽ tiến hành cài Openstack trên 1 node. Sau đó, bạn có thể thêm các node compute khác vào.

## Mục lục

### I. Requirements

### II. Install

- Add Icehouse repositories

- Update system

- 1. MySQL & RabbitMQ

- 2. Databases

- Others

- 3. Keystone

- 4. Glance

- 5. Neutron

- 5.1. OpenVSwitch

- 5.2. OpenVSwitch

- 5.3. Neutron-\*

- 6. Nova

- 6.1. KVM

- 6.2. Nova-\*

- 7. Cinder

- 8. Horizon

### III. Create VMs

## **Chú thích:**

**Màu A:** Lệnh

**Màu B:** Nội dung file config cần chỉnh sửa

Các ip trong tài liệu mang tính minh họa, hãy điều chỉnh phù hợp với hệ thống của bạn

Tài liệu có tham khảo từ 2 bài viết:

<https://github.com/fornyx/OpenStack-Havana-Install-Guide/blob/master/OpenStack-Havana-Install-Guide.rst#21-preparing-ubuntu>

<https://github.com/vietstacker/icehouse-aio-ubuntu>

## I. Requirements

Install Openstack on Ubuntu server 12.04 (64 bit)

# Change hosts

`nano /etc/hosts`

127.0.0.1 change to 10.1.3.160

# Config network

`nano /etc/network/interfaces`

#For Exposing OpenStack API over the internet

auto eth0

iface eth0 inet static

address 192.169.60.160

netmask 255.255.255.0

gateway 192.169.60.1

dns-nameservers 8.8.8.8

#Not internet connected(used for OpenStack management)

auto eth1

iface eth1 inet static

address 10.10.3.160

netmask 255.255.255.0

`service networking restart`

## II. Install

# Add Icehouse repositories

`apt-get install python-software-properties`

`add-apt-repository cloud-archive:icehouse`

# Update system

`apt-get -y update && apt-get -y upgrade && apt-get -y dist-upgrade`

### 1. MySQL & RabbitMQ

# Install MySQL:

`apt-get install -y mysql-server python-mysqldb`

# Configure mysql to accept all incoming requests:

`sed -i 's/127.0.0.1/0.0.0.0/g' /etc/mysql/my.cnf`

```
service mysql restart
```

```
# Install RabbitMQ:
```

```
apt-get install -y rabbitmq-server
```

```
# Install NTP service:
```

```
apt-get install -y ntp
```

## 2. Databases

```
# Download
```

```
wget https://raw2.github.com/Ch00k/OpenStack-Havana-Install-Guide/master/populate_database.sh
```

```
# Change ip in file populate_database.sh:
```

```
nano populate_database.sh
```

```
# Run
```

```
sh populate_database.sh
```

## # Others

```
# Install other services:
```

```
apt-get install -y vlan bridge-utils
```

```
# Enable IP_Forwarding:
```

```
sed -i 's/#net.ipv4.ip_forward=1/net.ipv4.ip_forward=1/' /etc/sysctl.conf
```

```
# To save you from rebooting, perform the following:
```

```
sysctl net.ipv4.ip_forward=1
```

## 3. Keystone

```
# Start by the keystone packages:
```

```
apt-get install -y keystone
```

```
#Verify your keystone is running:
```

```
service keystone status
```

```
# Adapt the connection attribute in the /etc/keystone/keystone.conf to the new database:
```

```
connection = mysql://keystone:pass_keystone@10.10.3.160/keystone
```

# Remove Keystone SQLite database:

```
rm /var/lib/keystone/keystone.db
```

# Restart the identity service then synchronize the database:

```
service keystone restart
```

```
keystone-manage db_sync
```

# Fill up the keystone database using the two scripts available in the Scripts folder of this git repository:

# Modify the HOST\_IP and EXT\_HOST\_IP variables before executing the scripts

```
wget https://raw2.github.com/Ch00k/OpenStack-Havana-Install-Guide/master/keystone_basic.sh
```

```
wget https://raw2.github.com/Ch00k/OpenStack-Havana-Install-Guide/master/keystone_endpoints_basic.sh
```

# Edit your ip, user, pass 2 file keystone\_basic.sh and keystone\_endpoints\_basic.sh

```
nano keystone_basic.sh
```

```
nano keystone_endpoints_basic.sh
```

# Run:

```
sh keystone_basic.sh
```

```
sh keystone_endpoints_basic.sh
```

# Create a simple credential file and load it so you won't be bothered later:

```
nano/vi keystone_source
```

#Paste the following:

```
export OS_TENANT_NAME=admin
```

```
export OS_USERNAME=admin
```

```
export OS_PASSWORD=$pass_admin
```

```
export OS_AUTH_URL="http://192.169.60.160:5000/v2.0/"
```

# Load it:

```
source keystone_source
```

# To test Keystone, just use a simple CLI command:

```
keystone user-list
```

## 4. Glance

# We Move now to Glance installation:

```
apt-get install -y glance
```

# Verify your glance services are running:

```
service glance-api status
```

```
service glance-registry status
```

# Sửa file /etc/glance/glance-api.conf với nội dung:

```
[DEFAULT]
default_store = file
bind_host = 0.0.0.0
bind_port = 9292
log_file = /var/log/glance/api.log
backlog = 4096
workers = 1
registry_host = 0.0.0.0
registry_port = 9191
registry_client_protocol = http
rabbit_host = localhost
rabbit_port = 5672
rabbit_use_ssl = false
rabbit_userid = guest
rabbit_password = guest
rabbit_virtual_host = /
rabbit_notification_exchange = glance
rabbit_notification_topic = notifications
rabbit_durable_queues = False
qpid_notification_exchange = glance
qpid_notification_topic = notifications
qpid_hostname = localhost
qpid_port = 5672
qpid_username =
qpid_password =
qpid_sasl_mechanisms =
```

```

qpidd_reconnect_timeout = 0
qpidd_reconnect_limit = 0
qpidd_reconnect_interval_min = 0
qpidd_reconnect_interval_max = 0
qpidd_reconnect_interval = 0
qpidd_heartbeat = 5
qpidd_protocol = tcp
qpidd_tcp_nodelay = True
filesystem_store_datadir = /var/lib/glance/images/
swift_store_auth_version = 2
swift_store_auth_address = 127.0.0.1:5000/v2.0/
swift_store_user = jdoe:jdoe
swift_store_key = a86850deb2742ec3cb41518e26aa2d89
swift_store_container = glance
swift_store_create_container_on_put = False
swift_store_large_object_size = 5120
swift_store_large_object_chunk_size = 200
swift_enable_snet = False
s3_store_host = 127.0.0.1:8080/v1.0/
s3_store_access_key = <20-char AWS access key>
s3_store_secret_key = <40-char AWS secret key>
s3_store_bucket = <lowercased 20-char aws access key>glance
s3_store_create_bucket_on_put = False
sheepdog_store_address = localhost
sheepdog_store_port = 7000
sheepdog_store_chunk_size = 64
delayed_delete = False
scrub_time = 43200
scrubber_datadir = /var/lib/glance/scrubber
image_cache_dir = /var/lib/glance/image-cache/
[database]
# sqlite_db = /var/lib/glance/glance.sqlite
backend = sqlalchemy

```

```

connection = mysql://glance:$MYSQL_PASS@192.168.50.160/glance
[keystone_authtoken]
auth_host = 127.0.0.1
auth_port = 35357
auth_protocol = http
admin_tenant_name = service
admin_user = glance
admin_password = $ADMIN_PASS
[paste_deploy]
flavor=keystone
[store_type_location_strategy]

```

# Sửa file /etc/glance/glance-registry.conf với nội dung:

```

[DEFAULT]
bind_host = 0.0.0.0
bind_port = 9191
log_file = /var/log/glance/registry.log
backlog = 4096
api_limit_max = 1000
limit_param_default = 25
[database]
backend = sqlalchemy
connection = mysql://glance:$MYSQL_PASS@192.169.60.160/glance
[keystone_authtoken]
auth_host = 127.0.0.1
auth_port = 35357
auth_protocol = http
admin_tenant_name = service
admin_user = glance
admin_password = $ADMIN_PASS
[paste_deploy]
flavor=keystone

```

# Remove Glance's SQLite database:

```
rm /var/lib/glance/glance.sqlite
```

# Restart the glance-api and glance-registry services:

```
service glance-api restart; service glance-registry restart
```

# Synchronize the glance database:

```
glance-manage db_sync
```

# Restart the services again to take into account the new modifications:

```
service glance-registry restart; service glance-api restart
```

# To test Glance, upload the cirros cloud image and Ubuntu cloud image:

```
glance image-create --name myFirstImage --is-public true --container-format bare --disk-format qcow2 --location https://launchpad.net/cirros/trunk/0.3.0/+download/cirros-0.3.0-x86_64-disk.img
```

(mind you will be able to access VMs created with such image with the following credentials: user:cirros passwd: cubswin:))

```
wget http://cloud-images.ubuntu.com/precise/current/precise-server-cloudimg-amd64-disk1.img
```

```
glance add name="Ubuntu 12.04 cloudimg amd64" is_public=true container_format=ovf disk_format=qcow2 < ./precise-server-cloudimg-amd64-disk1.img
```

# Now list the image to see what you have just uploaded:

```
glance image-list
```

## 5. Neutron

### 5.1. OpenVSwitch

# Install the openVSwitch:

```
apt-get install -y openvswitch-controller openvswitch-switch openvswitch-datapath-dkms
```

# Restart openVSwitch:

```
service openvswitch-switch restart
```

# Create the bridges:

#br-int will be used for VM integration

```
ovs-vsctl add-br br-int
```



#br-ex is used to make VMs to access the internet  
 ovs-vsctl add-br br-ex

## 5.2. OpenVSwitch

# This will guide you to setting up the br-ex interface. Edit the eth1 in /etc/network/interfaces to become like this:

```
# VM internet Access
auto eth0
iface eth0 inet manual
up ifconfig $IFACE 0.0.0.0 up
up ip link set $IFACE promisc on
down ip link set $IFACE promisc off
down ifconfig $IFACE down
```

# Add the eth1 to the br-ex:

# Internet connectivity will be lost after this step but this won't affect OpenStack's work

[ovs-vsctl add-port br-ex eth0](#)

# If you want to get internet connection back, you can assign the eth1's IP address to the br-ex in the /etc/network/interfaces file:

```
auto br-ex
iface br-ex inet static
address 192.169.60.160
netmask 255.255.255.0
gateway 192.169.60.1
dns-nameservers 8.8.8.8
```

# If you want IMMEDIATELY want your FULL networking features back I suggest:

[reboot](#)

[source keystone\\_source](#)

## 5.3. Neutron-\*

# Install the Neutron components:

[apt-get install -y neutron-server neutron-plugin-openvswitch neutron-plugin-openvswitch-agent dnsmasq neutron-dhcp-agent neutron-l3-agent neutron-metadata-agent](#)

# Verify all Neutron components are running:

[cd /etc/init.d/; for i in \\$\(ls neutron-\\*\); do sudo service \\$i status; cd; done](#)

# Sửa file /etc/neutron/neutron.conf với nội dung sau:

```
[DEFAULT]
state_path = /var/lib/neutron
lock_path = \${state_path}/lock
core_plugin = ml2
service_plugins = router
auth_strategy = keystone
allow_overlapping_ips = True
rpc_backend = neutron.openstack.common.rpc.impl_kombu

rabbit_host = 192.169.60.160
rabbit_password = $ADMIN_PASS
rabbit_userid = guest

notification_driver = neutron.openstack.common.notifier.rpc_notifier
notify_nova_on_port_status_changes = True
notify_nova_on_port_data_changes = True
nova_url = http://192.169.60.160:8774/v2
nova_admin_username = nova
nova_admin_tenant_id = $SERVICE_ID
nova_admin_password = $ADMIN_PASS
nova_admin_auth_url = http://192.169.60.160:35357/v2.0

[quotas]

[agent]
root_helper = sudo /usr/bin/neutron-rootwrap /etc/neutron/rootwrap.conf

[keystone_authtoken]
auth_host = 127.0.0.1
auth_port = 35357
auth_protocol = http
```

```

admin_tenant_name = service
admin_user = neutron
admin_password = $ADMIN_PASS
signing_dir = \$state_path/keystone-signing

[database]
connection = mysql://neutron:$MYSQL_PASS@192.169.60.160/neutron
[service_providers]
service_provider=LOADBALANCER:Haproxy:neutron.services.loadbalancer.drivers.haproxy.plu
gin_driver.HaproxyOnHostPluginDriver:default
service_provider=VPN:openswan:neutron.services.vpn.service_drivers.ipsec.IPsecVPNDriver:de
fault

```

# Sửa file /etc/neutron/plugins/ml2/ml2\_conf.ini với nội dung sau:

```

[ml2]
type_drivers = gre
tenant_network_types = gre
mechanism_drivers = openvswitch

[ml2_type_flat]
[ml2_type_vlan]
[ml2_type_gre]
tunnel_id_ranges = 1:1000

[ml2_type_vxlan]
[securitygroup]
enable_security_group = True
firewall_driver = neutron.agent.linux.iptables_firewall.OVSHybridIptablesFirewallDriver

[ovs]
local_ip = 10.10.3.160
tunnel_type = gre
enable_tunneling = True

```

# Sửa file /etc/neutron/metadata\_agent.ini với nội dung sau:

```

[DEFAULT]

```

```

verbose = True
auth_url = http://localhost:5000/v2.0
auth_region = RegionOne
admin_tenant_name = service
admin_user = neutron
admin_password = $ADMIN_PASS
nova_metadata_ip = 192.169.60.160
metadata_proxy_shared_secret = $METADATA_SECRET

```

# Sửa file /etc/neutron/dhcp\_agent.ini với nội dung sau:

```

verbose = True
interface_driver = neutron.agent.linux.interface.OVSInterfaceDriver
dhcp_driver = neutron.agent.linux.dhcp.Dnsmasq
use_namespaces = True

```

# Sửa file /etc/neutron/l3\_agent.ini với nội dung sau:

```

[DEFAULT]
verbose = True
interface_driver = neutron.agent.linux.interface.OVSInterfaceDriver
use_namespaces = True

```

# Remove Neutron's SQLite database:

```
rm /var/lib/neutron/neutron.sqlite
```

# Restart all neutron services:

```
cd /etc/init.d/; for i in $( ls neutron-* ); do sudo service $i restart; cd /root/; done
service dnsmasq restart
```

# and check status:

```
cd /etc/init.d/; for i in $( ls neutron-* ); do sudo service $i status; cd /root/; done
service dnsmasq status
```

# then check all neutron agents, hopefully you'll enjoy smiling faces :-)

```
neutron agent-list
```

## 6. Nova

### 6.1. KVM

# Make sure that your hardware enables virtualization:

```
apt-get install -y cpu-checker
kvm-ok
```

# it could be necessary to do:

```
sudo modprobe kvm_intel
kvm-ok
```

# Finally you should get:

INFO: /dev/kvm exists

KVM acceleration can be used

# Let's go for KVM installation:

```
apt-get install -y kvm libvirt-bin pm-utils
```

# Edit the cgroup\_device\_acl array in the /etc/libvirt/qemu.conf file to:

```
cgroup_device_acl = [
    "/dev/null", "/dev/full", "/dev/zero",
    "/dev/random", "/dev/urandom",
    "/dev/ptmx", "/dev/kvm", "/dev/kqemu",
    "/dev/rpc", "/dev/hpet", "/dev/net/tun"
]
```

# Delete default virtual bridge

```
virsh net-destroy default
virsh net-undefine default
```

# Enable live migration by updating /etc/libvirt/libvirtd.conf file:

```
listen_tls = 0
listen_tcp = 1
auth_tcp = "none"
```

# Edit libvirtd\_opts variable in /etc/init/libvirt-bin.conf file:

```
env libvirtd_opts="-d -l"
```

# Edit /etc/default/libvirt-bin file

```
libvirtd_opts="-d -l"
```

# Restart the libvirt service and dbus to load the new values:

```
service dbus restart && service libvirt-bin restart
```

then check status:

```
service dbus status && service libvirt-bin status
```

## 6.2. Nova-\*

# Start by installing nova components:

```
apt-get install -y nova-api nova-cert novnc nova-consoleauth nova-scheduler nova-novncproxy  
nova-doc nova-conductor nova-compute-kvm
```

# Kiểm tra tất cả các dịch vụ nova:

```
cd /etc/init.d/; for i in $( ls nova-* ); do service $i status; cd; done
```

# Sửa file /etc/nova/nova.conf với nội dung như sau:

```
[DEFAULT]  
dhcpbridge_flagfile=/etc/nova/nova.conf  
dhcpbridge=/usr/bin/nova-dhcpbridge  
logdir=/var/log/nova  
state_path=/var/lib/nova  
lock_path=/var/lock/nova  
force_dhcp_release=True  
iscsi_helper=tgtadm  
libvirt_use_virtio_for_bridges=True  
connection_type=libvirt  
root_helper=sudo nova-rootwrap /etc/nova/rootwrap.conf  
verbose=True  
ec2_private_dns_show_ip=True  
api_paste_config=/etc/nova/api-paste.ini  
volumes_path = /var/lib/nova/volumes  
enabled_apis = ec2,osapi_compute,metadata  
  
# Khai báo GLANCE  
glance_host = 192.169.60.160
```

```

# Khai bao RABBITMQ
rpc_backend = rabbit
rabbit_host = 192.169.60.160
rabbit_userid = guest
rabbit_password = $RABBIT_PASS


# Cau hinh VNC
my_ip = 192.169.60.160
vnserver_listen = 192.169.60.160
vnserver_proxyclient_address = 192.169.60.160
auth_strategy = keystone
novncproxy_base_url = http://192.169.60.160:6080/vnc_auto.html


# Tu dong start may ao khi reboot server openstack
resume_guests_state_on_host_boot=True


#Cho phep dat password cho Instance khi khoi tao
libvirt_inject_password = True
enable_instance_password = True


network_api_class = nova.network.neutronv2.api.API
neutron_url = http://192.169.60.160:9696
neutron_auth_strategy = keystone
neutron_admin_tenant_name = service
neutron_admin_username = neutron
neutron_admin_password = $ADMIN_PASS
neutron_admin_auth_url = http://192.169.60.160:35357/v2.0
linuxnet_interface_driver = nova.network.linux_net.LinuxOVSIfaceDriver
firewall_driver = nova.virt.firewall.NoopFirewallDriver
security_group_api = neutron
service_neutron_metadata_proxy = true
neutron_metadata_proxy_shared_secret = $METADATA_SECRET

```

```
[database]
connection = mysql://nova:$MYSQL_PASS@192.168.50.160/nova
```

```
[keystone_authtoken]
auth_uri = http://192.169.60.160:5000
auth_host = 192.169.60.160
auth_port = 35357
auth_protocol = http
admin_tenant_name = service
admin_user = nova
admin_password = $ADMIN_PASS
```

# Restart and check nova-\* services:

```
cd /etc/init.d/; for i in $( ls nova-* ); do sudo service $i restart; cd /root;/done
cd /etc/init.d/; for i in $( ls nova-* ); do sudo service $i status; cd /root;/done
(mind nova cert is ok if it's down: still the db has to be built up!)
```

# Remove Nova's SQLite database:

```
rm /var/lib/nova/nova.sqlite
```

# Synchronize your database:

```
nova-manage db sync
```

# Restart nova-\* services:

```
cd /etc/init.d/; for i in $( ls nova-* ); do sudo service $i restart; cd /root;/done
```

# ...and check:

```
cd /etc/init.d/; for i in $( ls nova-* ); do sudo service $i status; cd /root;/done
```

# Hopefully you should enjoy smiling faces on nova-\* services to confirm your installation:

```
nova-manage service list
```

## 7. Cinder

# Install the required packages:

```
apt-get install -y cinder-api cinder-scheduler cinder-volume iscsitarget open-iscsi iscsitarget-dkms
```



# Configure the iscsi services:

```
sed -i 's/false/true/g' /etc/default/iscsitarget
```

# Start the services:

```
service iscsitarget start
```

```
service open-iscsi start
```

# Configure /etc/cinder/api-paste.ini like the following:

```
[filter:authtoken]
paste.filter_factory = keystoneclient.middleware.auth_token:filter_factory
service_protocol = http
service_host = 192.169.60.160
service_port = 5000
auth_host = 10.10.3.160
auth_port = 35357
auth_protocol = http
admin_tenant_name = service
admin_user = cinder
admin_password = $pass_admin
```

# Edit the /etc/cinder/cinder.conf to:

```
[DEFAULT]
rootwrap_config=/etc/cinder/rootwrap.conf
sql_connection = mysql://cinder:$pass_cinderdb@10.10.3.160/cinder
api_paste_config = /etc/cinder/api-paste.ini
iscsi_helper=ietadm
volume_name_template = volume-%s
volume_group = cinder-volumes
verbose = True
auth_strategy = keystone
#osapi_volume_listen_port=5900
```

# Remove Cinder's SQLite database:

```
rm /var/lib/cinder/cinder.sqlite
```

# Then, synchronize your database:

```
cinder-manage db sync
```

# Finally, don't forget to create a volumegroup and name it cinder-volumes:

```
dd if=/dev/zero of=cinder-volumes bs=1 count=0 seek=2G
```

```
losetup /dev/loop2 cinder-volumes
fdisk /dev/loop2
```

```
#Type in the followings:
```

```
n
p
1
ENTER
ENTER
t
8e
w
```

```
# Proceed to create the physical volume then the volume group:
```

```
pvccreate /dev/loop2
vgcreate cinder-volumes /dev/loop2
```

```
# Note: Beware that this volume group gets lost after a system reboot.
```

```
Restart the cinder services:
```

```
cd /etc/init.d/; for i in $( ls cinder-* ); do sudo service $i restart; cd /root/; done
```

```
Verify if cinder services are running:
```

```
cd /etc/init.d/; for i in $( ls cinder-* ); do sudo service $i status; cd /root/; done
```

## 8. Horizon

```
# To install horizon, proceed like this
```

```
apt-get -y install openstack-dashboard memcached
```

```
# If you don't like the OpenStack ubuntu theme, you can remove the package to disable it:
```

```
dpkg --purge openstack-dashboard-ubuntu-theme
```

```
# Reload Apache and memcached:
```

```
service apache2 restart; service memcached restart
```

```
# You can now access your OpenStack 192.169.60.160/horizon with credentials
admin:Passadmin.
```

### III. Create VMs

Việc tạo network và tạo máy ảo bạn hoàn toàn có thể thực hiện thông qua giao diện. Có thể tham khảo 2 bài viết sau:

<http://mhst13-06-openstack.blogspot.com/2013/07/huong-dan-su-dung-openstack-dashboard.html>

[http://mhst13-06-openstack.blogspot.com/2013/07/huong-dan-su-dung-openstack-dashboard\\_23.html](http://mhst13-06-openstack.blogspot.com/2013/07/huong-dan-su-dung-openstack-dashboard_23.html)

Có một chú ý là khi ta tạo máy ảo, máy ảo không ra được internet có thể do sai dns. Cách khắc phục:

# liệt kê các dải mạng

`neutron subnet-list`

# cấu hình DNS cho dải mạng

`neutron subnet-update 44453bfa-14b9-445c-b8f4-33d7ba22455f --dns_nameservers 8.8.8.8 8.8.4.4`

# Với `44453bfa-14b9-445c-b8f4-33d7ba22455f` là id của network máy ảo 10.10.10.0/24