

GROVOLT

We bring the sun to Earth



Detachable LCD panel

RAGNAR 8.2



**Hybrid
System**
2 MPPT Chargers

Main Features:

- * Pure sinewave solar inverter On-grid/Off-Grid
- * OutPUT power Factor 1.0
- * Battery independent design
- * Built-in 150A MPPT Solar charger (2*80)
- * Wide PV input voltage range (90-450VDC)
- * Built-in Wi-Fi with IOS & Android App.
- * Smart battery charger design
- * Built-in parallel kit support parallel up to 6Units.
- * RGB lighting for different working modes

We bring the sun to Earth



Technical specs:

Line Mode	Model Name	Ragnar 8.2kw
	Model Number	GI-R48-8.2Kw
	Maximum PV input Power	10000W
	Rated output Power	8200W
	Nominal input voltage	230VAC
	Maximum Input AC Voltage	230VAC
	Maximum Input Current	60A
	Nominal input frequency	50/60Hz (Auto Sensing)
	Output circuit protection	Circuit breaker
	Output voltage range	184-264.5VAC or 195.5-253VAC
	Efficiency	95%
Inverter	Nominal input voltage	48VDC
	Output voltage waveform	Pure sinewave
	Output voltage regulation	230Vac +/-5%.
	Output frequency	50Hz/60Hz
	Power Factor	>0.99
Solar /Charging mode	Maximum PV array	10000W
	Maximum PV open circuit voltage	500VDC
	Nominal PV voltage	340VDC
	Number of MPPT trackers	2
	PV array MPPT range	90 to 450VDC
	High PV cutt-off voltage	500VDC
	High PV recovery voltage	490VDC
	Maximum input current	2 * 18A
	Maximum charging current	150A
	Over temperature protection	Available
	Over-load short circuit protection	Available
Parallel	Reserve current protection	Available
	Startup voltage	80V +/- 5Vdc
	Max parallel numbers	Up to 6 units
	Parallel system output power	49.2KW
	Circulation Current (@no Load)	Max 2A
	Power Unbalance Ratio	<5% @ 100% Load
	Nominal output voltage	220/230/240 VAC
connection	Dry contact	CAN for BMS
	USB connection	Available
	BMS Connection	(RS232/RS485/CAN)
	Serial connection	RS232
	Wi-Fi	Built-in module
	Parallel connection	Built-in Parallel kit (supports 6 units)



Made in CHINA
Designed in CANADA

