

EXTENDS *TLC, Integers, FiniteSets, Sequences, Reals*

CONSTANTS *PRODUCTS, APPS, IDs, GATEAPPS*

ASSUME *Cardinality(APPS) > 0*

$PT \triangleq$ INSTANCE *PT*

$set ++ item \triangleq set \cup \{item\}$

$set -- item \triangleq set \setminus \{item\}$

In shopping list, the product is in fact the identifier. Any item could have an information for how much of a product one wants to buy (not relevant in this specification).

$ShopyItems \triangleq [id : PRODUCTS, bought : BOOLEAN]$

$ADD_ACTION \triangleq$ "add"

$RM_ACTION \triangleq$ "rm"

$SET_BOUGHT_ACTION \triangleq$ "set_bought"

$REQ_SYNC_ACTION \triangleq$ "req_sync"

$RESP_SYNC_ACTION \triangleq$ "resp_sync"

$END_SYNC_ACTION \triangleq$ "end_sync"

Actions is the set of all possible actions in the system.

$Actions \triangleq \{$
 $ADD_ACTION,$
 $RM_ACTION,$
 $SET_BOUGHT_ACTION,$
 $REQ_SYNC_ACTION,$
 $RESP_SYNC_ACTION,$
 END_SYNC_ACTION
 $\}$

$SyncActions \triangleq \{REQ_SYNC_ACTION, RESP_SYNC_ACTION\}$

SyncMsgs is the set of all possible messages sent for synchronisation of shopy lists.

$SyncMsgs \triangleq$
 $[id : IDs,$
 $app : APPS,$
 $list : SUBSET ShopyItems,$
 $mergedList : SUBSET ShopyItems,$
 $type : SyncActions]$

Messages sent for joining the network.

$JoinRespMsgs \triangleq$
 $[app : APPS,$
 $knownHosts : PT!SeqOf(APPS, Cardinality(APPS))]$

$$\text{JoinReqMsgs} \triangleq \\ [app : APPS]$$

Messages sent for notifications about new joiners in the network.

$$\text{JoinNotifMsgs} \triangleq \\ [app : APPS]$$

The spec now depicts a shopping-list *app* where the server *app* manages several users and hence multiple lists of items that synch eventually.

The list contains unique items, thus we use a set.

--algorithm *OptiShopyList*

variable

whether an *app* is a gate
 $isGate = [a \in APPS \mapsto a \in GATEAPPS],$
 one shopping list for all *APPS*
 $shopyList = [a \in APPS \mapsto \{\}],$
 sync *shopyList* requests/responses
 $syncReqQueue = [a \in APPS \mapsto \langle \rangle],$
 $syncRespQueue = [a \in APPS \mapsto \langle \rangle],$
 join to network requests/responses
 $joinReqQueue = [a \in APPS \mapsto \langle \rangle],$
 $joinRespQueue = [a \in APPS \mapsto \langle \rangle],$
 new joiner notifications
 $newJoinerNotif = [a \in APPS \mapsto \langle \rangle],$
 set of taken *IDs*
 $takenIDs = \{\};$

define

A couple of helpers for shopy-list items

$\text{NewShopyItem}(list) \triangleq$
 $[id \mapsto (\text{CHOOSE } x \in PRODUCTS : \neg \exists i \in list : x = i.id),$
 $bought \mapsto \text{FALSE}]$

$\text{ExistingShopyItem}(list) \triangleq \text{CHOOSE } x \in list : \text{TRUE}$

$\text{ExistingNotBoughtShopyItem}(list) \triangleq \text{CHOOSE } x \in list : x.bought = \text{FALSE}$

Helpers for *Sync* messages request/response.

$\text{NewSyncMsg}(id, a, l, ml, t) \triangleq$
 $[id \mapsto id,$
 $app \mapsto a,$
 $list \mapsto l,$
 $mergedList \mapsto ml,$

$$\begin{aligned}
& type \mapsto t] \\
NewSyncReqMsg(a, l, ml, t) & \triangleq \\
& NewSyncMsg(\\
& \quad (CHOOSE \ i \in \ IDs : \forall \ ti \in \ takenIDs : i = ti), \\
& \quad a, l, ml, t \\
&) \\
NewSyncReq(app) & \triangleq \\
& NewSyncReqMsg(app, shopyList[app], \{\}, REQ_SYNC_ACTION) \\
NewSyncResp(app, mergeResult, id) & \triangleq \\
& NewSyncMsg(id, app, shopyList[app], mergeResult, RESP_SYNC_ACTION)
\end{aligned}$$

Helpers for the decentralized network features.

$$\begin{aligned}
NewJoinReqMsg(app) & \triangleq [app \mapsto app] \\
NewJoinRespMsg(app, hosts) & \triangleq \\
& [app \mapsto app, \\
& \quad knownHosts \mapsto hosts] \\
GateApps & \triangleq \{a \in APPS : isGate[a]\} \\
NewJoinerNotifReq(app) & \triangleq [app \mapsto app] \\
PickGossipFriends(app, knownApps) & \triangleq \\
& LET \ Opposit \triangleq \\
& \quad PT!Index(knownApps, app) + (Len(knownApps) \div 2) - (Len(knownApps) \% 2) \\
& \quad PreviousIndex(i) \triangleq \\
& \quad \quad IF \ Len(knownApps) < 3 \\
& \quad \quad THEN \ 1 \\
& \quad \quad ELSE \ IF \ i = 1 \ THEN \ Len(knownApps) \ ELSE \ i - 1 \\
& \quad NextIndex(i) \triangleq \\
& \quad \quad IF \ Len(knownApps) < 3 \\
& \quad \quad THEN \ Len(knownApps) \\
& \quad \quad ELSE \ IF \ i = Len(knownApps) \ THEN \ 1 \ ELSE \ i + 1 \\
& \quad IN \ \{knownApps[PreviousIndex(Opposit)], knownApps[NextIndex(Opposit)]\}
\end{aligned}$$

Not used, it's an example of how we'd keep the ordering of the responded *knownApps* sequence on joining. If it's used, it should be with small sequences to not generate enormous sets.

$$\begin{aligned}
MergeKnownApps(apps1, apps2) & \triangleq \\
& LET \ AppSeq(n) \triangleq PT!SeqOf(APPS, n) \\
& \quad Contains(appSeq, appItem) \triangleq \\
& \quad \quad Cardinality(PT!Matching(appSeq, appItem)) > 0
\end{aligned}$$

```

    f[args ∈ AppSeq(Len(apps1))
      × AppSeq(Len(apps2))
      × AppSeq(Len(apps1) + Len(apps2))]  $\triangleq$ 

    LET l1  $\triangleq$  args[1]

    l2  $\triangleq$  args[2]

    acc  $\triangleq$  args[3]

    PickFromL1  $\triangleq$  f[(
      Tail(l1),
      l2,
      Append(acc, Head(l1)))])

    SkipOneL1  $\triangleq$  f[(
      Tail(l1),
      l2,
      acc)]

    PickFromL2  $\triangleq$  f[(
      l1,
      Tail(l2),
      Append(acc, Head(l2)))])

    SkipOneL2  $\triangleq$  f[(
      l1,
      Tail(l2),
      acc)]

  IN
    IF Len(l2) = 0
    THEN IF Len(l1) = 0
    THEN acc
    ELSE IF Contains(acc, Head(l1)) THEN SkipOneL1 ELSE PickFromL1
    ELSE IF Head(l1) ≠ Head(l2)
    THEN IF Contains(acc, Head(l2)) THEN SkipOneL2 ELSE PickFromL2
    ELSE IF Contains(acc, Head(l1)) THEN SkipOneL1 ELSE PickFromL1

    IN f[(apps1, apps2, ⟨⟩)]
end define ;

macro Notify(gossipFriends, newJoiner)
begin
  with a ∈ gossipFriends
  do
    newJoinerNotif[a] := Append(newJoinerNotif[a], NewJoinerNotifReq(app));
  end with ;
end macro ;

```

This process represents a shopy-list running in one of the several network clients.

Since Opti-shopylist is a decentralized program, the user creates a network of connected instances of Opti-shopylist.

We assume that every client *app* has only one shopy-list.

fair process *ClientApp* $\in APPS$

variables

joined = FALSE,
gossipFriends = {},
knownApps = $\langle self \rangle$;

begin *AppLoop*:

while TRUE **do**

Below are actions to manage the connection to the network.

either

SEND JOIN REQUEST

with $a \in (GateApps -- self)$

do

$joinReqQueue[a] := Append(joinReqQueue[a], NewJoinReqMsg(self))$;

end with ;

or

RESPOND TO JOIN REQUEST

if *isGate*[*self*] **then**

await $joinReqQueue[self] \neq \langle \rangle$;

with $joinRequest = Head(joinReqQueue[self])$,

$updatedKnownApps = Append(knownApps, joinRequest.app)$

do

$joinRespQueue[joinRequest.app] := Append($
 $joinRespQueue[joinRequest.app],$
 $NewJoinRespMsg(self, SelectSeq(knownApps,$
 $LAMBDA app : app \neq joinRequest.app)))$;

if $joinRequest.app \notin PT!Range(knownApps)$

then

$knownApps := updatedKnownApps$;

$gossipFriends := PickGossipFriends(self, Tail(updatedKnownApps))$;

end if ;

$joinReqQueue[self] := Tail(joinReqQueue[self])$;

$joined := TRUE$;

end with ;

end if ;

or

RECEIVE JOIN RESPONSE

```

await joinRespQueue[self]  $\neq \langle \rangle$  ;
with joinResponse = Head(joinRespQueue[self]),
      newKnownApps = PT!Range(joinResponse.knownHosts) \ PT!Range(knownApps)
do
  gossipFriends := PickGossipFriends(self, joinResponse.knownHosts);

  knownApps := knownApps  $\circ$  PT!OrderSet(newKnownApps);

  joinRespQueue[self] := Tail(joinRespQueue[self]);

  joined := TRUE;
end with ;

```

Following are the actions applying to the shopy-list managed by the *app*.

```

or
  ADD
  await Cardinality(shopyList[self]) < Cardinality(PRODUCTS);
  shopyList[self] := shopyList[self] ++ NewShopyItem(shopyList[self]);
or
  REMOVE
  await shopyList[self]  $\neq \{\}$ ;
  shopyList[self] := shopyList[self] -- ExistingShopyItem(shopyList[self]);
or
  ITEM HAS BEEN BOUGHT
  await shopyList[self]  $\neq \{\}$ ;
  await  $\exists item \in shopyList[self] : \neg item.bought$ ;
  with modifiedItem = ExistingNotBoughtShopyItem(shopyList[self])
  do
    shopyList[self] := shopyList[self] -- modifiedItem ++ [modifiedItem EXCEPT !.bought = TRUE]
  end with ;

```

Below actions manage the synchronization of the list.

```

or
  SEND SYNC REQUEST
  with  $a \in (PT!Range(knownApps) -- self)$ 
  do
    syncReqQueue[a] := Append(syncReqQueue[a], NewSyncReq(self));
  end with ;
or
  RCV SYNC REQUEST
  await syncReqQueue[self]  $\neq \langle \rangle$  ;
  with syncRequest = Head(syncReqQueue[self]),
        mergeResult = shopyList[self]  $\cup$  syncRequest.list,
        newResp = NewSyncResp(self, mergeResult, syncRequest.id)
  do

```

```

    syncReqQueue[self] := Tail(syncReqQueue[self]);
    merge from request app
    shopyList[self] := mergeResult;
    syncRespQueue[syncRequest.app] := Append(syncRespQueue[syncRequest.app], newResp);
  end with ;
or
  RCV SYNC RESPONSE
  await syncRespQueue[self] ≠ ⟨⟩ ;
  with syncResponse = Head(syncRespQueue[self]),
    mergeResult = shopyList[self] ∪ syncResponse.list
  do
    shopyList[self] := mergeResult;
    syncRespQueue[self] := Tail(syncRespQueue[self]);
  end with ;
end either ;
end while ;
end process ;

```

```

end algorithm ;
BEGIN TRANSLATION (chksum(pcal) = "a4dd4f8d" ∧ chksum(tla) = "e6dbda73")
VARIABLES isGate, shopyList, syncReqQueue, syncRespQueue, joinReqQueue,
  joinRespQueue, newJoinerNotif, takenIDs

```

```

define statement
NewShopyItem(list)  $\triangleq$ 
  [id  $\mapsto$  (CHOOSE  $x \in PRODUCTS : \neg \exists i \in list : x = i.id$ ),
   bought  $\mapsto$  FALSE]

ExistingShopyItem(list)  $\triangleq$  CHOOSE  $x \in list : \text{TRUE}$ 

ExistingNotBoughtShopyItem(list)  $\triangleq$  CHOOSE  $x \in list : x.bought = \text{FALSE}$ 

```

```

NewSyncMsg(id, a, l, ml, t)  $\triangleq$ 
  [id  $\mapsto$  id,
   app  $\mapsto$  a,
   list  $\mapsto$  l,
   mergedList  $\mapsto$  ml,
   type  $\mapsto$  t]

```

```

NewSyncReqMsg(a, l, ml, t)  $\triangleq$ 
  NewSyncMsg(
    (CHOOSE  $i \in IDs : \forall ti \in takenIDs : i = ti$ ),
    a, l, ml, t
  )

```

$$\begin{aligned}
&) \\
& \text{NewSyncReq}(app) \triangleq \\
& \quad \text{NewSyncReqMsg}(app, \text{shopyList}[app], \{\}, \text{REQ_SYNC_ACTION}) \\
& \text{NewSyncResp}(app, \text{mergeResult}, id) \triangleq \\
& \quad \text{NewSyncMsg}(id, app, \text{shopyList}[app], \text{mergeResult}, \text{RESP_SYNC_ACTION}) \\
& \\
& \text{NewJoinReqMsg}(app) \triangleq [app \mapsto app] \\
& \text{NewJoinRespMsg}(app, \text{hosts}) \triangleq \\
& \quad [app \mapsto app, \\
& \quad \quad \text{knownHosts} \mapsto \text{hosts}] \\
& \text{GateApps} \triangleq \{a \in APPS : \text{isGate}[a]\} \\
& \text{NewJoinerNotifReq}(app) \triangleq [app \mapsto app] \\
& \text{PickGossipFriends}(app, \text{knownApps}) \triangleq \\
& \quad \text{LET } Opposit \triangleq \\
& \quad \quad PT!Index(\text{knownApps}, app) + (\text{Len}(\text{knownApps}) \div 2) - (\text{Len}(\text{knownApps}) \% 2) \\
& \quad \text{PreviousIndex}(i) \triangleq \\
& \quad \quad \text{IF } \text{Len}(\text{knownApps}) < 3 \\
& \quad \quad \quad \text{THEN } 1 \\
& \quad \quad \quad \text{ELSE IF } i = 1 \text{ THEN } \text{Len}(\text{knownApps}) \text{ ELSE } i - 1 \\
& \quad \text{NextIndex}(i) \triangleq \\
& \quad \quad \text{IF } \text{Len}(\text{knownApps}) < 3 \\
& \quad \quad \quad \text{THEN } \text{Len}(\text{knownApps}) \\
& \quad \quad \quad \text{ELSE IF } i = \text{Len}(\text{knownApps}) \text{ THEN } 1 \text{ ELSE } i + 1 \\
& \text{IN } \{\text{knownApps}[\text{PreviousIndex}(Opposit)], \text{knownApps}[\text{NextIndex}(Opposit)]\} \\
& \\
& \text{MergeKnownApps}(\text{apps1}, \text{apps2}) \triangleq \\
& \quad \text{LET } AppSeq(n) \triangleq PT!SeqOf(APPS, n) \\
& \quad \text{Contains}(appSeq, appItem) \triangleq \\
& \quad \quad \text{Cardinality}(PT!Matching(appSeq, appItem)) > 0 \\
& \quad f[\text{args} \in AppSeq(\text{Len}(\text{apps1})) \\
& \quad \quad \times AppSeq(\text{Len}(\text{apps2})) \\
& \quad \quad \times AppSeq(\text{Len}(\text{apps1}) + \text{Len}(\text{apps2}))] \triangleq
\end{aligned}$$


```

LET  $l1 \triangleq args[1]$ 
 $l2 \triangleq args[2]$ 
 $acc \triangleq args[3]$ 
 $PickFromL1 \triangleq f[(<$ 
     $Tail(l1),$ 
 $l2,$ 
 $Append(acc, Head(l1)))>]$ 
 $SkipOneL1 \triangleq f[(<$ 
     $Tail(l1),$ 
 $l2,$ 
 $acc>]$ 
 $PickFromL2 \triangleq f[(<$ 
     $l1,$ 
 $Tail(l2),$ 
 $Append(acc, Head(l2)))>]$ 
 $SkipOneL2 \triangleq f[(<$ 
     $l1,$ 
 $Tail(l2),$ 
 $acc>]$ 
IN
  IF  $Len(l2) = 0$ 
  THEN IF  $Len(l1) = 0$ 
    THEN  $acc$ 
    ELSE IF  $Contains(acc, Head(l1))$  THEN  $SkipOneL1$  ELSE  $PickFromL1$ 
  ELSE IF  $Head(l1) \neq Head(l2)$ 
    THEN IF  $Contains(acc, Head(l2))$  THEN  $SkipOneL2$  ELSE  $PickFromL2$ 
    ELSE IF  $Contains(acc, Head(l1))$  THEN  $SkipOneL1$  ELSE  $PickFromL1$ 
  IN  $f[⟨apps1, apps2, \rangle⟩]$ 

VARIABLES  $joined, gossipFriends, knownApps$ 

vars  $\triangleq \langle isGate, shopyList, syncReqQueue, syncRespQueue, joinReqQueue,$ 
     $joinRespQueue, newJoinerNotif, takenIDs, joined, gossipFriends,$ 
     $knownApps \rangle$ 

ProcSet  $\triangleq (APPS)$ 

Init  $\triangleq$  Global variables
     $\wedge isGate = [a \in APPS \mapsto a \in GATEAPPS]$ 
     $\wedge shopyList = [a \in APPS \mapsto \{\}]$ 
     $\wedge syncReqQueue = [a \in APPS \mapsto \langle \rangle]$ 
     $\wedge syncRespQueue = [a \in APPS \mapsto \langle \rangle]$ 

```

$$\begin{aligned}
& \wedge \text{joinReqQueue} = [a \in APPS \mapsto \langle \rangle] \\
& \wedge \text{joinRespQueue} = [a \in APPS \mapsto \langle \rangle] \\
& \wedge \text{newJoinerNotif} = [a \in APPS \mapsto \langle \rangle] \\
& \wedge \text{takenIDs} = \{\} \\
& \text{Process } \text{ClientApp} \\
& \wedge \text{joined} = [self \in APPS \mapsto \text{FALSE}] \\
& \wedge \text{gossipFriends} = [self \in APPS \mapsto \{\}] \\
& \wedge \text{knownApps} = [self \in APPS \mapsto \langle self \rangle] \\
\\
\text{ClientApp}(self) & \triangleq \wedge \vee \wedge \exists a \in (\text{GateApps} -- self) : \\
& \quad \text{joinReqQueue}' = [\text{joinReqQueue} \text{ EXCEPT } ![a] = \text{Append}(\text{joinReqQueue}[a], \text{NewJoinerNotif}[a])] \\
& \quad \wedge \text{UNCHANGED } \langle \text{shopyList}, \text{syncReqQueue}, \text{syncRespQueue}, \text{joinRespQueue}, \text{joined}, \\
& \quad \vee \wedge \text{IF } \text{isGate}[self] \\
& \quad \quad \text{THEN } \wedge \text{joinReqQueue}[self] \neq \langle \rangle \\
& \quad \quad \quad \wedge \text{LET } \text{joinRequest} \triangleq \text{Head}(\text{joinReqQueue}[self]) \text{ IN} \\
& \quad \quad \quad \text{LET } \text{updatedKnownApps} \triangleq \text{Append}(\text{knownApps}[self], \text{joinRequest}.app) \\
& \quad \quad \quad \wedge \text{joinRespQueue}' = [\text{joinRespQueue} \text{ EXCEPT } ![\text{joinRequest}.app] = \text{Append}(\text{joinRespQueue}[\text{joinRequest}.app], \text{joinRequest}.resp)] \\
& \quad \quad \quad \wedge \text{IF } \text{joinRequest}.app \notin PT!Range(\text{knownApps}[self]) \\
& \quad \quad \quad \quad \text{THEN } \wedge \text{knownApps}' = [\text{knownApps} \text{ EXCEPT } ![self] = \text{updatedKnownApps}] \\
& \quad \quad \quad \quad \wedge \text{gossipFriends}' = [\text{gossipFriends} \text{ EXCEPT } ![self] = \text{Append}(\text{gossipFriends}[self], \text{joinRequest}.gossip)] \\
& \quad \quad \quad \quad \text{ELSE } \wedge \text{TRUE} \\
& \quad \quad \quad \quad \wedge \text{UNCHANGED } \langle \text{gossipFriends}, \\
& \quad \quad \quad \quad \quad \text{knownApps} \rangle \\
& \quad \quad \quad \wedge \text{joinReqQueue}' = [\text{joinReqQueue} \text{ EXCEPT } ![self] = \text{Tail}(\text{joinReqQueue}[self])] \\
& \quad \quad \quad \wedge \text{joined}' = [\text{joined} \text{ EXCEPT } ![self] = \text{TRUE}] \\
& \quad \quad \text{ELSE } \wedge \text{TRUE} \\
& \quad \quad \quad \wedge \text{UNCHANGED } \langle \text{joinReqQueue}, \\
& \quad \quad \quad \quad \text{joinRespQueue}, \text{joined}, \\
& \quad \quad \quad \quad \text{gossipFriends}, \text{knownApps} \rangle \\
& \quad \quad \wedge \text{UNCHANGED } \langle \text{shopyList}, \text{syncReqQueue}, \text{syncRespQueue} \rangle \\
& \quad \vee \wedge \text{joinRespQueue}[self] \neq \langle \rangle \\
& \quad \quad \wedge \text{LET } \text{joinResponse} \triangleq \text{Head}(\text{joinRespQueue}[self]) \text{ IN} \\
& \quad \quad \quad \text{LET } \text{newKnownApps} \triangleq PT!Range(\text{joinResponse}.knownHosts) \setminus PT!Range(\text{knownApps}[self]) \\
& \quad \quad \quad \wedge \text{gossipFriends}' = [\text{gossipFriends} \text{ EXCEPT } ![self] = \text{PickGossipFriends}(self, \text{joinResponse}.gossip)] \\
& \quad \quad \quad \wedge \text{knownApps}' = [\text{knownApps} \text{ EXCEPT } ![self] = \text{knownApps}[self] \circ PT!OrderS] \\
& \quad \quad \quad \wedge \text{joinRespQueue}' = [\text{joinRespQueue} \text{ EXCEPT } ![self] = \text{Tail}(\text{joinRespQueue}[self])] \\
& \quad \quad \quad \wedge \text{joined}' = [\text{joined} \text{ EXCEPT } ![self] = \text{TRUE}] \\
& \quad \quad \quad \wedge \text{UNCHANGED } \langle \text{shopyList}, \text{syncReqQueue}, \text{syncRespQueue}, \text{joinReqQueue} \rangle \\
& \quad \vee \wedge \text{Cardinality}(\text{shopyList}[self]) < \text{Cardinality}(\text{PRODUCTS}) \\
& \quad \quad \wedge \text{shopyList}' = [\text{shopyList} \text{ EXCEPT } ![self] = \text{shopyList}[self] ++ \text{NewShopyItem}(\text{shopyList}[self])] \\
& \quad \quad \wedge \text{UNCHANGED } \langle \text{syncReqQueue}, \text{syncRespQueue}, \text{joinReqQueue}, \text{joinRespQueue}, \text{joined} \rangle \\
& \quad \vee \wedge \text{shopyList}[self] \neq \{\}
\end{aligned}$$

$$\begin{aligned}
& \wedge \text{shopyList}' = [\text{shopyList} \text{ EXCEPT } ![self] = \text{shopyList}[self] \text{ -- ExistingShopyItem}(s) \\
& \wedge \text{UNCHANGED } \langle \text{syncReqQueue}, \text{syncRespQueue}, \text{joinReqQueue}, \text{joinRespQueue}, \text{joined}, \text{gossipFriends}, \text{knownApps} \rangle \\
\vee & \wedge \text{shopyList}[self] \neq \{\} \\
& \wedge \exists \text{item} \in \text{shopyList}[self] : \neg \text{item.bought} \\
& \wedge \text{LET } \text{modifiedItem} \triangleq \text{ExistingNotBoughtShopyItem}(\text{shopyList}[self]) \text{ IN} \\
& \quad \text{shopyList}' = [\text{shopyList} \text{ EXCEPT } ![self] = \text{shopyList}[self] \text{ -- modifiedItem} ++ [\text{modifiedItem}]] \\
& \wedge \text{UNCHANGED } \langle \text{syncReqQueue}, \text{syncRespQueue}, \text{joinReqQueue}, \text{joinRespQueue}, \text{joined}, \text{gossipFriends}, \text{knownApps} \rangle \\
\vee & \wedge \exists a \in (PT! \text{Range}(\text{knownApps}[self]) \text{ -- self}) : \\
& \quad \text{syncReqQueue}' = [\text{syncReqQueue} \text{ EXCEPT } ![a] = \text{Append}(\text{syncReqQueue}[a], \text{NewSyncReq}(a))] \\
& \wedge \text{UNCHANGED } \langle \text{shopyList}, \text{syncRespQueue}, \text{joinReqQueue}, \text{joinRespQueue}, \text{joined}, \text{gossipFriends}, \text{knownApps} \rangle \\
\vee & \wedge \text{syncReqQueue}[self] \neq \langle \rangle \\
& \wedge \text{LET } \text{syncRequest} \triangleq \text{Head}(\text{syncReqQueue}[self]) \text{ IN} \\
& \quad \text{LET } \text{mergeResult} \triangleq \text{shopyList}[self] \cup \text{syncRequest.list} \text{ IN} \\
& \quad \text{LET } \text{newResp} \triangleq \text{NewSyncResp}(\text{self}, \text{mergeResult}, \text{syncRequest.id}) \text{ IN} \\
& \quad \wedge \text{syncReqQueue}' = [\text{syncReqQueue} \text{ EXCEPT } ![self] = \text{Tail}(\text{syncReqQueue}[self])] \\
& \quad \wedge \text{shopyList}' = [\text{shopyList} \text{ EXCEPT } ![self] = \text{mergeResult}] \\
& \quad \wedge \text{syncRespQueue}' = [\text{syncRespQueue} \text{ EXCEPT } ![\text{syncRequest.app}] = \text{Append}(\text{syncRespQueue}[\text{syncRequest.app}], \text{newResp})] \\
& \wedge \text{UNCHANGED } \langle \text{joinReqQueue}, \text{joinRespQueue}, \text{joined}, \text{gossipFriends}, \text{knownApps} \rangle \\
\vee & \wedge \text{syncRespQueue}[self] \neq \langle \rangle \\
& \wedge \text{LET } \text{syncResponse} \triangleq \text{Head}(\text{syncRespQueue}[self]) \text{ IN} \\
& \quad \text{LET } \text{mergeResult} \triangleq \text{shopyList}[self] \cup \text{syncResponse.list} \text{ IN} \\
& \quad \wedge \text{shopyList}' = [\text{shopyList} \text{ EXCEPT } ![self] = \text{mergeResult}] \\
& \quad \wedge \text{syncRespQueue}' = [\text{syncRespQueue} \text{ EXCEPT } ![self] = \text{Tail}(\text{syncRespQueue}[self])] \\
& \wedge \text{UNCHANGED } \langle \text{syncReqQueue}, \text{joinReqQueue}, \text{joinRespQueue}, \text{joined}, \text{gossipFriends}, \text{knownApps} \rangle \\
& \wedge \text{UNCHANGED } \langle \text{isGate}, \text{newJoinerNotif}, \text{takenIDs} \rangle
\end{aligned}$$

$$\text{Next} \triangleq (\exists \text{self} \in \text{APPS} : \text{ClientApp}(\text{self}))$$

$$\begin{aligned}
\text{Spec} & \triangleq \wedge \text{Init} \wedge \Box [\text{Next}]_{\text{vars}} \\
& \wedge \forall \text{self} \in \text{APPS} : \text{WF}_{\text{vars}}(\text{ClientApp}(\text{self}))
\end{aligned}$$

END TRANSLATION

$$\begin{aligned}
\text{NoDuplicates}(\text{seq}) & \triangleq \\
& \forall i, j \in \text{DOMAIN } \text{seq} : \\
& \quad i \neq j \Rightarrow \text{seq}[i] \neq \text{seq}[j]
\end{aligned}$$

$$\begin{aligned}
\text{CountNumberOfGossips}(\text{app}) & \triangleq \\
& PT! \text{ReduceSet} (\\
& \quad \text{LAMBDA } a, \text{acc} : \text{acc} + (\text{IF } \text{app} \in \text{gossipFriends}[a] \\
& \quad \quad \text{THEN } 1 \text{ ELSE } 0), \\
& \quad \text{APPS}, \\
& \quad 0)
\end{aligned}$$

$$\begin{aligned}
\text{ExistsRoute}(\text{from}, \text{to}, \text{gossipFriends}) & \triangleq \\
& \text{LET } f[\langle \text{app}, \text{visited} \rangle \in \text{APPS} \times \text{SUBSET } \text{APPS}] \triangleq \\
& \quad \text{to} \in \text{gossipFriends}[\text{app}]
\end{aligned}$$

$$\begin{aligned}
& \vee \exists a \in (_gossipFriends[app] \setminus visited) : f[a, visited ++ app] \\
\text{IN } & from = to \vee f[\langle from, \{\} \rangle] \\
TypeOK & \triangleq \\
& \wedge \forall a \in APPS : \\
& \quad \text{Checking on variables' domains.} \\
& \quad \wedge shopyList[a] \subseteq ShopyItems \\
& \quad \wedge PT!Range(syncReqQueue[a]) \subseteq SyncMsgs \\
& \quad \wedge PT!Range(syncRespQueue[a]) \subseteq SyncMsgs \\
& \quad \text{The queue for join requests is only for gate apps} \\
& \quad \wedge \text{IF } isGate[a] \\
& \quad \quad \text{THEN } PT!Range(joinReqQueue[a]) \subseteq JoinReqMsgs \\
& \quad \quad \quad \wedge \forall req \in PT!Range(joinReqQueue[a]) : req.app \neq a \\
& \quad \quad \text{ELSE } joinReqQueue[a] = \langle \rangle \\
& \quad \wedge PT!Range(joinRespQueue[a]) \subseteq JoinRespMsgs \\
& \quad \wedge PT!Range(newJoinerNotif[a]) \subseteq JoinNotifMsgs \\
& \quad \text{knownApps is a collection of unique, ordered apps.} \\
& \quad \wedge PT!Range(knownApps[a]) \subseteq APPS \\
& \quad \wedge NoDuplicates(knownApps[a]) \\
& \quad \text{Apps don't gossip themselves} \\
& \quad \wedge gossipFriends[a] \subseteq (APPS -- a) \\
& \quad \text{Invariant when we're connected or not.} \\
& \quad \wedge gossipFriends[a] \neq \{\} \\
& \quad \quad \equiv knownApps[a] \neq \langle a \rangle \\
& \wedge takenIDs \subseteq IDs \\
Liveness & \triangleq \\
& \wedge \forall a \in APPS : \\
& \quad joined[a] \\
& \quad \text{there's a route from every other connected app to a} \\
& \quad \leadsto \forall a2 \in \{j \in (APPS -- a) : joined[j]\} : \\
& \quad \quad ExistsRoute(a2, a, gossipFriends)
\end{aligned}$$

\ * Modification History
\ * Last modified Tue Mar 16 19:24:39 CET 2021 by *davd*
\ * Created Tue Mar 02 12:33:43 CET 2021 by *davd*