


Component Reference Designators
Revised 4/24/24




CONTROLS AND FEATURES

- Harmonics
- Bright
- Low

All trademarks and registered trademarks are the property of their respective owners. The company, product, and service names used in this web site are for identification purposes only. Use of these names, logos, and brands does not imply endorsement.



Component Values



All trademarks and registered trademarks are the property of their respective owners. The company, product, and service names used in this web site are for identification purposes only. Use of these names, logos, and brands does not imply endorsement.




Skeptical Buffer

Parts List (Page 1 of 1)

| LOCATION | VALUE | TYPE | NOTES |
|--------------|------------|-------------------------------|---------------------------------|
| R1 | 3M3 | Resistor, 1/4W | |
| R2 | 11K | Resistor, 1/4W | |
| R3 | 1K5 | Resistor, 1/4W | |
| R4 | 470R | Resistor, 1/4W | |
| R5 | 3M3 | Resistor, 1/4W | |
| R6 | 22K | Resistor, 1/4W | |
| R7 | 220K | Resistor, 1/4W | |
| R8 | 1K5 | Resistor, 1/4W | |
| R9 | 100K | Resistor, 1/4W | |
| R10 | 1K5 | Resistor, 1/4W | |
| R11 | 1K5 | Resistor, 1/4W | |
| R12 | 220K | Resistor, 1/4W | |
| R13 | 10R | Resistor, 1/4W | |
| R14 | 3M3 | Resistor, 1/4W | |
| CLR | 4K7 | Resistor, 1/4W | * LED current limiting resistor |
| | 1131 | | carrent mining redictor |
| C1 | 3p | Ceramic capacitor | |
| C2 | 1u | Film capacitor, 7.2 x 5.0mm | |
| C3 | 1u | Tantalum capacitor | |
| C4 | 100n | Film capacitor, 7.2 x 2.5mm | |
| C5 | 220n | Film capacitor, 7.2 x 5.0mm | |
| C6 | 10u | Tantalum capacitor | |
| C7 | 1u | Film capacitor, 7.2 x 5.0mm | |
| C8 | 1u | Tantalum capacitor | |
| C9 | 1u | Film capacitor, 7.2 x 5.0mm | |
| C10 | 47u | Tantalum capacitor | |
| C100 | 100u | Electrolytic capacitor, 5mm | 25V minimum |
| C100 | 10u | Electrolytic capacitor, 5mm | 25V minimum |
| C102 | 10u | Electrolytic capacitor, 5mm | 25V minimum |
| C103 | 10u | Electrolytic capacitor, 5mm | 25V minimum |
| C104 | 10u | Electrolytic capacitor, 5mm | 25V minimum |
| C105 | 10u | Electrolytic capacitor, 5mm | 25V minimum |
| C106 | 10u | Electrolytic capacitor, 5mm | 25V minimum |
| C 100 | Tou | Liectrorytic capacitor, Smith | 237 1111111111111 |
| D100 | 1N5817 | Schottky diode, DO-41 | |
| D100 | 1N5817 | Schottky diode, DO-41 | |
| D101 D102 | 1N5817 | Schottky diode, DO-41 | |
| D102 D103 | 1N5817 | Schottky diode, DO-41 | |
| D103 | 1N5817 | Schottky diode, DO-41 | |
| D 104 | TINGOTI | Schollky diode, DO-41 | |
| IC1 | TL072 | Dual on amp DID9 | |
| IC100 | | Dual op-amp, DIP8 | |
| 10100 | TC1044SCPA | Charge pump IC, DIP8 | |
| CW P | ON/ON | Toggle switch CDDT | 2 position (ON/ON) |
| SW_B SW_H | ON/ON | Toggle switch, SPDT | 2-position (ON/ON) |
| | ON/ON | Toggle switch, SPDT | 2-position (ON/ON) |
| SW_L | ON/ON | Toggle switch, SPDT | 2-position (ON/ON) |
| | | | |
| | | | |




Skeptical Buffer Schematic Diagram





Skeptical Buffer Wiring Diagram






Skeptical Buffer

Drill Template

125B Enclosure




For Revision 2 PCB See next page for Revision 1



Skeptical Buffer

Drill Template

125B Enclosure



For Revision 1 PCB only