NO.:
DATE:

Rivas, Dave Aillerr C.
BSIT 2-3

Midterm Seatwork #2 - Smart Wallet System
March 25, 2026

1. Java Program:

```
import java.util.Scanner;
public class SmartWallet System Rivas {
    public static void main(String[] args){
        Scanner scanner = new Scanner(System.in);
        int transaction_counter = 1;
        float balance = 5000;
        int choice;

        System.out.println("===== SMART WALLET MENU =====\n"
            + "1. View Balance\n"
            + "2. Cash In\n\n"
            + "3. Send Money\n"
            + "4. Exit");

        while(true){
            System.out.println("\nTransaction " + transaction_counter + ": ");
            System.out.print("Choice: ");
            choice = scanner.nextInt();

            switch(choice) {
                case 1:
                    System.out.println("Output: Balance = " + balance);
                    transaction_counter++;
                    break;
                case 2:
                    System.out.print("Cash In: ");
                    float cash_in = scanner.nextFloat();
                    if (cash_in <= 0) {
                        System.out.println("Invalid amount.");
```

```
        } else {
            balance += cash_in;
            transaction_counter++;
            System.out.println("Output: NewBalance = " + balance);
        }
        break;
    case 3:
        System.out.print("Send Money: ");
        float send_money = scanner.nextFloat();
        if (send_money < 100) {
            System.out.println("Output: Minimum amount is 100");
        } else if (send_money > 1500) {
            System.out.println("Output: Exceeds maximum limit");
        } else if (send_money > balance) {
            System.out.println("Output: Amount exceeds current balance");
        } else {
            balance -= send_money;
            transaction_counter++;
            System.out.println("Money sent successfully");
            System.out.println("New balance: " + balance);
        }
        break;
    case 4:
        System.out.println("In Transaction count: " + (transaction_counter-1));
        scanner.close();
        System.exit(0);
        break;
    default:
        System.out.println("Invalid");
        break;
    }
  }
}
```

NO.:
DATE:

Sample Execution

Transaction 1:

Choice: 1

Output: Balance = 5000.0

Transaction 2:

Choice: 2

Output: New Balance = 10000.0

Transaction 3:

Choice: 3

Send Money: 5600

Output: Exceeds maximum limit

Transaction 3:

Choice: 4

Transaction Count: 2

Short Explanation

- How the while loop keeps the program running
- How switch-case controls menu selection
- How if-else validates transactions

The while loop keeps the program running continuosly since I used true everytime in order for user to input and do actions. It stops when user selects 4 which have these System.exit(0) statement to terminate the program. The switch case statement controls the menu selection by evaluating the users choice and jumping directly to the matching case. Case 1 is for viewing balance, Case 2 for cash in, Case 3 for sending money, and Case 4 for exiting the program. If input does not match to anything, default block handles it.

VICTORY

CamScanner

NO.:
DATE:

The if-else statement is used to validate transactions by specifying ranges and checking conditions. In case 1, in rejects if the user input amounts below 0 or 0. Case 2 checks if the amount is below 100, exceeds 1,500, or if input is grater than the balance before allowing transactions to happen. transactions that passed the validation are counted as successfull and printed in final transaction count when exiting.